

# PHP var\_dump() Function

One of the built-in functions in PHP is the var\_dump() function. This function displays structured information such as type and the value of one or more expressions given as arguments to this function.

```
var_dump(mixed $value, mixed ...$values): void
```

This function returns all the public, private and protected properties of the objects in the output. The dump information about arrays and objects is properly indented to show the recursive structure.

For the built-in integer, float and Boolean variables, the var\_dump() function shows the type and value of the argument variable.

## Example 1

For example, here is an integer variable –

[Open Compiler](#)

```
<?php
    $x = 10;
    var_dump ($x);
?>
```

The dump information is as follows –

```
int(10)
```

## Example 2

Let's see how it behaves for a float variable –

[Open Compiler](#)

```
<?php
    $x = 10.25;
```

```
var_dump ($x);  
?>
```

The var\_dump() function returns the following **output** –

```
float(10.25)
```

Explore our [latest online courses](#) and learn new skills at your own pace. Enroll and become a certified expert to boost your career.

## Example 3

If the expression is a Boolean value –

```
</>  
  
<?php  
    $x = true;  
    var_dump ($x);  
?>
```

[Open Compiler](#)

It will produce the following **output** –

```
bool(true)
```

## Example 4

For a string variable, the var\_dump() function returns the length of the string also.

```
</>  
  
<?php  
    $x = "Hello World";  
    var_dump ($x);  
?>
```

[Open Compiler](#)

It will produce the following **output** –

```
string(11) "Hello World"
```

Here we can use the `<pre>` HTML tag that displays preformatted text. Text in a `<pre>` element is displayed in a fixed-width font, and the text preserves both the spaces and the line breaks.

&lt;/&gt;

Open Compiler

```
<?php
    echo "<pre>";
    $x = "Hello World";
    var_dump ($x);
    echo "</pre>"
?>
```

It will produce the following **output** –

```
string(11) "Hello World"
```

## Example 5 - Studying the Array Structure Using var\_dump()

The `var_dump()` function is useful to study the array structure. In the following example, we have an array with one of the elements of the array being another array. In other words, we have a nested array situation.

&lt;/&gt;

Open Compiler

```
<?php
    $x = array("Hello", false, 99.99, array(10, 20, 30));
    var_dump ($x);
?>
```

It will produce the following **output** –

```
array(4) {
    [0]=>
    string(5) "Hello"
    [1]=>
    bool(false)
```

```
[2]=>
float(99.99)
[3]=>
array(3) {
    [0]=>
    int(10)
    [1]=>
    int(20)
    [2]=>
    int(30)
}
```

## Example 6

Since "\$x" is an **indexed array** in the previous example, the index starting with "0" along with its value is dumped. In case the array is an **associate array**, the key-value pair information is dumped.

&lt;/&gt;

Open Compiler

```
<?php
    $x = array(
        "Hello", false, 99.99,
        array(1=>10, 2=>20, 3=>30)
    );
    var_dump($x);
?>
```

Here, you will get the following **output** –

```
array(4) {
    [0]=>
    string(5) "Hello"
    [1]=>
    bool(false)
    [2]=>
    float(99.99)
    [3]=>
    array(3) {
        [1]=>
```

```
int(10)
[2]=>
int(20)
[3]=>
int(30)
}
}
```

When you use `var_dump()` to show array value, there is no need of using the end tag "`</pre>`".

## Example 7

The `var_dump()` function can also reveal the properties of an object representing a class. In the following example, we have declared a `Point` class with two private properties "x" and "y". The class constructor initializes the object "p" with the parameters passed to it.

The `var_dump()` function provides the information about the object properties and their corresponding values.

&lt;/&gt;

Open Compiler

```
<?php
class Point {
    private int $x;
    private int $y;

    public function __construct(int $x, int $y = 0) {
        $this->x = $x;
        $this->y = $y;
    }
}

$p = new Point(4, 5);
var_dump($p)
?>
```

It will produce the following **output** –

```
object(Point)#1 (2) {
    ["x":"Point":private]=>
    int(4)
```

```
["y":"Point":private]=>  
int(5)  
}
```

There is a similar built-in function for producing dump in PHP, named as **get\_defined\_vars()**.

```
var_dump(get_defined_vars());
```

It will dump all the defined variables to the browser.