
GRASP, DCD & Testing Techniques

Responsibilities · nine guidelines · design class diagram · white/black box · cyclomatic complexity: exam-ready in 11 sheets



↑ the whole topic on one page: red = high-yield, green = method / applied

Syllabus coverage

"… **Designing Objects with responsibilities**. **GRASP patterns with General Principles in assigning responsibilities**: Information expert, Creator, Low Coupling and High Cohesion, **Creating design class diagrams and mapping design to codes**. Software Testing: **White Box and Black Box testing**. **Basis Path Testing**."

High-yield list

① GRASP = Carell & Fowler, 1991
② Info Expert = the class with the data
③ Creator = the container
④ Least dependent class wins
⑤ DCD adds operations + navigability
⑥ M = conditions + 1

Legend: **yellow** = key term · **red circle** = must-memorise fact · **purple box** = memory trick · **red box** = exam trap · **green** = worked example

Contents

✓ GRASP: origin & the guidelines …… p. 2
✓ Information Expert & Creator …… p. 3
✓ Low Coupling & High Cohesion …… p. 4
✓ The remaining guidelines …… p. 5
✓ DCD: domain model vs design …… p. 6
✓ DCD worked example + code …… p. 7
✓ White-box vs black-box, EP, BVA …… p. 8
✓ Coverage, cyclomatic, basis path …… p. 9
✓ Night-before sheet …… p. 10
✓ Practice MCQs + written …… p. 11


1 GRASP: the Responsibility-Assignment Problem

Definition: **GRASP** = **G**eneral **R**esponsibility **A**ssignment **S**oftware **P**atterns: **guidelines for deciding which object gets which responsibility**, so that the result is loosely coupled, cohesive, maintainable and reusable. Proposed by **James Carell and Martin Fowler, 1991** (*Toward Unified Design Methodologies*, *IEEE Computer*).

Two kinds of responsibility

- **Knowing** — the object's own attributes and the objects linked to it.
- **Doing** — the actions it performs (its operations).

A **pattern** (Singleton, Strategy, Observer …) is a named solution *with structure*. A GRASP guideline is one sentence with no class diagram attached — **it tells you where to put a responsibility, not what to build**.



the set sorted by the question each guideline answers

nine guidelines, three questions

The nine guidelines, in one line each

#	Guideline	The principle, in one line
1	**Information Expert**	Give it to the class that **has the information**
2	**Creator**	The class that contains, aggregates or initialises it creates it
3	**Low Coupling**	Assign to the class **least dependent** on others
4	**High Cohesion**	One class, **maximum related** responsibility
5	**Polymorphism**	Do not re-implement superclass behaviour in a subclass
6	**Pure Arbiters**	The object that **arbitrates between** two or more others
7	**Don't Talk to Strangers**	Ask **only immediate associates** for information
8	**Controller**	The first **non-UI** object to receive a system event
9	**Intermediary** (Pure Fabrication)	An **invented**, non-domain class breaks the dependency

Three more often listed with GRASP: **Indirection** — an intermediary links objects that must not know each other. **Protected Variations** — wrap every point of **predicted change** in an interface. **Known / Unknown Dependencies** — name a **known** dependency concretely; an interface in front of a **changeable** one.

Exam trap: GRASP is **guidelines for assigning responsibilities** by **Carell & Fowler (1991)** — not a pattern catalogue, and not the GoF patterns. **Pure Arbiters** is sometimes printed as "Pure Arbiters / Information Expert": do not count it twice.

2 Information Expert & Creator — Worked

Information Expert: Assign the responsibility to the object that has the **information** needed to carry it out.
Example: the *Invoice* should compute `getTotal()`, because the Invoice is the only class holding its list of *LineItem*s.

```
class LineItem {
    Product product;
    int quantity;
    double getSubTotal() {
        return product.price * quantity;
    }
}
class Invoice {
    List<LineItem> items;
    double getTotal() {
        return items.stream()
            .mapToDouble(LineItem::getSubTotal)
            .sum();
    }
}
```

Why this is the right answer


- Only the **Invoice** holds the line items, so only it can sum them.
- No parameters have to be passed in and no *LineItem* needs a back-pointer.
- The knowledge stays **inside the class that owns the data**: coupling falls, cohesion rises.

Exam trap: Information Expert is **not** "the class with the most methods". It is the class with the **data needed**. If the data lives elsewhere, the responsibility goes elsewhere.

2b Creator — Worked

Creator: Assign to class **B** the job of creating instances of class **A** if **any one** of these holds: B **contains** A · B **aggregates** A · B **records** A · B **closely uses** A · B **holds the data** that would initialise A.

```
class Sale {
    List<SalesLineItem> lines;
    SalesLineItem addLine(Product p, int q) {
        SalesLineItem l = new SalesLineItem(p, q);
        lines.add(l);
        return l;
    }
}
```



Sale contains the line items, so Sale is the Creator

Creator: the container creates what it contains

Memory trick: **Creator = "C for Container"**. Even when B does not contain A, if B can name the values that initialise every field of A, B is a natural Creator — creating A there **reduces** the arguments the caller must supply.

Exam trap: Creator is not "the class that uses it". In a POS, **Sale** — not **Register**, **ProductCatalog** or **Payment** — creates **SalesLineItem**, because Sale *contains* the line items.

3 Low Coupling & High Cohesion — Worked

Low Coupling: Assign responsibilities so that **unnecessary dependencies are minimised**. The rule to quote: **give the responsibility to the class least dependent on other classes**. Dependence is measured by how much of another object's **state** a class must know.

Bad — high coupling

```
class Customer {
    String name;
    void saveToDatabase() {
        // opens a JDBC connection,
        // builds SQL, commits a tx
    }
}
```

Cost: *Customer* now knows the DB, SQL, the driver and the network.

Good — low coupling

```
class CustomerRepository {
    void save(Customer c) {
        // all DB logic lives here
    }
}
class Customer {
    String name;  // no DB knowledge
}
```

Gain: *Customer* is reusable, the repository replaceable, the two unit-test separately.

3b High Cohesion — Worked

```
// LOW COHESION — the "god class"
class CustomerManager {
    void browseShop()  { }
    void chargeCard()  { }
    void shipOrder()   { }
    void sendEmail()   { }
    void updateDatabase(){ }
}
```


Five unrelated jobs: **no single reason to change it**, and every change risks all five.

```
// HIGH COHESION — split it
class Customer { /* customer data */ }
class Cart     { /* cart operations */ }
class Payment  { /* payment logic  */ }
class Shipping { /* delivery       */ }
class Notifier { /* e-mail         */ }
```

Each has **one clear reason to change** — SRP restated.

Memory trick: **Coupling is how many strings are tied to this balloon** — four strings and it cannot fly. **Cohesion is how tightly its own parts stick together**: five unrelated jobs is gravel, not rock.

Exam trap: The two are **different axes**: coupling is *between* classes, cohesion *within* one. A class can be cohesive yet coupled to three others.



the same four objects, two ways of connecting them

IT link: A bank core hides its ledger rules behind an interface: the SQL is swappable without touching the business classes.

4 Polymorphism, Controller, Intermediary & the Rest

Polymorphism: Do **not** assign to a subclass a behaviour its superclass already covers. Put it in the superclass or interface and let **polymorphism** choose the version at run time. CashPayment · CardPayment · MobileBanking share *process()*.

Pure Arbiters: Assign a responsibility to the object that **arbitrates between two or more others** — it holds the rules both sides need and neither owns. A *TaxPolicy* that *Invoice* and *Refund* both consult.

Don't Talk to Strangers: If a method knows too much about, or depends on, too many others, it breaks the rule. Ask **only immediate associates**. Never reach through *Order* to touch *Order.getCustomer().getAddress()*.


Controller: The first object **beyond the UI layer** to receive a system event such as *enterItem* and coordinate it. Two kinds: **facade controller** (the whole system) and **use-case / session controller** (one scenario). **Never in the UI class.**

Intermediary (Pure Fabrication):
A class that **represents no domain concept at all**, invented only to break an awkward dependency; normally placed in the **common low-level packages**. A *ReportService* between the invoice and the database.

Protected Variations: Identify the points of **predicted change** and put an interface or abstract class in front of each, so the unstable part can vary without touching the rest. Open/Closed Principle; usually the Strategy pattern.

How the guidelines stack up against SOLID

GRASP guideline	It is really this principle
High Cohesion	Single Responsibility Principle
Low Coupling	Dependency Inversion · Open/Closed
Protected Variations	Open/Closed Principle · Strategy
Polymorphism	Liskov Substitution
Indirection / Intermediary	Dependency Inversion Principle




Controller sits beyond the UI; a mediator kills the shortcut

Exam trap: The **Controller** guideline is **not** "the class the user clicks" — a UI class that receives the event is precisely what GRASP forbids. A **Pure Fabrication** differs from a **Domain Model** class: it has **no domain meaning** at all.

5 The Design Class Diagram (DCD)

Definition: The **Design Class Diagram** is the UML class diagram drawn at the **design level**: the domain-model class diagram extended with everything an implementer needs — **operations** with signatures, **types**, **visibility** markers and **navigability** arrows.

Domain / analysis model	Design class diagram
Conceptual view of the domain	**Software** view
Classes, attributes, associations, multiplicities	those **plus methods** and return types
Plural domain nouns (Sales)	**Singular** nouns (Sale)
No software-specific types	Concrete: **String, double, List**
No visibility markers	**+ public · − private · # protected**
Associations are undirected	**Navigability** — who holds the reference
No interface or packages	**<<interface>>**, **<<abstract>>**, packages



the same subject, drawn twice: conceptual, then designed

Mapping design to code: the one-to-one rules


Element in the DCD	Becomes in the code
One class box	One **class** — or an interface, if stereotyped <<interface>>
An attribute *− price : double*	One **field** / property of that type
An operation *+ total() : double*	One **method** with that return type
An association **1** → * with navigability	A reference field plus a **collection** (array / *List* / *Set*)
Aggregation ◇ or composition ◆	A whole–part reference owned by the whole
A generalisation △ / realisation ▷	**inheritance** / composition by delegation

Exam trap: The one thing a DCD shows and a domain model does **not** is **methods (operations) and navigability**. Conceptual classes, associations and multiplicities appear in **both**.

Memory trick: Domain model = **what exists**. DCD = **what exists, plus what it does**. A method signature with a return type means you are looking at a DCD.

Four steps to build a DCD: ① Make every concept-class name **singular** (Sales → *Sale*). ② Give attributes **software types** (age: Integer → *int*). ③ Write each class's responsibilities as operations **with return types**. ④ Mark every association that holds a reference with a **navigability arrow**.

6 A DCD Worked Through, and the Code It Becomes



one design class diagram — Customer 1 — * Cart — * Order — * Line — * Product, plus a Payment collaborator; every box now carries operations with return types

```
class Customer {
    String name;
    String email;
    Cart cart = new Cart();

    void checkout() {
```

```
class Cart {
    List<Line> items = new ArrayList<>();

    void add(Product p, int q) {
        items.add(new Line(p, q));
    }
```

```
        Order o = cart.createOrder();
        o.confirm();
    }
}
class Line {
    Product product;   // navigable ▸
    int qty;
    double subTotal() {
        return product.price * qty;
    }
}
```

```
    double calculateTotal() {
        return items.stream()
            .mapToDouble(Line::subTotal)
            .sum();
    }
    Order createOrder() {
        return new Order(items);
    }
}
```

Read the mapping off the picture: *Cart.items : List<Line>* → the field *List<Line> items*; *Line.product : Product* → the field *Product product*; *Line.subTotal() : double* → the method. **Nothing in the DCD has to be re-invented in the code** — the class names, attribute names, types and method names already are the identifiers the programmer needs.

Exam trap: A DCD is **not** the same artefact as the CRC card: CRC is how you *discover* responsibilities, the DCD is how you *record* them. "Design maps directly to code" means a **one-to-one mapping** — not one file per diagram element.

7 Structural vs Functional Testing, EP and BVA

Aspect	White-box (structural, glass-box)	Black-box (functional, behavioural)
Test cases derived from	the **internal structure** of the code	the **specification**, not the code
Tester's knowledge	knows the program internals	does **not** know how it is written
Also called	structural, clear-box, glass-box	functional, specification-based
Main question	"is every statement / branch **executed**?"	"is the **output** right for every valid input?"
Techniques	basis-path testing, coverage analysis	equivalence partitioning, BVA, cause-effect graphing
Best at finding	dead code, unexecuted branches, wrong loop limits	missing requirements, wrong outputs

Test basis: The document a test is derived from: for a **white-box** test the **design model / code**, for a **black-box** test the **requirement specification**. Testing can show the **presence** of defects, never their absence.

Exam trap: Testing **cannot prove a program correct**; it only raises confidence. A test that has **never failed** is not yet known to be a good test. Unit → integration → validation → system levels, debugging, maintenance and test metrics belong to **Testing Strategies, Maintenance, Quality & Metrics**.

7b Equivalence Partitioning & Boundary-Value Analysis


Equivalence class (age)	Kind	EP pick
age < 18	invalid	10
18 ≤ age ≤ 60	**valid**	35
age > 60	invalid	70

EP splits the input domain into classes handled the same way and tests **one representative** of each — few cases, wide coverage. Valid and invalid classes are counted **separately**.

Boundary	BVA picks
lower, 18	17 · **18** · 19
upper, 60	59 · **60** · 61

BVA tests **just below, exactly at and just above** each boundary. Off-by-one errors live **at the edge** — exactly where EP takes one arbitrary sample.

> **When to use which ✍️:** EP alone is enough for a small input domain. With a wide domain (years, amounts, dates) EP on its own grows risky, so add **BVA**: EP keeps the *representative*, BVA keeps the *extreme*, and a fault inside a class slips past EP, which always aims at the middle.




three equivalence classes; BVA adds the six values on the two edges

8 Coverage, Cyclomatic Complexity & Basis-Path Testing

Coverage criterion	How it is measured	Strength
Statement	executed ÷ total executable statements × 100 %	weakest — misses unexecuted branches
Branch / decision	outcomes taken ÷ total outcomes × 100 %	**the usual minimum target**
Condition	atomic conditions evaluated ÷ total × 100 %	both ways for each part of `a && b`
Multiple condition	every truth-value combination — 2^n	very strong, very costly
Path	executed paths ÷ total paths × 100 %	strongest, exponential effort

> **Cyclomatic complexity (McCabe, 1976):** **M = E − N + 2P** — **E** = edges of the control-flow graph, **N** = nodes, **P** = connected components. A normal module gives **P = 1**, so the familiar form is **M = E − N + 2**. **M** is exactly the number of **independent paths** — the regions of the flow graph — and for straight-line conditionals **M = (independent conditions) + 1**. No decision at all ⇒ **M = 1**.

```
double total(int qty, double price,
             boolean member) {
  if (qty > 0 && price > 0) {
    double t = qty * price;
    if (member && t > 1000)
      t = t * 0.90;
    return t;
  }
  return 0.0;
}
```



the control-flow graph: E = 12, N = 9, so five independent paths

1. Draw the flow graph
2. Compute **M**
3. Find the **M** independent paths
4. One test case per path

Worked example ✍️: Four atomic conditions give **M = 4 + 1 = 5**, matching **E − N + 2 = 12 − 9 + 2 = 5**. Basis set: P1 *qty=0 → 0.0* · P2 *price=0 → 0.0* · P3 *2×100, not member → 200* · P4 *2×100, member, t≤1000 → 200* · P5 *20×100, member → 2000×0.9 = 1800*.

Independent path: A path introducing at least one **new node** or **new condition** no earlier path used. The count equals **M**.

Design in the V-model: Business req ↔ **acceptance** · system req ↔ **system test** · **architecture** ↔ **integration** · **design** ↔ **unit test**.

Nesting & limits: statement ⊂ branch ⊂ condition ⊂ path; McCabe's traditional limit is **10**.

Specialised test targets: real-time → timing, stress · distributed → latency, partial failure · web → SQL injection, XSS · mobile → devices, screens · embedded → CPU, memory. Full path coverage grows exponentially, so "100 % path coverage" is never a realistic goal.

Night-Before-the-Exam Sheet

Fact sheet:


GRASP = General Responsibility Assignment Software Patterns	Carell & Fowler, 1991, IEEE Computer
Guidelines, not a pattern catalogue	Knowing responsibility + doing responsibility
Info Expert = the class with the data	Creator = contains · aggregates · initialises
Low Coupling = least dependent class wins	High Cohesion = one clear reason to change
Polymorphism = do not duplicate in a subclass	Pure Arbiters = arbitrates between two or more
Don't Talk to Strangers = ask only associates	Controller = first non-UI object after the UI
Intermediary / Pure Fabrication = invented class	Protected Variations = interface over change
High Cohesion ≈ SRP · Protected Variations ≈ OCP	Polymorphism ≈ LSP · Intermediary ≈ DIP
Domain model = conceptual, no operations	DCD = adds operations, types, navigability
DCD ↔ code is one-to-one	White box = structure · black box = specification
Testing shows presence of defects, not absence	Statement · Branch · Condition · Path coverage
Multiple-condition coverage needs 2^n combinations	$M = E - N + 2P$; $P = 1$ for a normal module
M = conditions + 1 ; no decision ⇒ M = 1	M = independent paths · McCabe's limit 10

Top 14 one-liners for MCQs

1. GRASP: **Carell and Fowler, 1991**
2. GRASP guides **responsibility assignment**
3. Information Expert ⟶ the class **holding the data**
4. Creator ⟶ the class that **contains** the other
5. Low Coupling ⟶ the **least dependent** class
6. High Cohesion ⟶ **one** clear purpose
7. Controller ⟶ the first **non-UI** object
8. Pure Fabrication = **no domain meaning**
9. Protected Variations ⟶ an **interface**
10. A DCD shows **operations and navigability**, a domain model does not
11. DCD elements map to code **one-to-one**
12. White box from **structure**; black box from the **spec**
13. **M = E − N + 2P** is the cyclomatic number
14. Basis-path needs exactly **M** test cases

Top traps: GRASP is not the GoF catalogue · Controller is not the UI class · Creator is not "whoever uses it" · coupling is *between* classes, cohesion *within* one · a domain model has no operations · "white box proves correctness" is wrong · statement coverage is the **weakest** · $M = E - N + 2$ only when $P = 1$ · basis path gives M cases, **not** full path coverage · BVA tests the edges, EP samples the class.

All tricks together: "Who has the data?" = Information Expert · "C for Container" = Creator · too many strings = coupling, gravel not a rock = cohesion · a return type means a DCD · white box walks the code, black box reads the spec · M = conditions + 1, and M paths need M cases · EP samples the middle, BVA walks the edge.



the coverage ladder — weakest and cheapest at the top

✓ Practice MCQs (exam pattern, 10 marks)

1. Uses the class that **has the data**:
(a) Creator (b) Controller
(c) Information Expert (d) Low Coupling

2. A **Sale** holds many **SalesLineItems**. Creator?
(a) Sale (b) Register
(c) ProductCatalog (d) Payment

3. Handles an event beyond the UI layer:
(a) Pure Fabrication (b) Controller
(c) Indirection (d) Polymorphism

4. In a DCD but **not** a domain model:
(a) Concept classes (b) Associations
(c) Operations, navigability (d) Multiplicities

5. GRASP was developed by:
(a) Booch & Rumbaugh (b) Carell & Fowler
(c) Beck & Cunningham (d) IEEE

6. Coupling measures dependence:
(a) Within one class (b) Between classes
(c) Between two phases (d) On hardware

7. Cyclomatic number, no decision:
(a) 0 (b) 1
(c) 2 (d) −1

8. E = 14, N = 11, P = 1 ⇒ M =:
(a) 3 (b) 4
(c) 5 (d) 23

9. Basis-path cases for M = 7:
(a) 6 (b) 7
(c) 8 (d) 14

10. Black-box cases come from:
(a) Source code (b) Flow graph
(c) The specification (d) The CRC card

Answer key → 1-c · 2-a · 3-b · 4-c · 5-b · 6-b · 7-b · 8-c · 9-b · 10-c

Written question 1: Define GRASP, name its authors and year, and explain **Information Expert** and **Creator** with one worked example each. 10 marks

1. **GRASP** = General Responsibility Assignment Software Patterns — guidelines for assigning responsibilities 2
2. **Authors** — James Carell and Martin Fowler, 1991, *Toward Unified Design Methodologies*, IEEE Computer 2
3. **Information Expert** — the class holding the information takes the job; *Invoice.getTotal()*, because the Invoice holds the line items 3
4. **Creator** — the class that contains, aggregates, records, closely uses or can initialise the other creates it; *Sale* creates *SalesLineItem* 3

condition	y	n	action
	Y	Y	accept
	Y	N	reject
	N	Y	reject
	N	N	reject

2 conditions → $2^2 = 4$ rows

cause–effect graphing yields a decision table

Written question 2: A method has two nested *if* statements and two *&&* conditions. Compute its cyclomatic number and state how many basis-path test cases are needed. 8 marks **Answer:** four atomic conditions ⇒ **M = 4 + 1 = 5**; confirm with **M = E − N + 2P**, then write exactly **five** cases.

Before the exam ✓

- ✓ Name GRASP's authors and the year
- ✓ Recite all nine guidelines, one line each
- ✓ Tell a domain model from a DCD in one test
- ✓ Compute M from E, N, P and from conditions

Neighbours: the use-case model and V-model are in **Waterfall & UML**; test levels, debugging and metrics in **Testing Strategies**.

✓ Distinguish EP from BVA with numbers