

# A Compositional Deadlock Detector for Android Java

Darius Muresan

Henrique Luz

Rui Xavier

Aarhus University  
Department of Computer Science

November 11, 2025



AARHUS UNIVERSITY

# Why Study Deadlocks?

- Deadlocks are a fundamental challenge in concurrent programming.
- They occur when threads cyclically wait on each other's locks, preventing further progress.
- Detecting and preventing them is critical for reliability, especially in large-scale systems.
- In industrial settings (e.g., Android applications at Facebook), codebases can exceed tens of millions of LoC, making traditional whole-program analyses infeasible.

# The Industrial Challenge

- Modern software development involves:
  - Massive, continuously evolving codebases.
  - Frequent commits and rapid code reviews.
  - Strong requirements for developer feedback in under 15 minutes.
- Conventional static analyses:
  - Require analyzing entire programs.
  - Are too slow or memory-intensive for this context.
  - Often produce many false positives.

## Goal

Enable fast, scalable, and accurate deadlock detection that integrates seamlessly into continuous integration pipelines.

# The Research Gap

- Most existing tools:
  - Lack compositionality by reanalyzing the whole program each time.
  - Sacrifice scalability for soundness.
- Desired: a compositional, mathematically grounded approach that can analyze only changed code and its dependents.

## Core Challenge

How can we design a deadlock analysis that is both **theoretically sound** and **practically scalable** to millions of lines of concurrent Android Java code?

# Our Research Question

## Research Question

Can we develop a **compositional deadlock detector** for **Android Java** that is sound, complete, and efficient enough to run on commercial-scale codebases under active development?

- Key aspects explored:
  - Abstract modeling of real Java concurrency (balanced, re-entrant locks).
  - Deadlock characterization via **critical pairs**.
  - Compositional analysis integrated into the **INFER** framework.
- Goal: bridge the gap between **theory** and **industrial-scale deployment**.

# Concurrent Programs

# How to look at Concurrent Programs?

```
type  $\alpha$  node = {  
  data :  $\alpha$ ;  
  mutable prev :  $\alpha$  node;  
  mutable next :  $\alpha$  node;  
}
```

*Gospel + OCaml*

**Definition** Node A ( $v: A$ ) ( $n\ p\ c: \text{loc}$ ) :  $\text{hprop} :=$   
 $c \mapsto \{ \text{data}' := v; \text{next}' := n; \text{prev}' := p \}.$

*CFML*

# Inner Node

```
type  $\alpha$  innerNode =  
  | Nil  
  | Cons of  $\alpha$  node
```

*Gospel + OCaml*

```
Definition InnerNode A (L: list A) (p: innerNode_ A) : hprop :=  
  match L with  
  | []  $\Rightarrow$  [p = Nil]  
  | _  $\Rightarrow$   $\exists$  (c q: loc), [p = Cons c]  $\star$  c  $\rightsquigarrow$  NodeSeg L c q q  
  end.
```

*CFML*



# Doubly Linked List

```
type  $\alpha$  dblist = {  
  mutable head :  $\alpha$  innerNode;  
  mutable tail :  $\alpha$  innerNode;  
  mutable length : int;  
}
```

*Gospel + OCaml*

**Definition** Dblist A (L: list A) (l: loc) : hprop :=  
  $\exists$  (p q: innerNode\_ A),  
 (l  $\mapsto$  '{ head' := p; tail' := q; length' := length L })  $\star$   
 (If L = [] then [p = Nil]  $\star$  [q = Nil]  
 else  
  $\exists$  x L' h t, [L = x :: L']  $\star$  [p = Cons h]  $\star$  [q = Cons t]  
  $\star$  (h  $\rightsquigarrow$  NodeSeg L h t t)).

*CFML*

# Program Executions and their traces

```
val create : unit →  $\alpha$  dblist
val is_empty :  $\alpha$  dblist → bool
val clear :  $\alpha$  dblist → unit
val remove_head :  $\alpha$  dblist →  $\alpha$  node
val remove_tail :  $\alpha$  dblist →  $\alpha$  node
val reverse :  $\alpha$  dblist → unit
val append :  $\alpha$  dblist →  $\alpha$  dblist →  $\alpha$  dblist
val josephus :  $\alpha$  dblist → int → unit
val fold_right : ( $\alpha \rightarrow \beta \rightarrow \beta$ ) →  $\alpha$  dblist →  $\beta \rightarrow \beta$ 
val fold_left : ( $\alpha \rightarrow \beta \rightarrow \alpha$ ) →  $\alpha \rightarrow \beta$  dblist →  $\alpha$ 
val iter_right : ( $\alpha \rightarrow \beta$ ) →  $\alpha$  dblist →  $\beta$ 
val iter_left : ( $\alpha \rightarrow \beta$ ) →  $\alpha$  dblist → unit
...
```

*GOSPEL + OCaml*

```
val create : unit → α dblist
val is_empty : α dblist → bool
val clear : α dblist → unit
val remove_head : α dblist → α node
val remove_tail : α dblist → α node
val reverse : α dblist → unit
val append : α dblist → α dblist → α dblist
val josephus : α dblist → int → unit
val fold_right : (α → β → β) → α dblist → β → β
val fold_left : (α → β → α) → α → β dblist → α
val iter_right : (α → β) → α dblist → β
val iter_left : ('a -> 'b) -> 'a dblist -> unit
...
```

*GOSPEL + OCaml*

# Predicates

Filliâtre and Pereira [6] introduced two key logical predicates, *permitted* and *complete*, which allow us to reason both about the correctness of an iterator's behavior and its termination.

## Permitted – Visited Elements

$$\textit{permitted}(v, s) \triangleq ||v|| \leq ||s|| \wedge \forall i : 0 \leq i \leq ||v|| \implies v[i] = s[i]$$

## Complete – Iteration Termination

$$\textit{complete}(v, s) \triangleq ||v|| = ||s||$$

# iter\_left Function

```
val iter_left : ( $\alpha \rightarrow \beta$ )  $\rightarrow \alpha$  dblist  $\rightarrow$  unit Gospel + OCaml  
(*@ r = iter_left f collection  
  iterspec  
  ~permitted: (fun v  $\rightarrow$  length v  $\leq$  length collection  $\wedge$   
                $\forall$  i.  $0 \leq i < \text{length } v \rightarrow v[i] = \text{collection}[i]$ )  
  ~complete: (fun v  $\rightarrow$  length v = length collection) *)
```

This specification is a recent addition to Gospel by Ion Chirica and Mário Pereira [3].

# Soundness and Completeness

# OCaml Code

```
let rec iter_left_aux f node tail =  
  f node.data;  
  if not (tail == node) then  
    iter_left_aux f node.next tail
```

```
let iter_left f db =  
  match db.head with  
  | Nil → ()  
  | Cons n →  
    match db.tail with  
    | Nil → assert false  
    | Cons tail → iter_left_aux f n tail
```

*OCaml*



# Consumer Function Specification

$\forall x \text{ L1 L2, } L = \text{L1} ++ x :: \text{L2} \rightarrow$   
    **SPEC** (f x)  
    **PRE** (I L1)  
    **POSTUNIT** (I (L1 & x))

*CFML*

# iter\_left Specification

**Lemma** Triple\_iter\_left :  $\forall (I: \text{list } A \rightarrow \text{hprop}) L (f: \text{val}) t,$   
     $(\forall x L1 L2, L = L1 ++ x :: L2 \rightarrow$   
        **SPEC** (f x)  
            **PRE** (I L1)  
            **POSTUNIT** (I (L1 & x)))  $\rightarrow$   
**SPEC** (iter\_left f t)  
    **PRE** (t  $\leadsto$  Dblist L  $\star$  I [])  
    **POSTUNIT** (t  $\leadsto$  Dblist L  $\star$  I L).

*CFML*

# iter\_left\_aux Specification


To verify the higher-level `iter_left` function, we require a more fine-grained specification for its auxiliary, lower-level implementation.

**Lemma** `Triple_iter_left_aux` :

$$\begin{aligned} &\forall (f: \text{val}) (I : \text{list } A \rightarrow \text{hprop}) (L \text{ L1 L2: list } A) \text{ n e h p}, \\ &\quad (\forall x \text{ L1 L2, } L = \text{L1} ++ x :: \text{L2} \rightarrow \\ &\quad \quad \text{SPEC } (f \ x) \\ &\quad \quad \text{PRE } (I \ \text{L1}) \\ &\quad \quad \text{POSTUNIT } (I \ (\text{L1} \ \& \ x))) \rightarrow \\ &\quad L = \text{L1} ++ \text{L2} \rightarrow \\ &\quad \text{L2} \neq \text{nil} \rightarrow \\ &\quad \text{SPEC } (\text{iter\_left\_aux } f \ \text{n e}) \\ &\quad \quad \text{PRE } (\text{n} \rightsquigarrow \text{NodeSeg } \text{L2} \ \text{h e p} \star I \ \text{L1}) \\ &\quad \quad \text{POSTUNIT } (\text{n} \rightsquigarrow \text{NodeSeg } \text{L2} \ \text{h e p} \star I \ \text{L}). \end{aligned}$$

*CFML*

# Upper Complexity Bounds



# Implementation

# Conclusion and Related Work

# Conclusions

- Designed and implemented a circular doubly linked list in OCaml.
- Verified key operations (such as `create`, `clear`, `iter_left`, `fold_left`) using CFML.
- Demonstrated feasibility of verifying mutable data structures in a functional language.
- Identified limitations within the current toolchain.



# Reflections & Future Work

## Reflections

- Formal verification remains time-intensive (some proofs may take months).
- Highlights both promise and current challenges in formally verifying real-world functional code.

## Future Work

- Verify the remaining operations and auxiliary lemmas.
- Perform the refinement by comparing manual specs with Peter-generated ones.

# Bibliography I

- [1] Arthur Charguéraud. “Characteristic formulae for the verification of imperative programs”. In: *SIGPLAN Not.* 46.9 (Sept. 2011), pp. 418–430. ISSN: 0362-1340. DOI: [10.1145/2034574.2034828](https://doi.org/10.1145/2034574.2034828). URL: <https://doi.org/10.1145/2034574.2034828>.
- [2] Arthur Charguéraud et al. “GOSPEL - Providing OCaml with a Formal Specification Language”. In: *Formal Methods - The Next 30 Years - Third World Congress, FM 2019, Porto, Portugal, October 7-11, 2019, Proceedings*. Ed. by Maurice H. ter Beek, Annabelle McIver, and José N. Oliveira. Vol. 11800. Lecture Notes in Computer Science. Springer, 2019, pp. 484–501. DOI: [10.1007/978-3-030-30942-8\\_29](https://doi.org/10.1007/978-3-030-30942-8_29). URL: [https://doi.org/10.1007/978-3-030-30942-8\\_29](https://doi.org/10.1007/978-3-030-30942-8_29).

## Bibliography II

- [3] Ion Chirica and Mário Pereira. “Unfolding Iterators: Specification and Verification of Higher-Order Iterators, in OCaml”. In: *arXiv preprint arXiv:2506.20310* (2024). DOI: 10.48550/arXiv.2506.20310. arXiv: 2506.20310 [cs.PL]. URL: <https://arxiv.org/abs/2506.20310>.
- [4] Michael R. Clarkson et al. *OCaml Programming: Correct + Efficient + Beautiful*. <https://cs3110.github.io/textbook/cover.html>. 2025.
- [5] Jean-Christophe Filliâtre and Clément Pascutto. “Ortac: Runtime Assertion Checking for OCaml (Tool Paper)”. In: *Runtime Verification: 21st International Conference, RV 2021, Virtual Event, October 11–14, 2021, Proceedings*. Berlin, Heidelberg: Springer-Verlag, 2021, pp. 244–253. ISBN: 978-3-030-88493-2. DOI: 10.1007/978-3-030-88494-9\_13. URL: [https://doi.org/10.1007/978-3-030-88494-9\\_13](https://doi.org/10.1007/978-3-030-88494-9_13).

## Bibliography III

- [6] Jean-Christophe Filliâtre and Mário Pereira. “A Modular Way to Reason About Iteration”. In: *NASA Formal Methods - 8th International Symposium, NFM 2016, Minneapolis, MN, USA, June 7-9, 2016, Proceedings*. Ed. by Sanjai Rayadurgam and Oksana Tkachuk. Vol. 9690. Lecture Notes in Computer Science. Springer, 2016, pp. 322–336. DOI: 10.1007/978-3-319-40648-0\\_24. URL: [https://doi.org/10.1007/978-3-319-40648-0%5C\\_24](https://doi.org/10.1007/978-3-319-40648-0%5C_24).
- [7] Marc Hermes and Robbert Krebbers. “Modular Verification of Intrusive List and Tree Data Structures in Separation Logic”. In: *15th International Conference on Interactive Theorem Proving (ITP 2024)*. Ed. by Yves Bertot, Temur Kutsia, and Michael Norrish. Vol. 309. Leibniz International Proceedings in Informatics (LIPIcs). Dagstuhl, Germany: Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2024, 19:1–19:18. ISBN: 978-3-95977-337-9. DOI: 10.4230/LIPIcs.ITP.2024.19. URL: <https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.ITP.2024.19>.

## Bibliography IV

- [8] Mário Pereira and António Ravara. “Cameleer: A Deductive Verification Tool for OCaml”. In: July 2021, pp. 677–689. ISBN: 978-3-030-81687-2. DOI: 10.1007/978-3-030-81688-9\_31.
- [9] Mário Pereira Rui Xavier and Tiago Soares. *Formal Verification of OCaml Programs with Dynamic Memory*. Companion Artifact. 2025. URL: <https://github.com/RuiXavier/adc-artifact-companion> (visited on 06/23/2025).
- [10] Tiago Lopes Soares, Ion Chirica, and M'ario Pereira. “Static and Dynamic Verification of OCaml Programs: The Gospel Ecosystem”. In: *Leveraging Applications of Formal Methods, Verification and Validation. Specification and Verification*. Ed. by Tiziana Margaria and Bernhard Steffen. Cham: Springer Nature Switzerland, 2025, pp. 247–265. ISBN: 978-3-031-75380-0.