

Cryptography: cryptographic hash functions and MACs

Markulf Kohlweiss & Myrto Arapinis
School of Informatics
University of Edinburgh

January 26, 2021

Introduction

Encryption \Rightarrow confidentiality against eavesdropping

Introduction

Encryption \Rightarrow confidentiality against eavesdropping

What about authenticity and integrity against an active attacker?

— \rightarrow cryptographic hash functions and Message authentication codes

— \rightarrow this lecture

One-way functions (OWFs)

A OWF is a function that is easy to compute but hard to invert:

Definition (One-way)

A function f is a one-way function if for all y there is no efficient algorithm which can compute x such that $f(x) = y$

One-way functions (OWFs)

A OWF is a function that is easy to compute but hard to invert:

Definition (One-way)

A function f is a one-way function if for all y there is no efficient algorithm which can compute x such that $f(x) = y$

Constant functions ARE NOT OWFs

any x is such that $f(x) = c$

One-way functions (OWFs)

A OWF is a function that is easy to compute but hard to invert:

Definition (One-way)

A function f is a one-way function if for all y there is no efficient algorithm which can compute x such that $f(x) = y$

Constant functions ARE NOT OWFs

any x is such that $f(x) = c$

The successor function in \mathbb{N} IS NOT a OWF

given $\text{succ}(n)$ it is easy to retrieve $n = \text{succ}(n) - 1$

One-way functions (OWFs)

A OWF is a function that is easy to compute but hard to invert:

Definition (One-way)

A function f is a one-way function if for all y there is no efficient algorithm which can compute x such that $f(x) = y$

Constant functions ARE NOT OWFs

any x is such that $f(x) = c$

The successor function in \mathbb{N} IS NOT a OWF

given $\text{succ}(n)$ it is easy to retrieve $n = \text{succ}(n) - 1$

Multiplication of large primes IS a OWF:

integer factorisation is a hard problem - given $p \times q$ (where p and q are primes) it is hard to retrieve p and q

Collision-resistant functions (CRFs)

A function is a CRF if it is hard to find two messages that get mapped to the same value through this function

Definition (Collision resistance)

A function f is collision resistant if there is no efficient algorithm that can find two messages m_1 and m_2 such that $f(m_1) = f(m_2)$

Collision-resistant functions (CRFs)

A function is a CRF if it is hard to find two messages that get mapped to the same value through this function

Definition (Collision resistance)

A function f is collision resistant if there is no efficient algorithm that can find two messages m_1 and m_2 such that $f(m_1) = f(m_2)$

Constant functions ARE NOT CRFs
for all m_1 and m_2 , $f(m_1) = f(m_2)$

Collision-resistant functions (CRFs)

A function is a CRF if it is hard to find two messages that get mapped to the same value through this function

Definition (Collision resistance)

A function f is collision resistant if there is no efficient algorithm that can find two messages m_1 and m_2 such that $f(m_1) = f(m_2)$

Constant functions ARE NOT CRFs

for all m_1 and m_2 , $f(m_1) = f(m_2)$

The successor function in \mathbb{N} IS a CRF

the predecessor of a positive integer is unique

Collision-resistant functions (CRFs)

A function is a CRF if it is hard to find two messages that get mapped to the same value through this function

Definition (Collision resistance)

A function f is collision resistant if there is no efficient algorithm that can find two messages m_1 and m_2 such that $f(m_1) = f(m_2)$

Constant functions ARE NOT CRFs

for all m_1 and m_2 , $f(m_1) = f(m_2)$

The successor function in \mathbb{N} IS a CRF

the predecessor of a positive integer is unique

Multiplication of large primes IS a CRF:

every positive integer has a unique prime factorisation

Quiz

Cryptographic hash functions

A cryptographic hash function takes messages of arbitrary length and returns a fixed-size bit string such that any change to the data will (with very high probability) change the corresponding hash value.

Definition (Cryptographic hash function)

A cryptographic hash function $H : \mathcal{M} \rightarrow \mathcal{T}$ is a function that satisfies the following 4 properties:

- ▶ $|\mathcal{M}| \gg |\mathcal{T}|$
- ▶ it is easy to compute the hash value for any given message
- ▶ it is hard to retrieve a message from its hashed value (OWF)
- ▶ it is hard to find two different messages with the same hash value (CRF)

Examples: MD4, MD5, SHA-1, RIPEMD160, SHA-256, SHA-512, ...

⇒ In new projects use SHA-256 or SHA-512

Cryptographic hash functions: applications

- ▶ **Commitments** - Allow a participant to commit to a value v by publishing the hash $H(v)$ of this value, but revealing v only later.
Ex: electronic voting protocols, digital signatures, ...

Cryptographic hash functions: applications

- ▶ **Commitments** - Allow a participant to commit to a value v by publishing the hash $H(v)$ of this value, but revealing v only later.
Ex: electronic voting protocols, digital signatures, ...
- ▶ **File integrity** - Hashes are sometimes posted along with files on “read-only” spaces to allow verification of integrity of the files. Ex: SHA-256 is used to authenticate Debian GNU/Linux software packages

Cryptographic hash functions: applications

- ▶ **Commitments** - Allow a participant to commit to a value v by publishing the hash $H(v)$ of this value, but revealing v only later.
Ex: electronic voting protocols, digital signatures, ...
- ▶ **File integrity** - Hashes are sometimes posted along with files on “read-only” spaces to allow verification of integrity of the files. Ex: SHA-256 is used to authenticate Debian GNU/Linux software packages
- ▶ **Password verification** - Instead of storing passwords in cleartext, only the hash digest of each password is stored. To authenticate a user, the password presented by the user is hashed and compared with the stored hash.


Cryptographic hash functions: applications

- ▶ **Commitments** - Allow a participant to commit to a value v by publishing the hash $H(v)$ of this value, but revealing v only later.
Ex: electronic voting protocols, digital signatures, ...
- ▶ **File integrity** - Hashes are sometimes posted along with files on “read-only” spaces to allow verification of integrity of the files. Ex: SHA-256 is used to authenticate Debian GNU/Linux software packages
- ▶ **Password verification** - Instead of storing passwords in cleartext, only the hash digest of each password is stored. To authenticate a user, the password presented by the user is hashed and compared with the stored hash.
- ▶ **Key derivation** - Derive new keys or passwords from a single, secure key or password.

Cryptographic hash functions: applications

- ▶ **Commitments** - Allow a participant to commit to a value v by publishing the hash $H(v)$ of this value, but revealing v only later.
Ex: electronic voting protocols, digital signatures, ...
- ▶ **File integrity** - Hashes are sometimes posted along with files on “read-only” spaces to allow verification of integrity of the files. Ex: SHA-256 is used to authenticate Debian GNU/Linux software packages
- ▶ **Password verification** - Instead of storing passwords in cleartext, only the hash digest of each password is stored. To authenticate a user, the password presented by the user is hashed and compared with the stored hash.
- ▶ **Key derivation** - Derive new keys or passwords from a single, secure key or password.
- ▶ **Building block of other crypto primitives** - Used to build MACs, block ciphers, PRG, ...

Collisions are unavoidable



The domain being much larger than the range, collisions necessarily exist

The birthday attack - attack on all schemes

The birthday attack - attack on all schemes

Theorem

Let $H : \mathcal{M} \rightarrow \{0,1\}^n$ be a cryptographic hash function ($|\mathcal{M}| \gg 2^n$)
Generic algorithm to find a collision in time $O(\sqrt{2^n}) = O(2^{n/2})$ hashes:

1. Choose $2^{n/2}$ random messages in \mathcal{M} : $m_1, \dots, m_{2^{n/2}}$
2. For $i = 1, \dots, 2^{n/2}$ compute $t_i = H(m_i)$
3. If there exists a collision ($\exists i, j. t_i = t_j$)
then return (m_i, m_j)
else go back to 1

Birthday paradox Let $r_1, \dots, r_\ell \in \{1, \dots, N\}$ be independent variables.


For $\ell = 1.2 \times \sqrt{N}$, $Pr(\exists i \neq j. r_i = r_j) \geq \frac{1}{2}$

\Rightarrow the expected number of iteration is 2

\Rightarrow running time $O(2^{n/2})$

\Rightarrow Cryptographic function used in new projects should have output length $n \geq 256$!

The Merkle-Damgård construction



- Compression function: $h : \mathcal{T} \times \mathcal{X} \rightarrow \mathcal{T}$
- PB: $1000 \dots 0 || \text{mes-len}$ (add extra block if needed)

Theorem

Let H be built using the MD construction to the compression function h . If H admits a collision, so does h .


Example of MD constructions: MD5, SHA-1, SHA-2, ...

Compression functions from block ciphers

Let $E : \mathcal{K} \times \{0, 1\}^n \rightarrow \{0, 1\}^n$ be a block cipher

Compression functions from block ciphers

Let $E : \mathcal{K} \times \{0, 1\}^n \rightarrow \{0, 1\}^n$ be a block cipher




Davies-Meyer

Source: https://en.wikipedia.org/wiki/One-way_compression_function

Example of cryptographic hash function: SHA-256


- ▶ Structure: Merkle-Damgard
- ▶ Compression function: Davies-Meyer
- ▶ Bloc cipher: SHACAL-2



Message Authentication Codes (MACs)



$e = E(K_E, \text{Transfer 100 € on Bob's account})$





$e = E(K_E, \text{Transfer 100 € on Bob's account})$



What if the encryption scheme E is the OTP -
 $e = K_E \oplus \text{Transfer 100 € on Bob's account}$?

Encryption is not always enough



$e = E(K_E, \text{Transfer 100 € on Bob's account})$



What if the encryption scheme E is the OTP -
 $e = K_E \oplus \text{Transfer 100 € on Bob's account}$?




e




$e \oplus 0 \dots 0 \text{Bob} 0 \dots 0 \oplus 0 \dots 0 \text{Eve} 0 \dots 0$
 $= E(K_E, \text{Transfer 100 € on Eve's account})$



Goal: message integrity



Goal: message integrity



A MAC is a pair of algorithms (S, V) defined over $(\mathcal{K}, \mathcal{M}, \mathcal{T})$:


- ▶ $S : \mathcal{K} \times \mathcal{M} \rightarrow \mathcal{T}$
- ▶ $V : \mathcal{K} \times \mathcal{M} \times \mathcal{T} \rightarrow \{\top, \perp\}$
- ▶ Consistency: $V(k, m, S(k, m)) = \top$

Unforgeability

It is hard to computer a valid pair $(m, S(k, m))$ without knowing k

File system protection

- At installation time



k derived from user password

- To check for virus file tampering/alteration:
 - reboot to clean OS
 - supply password
 - any file modification will be detected

Block ciphers and message integrity

Block ciphers and message integrity

Let (E, D) be a block cipher. We build a MAC (S, V) using (E, D) as follows:

- ▶ $S(k, m) = E(k, m)$
- ▶ $V(k, m, t) = \begin{array}{ll} \text{if } m = D(k, t) & \\ \text{then return } \top & \\ \text{else return } \perp & \end{array}$

Block ciphers and message integrity

Let (E, D) be a block cipher. We build a MAC (S, V) using (E, D) as follows:

- ▶ $S(k, m) = E(k, m)$
- ▶ $V(k, m, t) = \begin{array}{ll} \text{if } m = D(k, t) & \\ \text{then return } \top & \\ \text{else return } \perp & \end{array}$

But: block ciphers can usually process only 128 or 256 bits

Block ciphers and message integrity


Let (E, D) be a block cipher. We build a MAC (S, V) using (E, D) as follows:

- ▶ $S(k, m) = E(k, m)$
- ▶ $V(k, m, t) = \begin{array}{ll} \text{if } m = D(k, t) & \\ \text{then return } \top & \\ \text{else return } \perp & \end{array}$

But: block ciphers can usually process only 128 or 256 bits

Our goal now: construct MACs for long messages

ECBC-MAC




► $E : \mathcal{K} \times \{0, 1\}^n \rightarrow \{0, 1\}^n$ a block cipher

► $ECBC-MAC : \mathcal{K}^2 \times \{0, 1\}^* \rightarrow \{0, 1\}^n$

→ the last encryption is crucial to avoid forgeries!!

Ex: 802.11i (WPA for Wi-Fi) uses AES based ECBC-MAC

PMAC




- ▶ $E : \mathcal{K} \times \{0, 1\}^n \rightarrow \{0, 1\}^n$ a block cipher
- ▶ $P : \mathcal{K} \times \mathbb{N} \rightarrow \{0, 1\}^n$ any easy to compute function
- ▶ $PMAC : \mathcal{K}^2 \times \{0, 1\}^* \rightarrow \{0, 1\}^n$

HMAC

MAC built from cryptographic hash functions

$$HMAC(k, m) = H(k \oplus OP || H(k \oplus IP || m))$$

IP, OP : publicly known padding constants



Ex: SSL, IPsec, SSH, ...

Authenticated encryption

Plain encryption is malleable

- ▶ The decryption algorithm never fails
- ▶ Changing one bit of the i^{th} block of the ciphertext
 - ▶ CBC decryption: will affect i^{th} and $i + 1^{th}$ block of the plaintext
 - ▶ ECB decryption: will only affect the i^{th} block of the plaintext
 - ▶ CTR decryption: will only affect one bit of the i^{th} block of the plaintext

Decryption should fail if a ciphertext was not computed using the key

Goal

Simultaneously provide data **confidentiality**, **integrity** and **authenticity**
~> decryption combined with integrity verification in one step

Encrypt-then-MAC

1. Always compute the MACs on the ciphertext, never on the plaintext
2. Use two different keys, one for encryption (K_E) and one for the MAC (K_M)

Encryption

1. $C \leftarrow E_{AES}(K_E, M)$
2. $T \leftarrow \text{HMAC-SHA}(K_M, C)$
3. return $C || T$

Decryption

1. if $T = \text{HMAC-SHA}(K_M, C)$
2. then return $D_{AES}(K_E, C)$
3. else return \perp

Do not:

- ▶ Encrypt-and-MAC: $E_{AES}(K_E, M) || \text{HMAC-SHA}(K_M, M)$
- ▶ MAC-then-Encrypt: $E_{AES}(K_E, M || \text{HMAC-SHA}(K_M, M))$

Galois Counter Mode

Combines

1. **Galois field** based One-time MAC for authentication
2. **AES** based Counter Mode for encryption.

- ▶ **Trick:** One-time MAC is encrypted too
⇒ secure for many messages
- ▶ Widely adopted for its performance
- ▶ Many good implementations of this mode