Temporal Prototype Alignment

for Frozen-Feature Dataset Distillation

Rui Ding[1] Jing Hu[1] Mei Chen[1] Xi Wu[1] Hualin Zhou[3] Fan Wu[2] Kehua Guo[2*] Tao Gu[3]

[1] Chengdu University of Information Technology [2] Central South University [3] Macquarie University [*] Corresponding author


NeurIPS 2026

Project page


1 Why temporal reuse?

LGM stabilizes classifier gradients by averaging ten augmented views per step through frozen encoders. Processing these views together increases memory and I/O costs.

LGM: evidence across space




TPA: evidence across time



One fresh view + a running prototype

Fixed-size moments reuse gradient history across steps instead of concurrent views.

Memory and accuracy




81 → 7 GB **3.6 → 0.8 h** **84.9 → 86.7%**

CLIP, ImageNet-100, IPC = 1.
LGM: 4 × RTX 4090. TPA: 1 × RTX 4090.

2 How temporal prototypes guide synthesis

Real-data gradients build temporal prototypes. Frozen teachers align synthetic gradients to these targets. Only synthetic pixels are updated.



Upper path: temporal prototypes. Lower path: teacher-local class alignment.

Adaptive Temporal Momentum (ATM)

One view per step updates first and second moments. A **reliability-dependent gate** controls temporal updates. **Inverse-RMS weighting** builds the prototype, with bias correction for zero initialization. Real and synthetic batches share a freshly sampled classifier head.

Contrastive Consensus Alignment (CCA)

CCA matches same-class gradients and separates different classes **within each teacher**. CLIP, DINOv2 and MoCo-v3 jointly optimize **one shared image set**. Each teacher retains its own head and prototypes, so feature dimensions can differ.


3 Cross-encoder transfer

ImageNet-100, one image per class (IPC = 1). One distilled set is evaluated on nine unseen encoders with linear probing and training-free 1-shot inference.

+3.3 pp Linear probing

+7.7 pp 1-shot inference

Gain over LGM-D · mean of nine unseen encoders



TPA-CDM reaches **92.3%** linear-probe and **88.4%** 1-shot accuracy across nine unseen encoders. Multi-teacher synthesis improves both transfer metrics over LGM-D.

What does the distilled set look like?



Selected images from the paper's TPA-CDM set.