

Implementing Noise2Noise for Dynamic Scenes


Ruijie Song M.S.*¹

Abstract

Implementing Noise2Noise for Dynamic Scenes

1. Dataset

(a) Gaussian ($\sigma = 25$)



There's the dataset.

1.1. Codes

```
1 # Copyright (c) 2018, NVIDIA CORPORATION
2 #
3 # This work is licensed under the Creative
4 # Commons Attribution 4.0 International License. To view a copy of this license, visit
5 # http://creativecommons.org/licenses/by-nc-sa/4.0/
6 # Creative Commons, PO Box 1866, Mountain View, CA 94039, USA
7
8 import tensorflow as tf
9
10 def parse_tfrecord_tf(record):
11     features = tf.parse_single_example(record)
12     'shape': tf.FixedLenFeature([3], tf.int32)
13     'data': tf.FixedLenFeature([], tf.string)
14     data = tf.decode_raw(features['data'], tf.uint8)
15     return tf.reshape(data, features['shape'])
16
17 # [c, h, w] -> [h, w, c]
```

```
18 def chw_to_hwc(x):
19     return tf.transpose(x, perm=[1, 2, 0])
20
21 # [h, w, c] -> [c, h, w]
22 def hwc_to_chw(x):
23     return tf.transpose(x, perm=[2, 0, 1])
24
25 def resize_small_image(x):
26     shape = tf.shape(x)
27     return tf.cond(
28         tf.logical_or(
29             tf.less(shape[2], 256),
30             tf.less(shape[1], 256)
31         ),
32         true_fn=lambda: hwc_to_chw(tf.image.resize_images(x, [256, 256])),
33         false_fn=lambda: tf.cast(x, tf.float32)
34     )
35
36 def random_crop_noised_clean(x, add_noise):
37     cropped = tf.random_crop(resize_small_image(x), [256, 256])
38     return (add_noise(cropped), add_noise(cropped))
39
40 def create_dataset(train_tfrecords, minibatch_size, num_threads):
41     print('Setting up dataset source from', train_tfrecords)
42     buffer_mb = 256
43     num_threads = 2
44     dset = tf.data.TFRecordDataset(train_tfrecords)
45     dset = dset.repeat()
46     buf_size = 1000
47     dset = dset.prefetch(buf_size)
48     dset = dset.map(parse_tfrecord_tf, num_parallel_calls=num_threads)
49     dset = dset.shuffle(buffer_size=buf_size)
50     dset = dset.map(lambda x: random_crop_noised_clean(x, add_noise))
51     dset = dset.batch(minibatch_size)
52     it = dset.make_one_shot_iterator()
53     return it
```

A. Do not have an appendix here

Do not put content after the references. Put anything that you might normally include after the references in a separate supplementary file.

We recommend that you build supplementary material in a separate document. If you must create one PDF and cut

*Equal contribution ¹Department of Electrical and Computer Engineering, Purdue University, West Lafayette, USA. Correspondence to: Cieuu Vvvvv <c.vvvvv@google.com>, Eee Pppp <ep@eden.co.uk>.

it up, please be careful to use a tool that doesn't alter the margins, and that doesn't aggressively rewrite the PDF file. pdftk usually works fine.

Please do not use Apple's preview to cut off supplementary material. In previous years it has altered margins, and created headaches at the camera-ready stage.