

## Comments and Replies Model (comments app)

### Comment

Rating, author, text, created\_at, (content\_type, content\_object, object\_id)

Fields in () for associating a comment with an Application/Shelter.

### Reply

Same as comment fields.

Extra field: comment (for recording the comment that this reply is made for)

## Endpoints for Comments and Replies (comments app)

### Details page for single application comment, add an application reply

**Endpoint:** /{user\_id}/applications/{application\_id}/comments/{comment\_id}/

**Methods:** GET, POST

**Success Response:** (GET) Details of the specific application comment and all of its replies, including comment\_id, text, user\_id, created\_at, rating. (POST) New reply saved to db and the list of replies refreshes.

**Validation Errors:**

- User not authorized
- User/Application/Comment not found
- Reply content is required

**Additional Notes:** Only accessible for logged-in user (shelter who received the application or pet seeker who submitted the application).

### List of all application comments for single application, add an application comment

**Endpoint:** /{user\_id}/applications/{application\_id}/comments/

**Methods:** GET, POST

**Success Response:** (GET) List of all comments and their replies associated with an application, including comment\_id, text, user\_id, created\_at, rating, sorted by creation time in descending order. (POST) New comment saved to db and the list of comments refreshes.

**Validation Errors:**

- User not authorized
- User/Application not found
- Comment content/rating is required

**Additional Notes:** Only accessible for logged-in user (shelter who received the application or pet seeker who submitted the application).

### **Details page for single shelter comment, add a shelter reply**

**Endpoint:** /{user\_id}/shelters/{shelter\_id}/comments/{comment\_id}/

**Methods:** GET, POST

**Success Response:** (GET) Details of the specific shelter comment and all of its replies, including comment\_id, text, user\_id, created\_at, rating. (POST) New reply saved to db and the list of replies refreshes.

**Validation Errors:**

- User/Shelter/Comment not found
- Reply content is required

**Additional Notes:** Only accessible for logged-in user (shelter or pet seeker).

### **List of all shelter comments for single shelter, add a shelter comment**

**Endpoint:** /{user\_id}/shelters/{shelter\_id}/comments

**Methods:** GET, POST

**Success Response:** (GET) List of all comments and their replies for a shelter, including comment\_id, text, user\_id, created\_at, rating, sorted by creation time in descending order. This should look like a page full of shelter reviews (layout would be similar to youtube reviews under a video). (POST) New comment saved to db and the list of comments refreshes.

**Validation Errors:**

- User/Shelter not found
- Comment content/rating is required

**Additional Notes:** Only accessible for logged-in user (shelter or pet seeker).

## **Notifications Model (notifications app)**

### **Notification**

Recipient, created\_at, is\_read, (content\_type, content\_object, object\_id)

Fields in () for associating a comment with an Application/Shelter.

## **Endpoints for notifications**

### **List Notifications, Delete all notifications for a user**

**Endpoint:** /{user\_id}/notifications/

**Method:** GET, DELETE

**Success Response:** (GET) Retrieves a list of notifications for the logged-in user. Supports filtering by read/unread status and is sorted by creation time. (DELETE) Deletes all notifications for a user from the db.

**Retrieve a Single Notification (auto-update from unread to read), Delete a notification**

**Endpoint:** `/ {user_id} / notifications / {notification_id} /`

**Method:** GET, PATCH, DELETE

**Success Response:** (GET) Retrieves the details of a specific notification. (PATCH) Accessing this endpoint can automatically mark the notification as read. (DELETE) Deletes the specified notification from the db.

# Pet

## Model:

- Pet
- Attributes: id, name, gallery, specie, breed, age, size, color, gender, location, health, characteristics, story, status, shelter

## Endpoint: /pet:

- The api endpoint that handles the creation of a new pet object.
- method: POST
- Fields/Payload: id, name, gallery, specie, breed, age, size, color, gender, location, health, characteristics, story, status, shelter
- Response: Newly created pet object
- Validation Errors: GET not allowed, not authenticated, not shelter, missing field

## Endpoint: /pets/<pet\_id>:

- The api endpoint that handles the retrieve, update, and delete of a specific pet listing
- method: GET PUT DELETE
- Fields/Payload: id, name, gallery, specie, breed, age, size, color, gender, location, health, characteristics, story, status, shelter
- Response: Pet Detail if GET, Updated Pet Detail/403 if PUT, 204/403 if DELETE
- Validation Errors: not authenticated, not allowed(not a shelter, not owned by the shelter)
- Additional Note: Can edit not all the fields

## Endpoint: /pets:

- The api endpoint that retrieves all the pets filtered as a list
- method: GET
- Fields/Payload: id, name, gallery, specie, breed, age, size, color, gender, location, health, characteristics, story, status, shelter
- Response: List of Pet with details
- Additional Note: uses ' ' to separate values of a single filter, for example status=Available,Adopted

# Accounts

## Models

### CustomUser

- Extends: AbstractBaseUser
- Attributes: email, password, avatar
- Username field (primary key): email
- Email and password are required.

### Shelter

- Extends: CustomUser
- Attributes: organization, phone number, address, country, state, city, zip, mission statement
- All attributes are required.

### Seeker

- Extends: CustomUser
- Attributes: first name, last name, phone number, address, country, state, city, zip
- All attributes are optional.

### Preference

- Extends: Model
- Attributes: preference (choices), owner (foreign key: Seeker)
- Preference is required.
- One-to-many relationship with Seeker (a seeker can have many preferences or no preferences).

## Endpoints

### /api/token

For token-based authentication (login).

Methods:

- POST

- Payload: email, password
- Success response: Refresh token + access token.
- Errors:
  - This field is required.
  - No active account found with the given credentials

## **/api/token/refresher**

For token-based authentication (login).

Methods:

- POST
  - Payload: access token
  - Success response: new access token

## **/shelters**

For creating a shelter account (POST) or viewing a list of shelters (GET).

Methods:

- POST
  - Payload: email, password, organization, phone number, address, country, state, city, zip, mission statement
  - Success response: Newly created shelter object.
  - Errors:
    - This field is required.
    - Enter a valid email address.
    - Enter a valid phone number.
    - custom user with this email already exists.
- GET
  - Payload: none
  - Success response: List of all shelters.

## **/shelters/<int:pk>**

For retrieving (GET) or updating (PUT, PATCH) a shelter account.

Methods:

- GET
  - Payload: none
  - Success response: Shelter details of requested shelter.
  - Errors:

- Not found.
- PUT, PATCH
  - Payload: email, password, organization, phone number, address, country, state, city, zip, mission statement
  - Success response: Updated shelter details
  - Errors:
    - You do not have permission to perform this action.
    - Enter a valid email address.
    - Enter a valid phone number.
    - custom user with this email already exists.

## **/shelters/<int:pk>/pets**

For deleting all the pet listings of a shelter.

Methods:

- DELETE
  - Payload: none
  - Success response: Successfully deleted seeker's pet listings.
  - Errors:
    - You do not have permission to perform this action.

## **/seekers**

For creating a seeker account.

Methods:

- POST
  - Payload: email, password, first name, last name, phone number, address, country, state, city, zip
  - Success response: Newly created seeker object.
  - Errors:
    - This field is required.
    - Enter a valid email address.
    - Enter a valid phone number.
    - custom user with this email already exists.

## **/seekers/<int:pk>**

For retrieving (GET) or updating (PUT, PATCH) a seeker account.

Methods:

- GET
  - Payload: none
  - Success response: Seeker details of requested seeker.
  - Errors:
    - You do not have permission to perform this action.
- PUT, PATCH
  - Payload: email, password, first name, last name, phone number, address, country, state, city, zip
  - Success response: Updated seeker details.
  - Errors:
    - You do not have permission to perform this action.
    - Enter a valid email address.
    - Enter a valid phone number.
    - custom user with this email already exists.

## **/seekers/<int:pk>/applications**

For deleting all the applications of a seeker.

Methods:

- DELETE
  - Payload: none
  - Success response: Successfully deleted seeker's applications.
  - Errors:
    - You do not have permission to perform this action.



# Applications

## Models

### Application

- Extends: models.Model
- Attributes: seeker (foreign key), shelter (foreign key), pet (foreign key), status (pending, accepted, denied, withdrawn), message, created\_at, updated\_at
- Ordering: -created\_at, -updated\_at

## Endpoints

### /pets/<int:pk>/applications

For creating an application.

Methods:

- POST
  - Payload: message (optional)
  - Success response: A newly created application by the requested user (seeker) for the pet with ID “pk”.
  - Errors:
    - You do not have permission to perform this action.
    - Not found.
    - Duplicate application.

### /applications/<int:pk>

For retrieving an application (GET) or updating an application (PUT, PATCH).

Methods:

- GET
  - Payload: none
  - Success response: Details of requested application.
  - Errors:
    - You do not have permission to perform this action.
    - Not found.
- PUT, PATCH
  - Payload: status

- Success response: Application with updated status. Notification created for the shelter/seeker if the current user is seeker/shelter.
- Errors:
  - You do not have permission to perform this action.
  - Not found.

## **/applications**

For a shelter to retrieve a list of applications for their pets.

Methods:

- GET
  - Payload: none
  - Success response: A list of applications for the shelter making the request.
  - Errors:
    - You do not have permission to perform this action.