

Automated Offline Smartphone-Assisted Microfluidic Paper-Based Analytical Device for Biomarker Detection of Alzheimer's Disease

Sixuan Duan^{1,2}, Ruiqi Yong¹, Hang Yuan¹, Tianyu Cai¹, Kaizhu Huang³, Kai Hoettges², Eng Gee Lim^{1,2}, Pengfei Song^{1,2,*}

¹ School of Advanced Technology, Xi'an Jiaotong-Liverpool University, Suzhou, China

² Department of Electrical and Electronic Engineering, University of Liverpool, Liverpool, UK

³ Department of Electrical and Computer Engineering, Duke Kunshan University, Kunshan, China

* Contact: pengfei.song@xjtlu.edu.cn

Poster No. A3P-109

ABSTRACT

This paper presents a smartphone-assisted microfluidic paper-based analytical device (μ PAD) applied to detect Alzheimer's disease (AD) biomarkers, especially in resource-limited regions. This device implements deep learning (DL)-assisted offline smartphone detection, eliminating the requirement for large computing devices and cloud computing power. In addition, a smartphone-controlled rotary valve enables a fully automated colorimetric enzyme-linked immunosorbent assay (c-ELISA) on μ PADs.

INTRODUCTION

Alzheimer's disease (AD) is a progressively deteriorating neurological disease without effective treatment.

- ★ Early detection and timely intervention could control the progression of AD [1, 2].
- ★ Our platform implements an automated high-accuracy c-ELISA for early detection of AD, with the advantages of rapid detection, low cost, and ease of operation.
- ★ Our platform realizes offline detection of smartphones, and can implement real-time monitoring and rapid detection, even in areas with poorly developed communications.

RESULTS




Fig. 4. The calibration curve of sandwich c-ELISA detection ($n=5$).

Detected A β 1-42 peptide in artificial plasma (Fig. 4):
LOD = 15.07 pg/mL
 $R^2 = 0.995$

- ★ Constructed the dataset for training the YOLOv5 model by testing 30 human serum samples (healthy: 15, unhealthy: 15).

The YOLOv5 model achieved an accuracy of 88.5%, outperforming the ImageJ analysis, which had an accuracy of 76.67%.




Fig. 5. The confusion matrix of (a) conventional method (ImageJ analysis). (b) YOLOv5 model.

CONCLUSION

This paper introduced a fully automated μ PAD, controlled by a smartphone enhanced with DL, for accurate offline detection of AD biomarkers (A β 1-42).

METHODS




Fig. 1. The flow chart of implementing smartphone-based offline detection on μ PAD.

- ★ Developed an Android application under the integrated development environment Android Studio (Google, U.S.A.).

Automated μ PAD with mechanical rotary valves (Fig. 3)




Fig. 2. (a) The photo of smartphone-assisted μ PAD. (b) The photo of μ PAD and other components.




Fig. 3. The schematic diagram of the design of μ PAD.

Acknowledgements:

This work is supported by Natural Science Foundation of the Jiangsu Higher Education (22KJB460033), Jiangsu Science and Technology Programme - Young Scholar (BK20200251), XJTLU RDF project (RDF-18-02-20), XJTLU AI University Research Centre, Jiangsu Province Engineering Research Centre of Data Science, Cognitive Computation at XJTLU, and SIP AI innovation platform (YZCXP2022103), the State Key Laboratory for Manufacturing Systems Engineering via the open project (SK-LMS2023019), and the Key Laboratory of Bionic Engineering, Ministry of Education at Jilin University.

References:

- [1] L. Mosconi et al., "Early detection of Alzheimer's disease using neuroimaging," *Experimental gerontology*, vol. 42, no. 1-2, pp. 129-138, 2007.
- [2] M. Sjögren, N. Andreasen, and K. Blennow, "Advances in the detection of Alzheimer's disease—use of cerebrospinal fluid biomarkers," *Clinica Chimica Acta*, vol. 332, no. 1-2, pp. 1-10, 2003.



Ruiqi Yong

Undergraduate Student (Year 3)

Xi'an Jiaotong-Liverpool University

Email: ruiqi.yong1118@gmail.com

Web: <https://ruiqiyong.github.io/>



Find a Ph.D. Position