



Motivation & Problem

- **Refactoring is Essential.** Developers spend much of their time improving existing codebases, and refactoring helps reduce technical debt, improve readability, and simplify testing.
- **Extract Method matters.** Splitting large methods into smaller, named functions is one of the most common and effective refactorings. In garbage collected languages (Java, Python), this is trivial.
- **Rust is Different.** Ownership, borrowing and lifetimes – Rust’s safety guarantees – make naïve extraction nearly impossible.
 - Moving values breaks ownership
 - Borrows (`&T`, `&mut T`) can easily become invalid
 - Lifetimes may need explicit annotations the compiler won’t infer automatically
 - Non-local control flow (`return`, `break`) doesn’t trivially transfer to a new function
- **The gap.** Existing IDE tools (IntelliJ’s Rust Plugin, Rust Analyzer) handle only simple extractions. They often fail on asynchronous code, generics, macros or complex lifetimes. Developers are often left with uncompileable or subtly incorrect code.
- **Why this matters.** In high-assurance domains, a refactoring that might silently change semantics is unacceptable. Even in Rust, compilation success \neq semantic equivalence.

Approach & Pipeline



Proof Mechanics & Obligations



Verifying Extract Method Refactoring in Rust



Matthew Britton, Alex Potanin, Sasha Pak

Preliminary Results

We evaluated REM on a curated set of extraction sites adapted from the `rust-analyzer` test suite, selected to span diverse language features (loops, control flow, comments, etc.). Each site was automatically transformed and verified for observational equivalence. All 10/10 cases discharged successfully in Coq, with average verification time ≈ 2 s—fast enough for interactive IDE use. These results show REMV’s ability to scale beyond toy examples, and highlight opportunities for larger-scale evaluation on real-world crates.

ID	Focus	Extracted Signature	LOC(P \rightarrow P')	Equiv
0	break loop	n: i32 \rightarrow Option<i32>	11 \rightarrow 18	✓
1	Break with value	() \rightarrow Option<i32>	13 \rightarrow 19	✓
2	Comments in block	() \rightarrow i32	9 \rightarrow 10	✓
3	Extract from nested loop	() \rightarrow i32	9 \rightarrow 12	✓
4	Extract from trait impl	&self \rightarrow i32	11 \rightarrow 16	✓
5	Extract mutable reference	y: &mut Foo	14 \rightarrow 17	✓
6	Extract return statement	() \rightarrow u32	5 \rightarrow 8	✓
7	Extract mutable method call	mut n: i32	12 \rightarrow 15	✓
8	No arguments if let else	() \rightarrow i32	5 \rightarrow 8	✓
9	Try option with return	() \rightarrow Option<i32>	12 \rightarrow 16	✓

From Prototype to Production

- **Standalone CLI:** working tool outside of the research harness
- **Language Coverage:** already supports `async/await`, generics, macros, etc.
- **IDE integration:** VSCode extension provides proof – of – concept with live extract \rightarrow fix \rightarrow verify cycle.
- **Performance:** ~ 2 s proof cycles \rightarrow feels interactive
- **Robustness:** automated repair loop makes it work on real crates

“Not just theory – A usable developer tool”

Future Work

- **Scaling:** whole-crate coverage via caching + incremental re-verification.
- **New features:** unsafe code, concurrency, richer ownership patterns.
- **Diagnostics:** friendlier failure messages when proofs don’t go through
- **Large-scale evaluation:** across multiple community crates
- **Stronger guarantees:** beyond observational equivalence!

“Towards real-world scale”

GitHub



VSCode



DOI

