

Basics for a grammar engine to verbalize logical theories in isiZulu

C. Maria Keet¹ and Langa Khumalo²

¹ Department of Computer Science, University of Cape Town, South Africa,
mkeet@cs.uct.ac.za

² Linguistics Program, School of Arts, University of KwaZulu-Natal, South Africa,
Khumalol@ukzn.ac.za

RuleML'14, Prague, August 18-20, 2014


Outline

- 1 Motivation
- 2 isiZulu intro
- 3 isiZulu NLG
 - Universal Quantification
 - Subsumption
 - Conjunction
 - Existential Quantification
- 4 Discussion and Conclusions

Natural language interfaces with some NLG

- Many tools, webpages, etc. with some natural language component
- Querying of information in natural language (cf. a query language SQL, SPARQL)
- Business rules typically specified in a natural language
- etc.

Example: Saadiq Moolla's mobile healthcare app



[Home](#) » [History](#) » [Cardiovascular History](#)

Chest Pain


Have you had any recent pain in your chest? - Uke waba nobuhlungu esifubeni maduzane?

Does the pain radiate to your jaw, neck or arm? - Engabe ubuhlungu bakho bujikeleza emhlathini, emqaleni noma nasezingalweni?

Does anything precipitate or relieve the pain? - Ingabe ikhona into eyenza ubuhlungu buqhubeke noma eyehlisa ubuhlungu?

Dyspnoea

Are you breathless at any time? - Uke uphelelwe umoya kwezinye izikhathi?



[Home](#) » [History](#) » [Cardiovascular History](#)

Chest Pain

Have you had any recent pain in your chest? - Ingaba kutshanje ukhe weva iintlungu esifubeni?

Does the pain radiate to your jaw, neck or arm? - Ingaba iintlungu zinwenwela emhlathini, entanyeni okanye engalweni?

Does anything precipitate or relieve the pain? - Ingaba ikhona into ezivuselelayo okanye ezidambisayo iintlungu?

Dyspnoea

NLG, principal approaches

- Canned text
 - Templates
 - Notably for English [Fuchs et al.(2010), Schwitter et al.(2008), Third et al.(2011), Curland and Halpin(2007)],
 - but also other languages [Jarrar et al.(2006)]
 - Grammar engines, such as [Kuhn(2013)], Grammatical Framework (<http://www.grammaticalframework.org/>)
- ⇒ Controlled Natural Language

Question

- Can the template-based approach be used also for isiZulu NLG?
 - If so, create those templates
 - If not, start with basics for a grammar engine
- Use a practically useful language to benefit both ICT and linguists and, possibly, some subject domain (e.g., medicine, NRS [Alberts et al.(2012)])

A few features of isiZulu

- Most populous language in SA, first (home) language of $\pm 23\%$ (≥ 10 million)
- Member of the Bantu language group, spoken by some 300 million people
- Bantu languages have characteristically agglutinating morphology
- System of noun classes, controls the concordance of all words in a sentence

Abafana abancane bazozithenga izincwadi ezinkulu

aba-fana **aba**-ncane **ba**- zo- **zi**- thenga **izi**-ncwadi e-**zi**-nkulu

2.boy 2.small 2.SUBJ-FUT-10.OBJ-buy 10.book REL-10.big

'The little boys will buy the big books'

NC	AU	PRE	Stem (ex- ample)	Meaning	Example	
1 2	u- a-	m(u)- ba-	-fana -fana	humans and other animates	umfana abafana	boy boys
1a 2a	u- o-	- -	-baba -baba	kinship terms and proper names	ubaba obaba	father fathers
3a (2a)	u- o-	- -	-shizi -shizi	nonhuman	ushizi oshizi	cheese cheeses
3 4	u- i-	m(u)- mi-	-fula -fula	trees, plants, non-paired body parts	umfula imifula	river rivers
5 6	i- a-	(li)- ma-	-gama -gama	fruits, paired body parts, and natural phenomena	igama amagama	name names
7 8	i- i-	si- zi-	-hlalo -hlalo	inanimates and manner/ style	isihlalo izihlalo	chair chairs
9a (6)	i- a-	- ma-	-rabha -rabha	nonhuman	irabha amarabha	rubber rubbers
9 10	i(n)- i-	- zi(n)-	-ja -ja	animals	inja izinja	dog dogs
11 (10)	u- i-	(lu)- zi(n)-	-thi -thi	inanimates and long thin objects	uthi izinthi	stick sticks
14 15	u- u-	bu- ku-	-hle -cula	abstract nouns infinitives	ubuhle ukucula	beauty to sing
17		ku-		locatives, remote/ general		locative

Logic foundation for isiZulu NLG

- Roughly OWL 2 EL
- OWL 2 EL is a W3C-standardised profile of OWL 2
- Tools, ontologies in OWL 2 (notably SNOMED CT)
- On the 'roughly': minus transitivity, but with negation, amounting to \mathcal{ALC}
 - of that, we have patterns for universal and existential quantification, subsumption, negation (disjointness), and conjunction

Universal Quantification

- Consider here only the universal quantification at the start of the concept inclusion axiom (nominal head)
- 'all'/'each' uses *-onke*, prefixed with the oral prefix of the noun class of that first noun (OWL class/DL concept) on lhs of \sqsubseteq

(U1) Boy \sqsubseteq ...

wonke umfana ...

('each boy...'; *u-* + *-onke*)

bonke abafana ...

('all boys...'; *ba-* + *-onke*)

(U2) Phone \sqsubseteq ...

lonke ifoni ...

('each phone...'; *li-* + *-onke*)

onke amafoni ...

('all phones...'; *a-* + *-onke*)

NC	QC (all)		NEG SC	PRON	RC	QC _{dwa}	EC
	QC _{oral+onke}	QC _{nke}					
1	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
1a	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2a	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3a	u-onke → wonke	wo-	aka-	wona	o-	ye-	mu-
(2a)	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3	u-onke → wonke	wo-	awu-	wona	o-	wo-	mu-
4	i-onke → yonke	yo-	ayi-	yona	e-	yo-	mi-
5	li-onke → lonke	lo-	ali-	lona	eli-	lo-	li-
6	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
7	si-onke → sonke	so-	asi-	sona	esi-	so-	si-
8	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
9a	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
(6)	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
9	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
10	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
11	lu-onke → lonke	lo-	alu-	lona	olu-	lo-	lu-
(10)	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
14	ba-onke → bonke	bo-	abu-	bona	obu-	bo-	bu-
15	ku-onke → konke	zo-	aku-	khona	oku-	zo-	ku-

NC	QC (all)		NEG SC	PRON	RC	QC _{dwa}	EC
	QC _{oral+onke}	QC _{nke}					
1	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
1a	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2a	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3a	u-onke → wonke	wo-	aka-	wona	o-	ye-	mu-
(2a)	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3	u-onke → wonke	wo-	awu-	wona	o-	wo-	mu-
4	i-onke → yonke	yo-	ayi-	yona	e-	yo-	mi-
5	li-onke → lonke	lo-	ali-	lona	eli-	lo-	li-
6	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
7	si-onke → sonke	so-	asi-	sona	esi-	so-	si-
8	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
9a	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
(6)	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
9	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
10	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
11	lu-onke → lonke	lo-	alu-	lona	olu-	lo-	lu-
(10)	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
14	ba-onke → bonke	bo-	abu-	bona	obu-	bo-	bu-
15	ku-onke → konke	zo-	aku-	khona	oku-	zo-	ku-

NC	QC _{oral}	QC (all) -onke	QC _{nke}	NEG SC	PRON	RC	QC _{dwa}	EC
1	u-onke	→ wonke	wo-	aka-	yena	o-	ye-	mu-
2	ba-onke	→ bonke	bo-	aba-	bona	aba-	bo-	ba-
1a	u-onke	→ wonke	wo-	aka-	yena	o-	ye-	mu-
2a	ba-onke	→ bonke	bo-	aba-	bona	aba-	bo-	ba-
3a	u-onke	→ wonke	wo-	aka-	wona	o-	ye-	mu-
(2a)	ba-onke	→ bonke	bo-	aba-	bona	aba-	bo-	ba-
3	u-onke	→ wonke	wo-	awu-	wona	o-	wo-	mu-
4	i-onke	→ yonke	yo-	ayi-	yona	e-	yo-	mi-
5	li-onke	→ lonke	lo-	ali-	lona	eli-	lo-	li-
6	a-onke	→ onke	o-	awa-	wona	a-	wo-	ma-
7	si-onke	→ sonke	so-	asi-	sona	esi-	so-	si-
8	zi-onke	→ zonke	zo-	azi-	zona	ezi-	zo-	zi-
9a	i-onke	→ yonke	yo-	ayi-	yona	e-	yo-	yi-
(6)	a-onke	→ onke	o-	awa-	wona	a-	wo-	ma-
9	i-onke	→ yonke	yo-	ayi-	yona	e-	yo-	yi-
10	zi-onke	→ zonke	zo-	azi-	zona	ezi-	zo-	zi-
11	lu-onke	→ lonke	lo-	alu-	lona	olu-	lo-	lu-
(10)	zi-onke	→ zonke	zo-	azi-	zona	ezi-	zo-	zi-
14	ba-onke	→ bonke	bo-	abu-	bona	obu-	bo-	bu-
15	ku-onke	→ konke	zo-	aku-	khona	oku-	zo-	ku-

Subsumption

- Two different ways of carving up the nouns to determine which rules apply: semantic and syntactic
- Syntactic: still two options for copulative, depending on second noun

(S1) MedicinalHerb \sqsubseteq Plant

ikhambi ngumuthi

('medicinal herb is a plant')

(S2) Giraffe \sqsubseteq Animal

indlulamithi yisilwane

('giraffe is a animal')

Subsumption: adding negation

- Copulative is omitted
- Combines the negative subject concord (NEG SC) of the noun class of the first noun (*azi-*) with the pronomial (PRON) of the noun class of second noun (*-yona*)

(SN1) Cup \sqsubseteq \neg Glass

zonke izindebe aziyona ingilazi

('all cups not a glass')

NC	QC (all) QC _{oral+onke}	QC _{nke}	NEG SC	PRON	RC	QC _{dwa}	EC
1	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
1a	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2a	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3a	u-onke → wonke	wo-	aka-	wona	o-	ye-	mu-
(2a)	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3	u-onke → wonke	wo-	awu-	wona	o-	wo-	mu-
4	i-onke → yonke	yo-	ayi-	yona	e-	yo-	mi-
5	li-onke → lonke	lo-	ali-	lona	eli-	lo-	li-
6	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
7	si-onke → sonke	so-	asi-	sona	esi-	so-	si-
8	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
9a	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
(6)	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
9	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
10	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
11	lu-onke → lonke	lo-	alu-	lona	olu-	lo-	lu-
(10)	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
14	ba-onke → bonke	bo-	abu-	bona	obu-	bo-	bu-
15	ku-onke → konke	zo-	aku-	khona	oku-	zo-	ku-

NC	QC (all)		NEG SC	PRON	RC	QC _{dwa}	EC
	QC _{oral} +onke	QC _{nke}					
1	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
1a	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2a	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3a	u-onke → wonke	wo-	aka-	wona	o-	ye-	mu-
(2a)	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3	u-onke → wonke	wo-	awu-	wona	o-	wo-	mu-
4	i-onke → yonke	yo-	ayi-	yona	e-	yo-	mi-
5	li-onke → lonke	lo-	ali-	lona	eli-	lo-	li-
6	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
7	si-onke → sonke	so-	asi-	sona	esi-	so-	si-
8	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
9a	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
(6)	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
9	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
10	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
11	lu-onke → lonke	lo-	alu-	lona	olu-	lo-	lu-
(10)	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
14	ba-onke → bonke	bo-	abu-	bona	obu-	bo-	bu-
15	ku-onke → konke	zo-	aku-	khona	oku-	zo-	ku-

NC	QC (all)		NEG SC	PRON	RC	QC _{dwa}	EC
	QC _{oral} +onke	QC _{nke}					
1	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
1a	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2a	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3a	u-onke → wonke	wo-	aka-	wona	o-	ye-	mu-
(2a)	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3	u-onke → wonke	wo-	awu-	wona	o-	wo-	mu-
4	i-onke → yonke	yo-	ayi-	yona	e-	yo-	mi-
5	li-onke → lonke	lo-	ali-	lona	eli-	lo-	li-
6	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
7	si-onke → sonke	so-	asi-	sona	esi-	so-	si-
8	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
9a	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
(6)	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
9	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
10	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
11	lu-onke → lonke	lo-	alu-	lona	olu-	lo-	lu-
(10)	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
14	ba-onke → bonke	bo-	abu-	bona	obu-	bo-	bu-
15	ku-onke → konke	zo-	aku-	khona	oku-	zo-	ku-

Subsumption patterns

- Plain subsumption:
 - N_1 <copulative *ng/y* depending on first letter of N_2 > N_2 .
- And with negation:
 - <All-concord for NC_x >onke <plural N_1 , being of NC_x >
 <NEG SC of NC_x ><PRON of NC_y > < N_2 with NC_y >.

Algorithm 1 Determine the verbalization of simple taxonomic subsumption

1: \mathcal{C} set of classes, language \mathcal{L} with \sqsubseteq for subsumption and \neg for negation; variables: A axiom, NC_i nounclass, $c_1, c_2 \in \mathcal{C}$, a_1 term, a_2 letter; functions: *getFirstClass*(A), *getSecondClass*(A), *getNC*(C), *pluralizeNoun*(C, NC_i), *checkNegation*(A), *getFirstChar*(C), *getNSC*(NC_i), *getPNC*(NC_i).

Require: axiom A with a \sqsubseteq has been retrieved

```

2:  $c_1 \leftarrow \text{getFirstClass}(A)$                                 {get subclass}
3:  $c_2 \leftarrow \text{getSecondClass}(A)$                             {get superclass}
4:  $NC_1 \leftarrow \text{getNC}(c_1)$                                 {determine noun class by augment and prefix or dictionary}
5:  $NC_2 \leftarrow \text{getNC}(c_2)$                                 {determine noun class by augment and prefix or dictionary}
6: if checkNegation( $A$ ) = true then
7:    $NC'_1 \leftarrow$  lookup plural nounclass of  $NC_1$           {from known list}
8:    $c'_1 \leftarrow \text{pluralizeNoun}(c_1, NC'_1)$ 
9:    $a_1 \leftarrow$  lookup quantitative concord for  $NC'_1$       {from quantitative concord (QC(all)) list}
10:   $n \leftarrow \text{getNSC}(NC'_1)$                                 {get negative subject concord for  $c'_1$ }
11:   $p \leftarrow \text{getPNC}(NC_2)$                                 {get pronomial for  $c_2$ }
12:   $\text{RESULT} \leftarrow 'a_1 c'_1 np c_2.'$                         {verbalise the disjointness}
13: else
14:    $a_2 \leftarrow \text{getFirstChar}(c_2)$                           {retrieve first letter of  $c_2$ }
15:   select case
16:      $a_2 = \text{'i'}$  then
17:        $\text{RESULT} \leftarrow 'c_1 yc_2'$                             {verbalise as taxonomic subsumption with y}
18:      $a_2 = \{\text{'a'}, \text{'o'}, \text{'u'}\}$  then
19:        $\text{RESULT} \leftarrow 'c_1 ngc_2'$                             {verbalise as taxonomic subsumption with ng}
20:      $a_2 \notin \{\text{'a'}, \text{'i'}, \text{'o'}, \text{'u'}\}$  then
21:        $\text{RESULT} \leftarrow \text{'this is not a well-formed isiZulu noun'}$ 
22:   end select case
23: end if
24: return  $\text{RESULT}$ 

```

Algorithm 1 Determine the verbalization of simple taxonomic subsumption

1: \mathcal{C} set of classes, language \mathcal{L} with \sqsubseteq for subsumption and \neg for negation; variables: A axiom, NC_i nounclass, $c_1, c_2 \in \mathcal{C}$, a_1 term, a_2 letter; functions: $getFirstClass(A)$, $getSecondClass(A)$, $getNC(C)$, $pluralize(NC_i)$, $checkNegation(A)$, $lookupPluralNoun(c_1, NC_1)$, $lookupQuantitativeConcord(NC_1)$, $getNSC(NC_1)$, $getPNC(NC_2)$, $retrieveClassAndGetNounClass(A)$

Require: axiom A with a \sqsubseteq has been retrieved

```

2:  $c_1 \leftarrow getFirstClass(A)$                                 {get subclass}
3:  $c_2 \leftarrow getSecondClass(A)$                             {get superclass}
4:  $NC_1 \leftarrow getNC(c_1)$                                 {determine noun class by augment and prefix or dictionary}
5:  $NC_2 \leftarrow getNC(c_2)$                                 {determine noun class by augment and prefix or dictionary}
6: if  $checkNegation(A) = true$  then
7:    $NC'_1 \leftarrow lookupPluralNoun(c_1, NC_1)$               {from known list}
8:    $c'_1 \leftarrow pluralizeNoun(c_1, NC'_1)$ 
9:    $a_1 \leftarrow lookupQuantitativeConcord(NC'_1)$           {from quantitative concord (QC(all)) list}
10:   $n \leftarrow getNSC(NC'_1)$                                 {get negative subject concord for  $c'_1$ }
11:   $p \leftarrow getPNC(NC_2)$                                 {get pronomial for  $c_2$ }
12:   $RESULT \leftarrow 'a_1 c'_1 np c_2.'$                       {verbalise the disjointness}
13: else
14:    $a_2 \leftarrow getFirstChar(c_2)$                         {retrieve first letter of  $c_2$ }
15:   select case
16:      $a_2 = 'i'$  then
17:        $RESULT \leftarrow 'c_1 yc_2'$                           {verbalise as taxonomic subsumption with y}
18:      $a_2 = \{'a', 'o', 'u'\}$  then
19:        $RESULT \leftarrow 'c_1 ngc_2'$                           {verbalise as taxonomic subsumption with ng}
20:      $a_2 \notin \{'a', 'i', 'o', 'u'\}$  then
21:        $RESULT \leftarrow \text{'this is not a well-formed isiZulu noun'}$ 
22:   end select case
23: end if
24: return  $RESULT$ 

```

retrieve class and get
its noun class

Algorithm 1 Determine the verbalization of simple taxonomic subsumption

1: \mathcal{C} set of classes, language \mathcal{L} with \sqsubseteq for subsumption and \neg for negation; variables: A axiom, NC_i nounclass, $c_1, c_2 \in \mathcal{C}$, a_1 term, a_2 letter; functions: *getFirstClass*(A), *getSecondClass*(A), *getNC*(C), *pluralizeNoun*(C, NC_i), *checkNegation*(A), *getFirstChar*(C), *getNSC*(NC_i), *getPNC*(NC_i).

Require: axiom A with a \sqsubseteq has been retrieved

```

2:  $c_1 \leftarrow \text{getFirstClass}(A)$                                 {get subclass}
3:  $c_2 \leftarrow \text{getSecondClass}(A)$                           {get superclass}
4:  $NC_1 \leftarrow \text{getNC}(c_1)$                                 {determine noun class by augment and prefix or dictionary}
5:  $NC_2 \leftarrow \text{getNC}(c_2)$                                 {determine noun class by augment and prefix or dictionary}
6: if checkNegation( $A$ ) = true then
7:    $NC'_1 \leftarrow$  lookup plural nounclass of  $NC_1$           {from known list}
8:    $c'_1 \leftarrow \text{pluralizeNoun}(c_1, NC'_1)$ 
9:    $a_1 \leftarrow$  lookup quantitative concord for  $NC'_1$       {from quantitative concord (QC(all)) list}
10:   $n \leftarrow \text{getNSC}(NC'_1)$                                 {get noun class for  $c'_1$ }
11:   $p \leftarrow \text{getPNC}(NC_2)$                                 {get plural for  $c_2$ }
12:   $\text{RESULT} \leftarrow 'a_1 c'_1 np c_2.'$                       {validate the disjointness}
13: else
14:    $a_2 \leftarrow \text{getFirstChar}(c_2)$                           {retrieve first letter of  $c_2$ }
15:   select case
16:      $a_2 = \text{'i'}$  then
17:        $\text{RESULT} \leftarrow 'c_1 yc_2'$                             {verbalise as taxonomic subsumption with y}
18:      $a_2 = \{\text{'a'}, \text{'o'}, \text{'u'}\}$  then
19:        $\text{RESULT} \leftarrow 'c_1 ngc_2'$                             {verbalise as taxonomic subsumption with ng}
20:      $a_2 \notin \{\text{'a'}, \text{'i'}, \text{'o'}, \text{'u'}\}$  then
21:        $\text{RESULT} \leftarrow \text{'this is not a well-formed isiZulu noun'}$ 
22:   end select case
23: end if
24: return  $\text{RESULT}$ 

```

'simple' ISA

Algorithm 1 Determine the verbalization of simple taxonomic subsumption

1: \mathcal{C} set of classes, language \mathcal{L} with \sqsubseteq for subsumption and \neg for negation; variables: A axiom, NC_i nounclass, $c_1, c_2 \in \mathcal{C}$, a_1 term, a_2 letter; functions: *getFirstClass*(A), *getSecondClass*(A), *getNC*(C), *pluralizeNoun*(C, NC_i), *checkNegation*(A), *getFirstChar*(C), *getNSC*(NC_i), *getPNC*(NC_i).

Require: axiom A with a \sqsubseteq has been retrieved

```

2:  $c_1 \leftarrow \text{getFirstClass}(A)$  {get subclass}
3:  $c_2 \leftarrow \text{getSecondClass}(A)$  {get superclass}
4:  $NC_1 \leftarrow \text{getNC}(c_1)$  {determine noun class}
5:  $NC_2 \leftarrow \text{getNC}(c_2)$  {determine noun class by segment and prefix or dictionary}
6: if checkNegation( $A$ ) = true then
7:    $NC'_1 \leftarrow$  lookup plural nounclass of  $NC_1$  {from known list}
8:    $c'_1 \leftarrow \text{pluralizeNoun}(c_1, NC'_1)$ 
9:    $a_1 \leftarrow$  lookup quantitative concord for  $NC'_1$  {from quantitative concord (QC(all)) list}
10:   $n \leftarrow \text{getNSC}(NC'_1)$  {get negative subject concord for  $c'_1$ }
11:   $p \leftarrow \text{getPNC}(NC_2)$  {get pronomial for  $c_2$ }
12:   $\text{RESULT} \leftarrow 'a_1 c'_1 np c_2.'$  {verbalise the disjointness}
13: else
14:    $a_2 \leftarrow \text{getFirstChar}(c_2)$  {retrieve first letter of  $c_2$ }
15:   select case
16:      $a_2 = \text{'i'}$  then
17:        $\text{RESULT} \leftarrow 'c_1 yc_2'$  {verbalise as taxonomic subsumption with y}
18:      $a_2 = \{\text{'a'}, \text{'o'}, \text{'u'}\}$  then
19:        $\text{RESULT} \leftarrow 'c_1 ngc_2'$  {verbalise as taxonomic subsumption with ng}
20:      $a_2 \notin \{\text{'a'}, \text{'i'}, \text{'o'}, \text{'u'}\}$  then
21:        $\text{RESULT} \leftarrow \text{'this is not a well-formed isiZulu noun'}$ 
22:   end select case
23: end if
24: return  $\text{RESULT}$ 

```

Conjunction

- Conjunction as enumeration uses *na*
- Changes into (a + i =) *ne* or (a + u =) *no*, depending on the first letter of the second noun
- Prefixed to the second noun that drops its first letter
- Conjunction as connective of clauses: *kanye* or *futhi*

(C1) Milk \sqcap Butter

Ubisi nebhotela

(*Ubisi* + *na* + *Ibhotela*)

(C2) Butter \sqcap Milk

Ibhotela nobisi

(*Ibhotela* + *na* + *Ubisi*)

(C3) ... \exists has_filling.Cream \sqcap \exists has_Icing.Lemon_flavour...

...kune zigcwalisa ukhilimu kanye nezinye uqweqwe
olunambitheka_ulamula...

Algorithm 2 Determine the verbalization of conjunction in an axiom

1: \mathcal{R} is the set of relationships, \mathcal{A} of attributes, \mathcal{C} of classes, and language \mathcal{L} uses \sqcap to denote conjunction; variables: e_2 , c_1 a letter, A axiom; functions: $getNextVocabularyElement(A)$, $getFirstChar(e_2)$.

Require: axiom with a \sqcap has been retrieved and position in string is known

2: $e_2 \leftarrow getNextVocabularyElement(A)$ {retrieve element after the \sqcap }

3: **if** $e_2 \in \mathcal{R} \cup \mathcal{A}$ **then**

4: $RESULT \leftarrow \text{'kanye'}$ {verbalise \sqcap as kanye}

5: **else**

6: **if** $e_2 \in \mathcal{C}$ **then**

7: $c_1 \leftarrow getFirstChar(e_2)$ {retrieve first letter of e_2 }

8: **select case**

9: $c_1 = \text{'i'}$ **then**

10: $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$

11: $RESULT \leftarrow \text{'nee}_2^-$ {verbalise \sqcap with ne- prefix}

12: $c_1 = \text{'u'}$ **then**

13: $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$

14: $RESULT \leftarrow \text{'noe}_2^-$ {verbalise \sqcap with no- prefix}

15: $c_1 = \text{'a'}$ **then**

16: $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$

17: $RESULT \leftarrow \text{'nae}_2^-$ {verbalise \sqcap with na- prefix}

18: $c_1 \notin \{\text{'i'}, \text{'u'}, \text{'a'}\}$ **then**

19: $RESULT \leftarrow \text{'this is not a well-formed isiZulu noun'}$

20: **end select case**

21: **else**

22: $RESULT \leftarrow \text{'this is not a well-formed axiom'}$

23: **end if**

24: **end if**

25: **return** $RESULT$

Algorithm 2 Determine the verbalization of conjunction in an axiom

1: \mathcal{R} is the set of relationships, \mathcal{A} of attributes, \mathcal{C} of classes, \mathcal{L} of language \mathcal{L}
 uses \sqcap to denote conjunction; variables: e_1, e_2, c_1, c_2 ; functions:
 $getNextVocabularyElement(A)$, $getFirstChar(e)$

Require: axiom with a \sqcap has been retrieved and position of string is known

2: $e_2 \leftarrow getNextVocabularyElement(A)$ {retrieve element after the \sqcap }

3: **if** $e_2 \in \mathcal{R} \cup \mathcal{A}$ **then**

4: $RESULT \leftarrow \text{'kanye'}$ {verbalise \sqcap as kanye}

5: **else**

6: **if** $e_2 \in \mathcal{C}$ **then**

7: $c_1 \leftarrow getFirstChar(e_2)$ {retrieve first letter of e_2 }

8: **select case**

9: $c_1 = \text{'i'}$ **then**

10: $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$

11: $RESULT \leftarrow \text{'nee}_2^-$ {verbalise \sqcap with ne- prefix}

12: $c_1 = \text{'u'}$ **then**

13: $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$

14: $RESULT \leftarrow \text{'noe}_2^-$ {verbalise \sqcap with no- prefix}

15: $c_1 = \text{'a'}$ **then**

16: $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$

17: $RESULT \leftarrow \text{'nae}_2^-$ {verbalise \sqcap with na- prefix}

18: $c_1 \notin \{\text{'i'}, \text{'u'}, \text{'a'}\}$ **then**

19: $RESULT \leftarrow \text{'this is not a well-formed isiZulu noun'}$

20: **end select case**

21: **else**

22: $RESULT \leftarrow \text{'this is not a well-formed axiom'}$

23: **end if**

24: **end if**

25: **return** $RESULT$

Algorithm 2 Determine the verbalization of conjunction in an axiom

1: \mathcal{R} is the set of relationships, \mathcal{A} of attributes, \mathcal{C} of classes, and language \mathcal{L} uses \sqcap to denote conjunction; variables: e_2 , c_1 a letter, A axiom; functions: $getNextVocabularyElement(A)$, $getFirstChar(e_2)$

Require: axiom with a \sqcap has been retrieved and position of \sqcap is known

2: $e_2 \leftarrow getNextVocabularyElement(A)$ {retrieve element after the \sqcap }

3: **if** $e_2 \in \mathcal{R} \cup \mathcal{A}$ **then**

4: **RESULT** \leftarrow 'kanye' {verbalise \sqcap as kanye}

5: **else**

6: **if** $e_2 \in \mathcal{C}$ **then**

7: $c_1 \leftarrow getFirstChar(e_2)$ {retrieve first letter of e_2 }

8: **select case**

9: $c_1 = \text{'i'}$ **then**

10: $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$

11: **RESULT** \leftarrow 'nee $_2^-$ ' {verbalise \sqcap with ne- prefix}

12: $c_1 = \text{'u'}$ **then**

13: $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$

14: **RESULT** \leftarrow 'noe $_2^-$ ' {verbalise \sqcap with no- prefix}

15: $c_1 = \text{'a'}$ **then**

16: $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$

17: **RESULT** \leftarrow 'nae $_2^-$ ' {verbalise \sqcap with na- prefix}

18: $c_1 \notin \{\text{'i'}, \text{'u'}, \text{'a'}\}$ **then**

19: **RESULT** \leftarrow 'this is not a well-formed isiZulu noun'

20: **end select case**

21: **else**

22: **RESULT** \leftarrow 'this is not a well-formed axiom'

23: **end if**

24: **end if**

25: **return** **RESULT**

Algorithm 2 Determine the verbalization of conjunction in an axiom

1: \mathcal{R} is the set of relationships, \mathcal{A} of attributes, \mathcal{C} of classes, and language \mathcal{L} uses \sqcap to denote conjunction; variables: e_2 , c_1 a letter, A axiom; functions: $getNextVocabularyElement(A)$, $getFirstChar(e_2)$.

Require: axiom with a \sqcap has been retrieved and position in string is known

```

2:  $e_2 \leftarrow getNextVocabularyElement(A)$  {retrieve element after the  $\sqcap$ }
3: if  $e_2 \in \mathcal{R} \cup \mathcal{A}$  then
4:    $RESULT \leftarrow \text{'kanye'}$ 
5: else
6:   if  $e_2 \in \mathcal{C}$  then
7:      $c_1 \leftarrow getFirstChar(e_2)$  {retrieve first letter of  $e_2$ }
8:     select case
9:        $c_1 = \text{'i'}$  then
10:         $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$ 
11:         $RESULT \leftarrow \text{'nee}_2^-$  {verbalise  $\sqcap$  with ne- prefix}
12:        $c_1 = \text{'u'}$  then
13:         $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$ 
14:         $RESULT \leftarrow \text{'noe}_2^-$  {verbalise  $\sqcap$  with no- prefix}
15:        $c_1 = \text{'a'}$  then
16:         $e_2^- \leftarrow \text{drop } c_1 \text{ from } e_2$ 
17:         $RESULT \leftarrow \text{'nae}_2^-$  {verbalise  $\sqcap$  with na- prefix}
18:        $c_1 \notin \{\text{'i'}, \text{'u'}, \text{'a'}\}$  then
19:         $RESULT \leftarrow \text{'this is not a well-formed isiZulu noun'}$ 
20:       end select case
21:   else
22:      $RESULT \leftarrow \text{'this is not a well-formed axiom'}$ 
23:   end if
24: end if
25: return  $RESULT$ 

```

enumerative-and as kanye

Existential Quantification

- 'simple' option in front of the object property

(E1) Giraffe $\sqsubseteq \exists$ eats.Twig

zonke izindlulamithi zidla ihlamvana elilodwa

('all giraffes eat at least one twig')

- Some other examples, and breakdown:

noun	NC	RC	QC	QSuffix
<i>ihlamvana</i> ('twig')	class 5	<i>eli-</i>	<i>-lo-</i>	<i>-dwa</i>
<i>isifundo</i> ('module')	class 7	<i>esi-</i>	<i>-so-</i>	<i>-dwa</i>
<i>ushizi</i> ('cheese')	class 3a	<i>o-</i>	<i>-ye-</i>	<i>-dwa</i>

- Pattern: <All-concord for NC_x >onke <pl. N_1 , is in NC_x >
 <conjugated verb> < N_2 of NC_y > <RC for NC_y ><QC for NC_y >dwa.

NC	QC (all) QC _{oral+onke}	QC _{nke}	NEG SC	PRON	RC	QC _{dwa}	EC
1	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
1a	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2a	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3a	u-onke → wonke	wo-	aka-	wona	o-	ye-	mu-
(2a)	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3	u-onke → wonke	wo-	awu-	wona	o-	wo-	mu-
4	i-onke → yonke	yo-	ayi-	yona	e-	yo-	mi-
5	li-onke → lonke	lo-	ali-	lona	eli-	lo-	li-
6	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
7	si-onke → sonke	so-	asi-	sona	esi-	so-	si-
8	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
9a	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
(6)	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
9	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
10	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
11	lu-onke → lonke	lo-	alu-	lona	olu-	lo-	lu-
(10)	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
14	ba-onke → bonke	bo-	abu-	bona	obu-	bo-	bu-
15	ku-onke → konke	zo-	aku-	khona	oku-	zo-	ku-

NC	QC (all)		NEG SC	PRON	RC	QC _{dwa}	EC
	QC _{oral+onke}	QC _{nke}					
1	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
1a	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2a	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3a	u-onke → wonke	wo-	aka-	wona	o-	ye-	mu-
(2a)	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3	u-onke → wonke	wo-	awu-	wona	o-	wo-	mu-
4	i-onke → yonke	yo-	ayi-	yona	e-	yo-	mi-
5	li-onke → lonke	lo-	ali-	lona	eli-	lo-	li-
6	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
7	si-onke → sonke	so-	asi-	sona	esi-	so-	si-
8	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
9a	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
(6)	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
9	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
10	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
11	lu-onke → lonke	lo-	alu-	lona	olu-	lo-	lu-
(10)	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
14	ba-onke → bonke	bo-	abu-	bona	obu-	bo-	bu-
15	ku-onke → konke	zo-	aku-	khona	oku-	zo-	ku-

NC	QC (all)		NEG SC	PRON	RC	QC _{dwa}	EC
	QC _{oral+onke}	QC _{nke}					
1	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
1a	u-onke → wonke	wo-	aka-	yena	o-	ye-	mu-
2a	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3a	u-onke → wonke	wo-	aka-	wona	o-	ye-	mu-
(2a)	ba-onke → bonke	bo-	aba-	bona	aba-	bo-	ba-
3	u-onke → wonke	wo-	awu-	wona	o-	wo-	mu-
4	i-onke → yonke	yo-	ayi-	yona	e-	yo-	mi-
5	li-onke → lonke	lo-	ali-	lona	eli-	lo-	li-
6	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
7	si-onke → sonke	so-	asi-	sona	esi-	so-	si-
8	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
9a	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
(6)	a-onke → onke	o-	awa-	wona	a-	wo-	ma-
9	i-onke → yonke	yo-	ayi-	yona	e-	yo-	yi-
10	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
11	lu-onke → lonke	lo-	alu-	lona	olu-	lo-	lu-
(10)	zi-onke → zonke	zo-	azi-	zona	ezi-	zo-	zi-
14	ba-onke → bonke	bo-	abu-	bona	obu-	bo-	bu-
15	ku-onke → konke	zo-	aku-	khona	oku-	zo-	ku-

Algorithm 3 Determine the verbalization of existential quantification with object property (first, basic, version)

1: \mathcal{C} set of classes, language \mathcal{L} with \sqsubseteq for subsumption and \exists for existential quantification; variables: A axiom, NC_i noun class, $c_1, c_2 \in \mathcal{C}$, $o \in \mathcal{R}$, a_1 a term; r_2, q_2 concords; functions: $getFirstClass(A)$, $getSecondClass(A)$, $getNC(C)$, $pluralizeNoun(C, NC_i)$, $getRC(NC_i)$ $getQC(NC_i)$.

Require: axiom A with a \sqsubseteq and a \exists on the rhs of the inclusion has been retrieved

```

2:  $c_1 \leftarrow getFirstClass(A)$                                 {get subclass}
3:  $c_2 \leftarrow getSecondClass(A)$                             {get superclass}
4:  $o \leftarrow getObjProp(A)$                                   {get object property}
5:  $NC_1 \leftarrow getNC(c_1)$                                   {determine noun class by augment and prefix or dictionary}
6:  $NC_2 \leftarrow getNC(c_2)$                                   {determine noun class by augment and prefix or dictionary}
7:  $NC'_1 \leftarrow \text{lookup plural nounclass of } NC_1$           {from known list}
8:  $c'_1 \leftarrow pluralizeNoun(c_1, NC'_1)$ 
9:  $a_1 \leftarrow \text{lookup quantitative concord for } NC'_1$         {from quantitative concord (QC(all)) list}
10:  $o' \leftarrow AlgoConjugate(o, NC_1)$                        {call algorithm AlgoConjugate to conjugate  $o$ }
11:  $r_2 \leftarrow getRC(NC_2)$                                   {get relative concord for  $c_2$ }
12:  $q_2 \leftarrow getQC(NC_2)$                                 {get quantitative concord for  $c_2$  from the  $QC_{dwa}$ -list}
13:  $RESULT \leftarrow 'a_1 c'_1 o' c_2 r_2 q_2 \text{dwa.}'$           {verbalise the simple axiom}
14: return RESULT

```

Example

- $\forall x (\text{Professor}(x) \rightarrow \exists y (\text{teaches}(x, y) \wedge \text{Course}(y)))$
- $\text{Professor} \sqsubseteq \exists \text{ teaches. Course}$
- **Each Professor teaches at least one Course**
- $\forall x (\text{uSolwazi}(x) \rightarrow \exists y (\text{ufundisa}(x, y) \wedge \text{Isifundo}(y)))$
- $\text{uSolwazi} \sqsubseteq \exists \text{ ufundisa. Isifundo}$
- ?

Example

- $\forall x (\text{Professor}(x) \rightarrow \exists y (\text{teaches}(x, y) \wedge \text{Course}(y)))$
- $\text{Professor} \sqsubseteq \exists \text{ teaches. Course}$
- Each Professor teaches at least one Course
- $\forall x (\text{uSolwazi}(x) \rightarrow \exists y (\text{ufundisa}(x, y) \wedge \text{Isifundo}(y)))$
- $\text{uSolwazi} \sqsubseteq \exists \text{ ufundisa. Isifundo}$
- ?

$\forall x \text{ (uSolwazi}(x) \rightarrow \exists y \text{ (ufundisa}(x, y) \wedge \text{Isifundo}(y))))$

$\text{uSolwazi} \sqsubseteq \exists \text{ufundisa}.\text{Isifundo}$

$\forall x (u\text{Solwazi}(x) \rightarrow \text{NC}, \text{AU}, \text{PRE}), x, v) \wedge \text{Isifundo}(v))$
 $u\text{Solwazi} \sqsubseteq \exists u\text{fundo}$

look-up NC

pluralise

for-all

	NC	AU	PRE
1	u-	m(u)-	
2	a-	ba-	
1a	u-	-	
2a	o-	-	
3a	u-	-	
(2a)	o-	-	
3	u-	m(u)-	
4	i-	mi-	
5	i-	(li)-	
6	a-	ma-	
7	i-	si-	
8	i-	zi-	
9a	i-	-	
(6)	a-	ma-	
9	i(n)-	-	
10	i-	zi(n)-	
11	u-	(lu)-	
(10)	i-	zi(n)-	
14	u-	bu-	
15	u-	ku-	
17		ku-	

NC	QC (all)
	QC _{oral+onke}
1	u-onke → wonke
2	ba-onke → bonke
1a	u-onke → wonke
2a	ba-onke → bonke
3a	u-onke → wonke
(2a)	ba-onke → bonke
3	u-onke → wonke
4	i-onke → yonke
5	li-onke → lonke
6	a-onke → onke
7	si-onke → sonke
8	zi-onke → zonke
9a	i-onke → yonke
(6)	a-onke → onke
9	i-onke → yonke
10	zi-onke → zonke
11	lu-onke → lonke
(10)	zi-onke → zonke
14	ba-onke → bonke
15	ku-onke → konke

Bonke oSolwazi

$\forall x (uSolwazi(x) \rightarrow \exists y (ufundisa(x, y) \wedge Isifundo(y)))$

$uSolwazi \sqsubseteq \exists (ufundisa)!$... for relevant NC. Here:

AlgoConjugate

ngi-
u-
u-
si-
ni-
ba-



Bonke oSolwazi bafundisa

$\forall x (uSolwazi(x) \rightarrow \exists y (ufundisa(x, y) \wedge Isifundo(y)))$

$uSolwazi \sqsubseteq \exists ufundisa Isifundo$



Bonke oSolwazi bafundisa Isifundo

$$\forall x (u\text{Solwazi}(x) \rightarrow \exists y ((\text{NC } \text{AU } \text{PRE}) \wedge \text{RC } \text{QC}_{\text{dwa}})))$$

uSolwazi \nexists ufundisa.!

look-up NC

get RC

get QC

add -dwa

	NC	AU	PRE	RC	QC _{dwa}
1	u-	m(u)-			
2	a-	ba-		o-	ye-
1a	u-	-		aba-	bo-
2a	o-	-		o-	ye-
3a	u-	-		aba-	bo-
(2a)	o-	-		o-	ye-
3	u-	m(u)-		aba-	bo-
4	i-	mi-		o-	wo-
5	i-	(li)-		e-	yo-
6	a-	ma-		eli-	lo-
7	i-	si-		a-	wo-
8	i-	zi-		esi-	so-
9a	i-	-		ezi	zo-
(6)	a-	ma-		e-	yo-
9	i(n)-	-		a-	wo-
10	i-	zi(n)-		e-	yo-
11	u-	(lu)-		ezi-	zo-
(10)	i-	zi(n)-		olu-	lo-
14	u-	bu-		ezi-	zo-
15	u-	ku-		obu-	bo-
17		ku-		oku-	zo-

Bonke oSolwazi bafundisa Isifundo esisodwa

Discussion

- Template-based approach is not applicable to isiZulu (and, more generally: Bantu languages that have noun classes)
 - Or: grammar engine needed
- Devising the patterns hampered by outdated literature
- Several preferences for patterns
- Algorithms nontrivial; covering:
 - 'simple' existential and universal quantification
 - taxonomic subsumption
 - negation (class disjointness)
 - conjunction

Conclusions

- Verbalizing formally represented knowledge in isiZulu requires a grammar engine even for the relatively basic language constructs
- Due to, principally:
 - the system of noun classes,
 - the system of complex agreement,
 - phonological conditioned copulatives, and
 - verb conjugation

A few constructors, their typical verbalization in English, and the basic options in isiZulu

DL symbol	Sample verbalization English	Sample verbalization in isiZulu (see text for additional rules)
\sqsubseteq	... is a ...	Depends on what is on the rhs of \sqsubseteq and desideratum: A) semantic distinction i) yi/ongu/uyi/ngu (living thing) ii) iyi (non-living thing) B) syntactic distinction iii) ng (nouns commencing with a, o, or u) iv) y (nouns commencing with i)
\sqcap	... and ...	Depends on the use of the \sqcap : i) ... na/ne/no ... (list of things) ii) 1) ... futhi ... (connective) 2) ... kanye ... (connective)
\neg	not ...	angi/akusiso/akusona/akubona/akulona/asibona/akalona/akuyona
\exists	1) some ... 2) there exists ... 3) at least one ...	Depends on position in axiom: I. quantified over class, depends on meaning of class: i) kuno (living thing) ii) kune (non-living thing) II. includes relation (preposition issue omitted): 1) ... [concorde]dwa 2) ... noma [copulative + concord]phi ... 3) thize
\forall	1) for all ... 2) each ...	Depends on what it is quantified over: A) semantic distinction i) wonke/bonke/sonke/zonke (living thing) ii) onke/konke/lonke/yonke (non-living thing) B) another semantic distinction i) use noun class

Future work

- To be done for 'full' OWL 2 EL and \mathcal{ALC} , mainly:
 - Transitivity
 - More elaborate axioms, such as $\forall R.C \sqsubseteq \exists S.(D \sqcap E)$
 - Negation in other cases
 - Union
- Conjugation of verbs present and past tense, and the prepositions (*taught* by, works *for*)
- Implement it

References I



Ronell Alberts, Thomas Fogwill, and C. Maria Keet.

Several required OWL features for indigenous knowledge management systems.

In P. Klinov and M. Horridge, editors, *7th Workshop on OWL: Experiences and Directions (OWLED 2012)*, volume 849 of *CEUR-WS*, page 12p, 2012.
27-28 May, Heraklion, Crete, Greece.



M. Curland and T. Halpin.

Model driven development with NORMA.

In *Proceedings of the 40th International Conference on System Sciences (HICSS-40)*, pages 286a–286a. IEEE Computer Society, 2007.
Los Alamitos, Hawaii.



Norbert E. Fuchs, Kaarel Kaljurand, and Tobias Kuhn.

Discourse Representation Structures for ACE 6.6.

Technical Report ifi-2010.0010, Dept of Informatics, University of Zurich, Switzerland, 2010.



Mustafa Jarrar, C. Maria Keet, and Paolo Dongilli.

Multilingual verbalization of ORM conceptual models and axiomatized ontologies.

Starlab technical report, Vrije Universiteit Brussel, Belgium, February 2006.



Tobias Kuhn.

A principled approach to grammars for controlled natural languages and predictive editors.

Journal of Logic, Language and Information, 22(1):33–70, 2013.



R. Schwitter, K. Kaljurand, A. Cregan, C. Dolbear, and G. Hart.

A comparison of three controlled natural languages for OWL 1.1.

In *Proceedings of OWL: Experiences and Directions (OWLED'08 DC)*, 2008.
Washington, DC, USA metropolitan area, on 1-2 April 2008.

References II



Allan Third, Sandra Williams, and Richard Power.

OWL to English: a tool for generating organised easily-navigated hypertexts from ontologies.
poster/demo paper, 2011.

10th International Semantic Web Conference (ISWC'11), 23-27 Oct 2011, Bonn, Germany.

Thank you!