

# Optimized, Bottom-Up Semantic Web Reasoning based on OWL2 RL in Resource-Constrained Settings


**William Van Woensel**

# Context




- Clinical Practice Guidelines (CPG)
  - Disease-specific, evidence-based recommendations
  - Standard for decision making on diagnosis, prognosis and treatment
- a) Context-sensitive care recommendations
- b) Clinical workflow of relevant clinical activities


Algorithm for diagnosis of heart failure [1]



Pre-treatment assessment and correction of electrolytes [1]



ACEI upitration [1]



## Context (2)

### 1) Clinical Decision Support Systems (CDSS)

- Automated systems that incorporate computerized CPG
- Pro-actively guide physician through decision processes

➤ *Decision Logic (OWL2 DL), IF-THEN (SWRL) rules, ..*


#### Switch [2, 3]:

$SatisfiedCondition \cap \exists conditionOf. ActiveTask \cap \exists leadsTo. InactiveTask \cap \forall lessPriorityThan. UnsatisfiedCondition \subset ChosenCondition$

$UnsatisfiedCondition \cap \exists conditionOf. ActiveTask \cap \exists leadsTo. InactiveTask \subset DiscardedCondition$

$SatisfiedCondition \cap \exists conditionOf. ActiveTask \cap \exists leadsTo. InactiveTask \cap lessPriorityThan. SatisfiedCondition \subset DiscardedCondition$



...



# Context (2)




- 1) Clinical Decision Support Systems (CDSS)
  - Automated systems that incorporate computerized CPG
  - Pro-actively guide physician through decision processes
- 2) Involve patients in their own long-term care
  - Canadian Community Health Survey (2014):
    - Chronic illnesses affect ca. 40% of Canadians
    - With multi-morbidity of ca. 15%
  - Increase self-sufficiency and quality of life
  - Reduce healthcare costs
- Mobile patient diaries
  - IMPACT-AF project
  - Self-collect health data at any time and place
    - Using Bluetooth measurement devices (e.g., IBGStar, OneTouch, Withings, iHealth)
  - ✓ Increase mobility of chronic patients
  - ✓ Up-to-date health profile
  - ✓ No delays in supplying health-critical info



# Context (3)



- Requirements:
  - Connectivity
    - Cope with short/long-term disconnections (lack of WiFi, 3G)
    - Should not limit mobile patient diary usage
  - Response latency
    - Slow / lacking connectivity may occur frequently
    - Server = *single point of failure*
- Solutions:
  - Offline data entry (*BP, HR, ..*)
    - Synchronize with online EMR when connectivity is restored
  - **Local Clinical Decision Support System**
    - ✓ Independent of connectivity
    - ✓ Enables timely health alerts
  - **Distributed setup**
    - **Local:** lightweight, time-sensitive reasoning is deployed locally
    - **Remote:** heavyweight processes are delegated to the server



# Context (4)



- Ontology-based (OWL) reasoning
  - **OWL2 DL**: too resource-intensive on mobile systems
  - Recent empirical work by Bobed et al. [4]:
    - PC outperforms Android by **1,5 – 150**
    - Larger number of out-of-memory errors
  - Most mobile approaches are rule-based
    - E.g., OWL2 RL or custom entailment
- **OWL2 RL**
  - Suitable W3C OWL2 profile
    - Allows scalable reasoning without sacrificing too much expressivity
  - Adjust reasoning complexity to suit scenario & resources
    - Choose rule subsets based on task & overhead
  - Enhance any rule-based task with semantic features
    - I.e., include OWL2 RL (subset) into ruleset
    - Such as **computerized, rule-based CPG** in CDSS

# 1) Optimizing the OWL2 RL ruleset

## Multi-stage OWL2 RL ruleset selection

- Stable vs. volatile ontology
- Conformant

### 1) Equivalent OWL2 RL ruleset

- Removing logically equivalent rules
- Replace 2+ specific rules with more general rules & axioms
- Removing “stand-alone” schema inference rules

### 2) Purpose- and reference-based subsets

- Purpose*: inferencing vs. validation
- Reference*: instances vs. schema

### 3) Remove inefficient rules

- Leave out rules with large performance impact
  - E.g., *#eq-ref* infers each resource is equivalent to itself

### 4) Domain-based ruleset selection

- I.e., leave out rules not needed by ontology & dataset
- Forward-chaining algorithm (Tai et al. [8])

Non-conformant

Stable

# 1) Optimizing the OWL2 RL ruleset: Evaluation



OWL2 RL*					
AndroJena	original	2819 (88   2731)			
		volatile ontology	stable ontology		
	conformant	full	inf-schema	inf-inst	consist
		2639 (90   2549) + <u>entailed</u>	1001 (69   932)	1245 (187   1058) + <u>entailed</u> , <u>domain-based</u>	418 (195   223)
	non-conformant	full	inf-schema	inf-inst	
		1547 (93   1455) + <u>entailed</u> , <u>ineff</u>	919 (65   854) <u>inst-ent</u>	272 (165   106) + <u>entailed</u> , <u>domain-based</u> , <u>ineff</u> , <u>inst-ent</u>	

\* : [total-time] ([load-time] | [reason-time] ; applied selections are shown, if any.

\*\* : total-time

OWL2 DL**	
Hermit	21111
Pellet	6978
JFact	7034




# 1) Optimizing the OWL2 RL ruleset: Future work

- Rule instantiation [7, 9, 10]
  - 1) Materialize schema inferences in ontology
  - 2) Instantiate each *instance rule* with schema terms
    - Increase rule selectivity
    - Reduce # of joins
  - Requires a “stable” ontology
- Domain-specific rulesets
  - Large impact on performance
  - Currently, does not support “volatile” ontologies
    - Ruleset needs to be re-calculated on ontology changes
    - Avg. ca. 291ms (PC), 4183ms (mobile)
  - Deploy on mobile device, integrate with reasoner?

## 2) RETE Strategies for Resource-Constrained Settings



- RETE Algorithm
  - Well-known solution to implement production rule systems
  - **Rule premise** = *alpha node*
    - *Alpha memory*: keeps matched facts
  - **Join** = *beta node*
    - *Beta memory*: keeps join results
  - Useful in dynamic environments, due to its incremental nature
- Known for trading *memory* for *performance*
  - 1) *Alpha memories* will overlap depending on premise selectivity
  - 2) Many SW applications already involve an RDF store for query access
    - Collection of alpha memories **duplicate** RDF store
- Many rules will not be needed for domain
  - But, still consume computing & memory resources in RETE
  - Tailor RETE networks during execution
    - In light of dynamic & incremental situations



## 2) RETE Strategies for Resource-Constrained Settings (2)




- *Dataset-mask* memory strategy
  - Keep alpha memories as *masks* on the RDF store
  - Query RDF store using *joining token & rule premise* as constraint
  - **Hybrid version:** *dataset-mask* vs. regular memory, based on premise selectivity
- Dynamic tailoring of RETE networks
  - 1) *Avoid redundant join attempts* [11]
    - Unlink alpha memory from its beta node in case join attempts are useless
  - 2) *Avoid redundant token matches*
    - Pause alpha nodes in case they are unlinked from each rule
    - Requires separate RDF store for synchronizing alpha memory upon *resume*
  - **Join-utility heuristics**
    - Determine utility of join attempts
  - 1) *Empty sibling memory*
    - In case alpha ( $i \leq 2$ ) or beta ( $i > 2$ ) memory is empty, no joins are possible [10]
  - 2) *Lower failed alpha nodes*
    - Pointless to attempt joins in case a failed alpha node occurs lower down

# Dynamic tailoring of RETE networks



## Responsiveness to Incremental Reasoning Scenarios



# Dataset-mask: Evaluation (1)



strategy*	memory usage		reasoning performance (ms) <sup>†</sup> (P.3)	
	# $\alpha$ memories** (M.1)	$\alpha$ contents <sup>†</sup> (M.2)	PC	mobile
<i>regular-memory</i>	<b>r</b> : 46, <b>d</b> : 0	95342 (2900 - 747114)	15705 (18 - 322352)	24968 (1051 - 199974)
<i>dataset-mask</i>	<b>r</b> : 0, <b>d</b> : 46	46 (46 - 46)	51905 (51 - 1187570)	69573 (2903-542670)
<i>hybrid-0.1,0.25</i>	<b>r</b> : 42, <b>d</b> : 4	6224 (279 - 50827)	16303 (27 - 340194)	29287 (1526 - 212573)
<i>hybrid-0.5</i>	<b>r</b> : 43, <b>d</b> : 3	18885 (1115 - 188153)	16475 (23 - 338109)	26444 (1145 - 202646)
<i>hybrid-0.75,1</i>	<b>r</b> : 44, <b>d</b> : 2	43090 (1248 - 335444)	17715 (25 - 365843)	25203 (1115 - 198404)

**Table 1.** Benchmark results for RETE alpha memory strategies

\*: hybrid-[x]: **x** represents the utilized threshold (Section 4.2)

\*\*: **r** = regular memories, **d** = dataset-masks

<sup>†</sup>: showing averages, with min-max in parenthesis

## Dataset-mask: Evaluation (2)



### What if SW scenario does not include an RDF store?

- Introduce RDF store as *shared alpha memory pool*
- Updated memory reductions:
  - *Dataset-mask*: avg. ca. -55%
  - *Hybrid-0.1,0.25*: avg. ca. -27%
  - *Hybrid-0.5*: avg. ca. -9%
  - *Hybrid-0.75,1*: avg. ca. +1%
- RDF store update operations:
  - *PC*: avg. ca. +0,67s
  - *Mobile*: avg. ca. +1s

# Dynamic RETE tailoring: Evaluation



tailoring			reverting		
<i>queue-unlink</i>		<i>node-pause</i>	<i>queue-relink</i>		<i>node-resume</i>
#	<i>heuristic</i>		#	<i>heuristic</i>	
2625	(1)	44	14	(1)	2
24	(1), (2)				

**Table 4.** Dynamic tailoring statistics (T.2) (total number of tailoring operations) (PC)

config	RETE operation statistics (T.1)		reasoning times (ms)*			complete (T.4)
	# token matches	# join attempts	<i>preproc</i> (T.3)	<i>initial dataset</i> (P.3)	<i>incremental</i> (P.4)	
<i>default</i>	218038	2062420	n/a	pc: 825 mo: 2070	pc: 14065 mo: 23573	✓
<i>dynamic tailoring</i>	181687	657075			pc: 13989 mo: 20682	✓
<i>a priori tailoring</i>	132831	279997	pc: 291 mo: 4183	pc: 808 mo: 1529	pc: 13893 mo: 19356	X (- 11448)

**Table 5.** Comparison of three configurations for incremental reasoning.

\*: **pc** = PC performance, **mo** = mobile performance

## 2) RETE Strategies for Resource-Constrained Settings: Future work (in progress)





- Currently: mostly based on OWL2 RL ruleset in clinical decision support
  - Also, benchmarks done using OWL2 RL ruleset
  - Additional benchmarks needed for other rulesets
- More advanced heuristics to determine join utility
  - Eager vs. lazy algorithm
- More fine-grained memory strategy
  - Alpha memories will often subsume other memories
  - E.g., subsumed (virtual) alpha memories access their subsuming, concrete alpha memory behind-the-scenes (comparable to *dataset-mask* but with a smaller query access overhead)
- Dynamic *hybrid* memory strategies
  - Switch between regular and *dataset-mask* memories based on evolving selectivities



## 2) RETE Strategies for Resource-Constrained Settings: Future work (in progress) (2)





- Virtual materialization of OWL2 semantics in match & join operations
  - Consider OWL2 semantics when matching & joining tokens
  - Avoid explicit materialization, which takes up memory



## 2) RETE Strategies for Resource-Constrained Settings: Future work (in progress) (2)




- Virtual materialization of OWL2 semantics in match & join operations
  - Consider OWL2 semantics when matching & joining tokens
  - Avoid explicit materialization, which takes up memory



## 2) RETE Strategies for Resource-Constrained Settings: Future work (in progress) (2)



- Virtual materialization of OWL2 semantics in match & join operations
  - Consider OWL2 semantics when matching & joining tokens
  - Avoid explicit materialization, which takes up memory



**PropertyX** type *SymmetricProperty*

# Questions?



- E-mail: [william.van.woensel@gmail.com](mailto:william.van.woensel@gmail.com)

# References



- [1] S. Abidi. PhD Thesis, 2010.
- [2] B. Jafarpour. PhD Thesis, 2010.
- [3] B. Jafarpour, S. S. R. Abidi, S. R. Abidi. **Exploiting Semantic Web Technologies to Develop OWL-Based Clinical Practice Guideline Execution Engines.** *IEEE J. Biomed. Heal. Informatics*, 2014.
- [4] C. Bobed, R. Yus, F. Bobillo, E. Mena. **Semantic reasoning on mobile devices: Do androids dream of efficient reasoners?** *Web Semantics: Science, Services and Agents on the World Wide Web*, 35:167–183, December 2015.
- [5] S. Ali and S. Kiefer. **“microOR --- A Micro OWL DL Reasoner for Ambient Intelligent Devices.** In *Proceedings of the 4th International Conference on Advances in Grid and Pervasive Computing*, 2009, pp. 305–316.
- [6] T. Kim, I. Park, S. J. Hyun, D. Lee. **MiRE4OWL: Mobile Rule Engine for OWL.** In *Proceedings of the 2010 IEEE 34th Annual Computer Software and Applications Conference Workshops*, 2010, pp. 317–322.
- [7] B. Motik, I. Horrocks, S. M. Kim. **Delta-reasoner: A Semantic Web Reasoner for an Intelligent Mobile Platform.** In *Proceedings of the 21st International Conference Companion on World Wide Web*, 2012, pp. 63–72.
- [8] W. Tai, J. Keeney, D. O’Sullivan. **Resource-constrained reasoning using a reasoner composition approach.** *Semant. Web*, vol. 6 (1), pp. 35–59, 2015
- [9] J. Bak, M. Nowak, C. Jedrzejek. **RuQAR: Reasoning Framework for OWL 2 RL Ontologies.** In *The Semantic Web: ESWC 2014 Satellite Events, Anissaras, Crete, Greece, May 25-29, 2014*, 2014, vol. 8798, pp. 195–198.
- [10] G. Meditskos N. Bassiliades. **DLEJena: A Practical Forward-chaining OWL 2 RL Reasoner Combining Jena and Pellet.** *Web Semant.*, vol. 8, no. 1, pp. 89–94, Mar. 2010.
- [11] R.B. Doorenbos. **Combining Left and Right Unlinking for Matching a Large Number of Learned Rules.** In Hayes-Roth, B. and Korf, R.E. (eds.) *Proceedings of the 12th National Conference on Artificial Intelligence*, Seattle, WA, USA, July 31 - August 4, 1994, Volume 1. pp. 451–458.