



**Leo-III**

# The World's Most Widely Applicable Modal Logic Theorem Prover and its Associated Infrastructure

Alexander Steen  
Freie Universität Berlin

RuleML Webinar September 29th



1. Motivation
2. Flavours of modal logics
3. How it works (roughly)
4. Evaluation

## Reasoning in Non-Classical Logics

- ▶ Increasing interest in various fields
  - ▶ Artificial Intelligence (e.g. Agents, Knowledge)
  - ▶ Computer Linguistics (e.g. Semantics)
  - ▶ Mathematics (e.g. Geometry, Category theory)
  - ▶ Theoretical Philosophy (e.g. Metaphysics)
  - ▶ Legal Informatics (e.g. Computable/Smart contracts)
- ▶ Most powerful ATP/ITP: Classical logic only

Focus here: Modal logics

- ▶ Prover for (propositional) modal logics exist
  - ▶ ModLeanTAP, Molle, Bliksem, FaCT++,
  - ▶ MOLTAP, KtSeqC, STeP, TRP
  - ▶ ...
- ▶ Only few for quantified variants
  - ▶ MleanTAP, MleanCoP, MleanSeP (J. Otten)
  - ▶ f2p+MSPASS

## Reasoning in Non-Classical Logics

- ▶ Increasing interest in various fields
  - ▶ Artificial Intelligence (e.g. **Agents, Knowledge**)
  - ▶ Computer Linguistics (e.g. **Semantics**)
  - ▶ Mathematics (e.g. Geometry, Category theory)
  - ▶ Theoretical Philosophy (e.g. **Metaphysics**)
  - ▶ Legal Informatics (e.g. Computable/Smart contracts)
- ▶ Most powerful ATP/ITP: Classical logic only

## Focus here: Modal logics

- ▶ Prover for (propositional) modal logics exist
  - ▶ ModLeanTAP, Molle, Bliksem, FaCT++,
  - ▶ MOLTAP, KtSeqC, STeP, TRP
  - ▶ ...
- ▶ Only few for quantified variants
  - ▶ MleanTAP, MleanCoP, MleanSeP (J. Otten)
  - ▶ f2p+MSPASS

- ▶ Increasing interest in various fields
  - ▶ Artificial Intelligence (e.g. Agents, Knowledge)
  - ▶ Computer Linguistics (e.g. Semantics)
  - ▶ Mathematics (e.g. Geometry, Category theory)
  - ▶ Theoretical Philosophy (e.g. Metaphysics)
  - ▶ Legal Informatics (e.g. Computable/Smart contracts)
- ▶ Most powerful ATP/ITP: Classical logic only

- ▶ Prover for (propositional) modal logics exist
  - ▶ ModLeanTAP, Molle, Bliksem, FaCT++,
  - ▶ MOLTAP, KtSeqC, STeP, TRP
  - ▶ ...
- ▶ Only few for quantified variants
  - ▶ MleanTAP, MleanCoP, MleanSeP (J. Otten)
  - ▶ f2p+MSPASS

## Motivation

1. **First-order quantification is (sometimes) not enough**
2. Semantic diversity/flexibility needed




See studies in Metaphysics, e.g.

- Gödel's Ontological Argument [BenzmüllerW.-Paleo,2017] and several variants of it
- Anderson-Hájek Controversy [Benzm.WeberW.-Paleo,2017]

## Motivation

1. First-order quantification is (sometimes) not enough
2. **Semantic diversity/flexibility needed:**

Properties of modal operators *necessary* ( $\Box$ ) and *possibly* ( $\Diamond$ )



**... but that's not all of it!**


# Automation of Quantified Modal Logic

## Motivation

1. First-order quantification is (sometimes) not enough
2. Semantic diversity/flexibility needed

## Automation approach

- ▶ Indirect: Via encoding into (classical) HOL
- ▶ Use existing general purpose HOL reasoners





# Automation of Quantified Modal Logic

## Motivation

1. First-order quantification is (sometimes) not enough
2. Semantic diversity/flexibility needed

## Automation approach

- ▶ Indirect: Via encoding into (classical) HOL
- ▶ Use existing general purpose HOL reasoners

## Advantages

- ▶ Sophisticated existing systems
  - ▶ ATPs: TPS, agsyHOL, Satallax, LEO-II, Leo-III
  - ▶ Further: Isabelle, Nitpick
- ▶ Not fixed to any one proving system
- ▶ Semantic variations with minor adjustments
  - ▶ Axiomatization
  - ▶ Quantification semantics
  - ▶ ...

- ▶ **Simple types**  $\mathcal{T}$  generated by **base types** and mappings ( $\rightarrow$ )
- ▶ Usually, base types are  $o$  and  $l$

# Higher Order Modal Logic – Syntax

Based on Simple type theory [Church, J.Symb.L., 1940]  
augmented with modalities

- ▶ Simple types  $\mathcal{T}$  generated by base types and mappings ( $\rightarrow$ )
- ▶ Usually, base types are  $o$  and  $t$

Type of truth-values




# Higher Order Modal Logic – Syntax

Based on Simple type theory [Church, J.Symb.L., 1940]  
augmented with modalities

- ▶ Simple types  $\mathcal{T}$  generated by base types and mappings ( $\rightarrow$ )
- ▶ Usually, base types are  $o$  and  $i$

Type of individuals



# Higher Order Modal Logic – Syntax

Based on Simple type theory [Church, J.Symb.L., 1940]  
augmented with modalities

- ▶ Simple types  $\mathcal{T}$  generated by base types and mappings ( $\rightarrow$ )
- ▶ Usually, base types are  $o$  and  $i$
- ▶ Terms defined by  $(\alpha, \beta \in \mathcal{T}, c_\alpha \in \Sigma, X_\alpha \in \mathcal{V}, i \in I)$

$$s, t ::= c_\alpha \mid X_\alpha$$

- ▶ Allow infix notation for binary logical connectives
- ▶ Remaining logical connectives can be defined as usual
- ▶ Formulae of HOML are those terms with type  $o$

# Higher Order Modal Logic – Syntax

Based on Simple type theory [Church, J.Symb.L., 1940]  
augmented with modalities

- ▶ **Simple types**  $\mathcal{T}$  generated by **base types** and mappings ( $\rightarrow$ )
- ▶ Usually, base types are  $\circ$  and  $\iota$

- ▶ **Terms** defined by  $(\alpha, \beta \in \mathcal{T}, c_\alpha \in \Sigma, X_\alpha \in \mathcal{V}, i \in I)$

$$s, t ::= c_\alpha \mid X_\alpha \\ \mid (\lambda X_\alpha. s)_\alpha \rightarrow \beta \mid (s)_{\alpha \rightarrow \beta} t_\alpha)_\beta$$

- ▶ Allow infix notation for binary logical connectives
- ▶ Remaining logical connectives can be defined as usual
- ▶ Formulae of HOML are those terms with type  $\circ$

# Higher Order Modal Logic – Syntax

Based on Simple type theory [Church, J.Symb.L., 1940]  
augmented with modalities

- ▶ **Simple types**  $\mathcal{T}$  generated by **base types** and mappings ( $\rightarrow$ )
- ▶ Usually, base types are  $o$  and  $i$

- ▶ **Terms** defined by  $(\alpha, \beta \in \mathcal{T}, c_\alpha \in \Sigma, X_\alpha \in \mathcal{V}, i \in I)$

$$\begin{aligned} s, t ::= & c_\alpha \mid X_\alpha \\ & \mid (\lambda X_\alpha. s)_\alpha \mid (s \rightarrow_\beta t)_\beta \\ & \mid (\Box_{o \rightarrow o}^i s)_o \end{aligned}$$

- ▶ Allow infix notation for binary logical connectives
- ▶ Remaining logical connectives can be defined as usual
- ▶ Formulae of HOML are those terms with type  $o$

- ▶ Simple types  $\mathcal{T}$  generated by base types and mappings ( $\rightarrow$ )
- ▶ Usually, base types are  $o$  and  $l$

$$\begin{aligned} s, t &::= c_\alpha \mid X_\alpha \\ &\mid (\lambda X_\alpha. s_\beta)_{\alpha \rightarrow \beta} \mid (s_{\alpha \rightarrow \beta} t_\alpha)_\beta \\ &\mid (\Box_{o \rightarrow o}^i s_o)_o \end{aligned}$$

- ▶ Allow infix notation for binary logical connectives
- ▶ Remaining logical connectives can be defined as usual
- ▶ Formulae of HOML are those terms with type  $\circ$



# Higher Order Modal Logic – Syntax

Based on Simple type theory [Church, J.Symb.L., 1940]  
augmented with modalities

- ▶ **Simple types**  $\mathcal{T}$  generated by **base types** and mappings ( $\rightarrow$ )
- ▶ Usually, base types are  $o$  and  $i$

- ▶ **Terms** defined by  $(\alpha, \beta \in \mathcal{T}, c_\alpha \in \Sigma, X_\alpha \in \mathcal{V}, i \in I)$


$$\begin{aligned} s, t ::= & c_\alpha \mid X_\alpha \\ & \mid (\lambda X_\alpha. s_\beta)_{\alpha \rightarrow \beta} \mid (s_{\alpha \rightarrow \beta} t_\alpha)_\beta \\ & \mid (\Box_{o \rightarrow o}^i s_o)_o \end{aligned}$$

- ▶ Allow infix notation for binary logical connectives
- ▶ Remaining logical connectives can be defined as usual
- ▶ Formulae of HOML are those terms with type  $o$

## Higher Order Modal Logic – Semantics

Extend HOL models with Kripke structures

$$\mathcal{M} = (W, \{R^i\}_{i \in I}, \{\mathcal{D}_w\}_{w \in W}, \{\mathcal{I}_w\}_{w \in W})$$




## Higher Order Modal Logic – Semantics

Extend HOL models with Kripke structures

$$\mathcal{M} = (W, \{R^i\}_{i \in I}, \{\mathcal{D}_w\}_{w \in W}, \{\mathcal{I}_w\}_{w \in W})$$



Set of possible worlds




## Higher Order Modal Logic – Semantics

Extend HOL models with Kripke structures

$$\mathcal{M} = (W, \{R^i\}_{i \in I}, \{\mathcal{D}_w\}_{w \in W}, \{\mathcal{I}_w\}_{w \in W})$$




Family of accessibility relations  $R^i \subseteq W \times W$



## Higher Order Modal Logic – Semantics

Extend HOL models with Kripke structures

$$\mathcal{M} = (W, \{R^i\}_{i \in I}, \{\mathcal{D}_w\}_{w \in W}, \{\mathcal{I}_w\}_{w \in W})$$




Family of frames, one for every world  
Notion of frames  $\mathcal{D} = (D_\tau)_{\tau \in \mathcal{T}}$  as in HOL:

$$D_i \neq \emptyset$$

$$D_o = \{T, F\}$$


$$D_{\tau \rightarrow \nu} = D_\nu^{D_\tau}$$



## Higher Order Modal Logic – Semantics

Extend HOL models with Kripke structures


$$\mathcal{M} = (W, \{R^i\}_{i \in I}, \{\mathcal{D}_w\}_{w \in W}, \{\mathcal{I}_w\}_{w \in W})$$



Family of interpretation functions  $\mathcal{I}_w$

$$c_\tau \xrightarrow{\mathcal{I}_w} d \in D_\tau \in \mathcal{D}_w$$

Assume  $\mathcal{I}_w(\neg), \mathcal{I}_w(\vee) \dots$  is standard.



## Higher Order Modal Logic – Semantics

Extend HOL models with Kripke structures

$$\mathcal{M} = (W, \{R^i\}_{i \in I}, \{\mathcal{D}_w\}_{w \in W}, \{\mathcal{I}_w\}_{w \in W})$$


Value of a term (wrt. var. assignment  $g$ ):

$$\|X_\tau\|^{\mathcal{M}, g, w} = g_w(X)$$

$\vdots$  (not all shown here ...)

$$\|\Box_{o \rightarrow o}^i s_o\|^{\mathcal{M}, g, w} = \begin{cases} T & \text{if } \|s_o\|^{\mathcal{M}, g, v} = T \text{ for all } v \in W \text{ s.t. } (w, v) \in R^i \\ F & \text{otherwise} \end{cases}$$

Assume Henkin semantics



# Semantic variants of HOML

1. **Axiomatization of  $\Box^i$**
2. **Quantification**
3. **Rigidity**
4. **Consequence**







- What properties does the box operators have?

- ▶ What is the meaning of  $\forall$ ?

- Do all constants  $c \in \Sigma$  denote the same object at every world?

- ▶ Several popular choices exist

(1) Flexible constants: As introduced (unrestricted  $\mathcal{I}_w$ )

(2) Rigid constants:  $\mathcal{I}_W(c) = \mathcal{I}_V(c)$

for all worlds  $w, v \in W$  and all  $c \in \Sigma$

## 4. Consequence

# Semantic variants of HOML

## 1. Axiomatization of $\Box^i$

- ▶ What properties does the box operators have?

## 2. Quantification

- ▶ What is the meaning of  $\forall$ ?

## 3. Rigidity

- ▶ Do all constants  $c \in \Sigma$  denote the same object at every world?

## 4. Consequence

- ▶ What is an appropriate notion of logical consequence  $\models^{\text{HOML}}$ ?
- ▶ Many choices exist, two of them are
  - (1) Local consequence: ... *not displayed here* ...
  - (2) Global consequence: ... *not displayed here* ...

# Semantic variants of HOML

## 1. Axiomatization of $\Box^i$

- ▶ What properties does the box operators have?

## 2. Quantification

- ▶ What is the meaning of  $\forall$ ?

## 3. Rigidity

- ▶ Do all constants  $c \in \Sigma$  denote the same object at every world?

## 4. Consequence

- ▶ What is an appropriate notion of logical consequence  $\models^{\text{HOML}}$ ?

→ at least  $10 \times 4 \times 2 \times 2 = 160$  distinct logics

- What properties does the box operators have?

- ▶ What is the meaning of  $\forall$ ?

- Do all constants  $c \in \Sigma$  denote the same object at every world?

- ▶ What is an appropriate notion of logical consequence  $\models^{\text{HOML}}$ ?

Generated by **5**:  $\diamond^i s \supset \Box^i \diamond^i s$

$$S \supset \square^i \Diamond^i S,$$
$$\square^i S \supset S,$$
$$\forall X. \Box^i f X \supset \Box^i \forall X. f X$$

(symmetric  $r^i$ )

(reflexive  $r^i$ )

(Barcan formula)

HOL (meta-logic):  $s, t ::=$  [redacted]  
HOML (target logic):  $s, t ::=$  [redacted]

HOL (meta-logic):	$s, t ::=$	
HOML (target logic):	$s, t ::=$	

(1) Introduce new type  $\mu$  for worlds

(2) Introduce new constants  $r_{\mu \rightarrow \mu \rightarrow 0}^i$  for each  $i \in I$



HOL (meta-logic):	$s, t ::=$	
HOML (target logic):	$s, t ::=$	

(1) Introduce new type  $\mu$  for worlds


(2) Introduce new constants  $r_{\mu \rightarrow \mu \rightarrow 0}^i$  for each  $i \in I$

$$\begin{aligned} \neg_{o \rightarrow o} &= \text{blue bar} \\ \vee_{o \rightarrow o \rightarrow o} &= \text{blue bar} \\ \prod_{(\tau \rightarrow o) \rightarrow o}^{\tau} &= \text{blue bar} \\ \square_{o \rightarrow o} &= \text{blue bar} \end{aligned}$$

valid = [ ]

## Stand-alone tool

### Embedding procedure implemented as stand-alone tool



- ▶ Semantic specification is analyzed first
- ▶ (Meta-)logical notions are included as axioms/definitions
- ▶ Output format: "Plain THF" (TH0)
- ▶ Integrated as pre-processor into Leo-III

## Evaluation setting:

- ▶ Translated all 580 mono-modal QMLTP problems to modal THF
- ▶ Semantic setting:
  1. Modal operator axiom system  $\in \{K, D, T, S4, S5\}$
  2. Quantification semantics  $\in \{\text{constant, varying, cumul., decreasing}\}$
  3. Rigid constants
  4. Consequence  $\in \{\text{local, global}\}$
- ▶ Native modal logic prover: MleanCoP (J. Otten)
- ▶ HOL reasoners: Satallax, LEO-II, Nitpick
- ▶ Timeout 60s (2x AMD Opteron 2376 Quad Core/16 GB RAM)

## Comments on evaluation result:


- ▶ MleanCoP not applicable to modal logic K
- ▶ MleanCoP not applicable to decreasing domains semantics
- ▶ MleanCoP not applicable to problems with equality symbol
- ▶ MleanCoP not applicable for global consequence
- ▶ Only first-order modal logic problems
- ▶ Embedding approach **not restricted** to benchmark settings


## Evaluation setting:

- ▶ Translated all 580 mono-modal QMLTP problems to modal THF
- ▶ Semantic setting:
  1. Modal operator axiom system  $\in \{K, D, T, S4, S5\}$
  2. Quantification semantics  $\in \{\text{constant, varying, cumul., decreasing}\}$
  3. Rigid constants
  4. Consequence  $\in \{\text{local, global}\}$
- ▶ Native modal logic prover: MleanCoP (J. Otten)
- ▶ HOL reasoners: Satallax, LEO-II, Nitpick
- ▶ Timeout 60s (2x AMD Opteron 2376 Quad Core/16 GB RAM)

## Comments on evaluation result:

- ▶ MleanCoP not applicable to modal logic K
- ▶ MleanCoP not applicable to decreasing domains semantics
- ▶ MleanCoP not applicable to problems with equality symbol
- ▶ MleanCoP not applicable for global consequence
- ▶ Only first-order modal logic problems
- ▶ Embedding approach **not restricted** to benchmark settings

**Result excerpt: Theorems**

**Result excerpt: Counter satisfiable (CSA)**

## The penultimate slide

### Related work

- ▶ Generic theorem proving systems:  
The Logics Workbench, MetTeL2, LoTREC
- ▶ Embedding of further logics:  
Conditional logics, hybrid logics, many-valued logics, free logic, ...

### Conclusion

- ▶ Provided a quite general semantics for HOML
- ▶ Presented a procedure that automatically converts HOML into HOL
- ▶ Implemented a stand-alone tool (e.g. as preprocessor)
  - ▶ standard HOL provers can be used to reason about problems encoded in the modal THF syntax
- ▶ Approach feasible (no evaluation for higher-order problems yet)
- ▶ Many new problems contributed in the modal THF format

# The penultimate slide

## Related work

- ▶ Generic theorem proving systems:  
The Logics Workbench, MetTeL2, LoTREC
- ▶ Embedding of further logics:  
Conditional logics, hybrid logics, many-valued logics, free logic, ...

## Conclusion

- ▶ Provided a quite general semantics for HOML
- ▶ Presented a procedure that automatically converts HOML into HOL
- ▶ Implemented a stand-alone tool (e.g. as preprocessor)
  - ▶ standard HOL provers can be used to reason about problems encoded in the modal THF syntax
- ▶ Approach feasible (no evaluation for higher-order problems yet)
- ▶ Many new problems contributed in the modal THF format





**Thank you for your attention!**



# Embedding of HOML within HOL

**Automation approach:** Encode HOML semantics within (classical) HOL

HOL (meta-logic):  $s, t ::=$    
 HOML (target logic):  $s, t ::=$  









## Embedding of in

(1) Introduce new type  $\mu$  for worlds


HOML formulas  $s_o$  are mapped to HOL predicates  $s_{\mu \rightarrow o}$

(2) Introduce new constants  $r_{\mu \rightarrow \mu \rightarrow o}^i$  for each  $i \in I$

(3) Connectives:



 =   
 =   
 =   
 = 

(4) Meta-logical notions:

 = 

# Embedding of HOML within HOL

**Automation approach:** Encode HOML semantics within (classical) HOL

HOL (meta-logic):  $s, t ::=$    
 HOML (target logic):  $s, t ::=$  









## Embedding of in

(1) Introduce new type  $\mu$  for worlds


HOML formulas  $s_o$  are mapped to HOL predicates  $s_{\mu \rightarrow o}$

(2) Introduce new constants  $r_{\mu \rightarrow \mu \rightarrow o}^i$  for each  $i \in I$

(3) Connectives:



 =   
 =   
 =   
 = 

(4) Meta-logical notions:

 = 

# Embedding of HOML within HOL

**Automation approach:** Encode HOML semantics within (classical) HOL

HOL (meta-logic):  $s, t ::=$    
 HOML (target logic):  $s, t ::=$  




## Embedding of in

(1) Introduce new type  $\mu$  for worlds

HOML formulas  $s_o$  are mapped to HOL predicates  $s_{\mu \rightarrow o}$

(2) Introduce new constants  $r_{\mu \rightarrow \mu \rightarrow o}^i$  for each  $i \in I$

(3) Connectives:

 =   
 =   
 =   
 = 

(4) Meta-logical notions:

 = 

# Embedding of HOML within HOL

**Automation approach:** Encode HOML semantics within (classical) HOL

HOL (meta-logic):  $s, t ::=$  ████████████████████  
 HOML (target logic):  $s, t ::=$  ████████████████████

## Embedding of ████████ in ████████

(1) Introduce new type  $\mu$  for worlds

HOML formulas  $s_o$  are mapped to HOL predicates  $s_{\mu \rightarrow o}$

(2) Introduce new constants  $r_{\mu \rightarrow \mu \rightarrow o}^i$  for each  $i \in I$

(3) Connectives:

$$\begin{aligned} \neg_{o \rightarrow o} &= \lambda S_{\mu \rightarrow o}. \lambda W_{\mu}. \neg(S W) \\ \vee_{o \rightarrow o \rightarrow o} &= \lambda S_{\mu \rightarrow o}. \lambda T_{\mu \rightarrow o}. \lambda W_{\mu}. (S W) \vee (T W) \\ \prod_{(\tau \rightarrow o) \rightarrow o}^{\tau} &= \lambda P_{\tau \rightarrow \mu \rightarrow o}. \lambda W_{\mu}. \forall X_{\tau}. P X W \\ \Box_{o \rightarrow o} &= \lambda S_{\mu \rightarrow o}. \lambda W_{\mu}. \forall V_{\mu}. \neg(r^i W V) \vee S V \end{aligned}$$

(4) Meta-logical notions:

$$\text{████████} = \text{████████████████████}$$

**Automation approach:** Encode HOML semantics within (classical) HOL

HOL (meta-logic):	$s, t ::=$	
HOML (target logic):	$s, t ::=$	

## Embedding of $\mathbb{R}^n$ in $\mathbb{R}^m$

(1) Introduce new type  $\mu$  for worlds

HOML formulas  $s_o$  are mapped to HOL predicates  $s_{\mu \rightarrow o}$

(2) Introduce new constants  $r_{\mu \rightarrow \mu \rightarrow 0}^i$  for each  $i \in I$

(3) Connectives:

$$\neg_{o \rightarrow o} = \lambda S_{\mu \rightarrow o}. \lambda W_{\mu}. \neg(S W)$$

$$v_{o \rightarrow o \rightarrow o} = \lambda S_{\mu \rightarrow o} . \lambda T_{\mu \rightarrow o} . \lambda W_{\mu} . (S W) \vee (T W)$$

$$\Pi_{(\tau \rightarrow o) \rightarrow o}^\tau = \lambda P_{\tau \rightarrow \mu \rightarrow o}. \lambda W_\mu. \forall X_\tau. P X W$$

$$\Box_{0 \rightarrow 0} = \lambda S_{\mu \rightarrow 0}. \lambda W_{\mu}. \forall V_{\mu}. \neg (r^j W V) \vee S V$$

(4) Meta-logical notions:

$$\text{valid} = \lambda S_{\mu \rightarrow o}. \forall W_{\mu}. S W$$

## Embedding of HOML within HOL #2

### Embedding semantic variants

1. **Axiomatization of  $\Box^i$**
2. **Quantification**
3. **Rigidity**
4. **Consequence**

## 1. Axiomatization of $\square^i$

Name	Axiom scheme	Condition on $r^i$	Corr. formula
...	...	...	...
B	$s \supset \Box^i \Diamond^i s$	symmetric	$wR^i v \supset vR^i w$
...	...	...	...

2. Quantification
3. Rigidity
4. Consequence



## Embedding of HOML within HOL #2

### Embedding semantic variants

#### 1. Axiomatization of $\Box^i$

Postulate frame condition on  $r^i$  as HOL axiom

#### 2. Quantification

Choose appropriate definition/axiomatization of quantifier:  
Constant domains quantifier:

$$\Box_{(\tau \rightarrow o) \rightarrow o}^\tau = \lambda P_{\tau \rightarrow \mu \rightarrow o}. \lambda W_\mu. \forall X_\tau. P X W$$

Varying domains quantifier:

$$\Box^{\tau(\tau \rightarrow o) \rightarrow o, va} = \lambda P_{\tau \rightarrow \mu \rightarrow o}. \lambda W_\mu. \forall X_\tau. \neg(\text{eiw } X W) \vee (P X W)$$

Cumulative/decreasing domains quantifier:

Add axioms on eiw

#### 3. Rigidity

#### 4. Consequence

## 1. Axiomatization of $\square^i$

## 2. Quantification

### 3. Rigidity

Only translate Boolean types to predicates:  $\text{red} = \mu \rightarrow \text{blue}$

Also translate individuals types to predicates:  $\iota = \mu \rightarrow \iota$

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ↺ 🔍 ↻ 16

## Embedding of HOML within HOL #2

### Embedding semantic variants

#### 1. Axiomatization of $\Box^i$

Postulate frame condition on  $r^i$  as HOL axiom

#### 2. Quantification

Choose appropriate definition/axiomatization of quantifier

#### 3. Rigidity

Appropriate type lifting

#### 4. Consequence

Global consequence: Apply  $\text{valid}_{(\mu \rightarrow o) \rightarrow o}$  to all translated  $s_{\mu \rightarrow o}$

$$s_o = \text{valid}_{(\mu \rightarrow o) \rightarrow o} s_{\mu \rightarrow o}$$

Local consequence: Apply *actuality* operator  $\mathcal{A}$  to all translated  $s_{\mu \rightarrow o}$

$$s_o = \mathcal{A}_{(\mu \rightarrow o) \rightarrow o} s_{\mu \rightarrow o}$$

where  $\mathcal{A} = \lambda s_{\mu \rightarrow o}. s w_{\text{actual}}$  and  $w_{\text{actual}}$  is an uninterpreted symbol

# Problem representation

## Ongoing work: Extension of TPTP THF syntax for modal logic

### (1) Formula syntax

```
thf( classical, axiom, ! [X:$i]: (p @ X)).
```

↓ Extend syntax with modalities

```
thf( modal, axiom, ! [X:$i]: ($box @ (p @ X))).
thf( multi_modal, axiom, ! [X:$i]: ($box_int @ 1 @ (p @ X))).
```

### (2) Semantics configuration

Add "logic"-annotated statements to the problem:

```
thf(simple_s5, logic, ($modal := [
  $constants := $rigid,
  $quantification := $constant,
  $consequence := $global,
  $modalities := $modal_system_S5 ]))).
```

- ▶ Intended semantics is attached to the problem

## Problem representation

**Ongoing work:** Extension of TPTP THF syntax for modal logic

### (1) Formula syntax

```
thf( classical, axiom, ! [X:$i]: (p @ X)).
```

↓ Extend syntax with modalities

```
thf( modal, axiom, ! [X:$i]: ($box @ (p @ X))).  
thf( multi_modal, axiom, ! [X:$i]: ($box_int @ 1 @ (p @ X))).
```

### (2) Semantics configuration

Add "logic"-annotated statements to the problem:

```
thf(simple_s5, logic, ($modal := [  
  $constants := $rigid,  
  $quantification := $constant,  
  $consequence := $global,  
  $modalities := $modal_system_S5 ]))).
```

► Intended semantics is attached to the problem

## Problem representation

**Ongoing work:** Extension of TPTP THF syntax for modal logic

### (1) Formula syntax

```
thf( classical, axiom, ! [X:$i]: (p @ X)).
```

↓ Extend syntax with modalities

```
thf( modal, axiom, ! [X:$i]: ($box @ (p @ X))).  
thf( multi_modal, axiom, ! [X:$i]: ($box_int @ 1 @ (p @ X))).
```

### (2) Semantics configuration

Add "logic"-annotated statements to the problem:

```
thf(simple_s5, logic, ($modal := [  
  $constants := $rigid,  
  $quantification := $constant,  
  $consequence := $global,  
  $modalities := $modal_system_S5 ])).
```

- ▶ Intended semantics is attached to the problem

## Problem representation

**Ongoing work:** Extension of TPTP THF syntax for modal logic

### (1) Formula syntax

```
thf( classical, axiom, ! [X:$i]: (p @ X)).
```

↓ Extend syntax with modalities

```
thf( modal, axiom, ! [X:$i]: ($box @ (p @ X))).  
thf( multi_modal, axiom, ! [X:$i]: ($box_int @ 1 @ (p @ X))).
```

### (2) Semantics configuration

Add "logic"-annotated statements to the problem:

```
thf( mydomain_type , type , ( human : $tType ) ).  
thf( myconstant_declaration , type , ( myconstant : $i ) ).  
thf( complicated_s5 , logic , ( $modal := [  
  $constants := [ $rigid , myconstant := $flexible ] ,  
  $quantification := [ $constant , human := $varying ] ,  
  $consequence := [ $global , myaxiom := $local ] ,  
  $modalities := [ $modal_system_S5, $box_int @ 1 := $modal_system_T ] ] ) ).
```

- Intended semantics is attached to the problem