



Fallback property values in EPiServer using attributes

Fallback property values in EPiServer is a common, and often repetitive, requirement which can be simplified by decorating content type properties with an attribute to specify fallback behavior.

[Tweet](#) { 5 } [Gilla](#) [Dela](#) { 0 }

Common approach for property fallback values

Fallback values for content type properties are often implemented by **overriding property getters and setters**. While this is an effective way of implementing specialized logic for retrieving the fallback value, it's a bit cumbersome, verbose and repetitive for many of the more trivial cases:

```
1 public virtual string Title
2 {
3     get
4     {
5         var title = this.GetPropertyValue(page => page.Title);
6         if (!string.IsNullOrEmpty(title))
7         {
8             return title;
9         }
10        // Fallback to page name when title isn't set
11        return PageName;
12    }
13    set
14    {
15        this.SetPropertyValue(page => page.Title, value);
16    }
17 }
```

16
17
18
19

Revised approach based on attribute decoration

With our revised approach we can achieve the same result as before by decorating our property with a **Fallback attribute**:

```
1 [Fallback(PropertyName = "PageName")]  
2 public virtual string Title { get; set; }
```

?

Additional fallback options

We can specify a fallback value **explicitly**, for example to specify a default author:

```
1 [Fallback(Value = "Kevin Flynn")]  
2 public virtual string Author { get; set; }
```

?

We could use this in combination with a **PropertyName** parameter, using the default author name only if the fallback value is also empty:

```
1 [Fallback(PropertyName = "CompanyName", Value = "Kevin Flynn")]  
2 public virtual string Author { get; set; }
```

?

If our fallback value comes from a nested property of a complex type, like a **local block**, we can use **dot notation** for the property name:

```
1 [Fallback(PropertyName = "MyBlockProperty.CompanyName", Value = "Kevin Flynn")]  
2 public virtual string Author { get; set; }
```

?

The examples so far assume the fallback property is part of the **same content instance** as the original property.

If our fallback property is defined on **another content instance**, we can specify that the fallback content will be determined by a **ContentReference** property.

The following would use a **property** of a **local block** on the **start page** as the fallback value:

```

1  public class MyPageType: PageData
2  {
3      [Fallback(PropertyName = "SiteSettings.CompanyName", ContentReferencePropertyName = "SettingsPage", Value = "Kevin Flynn")]
4      public virtual string Author { get; set; }
5
6      public ContentReference SettingsPage
7      {
8          get { return ContentReference.StartPage; }
9      }
10 }

```

How it works

EPiServer intercepts all **getters** and **setters** of content type properties using an instance implementing **IInterceptor**, part of the **Castle Project**. The default interceptor in EPiServer is called **ContentDataInterceptor**, but using EPiServer's **IoC** container we can easily replace this with a custom interceptor which supports our **Fallback** attribute.

Creating the Fallback attribute

The **Fallback** attribute is quite trivial:

```

1  [AttributeUsage(AttributeTargets.Property, AllowMultiple = false, Inherited = true)]
2  public class FallbackAttribute : Attribute
3  {
4      public virtual string ContentReferencePropertyName { get; set; }
5
6      public virtual string PropertyName { get; set; }
7
8      public virtual object Value { get; set; }
9  }

```

Switch concrete implementation to a custom interceptor

One way to switch concrete implementations in EPiServer is to create a class implementing **IConfigurableModule**, an interface very similar to **IInitializableModule** with the addition of a **ConfigureContainer** method:

```

1 [InitializableModule]
2 [ModuleDependency(typeof(ServiceContainerInitialization))]
3 public class FallbackInitialization : IConfigurableModule
4 {
5     public void Initialize(EPiServer.Framework.Initialization.InitializationEngine context) { }
6     public void Preload(string[] parameters) { }
7     public void Uninitialize(EPiServer.Framework.Initialization.InitializationEngine context) { }
8     public void ConfigureContainer(ServiceConfigurationContext context)
9     {
10         // Register custom interceptor
11         context.Container.Configure(config => config.For<ContentDataInterceptor>()
12             .Use<FallbackValueContentDataInterceptor>());
13     }
14 }
15
16
17

```

Implementing the custom interceptor

This is where the magic happens. We inherit **ContentDataInterceptor** and add logic which uses the **Fallback** attribute to determine how a fallback value should be retrieved. This code is fairly lengthy, but the comments hopefully clarify what is going on:

```

1 using System;
2 using System.Reflection;
3 using Castle.DynamicProxy;
4 using EPiServer;
5 using EPiServer.Core;
6 using EPiServer.DataAbstraction.RuntimeModel;
7 using EPiServer.ServiceLocation;
8 using log4net;
9
10 namespace TedGustaf.Web.PropertyFallback
11 {
12     /// <summary>
13     /// Enables fallback attributes for content type properties
14     /// </summary>
15     /// <remarks>Configured through <see cref="FallbackInitialization"/></remarks>
16     /// <author>Ted Nyberg, @tednyberg</author>
17     public class FallbackValueContentDataInterceptor : ContentDataInterceptor
18     {
19         private static readonly ILog _logger = LogManager.GetLogger(typeof(FallbackValueContentDataInterceptor));
20
21         protected override void HandleGetterAccessor(IInvocation invocation, PropertyData propertyData)
22         {
23             base.HandleGetterAccessor(invocation, propertyData);
24
25         }
26     }
27 }

```

```

19         if (!IsNull(invocation.ReturnValue)) // Property value is set
20         {
21             return;
22         }
23
24         // Get the property definition of the content type, i.e. a property member with the same name as the content type prope
25         var propertyProperty = invocation.InvocationTarget.GetType().GetProperty(propertyData.Name);
26
27         if (propertyProperty == null)
28         {
29             _logger.WarnFormat("There is no property called {0} on type {1}, content type property does not map to model type",
30
31                 return;
32         }
33
34         // Get the fallback attribute, if any, decorating the property
35         var fallbackAttribute = Attribute.GetCustomAttribute(propertyProperty, typeof(FallbackAttribute), true) as FallbackAtt
36
37         if (fallbackAttribute == null) // No fallback attribute
38         {
39             return;
40         }
41
42         // Get the fallback value based on the fallback attribute parameters
43         invocation.ReturnValue = GetValue(invocation.InvocationTarget, propertyProperty, fallbackAttribute);
44     }
45
46     /// <summary>
47     /// Throw an exception if the attribute parameters are invalid
48     /// </summary>
49     protected virtual void ThrowOnInvalidAttributeParameters(FallbackAttribute attribute, PropertyInfo property)
50     {
51         if (string.IsNullOrEmpty(attribute.ContentReferencePropertyName)) // Fallback value will be retrieved from current
52         {
53             if (string.IsNullOrEmpty(attribute.PropertyName) && attribute.Value == null) // Neither property name nor fixe
54             {
55                 throw new NotSupportedException("Fallback value attribute must specify either a content reference property name
56             }
57
58             if (!string.IsNullOrEmpty(attribute.PropertyName) && attribute.PropertyName.Equals(property.Name)) // Fallback
59             {
60                 throw new NotSupportedException("Fallback property cannot be the same as the source property when no content re
61             }
62         }
63
64         if (attribute.Value != null && attribute.Value.GetType() != property.PropertyType) // The specified fallback value does
65         {
66             throw new InvalidCastException(string.Format("The explicit fallback value is of type {0}, but the property type is
67         }
68     }
69
70     /// <summary>
71     /// Gets the property value, or fallback value based on fallback attribute parameters
72     /// </summary>

```

```

62 protected virtual object GetValue(object instance, PropertyInfo property, FallbackAttribute attribute)
63 {
64     _logger.DebugFormat("Retrieving fallback value for '{0}' for instance of type {1}", property.Name, instance.GetType().Name);
65     object value = null;
66     ThrowOnInvalidAttributeParameters(attribute, property);
67     ContentReference fallbackValueContentReference = null;
68     if (!string.IsNullOrEmpty(attribute.ContentReferencePropertyName)) // A content reference property on the instance
69     {
70         // Resolve the content reference property on the current content instance
71         var fallbackValueContentReferenceProperty = ResolveProperty(attribute.ContentReferencePropertyName, instance);
72         if (fallbackValueContentReferenceProperty == null) // Content reference property not found
73         {
74             throw new NotSupportedException(string.Format("The content type {0} does not have a property called {1}", instance.GetType().Name, attribute.ContentReferencePropertyName));
75         }
76         fallbackValueContentReference = fallbackValueContentReferenceProperty.GetValue(instance) as ContentReference;
77         if (fallbackValueContentReference == null) // Content reference property is an incorrect type
78         {
79             throw new NotSupportedException(string.Format("The property named '{0}' is not a ContentReference", attribute.ContentReferencePropertyName));
80         }
81     }
82     if (!ContentReference.IsNullOrEmpty(fallbackValueContentReference)) // Get fallback value from content instance specified
83     {
84         var fallbackValueContentData = ServiceLocator.Current.GetInstance<IContentLoader>().Get<ContentData>(fallbackValueContentReference);
85         if (string.IsNullOrEmpty(attribute.PropertyName)) // Fallback property name not specified
86         {
87             attribute.PropertyName = property.Name; // Use property of same name from fallback content instance
88         }
89         var fallbackProperty = ResolveProperty(attribute.PropertyName, fallbackValueContentData);
90         if (fallbackProperty == null) // Specified property name does not exist on fallback content instance
91         {
92             _logger.WarnFormat("Fallback content instance '{0}' does not have a property called '{1}'", fallbackValueContentReference, attribute.PropertyName);
93         }
94         else
95         {
96             if (attribute.PropertyName.Contains(".")) // Nested fallback property, i.e. property of a complex property type
97             {
98                 var nestedPropertyInstance = ResolveInstance(attribute.PropertyName, fallbackValueContentData);
99                 value = fallbackProperty.GetValue(nestedPropertyInstance);
100             }
101             else
102             {
103                 value = fallbackProperty.GetValue(fallbackValueContentData);
104             }
105         }
106     }
107 }

```

```

105     }
106 }
107 else if (!string.IsNullOrEmpty(attribute.PropertyName)) // An fallback property name has been specified
108 {
109     var fallbackProperty = instance.GetType().GetProperty(attribute.PropertyName);
110     if (fallbackProperty == null)
111     {
112         _logger.WarnFormat("Current instance does not have a property called '{0}'", attribute.PropertyName);
113     }
114     else
115     {
116         value = fallbackProperty.GetValue(instance);
117     }
118 }
119
120 return value ?? attribute.Value; // Use explicit fallback value if no other fallback value could be found
121 }
122
123 /// <summary>
124 /// Resolves the instance containing the specified nested property
125 /// </summary>
126 /// <param name="sourceInstance">The original content instance for which the nested instance should be resolved</param>
127 /// <param name="propertyIdentifier">Dot notation to specify a nested property, like MyType.MyComplexProperty.NestedProperty
128 /// <returns></returns>
129 private object ResolveInstance(string propertyIdentifier, object sourceInstance)
130 {
131     if (sourceInstance == null)
132     {
133         throw new ArgumentNullException("sourceInstance", "No source instance specified, unable to resolve nested property");
134     }
135     if (string.IsNullOrEmpty(propertyIdentifier))
136     {
137         throw new ArgumentNullException("propertyIdentifier", "No property identifier specified, unable to resolve instance");
138     }
139     if (!propertyIdentifier.Contains("."))
140     {
141         throw new ArgumentException("Property identifier must be in dot notation to resolve nested property");
142     }
143     var segments = propertyIdentifier.Split('.');
144     object instance = sourceInstance;
145     // Resolve instances up until the final segment, i.e. the property for which the instance should be resolved
146     for (int i = 0; i < segments.Length - 1; i++)
147     {
148         var segment = segments[i];
149         var property = ResolveProperty(segment, instance);
150         if (property == null)
151         {
152             return null;
153         }
154         instance = property;
155     }
156     return ResolveProperty(segments[segments.Length - 1], instance);
157 }

```

```

148         _logger.WarnFormat("Unable to find property {0} on type {1}", segment, instance.GetType().Name);
149         return null;
150     }
151     instance = property.GetValue(instance);
152 }
153
154     return instance;
155 }
156
157 /// <summary>
158 /// Resolves a property on the specified instance, including dot notation to support nested properties
159 /// </summary>
160 /// <returns>Null if the property cannot be resolved</returns>
161 protected virtual PropertyInfo ResolveProperty(string propertyIdentifier, object instance)
162 {
163     if (string.IsNullOrEmpty(propertyIdentifier))
164     {
165         throw new ArgumentNullException("propertyIdentifier", "No property identifier specified");
166     }
167     PropertyInfo property = null;
168     if (!propertyIdentifier.Contains("."))
169     {
170         property = instance.GetType().GetProperty(propertyIdentifier);
171     }
172     else
173     {
174         var identifierSegments = propertyIdentifier.Split('.');
175         foreach (var segment in identifierSegments)
176         {
177             // Get property from original instance, or from nested property within it
178             if (property != null)
179             {
180                 instance = property.GetValue(instance);
181             }
182             property = ResolveProperty(segment, instance);
183             if (property == null)
184             {
185                 _logger.WarnFormat("No property called {0} on type {1}", segment, instance.GetType().Name);
186                 return null;
187             }
188         }
189     }
190     if (property == null)
191     {
192         _logger.WarnFormat("Unable to resolve property using identifier '{0}' on content type {1}", propertyIdentifier, ins

```



```
191         return property;
192     }
193
194     /// <summary>
195     /// Checks if a value is null, or should otherwise trigger fallback behavior
196     /// </summary>
197     protected virtual bool IsNull(object value)
198     {
199         // TODO Check for boundary DateTime etc that should trigger fallback behavior?
200         return value == null || (value is string && string.IsNullOrEmpty(value as string));
201     }
202 }
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
```

234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258

Notes of interest

Most aspect-oriented libraries, like **PostSharp**, can be used to easily extend support for the **Fallback** attribute to [intercept all properties](#), not just content type properties.

Disclaimer

The code is a first prototype draft and is provided as-is under [MIT license](#).

[← Previous](#)

[Next →](#)

0 Comments Ted & Gustaf

 Login ▾

 Recommend  Share

Sort by Best ▾



Start the discussion...

Be the first to comment.

 Subscribe

 Add Disqus to your site

 Privacy

**Ted Nyberg**

CEO and Founding Partner

+46 707 770 790

ted@tedgustaf.com[Twitter](#)[LinkedIn](#)

Tags

[episerver](#)[code samples](#)

Share it if you like it

[Tweet](#)

5

[Gilla](#)

0

[Articles on EPiServer](#)[More from the blog](#)[Keep in touch](#)

EPiServer Google Maps editor on NuGet

Fallback property values in EPiServer using attributes

Google Maps custom editor for EPiServer 7.5

Add a custom toolbar button in EPiServer 7

Create an EPiServer widget for edit mode

Usability testing of click behavior

Web Essentials plugin for Visual Studio 2013

Web Essentials plugin for Visual Studio 2013

Compile .less files online

Create Excel 2007/2010 spreadsheets with C# and EPPlus

Phone
E-mail
Address

+46 (8) 410 208 40
info@tedgustaf.com
Sveavägen 21
111 34 Stockholm

Copyright © 2015 Ted & Gustaf AB