

Spring Boot and Mongo DB (API)

Database: test

Collection: location (locationId, lat, lng, locationName)

Method Name	Url	Params	Method Type
getAll	http://localhost:8080/location/getAll		GET
delete	<a href="http://localhost:8080/location/delete/<locationId>">http://localhost:8080/location/delete/<locationId>	locationId	DELETE
add	http://localhost:8080/location/add	lng, lat, locationName	POST
getSpecific	<a href="http://localhost:8080/location/getSpecific/<locationName>">http://localhost:8080/location/getSpecific/<locationName>	locationName	GET
Update	http://localhost:8080/location/update	locationId, lng, lat, locationName	PUT

Below the Screen Shot of Postman:

Method Name: Add

POST <http://localhost:8080/location/add>

Authorization Headers Body Pre-request Script Tests

☒ form-data ☐ x-www-form-urlencoded ☐ raw ☐ binary

Key	Value
<input checked="" type="checkbox"/> lng	90.420000
<input checked="" type="checkbox"/> lat	23.803
<input checked="" type="checkbox"/> locationName	Baridhara data


New key Text Value

Body Cookies Headers (3) Test Results


Pretty Raw Preview JSON

```
1 {
2   "Time": "08:58:57 PM",
3   "message": "Location created successfully",
4   "status": "1",
5   "Location": {
6     "locationId": "5cbd1fe1288e04208cd99d3d",
7     "lat": "23.803",
8     "lng": "90.420000",
9     "locationName": "Baridhara data"
10  }
11 }
```


Method Name: Delete

DELETE  http://localhost:8080/location/5cbcfffe45388042fdcf216f7

Authorization Headers Body **Pre-request Script** Tests

Type No Auth 

Body Cookies Headers (3) Test Results


Pretty Raw Preview JSON 

```

1 {
2   "message": "Location deleted successfully",
3   "status": "1"
4 }

```

Method Name: Update


PUT  http://localhost:8080/location/update

Authorization Headers Body **Pre-request Script** Tests

☒ form-data ☐ x-www-form-urlencoded ☐ raw ☐ binary

	Key	Value	
<input checked="" type="checkbox"/>	locationId	5cbccbe5388041744ec92bc	
<input checked="" type="checkbox"/>	lat	23.1111111	
<input checked="" type="checkbox"/>	lng	90.420003	
<input checked="" type="checkbox"/>	locationName	Dhaka	
	New key	Value	

Body Cookies Headers (3) Test Results

Pretty Raw Preview JSON 

```

1 {
2   "location": {
3     "locationId": "5cbccbe5388041744ec92bc",
4     "lat": "23.1111111",
5     "lng": "90.420003",
6     "locationName": "Dhaka"
7   },
8   "message": "Location updated successfully",
9   "status": "1"
10 }

```

Method Name: getAll

GET

http://localhost:8080/location/getAll

AuthorizationHeadersBodyPre-request ScriptTests

Type

No Auth

BodyCookiesHeaders (3)Test Results

PrettyRawPreviewJSON

```
1 {
2   "totalLocation": 3,
3   "message": "Location found successfully",
4   "status": "1",
5   "Location": [
6     {
7       "locationId": "5cbccebe5388041744ec92bc",
8       "lat": "23.111111",
9       "lng": "90.420003",
10      "locationName": "Dhaka"
11    },
12    {
13      "locationId": "5cbcffe45388042fdc216f7",
14      "lat": "23.803",
15      "lng": "90.420000",
16      "locationName": "Baridhara data"
17    }
18  ]
19 }
```

Method Name: getSpecific

GET

http://localhost:8080/location/getSpecific/Dhaka

AuthorizationHeadersBodyPre-request ScriptTests

Type

No Auth

BodyCookiesHeaders (3)Test Results

PrettyRawPreviewJSON

```
1 {
2   "location": [
3     {
4       "locationId": "5cbccebe5388041744ec92bc",
5       "lat": "23.111111",
6       "lng": "90.420003",
7       "locationName": "Dhaka"
8     }
9   ],
10  "message": "Location found successfully",
11  "status": "1"
12 }
```