

- If expansion fails:
 - Original block is not freed

10. Fragmentation

- **External Fragmentation**
 - Free memory exists but in unusable chunks
 - Causes allocation failure despite available memory
- Handled by allocator, mostly out of programmer's control

11. Common Memory Errors

1. Memory Leak

- Allocated memory never freed
- Program memory usage grows uncontrollably

2. Dangling Pointer

- Pointer refers to freed memory
- Causes crashes and security vulnerabilities

3. Wild Pointer

- Pointer never initialized
- Points to random memory

4. Invalid Free

- Freeing memory that was never allocated
- Freeing memory twice

12. Best Practices

- Always initialize pointers (use NULL)
- Always free memory you allocate
- Set pointer to NULL after freeing
- Limit user-controlled memory sizes
- Validate allocation results (NULL checks)
- Be extra careful on constrained systems (embedded)

13. The Core Takeaways

- Stack is fast, automatic, limited
- Heap is flexible, manual, dangerous if mishandled
- C gives **full control** → also full responsibility
- Compiler will not protect you from memory mistakes
- Correct memory management = stable, efficient programs

Computer Science(UX Design) -Lecture 17

1. What “Decision Making” Means in Programming

- Programs don't always execute linearly.
- Decision making allows a program to **choose different execution paths** based on input or conditions.
- Internally, this is always driven by **boolean evaluations** (true / false).
- Real-world systems (GPS, camera modes, error handling) are just complex versions of the same idea.

2. Importance of Planning (Flowcharts & Logic)

- As programs grow, logic branches increase rapidly.
- Without planning, code becomes:
 - Hard to follow
 - Error-prone
 - Difficult to debug
- **Flowcharts** help:
 - Visualize control flow
 - Reduce ambiguity
 - Prevent tangled logic, especially with many conditions

3. Boolean Conditions (Foundation of Decisions)

- Every decision depends on a condition that evaluates to **true or false**.
- Comparison operators:
 - ==, !=, <, >, <=, >=
- These comparisons are **absolute**, not partial.
- Logical operators allow combining conditions:
 - && (AND) ◦ || (OR) ◦ ! (NOT)
- Operator precedence applies — grouping matters.

4. if Statement

- Executes code **only when a condition is true**.
- If the condition is false, execution continues normally.
- Curly braces {} are optional for single statements, but recommended for clarity.
- Common mistake:
 - Using = instead of == (assignment vs comparison)

5. if-else Statement

- Provides **two mutually exclusive execution paths**:
 - One for true ◦ One for false
- Helps remove ambiguity by explicitly handling both outcomes.
- Improves readability and predictability.

- Used when **multiple mutually exclusive conditions** exist.
- Conditions are evaluated **top to bottom**.
- Once a condition is satisfied:
 - Remaining else if and else blocks are skipped.
- Best for: Range-based checks (e.g., grading systems)
- If the ladder grows too long, consider switch.

7. Nested if Statements

- An if inside another if or else.
- Creates **hierarchical decision logic**.
- More powerful, but:
 - Easier to lose track of scope
 - Can lead to deeply nested, unreadable code
- Use carefully and consistently format your code.

8. switch Statement

- Used when selecting **one path from many discrete options**.
- Works like a multi-branch selection tree.
- Rules:
 - Expression must evaluate to **int or char**
 - case labels must be **constant values**
 - No duplicate cases
 - Break is essential:
 - Without it, execution “falls through” to the next cases
 - default handles unexpected values and ensures safe exit.

9. When to Use switch vs if-else

- Use switch when:
 - Comparing a single variable against fixed values
 - Logic is menu-like (e.g., USSD menus)
- Use if-else when:
 - Conditions involve ranges
 - Complex logical expressions are needed

10. Conditional (Ternary) Operator ?:

- Compact alternative to simple if-else.

```
condition ? value_if_true : value_if_false
```

Syntax

if-else

- Useful for: Simple assignments & Short, readable decisions
- Limitations:
 - Becomes unreadable when nested
 - Not suitable for complex logic

• Used for **dynamic memory allocation**

- Memory allocated at runtime
- Characteristics:
 - Slower than stack, Much larger & Size can grow/shrink dynamically
- Programmer must manually manage it
- Incorrect handling leads to:
 - **Memory leaks**, Crashes, Undefined behavior

7. Program Memory Layout (Low → High Address)

1. Text Segment

- Executable code, Read-only, Shareable across processes

2. Initialized Data Segment

- Global/static variables with initial values, Read-write

3. Uninitialized Data Segment (BSS)

- Global/static variables without initialization

- Contains garbage values initially
- **Stack**: Function calls, local variables
- **Heap**: Dynamically allocated memory

8. Dynamic Memory Allocation in C

- Used when data size is unknown at compile time
- Overcomes fixed-size array limitations
- Defined in standard library headers

Four Core Functions

1. malloc

- Allocates memory (uninitialized)

2. calloc

- Returns pointer or NULL
- Allocates memory and initializes to zero
- Returns pointer or NULL

3. free

- Deallocates memory
- Does not return anything
- Freeing invalid or already freed memory → undefined behavior

4. realloc

- Resizes previously allocated memory
- Preserves old data up to smaller size
- May move memory to a new location
- Returns NULL on failure (old block remains valid)

9. Special realloc Behaviors

- realloc(NULL, size) → same as malloc(size)
- realloc(ptr, 0) → frees memory, returns NULL

Computer Science(UX Design) -Lecture 24

1. What Memory Is

- Memory stores **data** (binary 0s and 1s) used by the computer.
- Data is unprocessed information; instructions operate on it to produce results.
- Physically implemented using **transistors and capacitors** representing charge.

2. Memory Hierarchy (Closest → Farthest from CPU)

1. CPU Registers

- Smallest, fastest, most expensive
- Directly accessed by CPU

2. Cache

- Slightly slower than registers
- Stores data likely needed soon
- Usually only a few MB

3. RAM (Main Memory)

- Largest working memory
- Slower than cache
- Programs can run directly from RAM

4. Secondary Storage (Disk)

- Very slow compared to RAM
- Used when RAM is insufficient

3. Latency and Performance

- **Latency** = time to complete a read/write
- Higher latency → slower memory
- Performance depends on:
 - Speed (latency)
 - Size
 - Cost
 - Distance from CPU

4. Memory Allocation at Program Start

- When a program starts:
 - OS assigns memory via the **memory manager**
 - Allocator decides how memory is distributed
- Memory movement between RAM and disk is handled by OS
- Programmer declares variables → compiler converts them to **memory addresses**
- Variable names mean nothing at runtime; only addresses matter

5. Stack Memory

- Stores **automatic (local) variables**
- Memory freed automatically when variables go out of scope
- Characteristics:
 - Fast access, Size must be known at compile time & Limited size
- Uses **LIFO (Last In, First Out)**
- Each function call:
 - Pushes return address and local variables
- Recursive calls rely heavily on stack behavior

6. Heap Memory

- Both outcomes must be of the **same type**.

11. goto Statement

- Transfers control unconditionally to a labeled section.
- Strongly discouraged because it:
 - Breaks logical flow
 - Creates “spaghetti code”
 - Makes debugging difficult
- Not a true decision structure on its own.
- Should be avoided in structured programming.

12. The Core Takeaways

- Always prioritize **readability over cleverness**.
- Avoid deeply nested logic where simpler structures exist.
- Use:
 - if for conditional execution
 - if-else for binary decisions
 - else if for ordered conditions
 - switch for discrete selections
 - ternary operator for simple assignments only
- Plan before coding when logic becomes non-trivial.

1. Repetition in Programming

- Repetition allows a program to execute the same block of code multiple times.
- Computers excel at repetition because they execute instructions consistently.
- Repetition is implemented using:
 - while / do-while loops & for loops & Recursion

2. While Loop

2.1 Concept

- Repeats a block of code as long as a condition remains true.
- Condition is checked **before** each iteration.
- May execute zero or more times.

2.2 Key Characteristics

- Controlled by a boolean condition.
- Uses a control variable.
- Control variable must be modified inside the loop.

2.3 Execution Flow

1. Evaluate condition
2. If true → execute loop body
3. Modify control variable
4. Re-evaluate condition
5. Exit when condition becomes false

2.4 Common Uses

- Unknown number of iterations, input validation & Event-driven repetition

3. Do-While Loop

3.1 Concept

- Executes the loop body first, then evaluates the condition.
- Guaranteed to run at least once.

3.2 Difference from While Loop

- while: entry-controlled loop
- do-while: exit-controlled loop

3.3 When to Use

- When the condition depends on user input
- When the condition must be established after execution

4. Common Loop Errors

4.1 Unreachable Loop

- Condition is never true & Loop body never executes.

4.2 Infinite Loop

- Condition never becomes false.
- Caused by: Incorrect update of control variable & Missing update

10. Hosted vs Freestanding Environments

- stdlib.h → memory allocation, conversions, utilities
- string.h → string manipulation
- time.h → date and time functions (second-level precision)

13. POSIX Standard

- Superset of the C standard library
- Adds:
 - Multithreading
 - Networking
 - Regex
- Focused on **Unix-like systems**
- Improves OS-level compatibility, not portability across all platforms

14. The Core Takeaways

- Preprocessor runs **before compilation**
- #include performs **text substitution**
- Header files define interfaces, not logic
- Standard library is intentionally minimal
- Portability depends on sticking to standard headers
- POSIX ≠ Standard C
- Compiler behavior ≠ Preprocessor behavior
- Freestanding ≠ Hosted environments
- Comments never reach the compiler
- Multiple inclusion must be controlled

11. User-Defined Header Files

- Created to build **custom libraries**
- Included using quotes "file.h"
- Behave exactly like standard headers
- Excessive non-standard headers hurt portability

12. C Standards Overview

- ANSI C
 - First formal standard (1980s)
 - C89 / C90
- ISO C
 - Adopted in 1990
 - Revisions:
 - C99
 - C11
 - C18 (latest)

- What the Standard Defines
 - Program representation
 - Syntax and constraints
 - Semantics
 - Input representation
 - Output representation

- Ignored if unsupported
- From **C99**, can be generated via macros

Used mainly in **large or specialized builds**

6. Header Files: Key Rules

- Typically use .h, sometimes .hpp
- Meant to be **included once**
- Multiple inclusion causes errors unless guarded
- Contain:
 - Function declarations
 - Macros
 - Type definitions

Special Case

- assert.h **can be included multiple times**
 - Used to enable/disable assertions

9. Important Standard Header Files (Grouped)

Debugging
assert.h

→ runtime checks, aborts on failure

Error Handling
errno.h

→ global error reporting via errno

Variadic Functions
stdarg.h

- Rules:
 - At least one fixed argument
 - va_end must be called
 - Type promotion rules apply

Signals (Mostly Unix)
signal.h

→ asynchronous signal handling

- **Not portable**

Core Utilities

- stddef.h → common types and macros
- stdio.h → input/output (files, streams, devices)

7. Why Header Files Exist

- Avoid rewriting common functionality
- Improve portability
- Separate **interface** from **implementation**
- Enable reuse and standardization

8. The C Standard Library

- Collection of standard header files
- Defined by ANSI → ISO standards
- Intentionally **small and minimal**
- Designed for:
 - Portability
 - Low-level system access
 - Predictable behavior across platforms

Character Handling
ctype.h

→ character classification & mapping

Mathematics
math.h, float.h, limits.h

→ Advanced math, floating-point behavior, type limits

Control Flow
setjmp.h

→ non-local jumps (manual exception-like behavior)

Localization
locale.h

→ regional formats (date, time, currency)

4.3 Uninitialized Control Variables

- Causes unpredictable behavior.
- Code may compile but behave inconsistently.

4.4 Rules to Remember

- Condition must be satisfiable.
- Condition must eventually become false.
- Control variables must be initialized.
- Condition must clearly define continuation and termination.

5. For Loop

5.1 Concept

- Used when the number of iterations is known in advance.
- Combines initialization, condition, and update in one statement.

5.2 Execution Order

1. Initialization (once)
2. Condition check
3. Execute loop body
4. Increment/decrement
5. Repeat condition check

5.3 Advantages

- Cleaner and more readable
- Lower risk of infinite loops
- Ideal for counting and traversal

5.4 Typical Use Cases

- Fixed iteration counts
- Array traversal
- Multiplication tables

6. While vs For Loop

Aspect	Iteration count	Control clarity	Error risk	Best use
While Loop	Unknown	Distributed	Higher	Input-driven logic
For Loop	Known	Centralized	Lower	Counting / traversal

7. Recursion

7.1 Concept

- A function calls itself to solve a problem.
- Each call works on a smaller version of the problem.

7.2 Essential Components

1. Base Case
 - Stops recursion
 - Solved without further recursive calls
2. Recursive Case
 - Reduces problem size
 - Moves toward base case

7.3 Execution Behavior

- Function calls stack until base case is reached.
- Results are resolved in reverse order.

8. Example: Factorial

- Recursive definition:

1. Purpose of Revisiting the Compilation Process

- To understand where header files fit in compilation.
- Explains why header files behave differently from normal source code.
- Critical for understanding preprocessor rules and limitations.

2. High-Level Compilation Pipeline

1. Preprocessor
 2. Compiler → produces relocatable code
 3. Assembler → produces assembly
 4. Linker & Loader → produces machine code
- Each stage transforms code into a different form.

3. The Preprocessor (Core Focus)

- Main Responsibilities
- Header file inclusion
 - Macro expansion
 - Conditional compilation
 - Line control

4. Preprocessing Stages (In Order)

1. Trigraph Replacement
 - Converts trigraph sequences into single characters
2. Line Splicing
 - Rarely used today, mostly legacy
3. Tokenization
 - Joins physical lines split using \

- Breaks code into tokens and whitespace
- Comments are removed entirely

4. Directive & Macro Processing

- Executes #include, #define, #if, etc.
- Inserts external file contents directly into code

5. Preprocessor Directives

5.1 #include

- Inserts file contents **textually**
 - Treated as if you wrote that code yourself
- Forms

- <file.h> → search standard include paths
- "file.h" → search project directory first

5.2 #pragma

- Requests **compiler-specific behavior**
- Syntax and supported tokens vary by compiler

- $n! = 1$ if $n = 0$ (base case)
 - $n! = n \times (n-1)!$ if $n > 0$ (recursive case)
- Demonstrates problem reduction and backtracking.

9. Applications of Recursion

- Mathematical computations
- Divide-and-conquer algorithms (e.g., merge sort)
- Data structures (linked lists, trees)
- Artificial intelligence problems
- Computer graphics (fractals)
- Classical puzzles (Towers of Hanoi)

10. Limitations of Recursion

- High memory usage due to call stack
- Slower than iteration in many cases
- Repeated computation of the same subproblems

11. Fibonacci and Algorithmic Complexity

- Naive recursive Fibonacci recalculates values repeatedly.
- Time complexity grows exponentially.
- Performance degrades rapidly for large inputs.
- Highlights why recursion must be used carefully.

12. Design Rules for Recursion

1. Always define a base case.
2. Each recursive call must move closer to the base case.
3. Assume recursive calls work correctly (inductive reasoning).
4. Avoid duplicate computation.

13. The Core Takeaways

- Use **while loops** for unpredictable repetition.
- Use **do-while loops** when execution must occur at least once.
- Use **for loops** when iteration count is known.
- Always initialize and update control variables.
- Infinite loops are valid only when intentional.
- Recursion is powerful but costly — use it deliberately.
- Prefer iteration when performance is critical.
- Clear termination logic matters more than syntax.

23. The Core Takeaways

- Structures group **heterogeneous data**
- Unions share memory, only one member valid
- Structures consume more memory than unions
- Type casting controls precision and memory
- Explicit casting can cause data loss
- Implicit conversion is compiler-driven
- Parentheses affect casting correctness
- Built-in conversion functions lack robust error handling
- Typedef improves code clarity
- Use structures for records, unions for alternatives
- Memory safety matters when converting and copying data

Computer Science(UX Design) -Lecture 19

1. What Scope Means

- **Scope** defines where a variable or function is **visible and accessible** in a program.
- Two primary types:
 - **Global scope** → visible everywhere in the program
 - **Local (block) scope** → visible only inside the block { } where declared
- Scope boundaries are defined by **curly braces**.

2. Global vs Local Variables

- **Global variables**
 - Declared outside all functions
 - Accessible across functions and source files
- **Local variables**
 - Declared inside functions or blocks
 - Exist only within that scope
- **Rule:** Local variables take precedence over global variables if names collide.

3. Function Scope

- Variables declared inside a function:
 - Are created when the function is entered
 - Are destroyed when the function exits
- Function parameters also have **local scope**.
- In C, only **goto labels** have function scope (unique rule).

4. Why Scope Is Necessary

- Prevents variable name collisions
- Enforces **information hiding**
- Ensures predictable program behavior
- Improves **memory efficiency**
- Reduces unintended side effects
- Enables safer and more maintainable code

5. Scope and Memory Management

- Local variables:
 - Created only if their scope is executed
 - Destroyed when scope ends
- Unused scopes do not allocate memory
- Helps reduce memory footprint and waste

6. Storage Classes Overview

Storage classes define:

- **Lifetime & Memory location & Visibility & Linkage**
Four storage classes:
 - Auto, register, static & extern

7. Linkage (Visibility Across Scopes & Files)

Linkage controls whether identifiers refer to the same object across scopes.
Types of linkage:

1. **No linkage**
 - Block scope variables
 - Function parameters
2. **Internal linkage**
 - static variables at file scope
 - Visible within one source file
3. **External linkage**
 - Global non-static variables and functions
 - Visible across translation units

8. Translation Unit

- A **translation unit** = source file + included headers
- Determines visibility and linkage across files

9. Auto Storage Class

- Default for local variables
- Characteristics:
 - Block scope
 - Automatic lifetime
 - Uninitialized by default (garbage values)
 - Memory allocated: On block entry
 - Memory deallocated: On block exit
 - Rarely written explicitly

10. Register Storage Class

- Suggests storing variable in a **CPU register**
- Used for:
 - Frequently accessed variables
 - Loop counters
 - Characteristics:
 - Faster access
 - Not guaranteed (compiler decides)
- Restrictions:
 - No address (&) allowed
 - No pointers
 - Block scope only
 - Lifetime same as auto
 - No linkage

11. Static Storage Class

- Enforces **information hiding**
- Characteristics:
 - Static storage duration (entire program lifetime)

13. Implicit Type Conversion

- Done **automatically** by the compiler.
- Happens when:
 - data types are compatible
 - Lower types are promoted to higher types
- No casting operator needed
- type of the left-hand side variable
- Occurs during compilation

15. When Implicit Conversion Is Blocked

- If conversion may cause data loss:
 - compiler issues a warning
- Programmer must use **explicit casting**
- Protects accuracy by default

17. String to Number Functions

- atoi() → string to int
- atof() → string to double
- atol() → string to long
- Return 0 if conversion fails
- No error reporting beyond return value

19. Typedef (Type Alias)

- typedef creates an **alias** for an existing type
- Does **not** create a new data type
- Used to simplify:
 - complex structures
 - unions
 - pointer-heavy code
 - Improves readability and maintainability

21. Structures + Typedef (Common Pattern)

- Used together to:
 - simplify syntax
 - hide implementation details
 - make APIs cleaner
- Very common in professional C codebases

14. Rules of Implicit Conversion

- char and short → int
- Float hierarchy applies:
 - long double > double > float
- Signed vs unsigned handled carefully
- Final result is converted to: type of the left-hand side variable

16. Built-in Type Conversion Functions

- Provided via stdlib.h
- Mainly used for **string ↔ numeric** conversion

18. Number to String Functions

- itoa() → int to string
- ltoa() → long to string
- Require:
 - destination buffer
 - numerical base
- Buffer size must be sufficient
- Return pointer to null-terminated string

20. Typedef vs #define

- typedef
- handled by compiler
- type-safe
- scoped
- #define
- handled by preprocessor
- text substitution
- no type checking
- Prefer typedef for data types

22. Demo Program Key Concepts

- Structure definition using typedef
- Structure arrays for multiple records
- Function prototypes for scope visibility
- Constants used for array size safety
- Loop-based input and output
- Compound printf usage
- Clearing screen before output for clarity

6. What a Union Is

- A **union** is a composite data type similar to a structure.
- All members share the **same memory location**.
- Only **one member is valid at a time**.
- Size of a union = size of its **largest member**.

7. Structures vs Unions (Key Difference)

- **Structure:** All members exist simultaneously & More memory usage
- **Union:** Members overwrite each other & Memory-efficient
- Use unions when a value can take **only one form at a time**

8. Why Use Unions

- Save memory
- Ideal when:
 - data can be multiple types, but never simultaneously
- Common in:
 - embedded systems, low-level programming & protocol parsing

9. Type Casting (Concept)

- **Type casting** converts one data type into another.
- Ensures operations are performed correctly.
- Prevents unnecessary memory usage.
- Required when data types are **not naturally compatible**.

10. Type Promotion and Demotion

- **Promotion**
 - Smaller type → larger type
 - Safe (no data loss)
- **Demotion**
 - Larger type → smaller type
 - Risk of data loss
- Compiler follows a **data type hierarchy**

11. Explicit Type Casting

- Done **manually** by the programmer.
- Used when:
 - demotion is required, precision loss is acceptable
- Fractional parts are discarded when casting to int

Syntax

```
(type) expression
```

12. Correct Rounding Using Type Casting

- Add 0.5 **before casting** to int
- Parentheses are critical
- Prevents incorrect truncation
- Operator precedence matters

- Retains value between function calls
- Can be used: At file scope or At block scope
- Effects:
 - Internal linkage at file scope
 - Local scope but persistent lifetime inside functions
- Cannot be used in function parameter lists

12. Static Arrays in Function Parameters

- Indicates array pointer is:
 - Non-null
 - At least a certain size
- Helps compiler optimization and safety

13. Extern Storage Class

- Used for sharing variables across source files
- Characteristics:
 - External linkage (unless declared static)
 - Static storage duration
- Memory:
 - Allocated before main()
 - Deallocated when program ends
- **extern** keyword optional if:
 - Declaration is outside a function
 - Variable already has file scope

14. Scope Rules for extern

- Inside a block:
 - Refers to existing global variable
- Outside functions:
 - Creates external linkage unless static
- If variable was previously declared static, **extern** will not override it

15. Choosing the Right Storage Class

Guidelines:

- Use **static** → when value must persist across calls
- Use **register** → for heavily reused variables
- Use **extern** → for shared global data
- Use **auto** → default for most local variables

16. Scope and Code Security

- Scope limits access → reduces attack surface
- Variables should only be accessible where needed
- Improper scope increases vulnerability risk
- Security begins with **controlled visibility**

- 17. Environment Awareness**
- Program behavior depends on:
 - OS
 - Hardware
 - Execution environment
 - Portable code may expose new vulnerabilities
 - Environment-specific optimization improves:
 - Security
 - Performance

- 18. Scope as First Security Boundary**
- Defines what parts of the program can be accessed
 - Helps identify:
 - External interaction points
 - Attack surface
 - Secure scope design reduces misuse potential

- 19. Demo Key Takeaways**
- Function prototypes enable visibility before definition
 - Variables declared below main() are not visible unless prototyped
 - Local variables override globals with same name
 - Static variables persist across function calls
 - Scope position in code determines accessibility
 - Formatting specifiers control output precision

- 20. Core Things to Remember**
- Scope controls visibility
 - Storage class controls lifetime and linkage
 - Local > global in name conflicts
 - Static ≠ global (lifetime ≠ scope)
 - Extern links across files
 - Smaller scope = safer code
 - Secure code starts with proper scoping

- 5. Passing Structures to Functions**
- Can be passed: by value (copy) or by reference (pointer)
 - Passing by reference is preferred for:
 - performance & large structures
 - Supports comparisons and assignments

- 3. Structure Memory Behavior**
- Memory allocated = sum of sizes of all members (plus padding)
 - All members exist **at the same time**
 - Each member has its own address
 - Efficient for representing grouped data like:
 - student records
 - employee details
 - sensor data

- 2. Structures vs Arrays**
- **Arrays**
 - Store multiple values of the **same type**
 - **Structures**
 - Store multiple values of **different types**
 - Both use contiguous memory
 - Arrays model collections
 - Structures model **real-world records**

- 1. What a Structure Is**
- A **structure (struct)** is a **composite data type** in C.
 - It groups **different data types** under one name.
 - Members are stored in **contiguous memory**.
 - Represents a **record** (related fields grouped together).
 - Access members using the **dot (.) operator**.
 - Structure variables:
 - can be passed to functions
 - can be returned from functions
 - behave like ordinary variables

- Never dereference invalid memory
- Don't perform arithmetic on void pointers
- Only compare pointers within the same object
- Free memory and set pointer to NULL
- Prefer clarity over cleverness

16. The Core Takeaways

- Pointers are **fundamental**, not optional, in C
- They give **direct control over memory**
- With power comes responsibility:
 - Efficiency vs safety is a deliberate tradeoff
- Mastering pointers unlocks:
 - Dynamic memory
 - Data structures
 - Systems programming

Computer Science(UX Design) -Lecture 20

1. What an Array Is

- An **array** is a data structure that stores a **collection of elements of the same data type**.
- Elements are stored in **contiguous memory locations**.
- All elements are accessed using:
 - one variable name
 - an **index** to identify each element
- Arrays are **homogeneous** (same data type).

2. Why Arrays Are Needed

- Managing large collections of data (e.g., 1000 values) using individual variables is:
 - inefficient
 - unreadable
 - wasteful
- Arrays allow:
 - compact code
 - loop-based processing
 - scalable data handling
- Arrays are foundational to:
 - searching algorithms
 - sorting algorithms
 - stacks, queues, hash tables, linked lists
 - strings
 - databases
 - graphics and mathematical models

3. Historical Context (Conceptual)

- Early arrays were implemented via:
 - self-modifying code
 - memory segmentation
- Modern high-level languages provide native array support
- CPUs are often optimized for array operations

4. Array Declaration Methods

Method 1: Declare and initialize

```
int a[] = {1, 2, 3, 4};
```

- Compiler infers array size.

Method 2: Declare with size, initialize later

```
int a[10];
```

- Elements assigned at runtime (input, computation, file I/O).

5. Array Size Rules

- Size must be specified at compile time (except VLAs).
- Size **cannot be changed after compilation**.
- From C99 onward:
 - **Variable Length Arrays (VLA)** are supported.
- Over-allocating wastes memory.

6. Indexing Rules

- Array indices start at 0.
- Valid indices:
 - 0 to size - 1
- Accessing out-of-bounds indices:
 - causes undefined behavior
 - may not be caught at compile time
 - often leads to runtime bugs

7. Arrays and Memory

- Arrays occupy **contiguous memory**.
- Memory usage = size × sizeof(data_type)
- Example:
 - int ages[14];
 - If sizeof(int) = 4 bytes, total = 56 bytes
- Efficient access due to predictable memory layout.

8. Using Loops with Arrays

- **for-loops** are the primary tool for array traversal.
- Common pattern:
 - iterate from 0 to size - 1
- Allows:
 - sequential access
 - bulk operations
 - scalable logic

9. Assigning and Accessing Elements

```
----- Assign using index: -----
ages[5] = 21;
-----</pre>
```

- Random access is allowed (not just sequential).
- Arithmetic and logical operations work the same as with normal variables.

10. Common Array Errors

- Incorrect index calculations
- Mixing loop bounds
- Off-by-one errors
- Using uninitialized arrays
- Runtime errors instead of compile-time errors
- Most array bugs come from **index misuse**

11. Arithmetic Operations on Arrays

- Element-wise operations using loops:
 - addition, subtraction, multiplication, division, modulus

10. How Pointer Arithmetic Works

- Pointer arithmetic is scaled by data type size
- Example:
 - int *p
 - p++ moves 4 bytes, not 1

Formula

new_address = old_address + (offset × sizeof(type))

11. Arrays and Pointers (Critical Relationship)

- Array name = base address
- Arrays decay into pointers when passed to functions

```
----- Access elements using: -----
*(p + i)
-----</pre>
```

- Incrementing a pointer walks through array elements.
- Never exceed array bounds → undefined behavior / crash.

12. Operator Precedence with Pointers

Key distinctions:

Description	*p++	(*p)++	Increment value	Increment value	Increment pointer
					++p

- * and + have same precedence
- **Associativity resolves ambiguity**
- Parentheses are strongly recommended

13. Linked Lists (Why Pointers Matter)

- Non-contiguous memory
- Advantages:
 - Easy insertion/deletion
- Each node contains:
 - Data
 - Pointer to next node
- Disadvantages:
 - No random access
 - Cache inefficiency
 - Extra memory per node

14. Dangling Pointers (Major Danger)

Occurs when:

1. Memory is freed but pointer still references it
2. Variable goes out of scope
3. Pointer references local variables after function exit

Result:

- Dereferencing yields garbage
- High risk of crashes

15. Best Practices to Remember

- Always initialize pointers
- Use NULL for safety
- Avoid complex expressions with ++ and --

5. Pointer Declaration and Dereferencing

Declaration
int *p;

- * tells the compiler this variable is a pointer.
- Pointer must store an **address**, not a value.

Assignment
p = &x;

- & gives the base address of x.

Dereferencing
*p

- Accesses the **value stored at the address**.
- p → address
- *p → data at that address

6. Initialization Rules (Very Important)

- **Uninitialized pointers = undefined behavior**

- Always :
 - With a valid address
 - Or with NULL

Initialization
int *p = NULL;

- Use NULL, not 0, for clarity and safety.

7. Pointer Types

7.1 Data Pointers

- Point to variables of a specific type.

7.2 Function Pointers

- Store the address of a function.
- Used for:
 - Callbacks
 - Replacing switch statements
 - Avoiding code duplication

7.3 Void Pointers

- Generic pointer (void *)
- Can point to any data type
- **Cannot be dereferenced**
- Pointer arithmetic is **non-portable**

7.4 Double Pointers

- Pointer to another pointer (**)
- Used for:
 - Modifying pointers in functions
 - 2D arrays
 - API compatibility

8. Pass-by-Reference Using Pointers

- Allows a function to modify original data.
- Efficient for large data structures.
- Should only be used when modification is required.
- Improves performance and avoids unnecessary copying.

9. Pointer Arithmetic (Rules That Matter)

Allowed Operations:

- Increment (p++), Decrement (p--)
- Add/subtract integer
- Subtract two pointers (same object only)
- Comparison (same object only)
- Assignment

Forbidden / Dangerous

- Adding two pointers
- Multiplication/division
- Arithmetic on unrelated memory
- Crossing array bounds

- Data type choice matters:
 - int division loses fractional part
 - Use float arrays for division results

12. Example Pattern (Two Arrays)

- Read values into arrays A and B
- Perform operations element-wise
- Store results in separate arrays
- Display results in tabular format

13. Logical Operations on Arrays

- Logical checks can be applied per element
- Index correctness is critical
- Useful for:
 - filtering data
 - condition-based processing

14. Strings as Arrays

- In C, a **string is a character array**.
- Ends with a **null terminator** '\0'.
- Each element occupies **1 byte**.

Syntax
char name[20];

15. String Initialization Methods

Using string literal:
char s[] = "Hello";

Specify size:
char s[10] = "Hello";

Character-by-character:
char s[] = {'H','e','l','l','o','\0'};

Character-by-character with size specified
char s[6] = {'H','e','l','l','o','\0'};

- '\0' must be included when manually initializing.

16. Reading Strings with scanf

- %s stops at whitespace.
 - Cannot read full names with spaces.
 - Solution: **edit set conversion**
- scanf("%[^\n]", name);
- Reads until newline.

17. string.h Header File

Provides utilities for string manipulation:

- Reduces manual errors
- Must be included explicitly
- Header files should be explored before use

18. Common String Functions (Core)

- strcat() → concatenate strings
- strncat() → concatenate first n characters
- strcmp() → compare strings
- strncmp() → compare first n characters
- strcpy() → copy string
- strncpy() → copy first n characters
- strlen() → length excluding '\0'
- strchr() → first occurrence of character
- strrchr() → last occurrence of character

- 1. What a Pointer Is (Core Idea)**
- A **pointer** is a variable that stores a memory address, not a value.
 - That address usually points to another variable.
 - Pointers exist because programs ultimately operate on **memory locations**, not names.
 - Especially critical in **C, low-level programming, OS kernels, embedded systems, and drivers.**
- Key Point:** Pointer = reference / direction sign, not the destination itself.

- 2. Memory, Addresses, and Base Address**
- **Byte** is the smallest addressable unit of memory.
 - Variables may occupy **multiple bytes** (e.g., long long int → 8 bytes).
 - The **base address** = address of the first byte of a variable.
 - Only the base address is needed because:
 - The compiler already knows the variable's size.
 - It computes the full memory span automatically.
- 3. Data Primitives vs Data Aggregates**
- **Data primitive:** single readable/writable unit in memory.
 - **Data aggregate:** group of primitives treated as one object.
 - Examples: arrays, structures.
 - Arrays are:
 - Contiguous in memory
 - Each element has its own address
 - The array name refers to the **base address**
- 4. Why Pointers Exist (Practical Reasons)**
- Pointers are essential for:
- 1. Dynamic data structures**
 - Linked lists, trees, graphs
 - 2. Dynamic memory allocation**
 - malloc, calloc, free
 - 3. Efficiency**
 - Passing addresses instead of copying data
 - 4. Pass-by-reference**
 - Modify variables across functions
 - 5. Returning multiple values**
 - Via output parameters
 - 6. Interfacing with low-level APIs**
 - 7. Reducing memory footprint**
 - Especially for arrays and large structures

- 20. Multi-Dimensional Arrays**
- Arrays can have multiple dimensions.
 - A **2D array** represents:
 - rows × columns (table)
 - int a[rows][cols];
 - First index → row
 - Second index → column
- 21. Higher-Dimensional Arrays**
- 3D and beyond supported:
int a[x][y][z];
 - Used in:
 - graphics
 - simulations
 - mathematical modeling
 - 3D data representation
- 22. Two-Dimensional Array Access**
- Requires **nested loops**:
 - outer loop → rows
 - inner loop → columns
 - Enables structured data processing
- 23. Demo: Multiplication Table**
- Uses:
 - 2D array
 - nested loops
 - Stores multiplication results
 - Displays formatted table
 - Demonstrates:
 - real-world array usage
 - separation of computation and display
- 24. The Core Takeaways**
- Arrays store homogeneous data
 - Indexing starts at zero
 - Out-of-bounds access is dangerous
 - Arrays occupy contiguous memory
 - Size must match actual usage
 - Loops are essential for arrays
 - Strings are character arrays
 - '\0' terminator is mandatory
 - String functions require caution
 - Most array bugs are logic bugs, not syntax errors
 - Multi-dimensional arrays model structured data naturally