www.agelectronica.com
www.agelectronica.com

International
IOR Rectifier

Data Sheet No. PD-6.043C

IR2101

HIGH AND LOW SIDE DRIVER

Features

- Floating channel designed for bootstrap operation
  Fully operational to +600V
  Tolerant to negative transient voltage
  dV/dt immune
- Gate drive supply range from 10 to 20V
- Undervoltage lockout
- 5V Schmitt-triggered input logic
- Matched propagation delay for both channels
- Outputs in phase with inputs

Product Summary

V_{OFFSET}	600V max.
I_O+/-	100 mA / 210 mA
V_{OUT}	10 - 20V
$t_{on/off}$ (typ.)	130 & 90 ns
Delay Matching	30 ns

Description

The IR2101 is a high voltage, high speed power MOSFET and IGBT driver with independent high and low side referenced output channels. Proprietary HVIC and latch immune CMOS technologies enable ruggedized monolithic construction. The logic input is compatible with standard CMOS or LSTTL outputs. The output drivers feature a high pulse current buffer stage designed for minimum driver cross-conduction. The floating channel can be used to drive an N-channel power MOSFET or IGBT in the high side configuration which operates up to 600 volts.

Packages



Typical Connection



www.agelectronica.com
www.agelectronica.com

Absolute Maximum Ratings

Absolute Maximum Ratings indicate sustained limits beyond which damage to the device may occur. All voltage parameters are absolute voltages referenced to COM. The Thermal Resistance and Power Dissipation ratings are measured under board mounted and still air conditions.

Parameter			Value		
Symbol	Definition		Min.	Max.	Units
V_B	High Side Floating Supply Voltage		-0.3	625	V
V_S	High Side Floating Supply Offset Voltage		V_B - 25	V_B + 0.3	
V_{HO}	High Side Floating Output Voltage		V_S - 0.3	V_B + 0.3	
V_{CC}	Low Side and Logic Fixed Supply Voltage		-0.3	25	
V_{LO}	Low Side Output Voltage		-0.3	V_{CC} + 0.3	
V_{IN}	Logic Input Voltage (HIN & LIN)		-0.3	V_{CC} + 0.3	
dV_S/dt	Allowable Offset Supply Voltage Transient		—	50	V/ns
P_D	Package Power Dissipation @ $T_A \leq +25°C$	(8 Lead DIP)	—	1.0	W
		(8 Lead SOIC)	—	0.625	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(8 Lead DIP)	—	125	°C/W
		(8 Lead SOIC)	—	200	
T_J	Junction Temperature		—	150	°C
T_S	Storage Temperature		-55	150	
T_L	Lead Temperature (Soldering, 10 seconds)		—	300	

Recommended Operating Conditions

The Input/Output logic timing diagram is shown in Figure 1. For proper operation the device should be used within the recommended conditions. The V_S offset rating is tested with all supplies biased at 15V differential.

Parameter		Value		
Symbol	Definition	Min.	Max.	Units
V_B	High Side Floating Supply Absolute Voltage	V_S + 10	V_S + 20	V
V_S	High Side Floating Supply Offset Voltage	Note 1	600	
V_{HO}	High Side Floating Output Voltage	V_S	V_B	
V_{CC}	Low Side and Logic Fixed Supply Voltage	10	20	
V_{LO}	Low Side Output Voltage	0	V_{CC}	
V_{IN}	Logic Input Voltage (HIN & LIN)	0	V_{CC}	
T_A	Ambient Temperature	-40	125	°C

Note 1: Logic operational for V_S of -5 to +600V. Logic state held for V_S of -5V to $-V_{BS}$.

www.agelectronica.com
www.agelectronica.com

Dynamic Electrical Characteristics

V_{BIAS} (V_{CC}, V_{BS}) = 15V, C_L = 1000 pF and T_A = 25°C unless otherwise specified.

Symbol	Parameter Definition	Value Min.	Typ.	Max.	Units	Test Conditions
t_{on}	Turn-On Propagation Delay	—	130	200	ns	V_S = 0V
t_{off}	Turn-Off Propagation Delay	—	90	200		V_S = 600V
t_r	Turn-On Rise Time	—	80	120		
t_f	Turn-Off Fall Time	—	40	70		
MT	Delay Matching, HS & LS Turn-On/Off	—	30	—		

Static Electrical Characteristics

V_{BIAS} (V_{CC}, V_{BS}) = 15V and T_A = 25°C unless otherwise specified. The V_{IN}, V_{TH} and I_{IN} parameters are referenced to COM. The V_O and I_O parameters are referenced to COM and are applicable to the respective output leads: HO or LO.

Symbol	Parameter Definition	Value Min.	Typ.	Max.	Units	Test Conditions
V_{IH}	Logic "1" Input Voltage	2.7	—	—	V	V_{CC} = 10V to 20V
V_{IL}	Logic "0" Input Voltage	—	—	0.8		V_{CC} = 10V to 20V
V_{OH}	High Level Output Voltage, V_{BIAS} - V_O	—	—	100	mV	I_O = 0A
V_{OL}	Low Level Output Voltage, V_O	—	—	100		I_O = 0A
I_{LK}	Offset Supply Leakage Current	—	—	50	µA	V_B = V_S = 600V
I_{QBS}	Quiescent V_{BS} Supply Current	—	20	50		V_{IN} = 0V or 5V
I_{QCC}	Quiescent V_{CC} Supply Current	—	140	240		V_{IN} = 0V or 5V
I_{IN+}	Logic "1" Input Bias Current	—	20	40		V_{IN} = 5V
I_{IN-}	Logic "0" Input Bias Current	—	—	1.0		V_{IN} = 0V
V_{CCUV+}	V_{CC} Supply Undervoltage Positive Going Threshold	8.8	9.3	9.8	V	
V_{CCUV-}	V_{CC} Supply Undervoltage Negative Going Threshold	7.5	8.2	8.6		
I_{O+}	Output High Short Circuit Pulsed Current	100	125	—	mA	V_O = 0V, V_{IN} = 5V PW ≤ 10 µs
I_{O-}	Output Low Short Circuit Pulsed Current	210	250	—		V_O = 15V, V_{IN} = 0V PW ≤ 10 µs

www.agelectronica.com
www.agelectronica.com

Functional Block Diagram



Lead Definitions

Lead Symbol	Description
HIN	Logic input for high side gate driver output (HO), in phase
LIN	Logic input for low side gate driver output (LO), in phase
V_B	High side floating supply
HO	High side gate drive output
V_S	High side floating supply return
V_{CC}	Low side and logic fixed supply
LO	Low side gate drive output
COM	Low side return

Lead Assignments

	
8 Lead DIP	SO-8
IR2101	**IR2101S**

www.agelectronica.com
www.agelectronica.com

Device Information

Process & Design Rule			HVDCMOS 4.0 µm
Transistor Count			168
Die Size			67 X 91 X 26 (mil)
Die Outline			
Thickness of Gate Oxide			800Å
Connections		Material	Poly Silicon
	First Layer	Width	4 µm
		Spacing	6 µm
		Thickness	5000Å
		Material	Al - Si (Si: 1.0% ±0.1%)
	Second Layer	Width	6 µm
		Spacing	9 µm
		Thickness	20,000Å
Contact Hole Dimension			5 µm X 5 µm
Insulation Layer		Material	PSG (SiO_2)
		Thickness	1.5 µm
Passivation		Material	PSG (SiO_2)
		Thickness	1.5 µm
Method of Saw			Full Cut
Method of Die Bond			Ablebond 84 - 1
Wire Bond		Method	Thermo Sonic
		Material	Au (1.0 mil / 1.3 mil)
Leadframe		Material	Cu
		Die Area	Ag
		Lead Plating	Pb : Sn (37 : 63)
Package		Types	8 Lead PDIP / SO-8
		Materials	EME6300 / MP150 / MP190
Remarks:			

www.agelectronica.com
www.agelectronica.com



Figure 1. Input/Output Timing Diagram



Figure 2. Switching Time Waveform Definitions



Figure 3. Delay Matching Waveform Definitions