2-1

```
Create or replace view test2_01 as
   select distinct pub.student.sid, pub.student.name
   from pub.student , pub.student_course
   where pub.student.sid not in(
      select distinct sid
      from    pub.student_course
   )
```

2-2

```
create or replace view test2_02 as
(select distinct pub.student.sid, pub.student.name
   from pub.student,pub.student_course
   where pub.student.sid= pub.student_course.sid and pub.student_course.cid in
(select distinct pub.student_course.cid
   from pub.student_course
   where pub.student_course.sid = 200900130417
))minus
(select distinct pub.student.sid, pub.student.name
   from pub.student
   where pub.student.sid = 200900130417
   )
```

2-3

```
create or replace view test2_03 as
select pub.student.sid, pub.student.name
from pub.student, pub.student_course
where pub.student.sid = pub.student_course.sid
   and
   pub.student_course.cid in
(select cid
   from pub.course
   where pub.course.fcid = 300002
)
```

2-4

```
create or replace view test2_04 as
(select pub.student.sid, pub.student.name
   from pub.student, pub.student_course a,pub.student_course b,pub.course c, pub.course d
  where pub.student.sid = a.sid
   and pub.student.sid = b.sid
   and a.cid = c.cid
   and b.cid = d.cid
   and c.name = '操作系统'
   and d.name = '数据结构'
)minus
(select pub.student.sid, pub.student.name
```

```
   from pub.student,pub.student_course, pub.course
   where pub.student.sid = pub.student_course.sid
   and pub.student_course.cid = pub.course.cid
   and pub.course.name = '程序设计语言'



   )
2-5
create or replace view test2_05 as
select a.sid,c.cid, c.name, b.score
       from pub.student_course b, pub.course c, pub.student a
       where b.cid = c.cid
       and a.sid = b.sid
       and a.name = '李龙'
2-6
create or replace view test2_06 as
select pub.student_course.sid, pub.student.name, pub.student_course.score
   from pub.student_course, pub.student, pub.course
   where pub.student_course.sid = pub.student.sid
   and pub.student_course.cid = pub.course.cid
   and pub.student.class = 2010
   and pub.student.dname = '计算机科学与技术学院'
   and pub.course.name = '操作系统'
2-7
create or replace view test2_07 as
(select all pub.student.sid, pub.student.name
   from pub.student)
   minus
   ((select all pub.student.sid, pub.student.name
   from pub.student
   where pub.student.name like'张%'
   )union
   (select all pub.student.sid, pub.student.name
   from pub.student
   where pub.student.name like'李%')
   union
   select all pub.student.sid, pub.student.name
   from pub.student
   where pub.student.name like'王%'
   )
2-8
create or replace view test2_08 as
select a.cid, a.name
from pub.course a, pub.course b
```

```
where a.fcid = b.cid and b.fcid is not null
```

2-9

```
create or replace view test2_09 as
select a.sid, a.name ,b.score
from pub.student a, pub.student_course b
where a.sid = b.sid
and b.cid = 300003
```

2-10

```
create or replace view test2_10 as
select pub.student.sid, pub.student.name
   from pub.student, pub.student_course
   where pub.student.sid = pub.student_course.sid
   group by pub.student.name, pub.student.sid
   having count(pub.student_course.cid)
   = (select count(distinct cid)
      from pub.student_course
   )
```