3-1

```
create table test3_01 as
select *
from pub.student_31

delete from test3_01
where not regexp_like(sid,'[0-9]{12}')
```

3-2

```
create table test3_02 as
(select *
   from pub.student_31)

delete from test3_02
where (2012 - extract(year from test3_02.birthday)) <> test3_02.AGE
```

3-3

```
create table test3_03 as
(select *
   from pub.student_31)

delete from test3_03
where sex not in('男','女','null')
```

3-4

```
create table test3_04 as
(select *
   from pub.student_31)

delete from test3_04
where test3_04.dname like '%%' or length(test3_04.dname)<3 or test3_04.dname is null
```

3-5

```
create table test3_05 as
(select *
   from
   pub.student_31
   )

select class,count(*)
from test3_05
group by class

delete
   from test3_05
```

```
   where class in
(select class
   from test3_05
   group by class
   having count(*)<100
)
3-6
create table test3_06 as(
   select *
   from pub.student_31
)

delete
from test3_06 a
where    not regexp_like(a.sid,'[0-9]{12}')
or a.age != 2012 - extract(year from a.birthday)
or a.name like '% %'
or length(a.name)<2
or a.sex not in('男','女','null')
or dname like '% %'
or dname is null
or length(a.dname)<3
or class in (
   select class
   from test3_06
   group by class
   having count(*)<100
)

3-7
create table test3_07 as
(
   select *
   from pub.student_course_32
)

delete
from test3_07
where test3_07.sid    not in(
   select sid
   from pub.student
)
3-8
create table test3_08 as(
```

```
    select *
    from pub.student_course_32
)

delete
from test3_08
where (test3_08.tid, test3_08.cid)not in(
    select a.tid, a.cid
    from test3_08 a, pub.teacher_course b
    where a.tid = b.tid and a.cid = b.cid
)
3-9
create table test3_09 as
(
    select *
    from pub.student_course_32)

delete
from test3_09
where test3_09.score<0 or test3_09.score >100
3-10
create table test3_10 as
(select *
    from pub.student_course_32
)

delete
from test3_10 a
where a.sid not in(
    select sid
    from pub.student
)
or a.cid not in(
    select cid
    from pub.course
)
    or a.score <0
    or a.score >100
or a.tid not in(
    select tid
    from pub.teacher
)
or(a.cid, a.tid) not in(
    select b.cid, b.tid
```

```
    from test3_10 b, pub.teacher_course c
    where b.cid = c.cid and b.tid = c.tid
)
```