4-1

```
create table test4_01 as
(select *
   from pub.student_41
)

alter table test4_01 add sum_score int

update test4_01 a
set a.sum_score = (
select sum(b.score)
from pub.student_course b

where a.sid = b.sid
)
```

4-2

```
create table test4_02 as
(select *
   from pub.student_41)

alter table test4_02 add avg_score numeric(4,1)

update test4_02
set avg_score = (
   select avg(pub.student_course.score)
   from pub.student_course
      where test4_02.sid = pub.student_course.sid
   group by pub.student_course.sid

)
```

4-3

```
create table test4_03 as
(select *
   from pub.student_41)

alter table test4_03 add sum_credit int

update test4_03
set sum_credit = (
   select sum(a.credit)
   from pub.course a,(select distinct sid, cid
   from pub.student_course
   where pub.student_course.score >= 60
   )   b
```

```
   where a.cid = b.cid and test4_03.sid = b.sid
   group by b.sid
)
4-4
create table test4_04 as
(
   select *
   from pub.student_41
)

update test4_04 a
set a.dname = case
when exists(    select did from pub.department b
                where a.dname = b.dname)
       then (select did from pub.department b where a.dname = b.dname)
       else a.dname
end
4-5
create table test4_05 as
(select *
   from pub.student_41)
alter table test4_05 add sum_score int
alter table test4_05 add avg_score numeric(4,1)
alter table test4_05 add    sum_credit int
alter table test4_05 add    did varchar(2)
update test4_05 a
set sum_score = (
   select sum(b.score)
   from pub.student_course b
   where a.sid = b.sid
)
update test4_05 a
set avg_score = (
   select avg(b.score)
   from pub.student_course b
   where a.sid = b.sid
)
update test4_05 a
set sum_credit= (
   select sum(d.credit)
   from (select distinct b.sid, b.cid, c.credit
               from pub.student_course b ,pub.course c
                 where b.score >= 60 and c.cid = b.cid
   ) d
```

```
   where a.sid = d.sid
)
update test4_05 a
set did = case
when exists(
( select *
   from pub.department b1
      where a.dname    = b1.dname)
   union
   (select *
   from pub.department_41 b2
      where a.dname = b2.dname)
   )
   then (
   (select b1.did
   from pub.department b1
   where a.dname    = b1.dname)
   union(
   select b2.did
   from pub.department_41 b2
   where a.dname = b2.dname
   )
   )
   else '00'
   end
4-6
create table test4_06 as
(
   select *
   from pub.student_42
)
update test4_06 a
set name = case
when a.name not like '% %'
   then a.name
else (
   select regexp_replace(b.name,' ','')
   from test4_06 b
   where b.sid = a.sid
   )
end
4-7
create table test4_07 as
(
```

```
    select *
    from pub.student_42
)
update test4_07
set sex = case
when sex like '%男%' then '男'
when sex like '%女%' then '女'
else null
end
4-8
create table test4_08 as
(
    select *
    from pub.student_42
)
select class,count(*)
from test4_08
group by class

update test4_08
set class = regexp_replace(class,'级','')

4-9
create table test4_09 as(
    select*
    from pub.student_42
)
select age,count(*)
from test4_09
group by age

update test4_09
set age = case
when age is    null then    2012 - extract(year from birthday)
else age
end
4-10
create table test4_10 as(
    select *
    from pub.student_42
)
update test4_10
set name = regexp_replace(name, ' ','')
update test4_10
```

```
set dname = regexp_replace(dname, ' ','')
update test4_10
set sex = regexp_replace(sex, '性','')
update test4_10
set sex = regexp_replace(sex,' ','')
update test4_10
set class = regexp_replace(class,'级','')
update test4_10
set age = case
when age is null then 2012 - extract(year from birthday)
else age
end
```