6-1

```
create or replace view test6_01 as
select distinct sid,name,dname
   from pub.student
   where age <20 and dname ='物理学院'
   order by sid
```

6-2

```
create or replace view test6_02 as
select sid,name,sum(score)sum_score
from pub.student natural join pub.student_course
   where dname = '软件学院'and class = 2009
group by sid,name
union
select sid,name, (null)sum_score
from pub.student
where dname = '软件学院'and class = 2009 and sid
not in (select sid from pub.student natural join pub.student_course)
```

6-3

```
create or replace view test6_03 as
select a.cid, name, max(score)max_score,
   (select count(distinct sid)
   from pub.student_course c
   where c.cid = a.cid and score in(
   select max(score)score
   from pub.student_course d
   where d.cid = c.cid
   )
   group by c.cid
   )max_score_count
from    pub.course b, pub.student_course a
where a.cid = b.cid
group by a.cid, name
```

6-4

```
create or replace view test6_04 as
select distinct    a.sid, a.name
from pub.student a, pub.course b, pub.student_course c
where a.sid = c.sid and b.cid = c.cid and a.sex = '男'and
   ((b.name = '操作系统' and c.score>=60) or(b.name = '数据结构' and c.score>=60))
minus
select distinct a.sid,a.name
from pub.student a, pub.course b, pub.student_course c
where a.sid = c.sid and b.cid = c.cid and a.sex = '男'and
(b.name = '程序设计语言' and c.score >=60)
```

6-5

```
create or replace view test6_05 as
select distinct a.sid, a.name,round(avg(score),0)avg_score,sum(score)sum_score
from pub.student a, pub.student_course b
where a.sid = b.sid and age = 20
group by a.sid,a.name
```

6-6

```
create or replace view test6_06 as
select distinct a.sid, a.name
from pub.student a, pub.student_course b
where a.sid = b.sid and b.score < 60
group by a.sid,a.name, b.cid
having count(*) >= 2
```

6-7

```
create or replace view test6_07 as
select distinct sid , name
from pub.student
where sid not in(
   select sid
   from (
   select sid, cid
   from pub.student, pub.course
   minus
   select sid, cid
   from pub.student_course
   )
) and sid not in(
   select distinct sid
   from pub.student_course
   where score<60
   )
```

6-8

```
create or replace view test6_08 as
select sid,name
from pub.student
where sid not in(
   select sid
   from(
   select sid,cid
   from pub.student, pub.course
   minus
   select sid,cid
   from pub.student_course
   )
```

```
)and sid not in(
    select sid
    from pub.student_course
    group by sid,cid
    having max(score)<60
)
6-9
create or replace view test6_09 as
select distinct a.sid,a.name ,(
select sum(temp.credit)
    from (
    select distinct b.sid, b.cid, c.credit
    from pub.student_course b ,pub.course c
    where b.cid = c.cid
    group by    b.sid,b.cid,c.credit
    having max(b.score)>=60
    )temp
    where temp.sid = a.sid) sum_credit
from pub.student a
where class = 2010 and dname = '化学与化工学院' and sid in(
    select sid
    from pub.student natural join pub.student_course
    where score >= 60 and class = 2010 and dname = '化学与化工学院'
)
6-10
create or replace view test6_10 as
select distinct substr(name,1,1)second_name,
    (select count(*)
    from pub.student b
    where substr(b.name,1,1) = substr(a.name,1,1)
    group by substr(b.name,1,1)
    )p_count
from pub.student a
```