

Cryptography Engineering

- Lecture 9 (Jan 16, 2024)
- Today's notes:
 - Recall previous contents
 - The OPAQUE protocol
 - Summary on password-based authentication
 - Notes on the final project
- Coding tasks/Homework:
 - Implement the OPAQUE protocol
 - **Bonus:** Implement OPAQUE using sockets

Previous lecture contents

- Welcome back from the Christmas holidays!
- L1: Recall some cryptographic primitives
- L2: Signature and Certificate
- L3: DHKE + Signature & Certificate = TLS handshake
- L4: Secure Messaging, E2EE, X3DH
- L5 & L6: Key chain, Double ratchet = Symmetric ratchet + DH ratchet
- L7: Passwords, Off/Online attacks, TLS + passwords, Salting
- L8: SCRAM (hashed+salted+iterated), Password-based AKE (EKE, SRP)

Previous Password-based Protocols

- TLS + hashed & salted passwords
- The SCRAM protocol
- The EKE protocol
- The SRP protocol

Previous Password-based Protocols

- TLS + hashed & salted passwords
 - The SCRAM protocol
 - The EKE protocol
 - The SRP protocol
-
- Goal: Authentication via passwords; Resistance to offline attacks.

Previous Password-based Protocols

- **TLS + hashed & salted passwords**
 - Store $(r, H(pw, r))$ in the server, where r is the salt.
 - Transport r to the client, then the client prove its identity by responding $H(pw, r)$
 - Encrypted by TLS
- The SCRAM protocol
- The SRP protocol

Previous Password-based Protocols

- TLS + hashed & salted passwords
- **The TLS + SCRAM protocol**
 - Store $(r, n, H^n(pw, r))$ in the server, where r is the salt and n is the number of iterations.
 - Transport r and n to the client, then the client prove its identity by responding $H^n(pw, r)$
 - Encrypted by TLS
- The SRP protocol

Previous Password-based Protocols

- TLS + hashed & salted passwords
- The TLS + SCRAM protocol
- **The SRP protocol**
 - Store $(r, H(pw, r))$ in the server, where r is the salt.
 - Password-based AKE:
 - Security guarantee even if the certificate is fake or the TLS connection is insecure.
 - Enhanced security via integrating with TLS

Previous Password-based Protocols

- TLS + hashed & salted passwords
- The TLS + SCRAM protocol
- The SRP protocol
- Advantage of storing hashed-salted passwords:
 1. Avoid cross-system leakage

Previous Password-based Protocols

- TLS + hashed & salted passwords
- The TLS + SCRAM protocol
- The SRP protocol
- Advantage of storing hashed-salted passwords:
 1. Avoid cross-system leakage
 2. Increase the time **required to recover the password after leakage.**

Previous Password-based Protocols

- TLS + hashed & salted passwords
- The TLS + SCRAM protocol
- The SRP protocol
- Advantage of storing hashed-salted passwords:
 1. Avoid cross-system leakage
 2. Increase the time **required to recover the password after leakage**.

Storage	Required Time after leakage
Plain pw	$O(1)$
$H(pw)$	$O(D)$
$r, H(pw, r)$	$O(D)$

Previous Password-based Protocols

- TLS + hashed & salted passwords
- The TLS + SCRAM protocol
- The SRP protocol
- Advantage of storing hashed-salted passwords:
 1. Avoid cross-system leakage
 2. Increase the time **required to recover the password after leakage**.

Storage	Required Time after leakage
Plain pw	$O(1)$
$H(\text{pw})$	$O(D)$
$r, H(\text{pw}, r)$	$O(D)$

This is also important in practice, e.g., notifying users to change their passwords after the leakage.

Previous Password-based Protocols

- TLS + hashed & salted passwords
- The TLS + SCRAM protocol
- The SRP protocol
- Advantage of storing hashed-salted passwords:
 1. Avoid cross-system leakage
 2. Increase the time **required to recover the password after leakage**.

Storage	Required Time after leakage
Plain pw	$O(1)$
$H(pw)$	$O(D)$
$r, H(pw, r)$	$O(D)$

- All protocols **reveal salt** (and the number of iterations) during the execution...

Previous Password-based Protocols



- TLS + hashed & salted passwords
- The TLS + SCRAM protocol
- The SRP protocol
- Advantage of storing hashed-salted passwords:
 1. Avoid cross-system leakage
 2. Increase the time **required to recover the password after leakage**.

Storage	Required Time after leakage
Plain pw	$O(1)$
$H(pw)$	$O(D)$
$r, H(pw, r)$	$O(D)$

- All protocols **reveal salt** (and the number of iterations) during the execution...
 - May lead to **Precomputation Attacks**
 - $O(|D|) \rightarrow O(\log|D|)$ or even $O(1)$



Precomputation Attacks on Passwords

- Suppose that the password is stored by hashing and salting.
 - **The adversary can learn the salt in some easy ways...**



Precomputation Attacks on Passwords

- Suppose that the password is stored by hashing and salting.
 - **The adversary can learn the salt in some easy ways...**




Username: Bob

Suppose that the adversary
knows the username...

Precomputation Attacks on Passwords


- Suppose that the password is stored by hashing and salting.
 - **The adversary can learn the salt in some easy ways...**



Suppose that the adversary knows the username...
Then it can get the salt...


Precomputation Attacks on Passwords

- Suppose that the password is stored by hashing and salting.
 - The adversary can learn the salt in some easy ways...
 - **Precompute a table containing all hashed passwords with the same salt:**



Precomputation Attacks on Passwords

- Suppose that the password is stored by hashing and salting.
 - The adversary can learn the salt in some easy ways...
 - **Precompute a table containing all hashed passwords with the same salt:**




$pw \in \text{Dict}$	The $H(pw, r)$ values
pw_1	$H(pw_1, r)$
pw_2	$H(pw_2, r)$
pw_3	$H(pw_3, r)$
pw_4	$H(pw_4, r)$
...	...

The table can be computed locally...

Precomputation Attacks on Passwords

- Suppose that the password is stored by hashing and salting.
 - The adversary can learn the salt in some easy ways...
 - **Precompute a table containing all hashed passwords with the same salt:**




$pw \in \text{Dict}$	The $H(pw, r)$ values
pw_1	$H(pw_1, r)$
pw_2	$H(pw_2, r)$
pw_3	$H(pw_3, r)$
pw_4	$H(pw_4, r)$
...	...

The table can be computed locally...


Precomputation Attacks on Passwords

- Suppose that the password is stored by hashing and salting.
 - The adversary can learn the salt in some easy ways...
 - **Precompute a table containing all hashed passwords with the same salt:**




Precomputation Attacks on Passwords

- Suppose that the password is stored by hashing and salting.
 - The adversary can learn the salt in some easy ways...
 - **Precompute a table containing all hashed passwords with the same salt:**




Precomputation Attacks on Passwords

- Suppose that the password is stored by hashing and salting.
 - The adversary can learn the salt in some easy ways...
 - **Precompute a table containing all hashed passwords with the same salt:**



Precomputation Attacks on Passwords

- Suppose that the password is stored by hashing and salting.
 - The adversary can learn the salt in some easy ways...
 - **Precompute a table containing all hashed passwords with the same salt:**



Precomputation Attacks on Passwords

- Comparison:

Attack Method to recover pw	Required Time <i>before</i> leakage	Required Time <i>after</i> leakage
Brute-force on Dictionary	-	$O(D)$
Precomputation	$\leq O(D \cdot \log D)$	$\leq O(\log D)$

Precomputation Attacks on Passwords

- Comparison:

Attack Method to recover pw	Required Time <i>before</i> leakage	Required Time <i>after</i> leakage
Brute-force on Dictionary	-	$O(D)$
Precomputation	$\leq O(D \cdot \log D)$	$\leq O(\log D)$

- Reveal salt during the protocol => Precomputation attacks
- How can we protect the salt?

Precomputation Attacks on Passwords

- Comparison:

Attack Method to recover pw	Required Time <i>before</i> leakage	Required Time <i>after</i> leakage
Brute-force on Dictionary	-	$O(D)$
Precomputation	$\leq O(D \cdot \log D)$	$\leq O(\log D)$


- Reveal salt during the protocol => Precomputation attacks
- How can we protect the salt?
 - No straight-forward solutions that without using algebraic structures
 - Solution using algebraic structures: **Oblivious Pseudorandom Function** (OPRF)
- PAKE without revealing salt: **OPAQUE**

DH-based OPRF

- Classical PRF:
 - Pseudorandomness: If the PRF key is random, then the output of PRF is pseudorandom


DH-based OPRF

- Classical PRF:
 - Pseudorandomness: If the PRF key is random, then the output of PRF is pseudorandom
- Oblivious PRF:
 - Pseudorandomness
 - PRF in the two-party (client-server) computation setting




DH-based OPRF

- Classical PRF:
 - Pseudorandomness: If the PRF key is random, then the output of PRF is pseudorandom
- Oblivious PRF:
 - Pseudorandomness
 - PRF in the two-party (client-server) computation setting
 - **Key privacy:** The client learns $\text{OPRF}(k, \text{input})$, **but it learns nothing about the key k**
 - **Input privacy:** The server knows the client has evaluated the ORRF, **but it does not know the input**



DH-based OPRF




(\mathbb{G}, g, q) :

A q -order group \mathbb{G} with a generator g


$h: \{0,1\}^* \rightarrow \mathbb{G}$

A hash function map the input into a group element


H : A normal hash function (e.g., SHA256,..)





DH-based OPRF



(\mathbb{G}, g, q) :
A q -order group \mathbb{G} with a generator g
 $h: \{0,1\}^* \rightarrow \mathbb{G}$
A hash function map the input into a group element
 H : A normal hash function (e.g., SHA256,..)



DH-based OPRF



Input: x

$$\alpha \leftarrow_{\$} \mathbb{Z}_q$$


$$(\mathbb{G}, g, q):$$

A q -order group \mathbb{G} with a generator g

$$h: \{0,1\}^* \rightarrow \mathbb{G}$$

A hash function map the input into a group element

H : A normal hash function (e.g., SHA256,..)



k

$$h(x)^\alpha$$


$$h(x)^{\alpha \cdot k} (= (h(x)^\alpha)^k)$$

Compute $\alpha^{-1} \in \mathbb{Z}_q$

$$h(x)^k = (h(x)^{\alpha \cdot k})^{\alpha^{-1}}$$

Compute $H(x, h(x)^k)$

DH-based OPRF




$$\alpha \leftarrow_{\$} \mathbb{Z}_q$$

Key Privacy: $h(x)^k$
 $\Rightarrow k$, solve dlog...

Compute $\alpha^{-1} \in \mathbb{Z}_q$
 $h(x)^k = (h(x)^{\alpha \cdot k})^{\alpha^{-1}}$
Compute $H(x, h(x)^k)$

(\mathbb{G}, g, q) :
A q -order group \mathbb{G} with a generator g
 $h: \{0,1\}^* \rightarrow \mathbb{G}$
A hash function map the input into a group element
 H : A normal hash function (e.g., SHA256,..)




$$h(x)^\alpha$$


$$h(x)^{\alpha \cdot k} (= (h(x)^\alpha)^k)$$

Input Privacy:
 $h(x)^\alpha$ is "random"...


DH-based OPRF



DH-based OPRF



DH-based OPRF



- Only the client knows the password

- Only the server knows the salt

DH-based OPRF



Input: pw

$$\alpha \leftarrow_{\$} \mathbb{Z}_q$$



Key: s (as the salt)

$$h(pw)^\alpha$$


$$h(pw)^{\alpha \cdot s}$$

$$h(pw)^s = (h(pw)^{\alpha \cdot s})^{\alpha^{-1}}$$
$$rw = H(pw, h(pw)^s)$$

- Only the client knows the password

- The rw value is pseudorandom by the pseudorandomness of OPRF, **but it can not be directly used as the session key!**
 - rw is always the same, but we expect that a new execution of the protocol produces a new session key...

DH-based OPRF



Input: pw

$$\alpha \leftarrow_{\$} \mathbb{Z}_q$$



Key: s (as the salt)

$$h(pw)^\alpha$$

$$h(pw)^{\alpha \cdot s}$$

$$h(pw)^s = (h(pw)^{\alpha \cdot s})^{\alpha^{-1}}$$
$$rw = H(pw, h(pw)^s)$$

- Only the client knows the password


- The rw value is pseudorandom by the pseudorandomness of OPRF, but it can not be directly used as the session key!
 - rw is always the same, but we expect that a new execution of the protocol produces a new session key...
- **Solution: Use AKE protocol to share a session key, and use rw to protect the AKE messages...**

DH-based OPRF + AKE

- Brief introduction of AKE (Authenticated Key Exchange)
 - Two parties share an authenticated key using their long-term key pairs


DH-based OPRF + AKE

- Brief introduction of AKE (Authenticated Key Exchange)
 - Two parties share an authenticated key using their long-term key pairs
 - For example:



- Security Requirement: Pseudorandom session key, authentication, ...

DH-based OPRF + AKE




pw



$$s, rw = H(pw, h(pw)^s)$$

Suppose that the
server has the *rw* value

DH-based OPRF + AKE



pw




$$s, rw = H(pw, h(pw)^s)$$


$(lpk_c, lsk_c) \leftarrow \text{AKE.KeyGen}$
 $(lpk_s, lsk_s) \leftarrow \text{AKE.KeyGen}$

Generate AKE key pairs

DH-based OPRF + AKE



pw



$$s, rw = H(pw, h(pw)^s)$$

$$(lpk_c, lsk_c) \leftarrow \text{AKE.KeyGen}$$

$$(lpk_s, lsk_s) \leftarrow \text{AKE.KeyGen}$$


$$\text{key_info} = (lpk_c, lsk_c, lpk_s)$$

$$rw_key = \text{KDF}(rw)$$

$$\text{enc_keys} = \text{AEAD}(rw_key, \text{key_info})$$

Encrypt generated keys
using rw

DH-based OPRF + AKE



pw



$$s, rw = H(pw, h(pw)^s)$$

$$(lpk_c, lsk_c), (lpk_s, lsk_s)$$

$$\text{key_info} = (lpk_c, lsk_c, lpk_s)$$

$$rw_key = \text{KDF}(rw)$$

$$\text{enc_keys} = \text{AEAD}(rw_key, \text{key_info})$$

DH-based OPRF + AKE



pw



$$s, rw = H(pw, h(pw)^s)$$

$$(lpk_c, lsk_c), (lpk_s, lsk_s)$$

$$\text{key_info} = (lpk_c, lsk_c, lpk_s)$$

$$rw_key = \text{KDF}(rw)$$

$$\text{enc_keys} = \text{AEAD}(rw_key, \text{key_info})$$

$$\alpha \leftarrow_{\$} \mathbb{Z}_q$$

$$h(pw)^\alpha$$

$$h(pw)^{\alpha \cdot s}$$

$$h(pw)^s = (h(pw)^{\alpha \cdot s})^{\alpha^{-1}}$$

$$rw = H(pw, h(pw)^s)$$

DH-based OPRF + AKE



pw



$$s, rw = H(pw, h(pw)^s)$$

$$(lpk_c, lsk_c), (lpk_s, lsk_s)$$

$$key_info = (lpk_c, lsk_c, lpk_s)$$

$$rw_key = KDF(rw)$$

$$enc_keys = AEAD(rw_key, key_info)$$

$$\alpha \leftarrow_{\$} \mathbb{Z}_q$$

$$h(pw)^\alpha$$

$$h(pw)^{\alpha \cdot s}, enc_keys$$


$$h(pw)^s = (h(pw)^{\alpha \cdot s})^{\alpha^{-1}}$$

$$rw = H(pw, h(pw)^s)$$


$$rw_key = KDF(rw)$$

$key_info = AEAD.Dec(rw_key, enc_keys)$ // Client gets (lpk_c, lsk_c, lpk_s)

DH-based OPRF + AKE



pw



$$s, rw = H(pw, h(pw)^s)$$

$$(lpk_c, lsk_c), (lpk_s, lsk_s)$$

$$key_info = (lpk_c, lsk_c, lpk_s)$$

$$rw_key = KDF(rw)$$

$$enc_keys = AEAD(rw_key, key_info)$$

$$\alpha \leftarrow_{\$} \mathbb{Z}_q$$

$$h(pw)^\alpha$$

$$h(pw)^{\alpha \cdot s}, enc_keys$$

$$h(pw)^s = (h(pw)^{\alpha \cdot s})^{\alpha^{-1}}$$


$$rw = H(pw, h(pw)^s)$$

$$rw_key = KDF(rw)$$


$$key_info = AEAD.Dec(rw_key, enc_keys) \quad // \text{ Client gets } (lpk_c, lsk_c, lpk_s)$$

Now the client can run the
AKE protocol with Server


OPQAUE – Overview of Registration



OPQAUE – Overview of Registration




OPQAUE – Stage 1: OPRF




Username, password: *pw*

$$\alpha \leftarrow_{\$} \mathbb{Z}_q$$


LoginRequest = (Username, $h(\textit{pw})^\alpha$)



OPQAUE – Stage 1: OPRF



Username, password: *pw*




$$\alpha \leftarrow_{\$} \mathbb{Z}_q$$


LoginRequest = (Username, $h(\textit{pw})^\alpha$)

Retrieve (*s*, *rw*, server_k_bundle, client_enc_k_bundle)
// ...corresponds to the username

OPQAUE – Stage 1: OPRF



Username, password: pw



$$\alpha \leftarrow_{\$} \mathbb{Z}_q$$

LoginRequest = (Username, $h(pw)^\alpha$)

Retrieve (s, rw , server_k_bundle, client_enc_k_bundle)

// ...corresponds to the username

$h(pw)^{\alpha \cdot s}$, client_enc_k_bundle


$$h(pw)^s = (h(pw)^{\alpha \cdot s})^{\alpha^{-1}}$$

$$rw = H(pw, h(pw)^s)$$


$$rw_key = \text{KDF}(rw)$$

$$\text{client_key_info} = \text{AEAD.Dec}(rw_key, \text{client_enc_k_bundle})$$

OPQAUE – Stage 1: OPRF



Username, password: pw



$$\alpha \leftarrow_{\$} \mathbb{Z}_q$$

LoginRequest = (Username, $h(pw)^\alpha$)

Retrieve (s, rw , server_k_bundle, client_enc_k_bundle)

// ...corresponds to the username

$h(pw)^{\alpha \cdot s}$, client_enc_k_bundle

$$h(pw)^s = (h(pw)^{\alpha \cdot s})^{\alpha^{-1}}$$

$$rw = H(pw, h(pw)^s)$$


$$rw_key = \text{KDF}(rw)$$

$$\text{client_key_info} = \text{AEAD.Dec}(rw_key, \text{client_enc_k_bundle})$$


$$\text{Parse client_key_info} = (lpk_c, lsk_c, lpk_s)$$

$$\text{Parse server_k_bundle} = (lpk_c, lpk_s, lsk_s)$$

OPQAUE – Stage 2: AKE




Username, password: *pw*




Parse *client_key_info* = (lpk_c, lsk_c, lpk_s)

Parse *server_k_bundle* = (lpk_c, lpk_s, lsk_s)

OPQAUE – Stage 2: AKE



Username, password: *pw*




Parse *client_key_info* = (lpk_c, lsk_c, lpk_s)


Parse *server_k_bundle* = (lpk_c, lpk_s, lsk_s)




OPQAUE – Stage 2: AKE



OPQAUE – Stage 3: Key Confirmation



Username, password: *pw*



OPRF stage

Parse *client_key_info* = (lpk_c, lsk_c, lpk_s)


Parse *server_k_bundle* = (lpk_c, lpk_s, lsk_s)

AKE stage (Homework)


$SK = \text{KeyClient}(\dots)$

$SK = \text{KeyServer}(\dots)$

OPQAUE – Stage 3: Key Confirmation



Username, password: *pw*



OPRF stage

Parse *client_key_info* = (lpk_c, lsk_c, lpk_s)

Parse *server_k_bundle* = (lpk_c, lpk_s, lsk_s)


AKE stage (Homework)

$SK = \text{KeyClient}(\dots)$

$SK = \text{KeyServer}(\dots)$

Key Confirmation (Homework)


OPQAUE – Summary



Username, password: *pw*

Registration:

Instead of storing (salt, $H(\text{salt } pw)$), we store
(salt, $rw = \text{DH-OPRF}(\text{salt}, pw)$, $\text{AEAD}(rw, [\text{AKE keys}], \dots)$)
// This allows the future messages exchange to not
reveal the salt (to prevent precomputation)



OPRF stage:

Allow the client to compute rw (to recover the
AKE keys) without revealing the salt

AKE stage:

Use AKE protocol to share a fresh session key

Key Confirmation:


Confirm both parties share the same key

Summary on Password-based Authentication

- Use passwords to authenticate identities
- Storage of passwords & Protocols:
 - Plaintext (or hashed without salt) password: 🚫
 - Hashed + salted password: 👍 (SRP, ...)
 - Hashed + salted + iterated password: 👍 👍 (SCRAM, ...)
 - OPRF passwords: 👍 👍 👍 (OPAQUE)
- In Practice: Run over TLS
- Password-based AKE protocols: (secure guarantee even in an insecure TLS connection...)
 - SRP
 - OPAQUE (stronger)

Homework

- Implement the DH-OPRF protocol, and use it to implement the OPAQUE registration phase.
- Implement the HMQRV AKE protocol



(The HMQRV-Kclient/KServer algorithms are given on the next page...)

Homework

HMQV-KClient(a, x, B, Y)


1. $d = \text{SHA256}(X, [\text{Server's Name}])$
2. $e = \text{SHA256}(Y, [\text{Client's Name}])$
3. $ss = (YB^e)^{x+da} \bmod q$
4. $SK = \text{HKDF}(ss)$

HMQV-KServer(b, y, A, X)


1. $d = \text{SHA256}(X, [\text{Server's Name}])$
2. $e = \text{SHA256}(Y, [\text{Client's Name}])$
3. $ss = (XA^d)^{y+eb} \bmod q$
4. $SK = \text{HKDF}(ss)$

Homework

- Implement the OPAQUE protocol instantiating with the HMQRV protocol, where the Key Confirmation works as follows:



Homework

- **(Bonus)** Implement the OPAQUE protocol (in the non-bonus homework) using sockets.
- **(Bonus)** What is the RTT of the OPAQUE protocol in the non-bonus homework? Can you improve it? If so, implement your improved version (can be without sockets)
 - One RTT = One “” in the protocol...
- Lots of homework this lecture => No mandatory homework in the next lecture

Further Reading

- OPAQUE paper: <https://eprint.iacr.org/2018/163>
- OPAQUE IETF draft: <https://www.ietf.org/archive/id/draft-irtf-cfrg-opaque-02.html>
- HMQV paper: <https://eprint.iacr.org/2005/176>

Notes on Homework

- 1 *non-bonus* homework question = 1 point
- 1 *bonus* homework question = 2 points
- How to calculate the final grade of homework (≤ 40):

$$40 \times \left(\frac{\text{points you obtain}}{\text{the number of questions}} \right)$$

// You need to get at least $40 \times 60\% = 24$ points to qualify for the final exam.

- You can submit **bonus homework before the final deadline: Feb 7th, 2025**
 - Please ensure that your code runs correctly, as you will not have an opportunity to resubmit it.
- If your code for **Homework Set 1 or 2 does not run correctly...**
 - You can resubmit it by the **extended deadline: January 21st, 2025.**
- Some suggestions:
 - **Include the sample input and its expected output** in the README file to help me verify your submission.