



# Cryptography Engineering

- Lecture 8 (Dec 11, 2024)
- Today's notes:
  - Protocol Study: The SCRAM protocol
  - Password-based Authenticated Key Exchange (PAKE)
  - An (In)secure Example: Encrypted-key-exchange protocol
  - Protocol study: The SRP protocol
- Coding tasks/Homework:
  - Implement the SCRAM protocol
  - **Bonus:** Informal analysis of SRP
  - **Bonus:** Implement pre-computation attacks on SRP

# TLS + Salted Hashes of Passwords

- TLS + salted & hashed passwords
  - Use TLS to protect the transmission of pw
  - No TLS handshake key => Cannot launch offline dictionary attacks

Account = "Runzhi"  
password =  $pw$   
where  $pw$  is some string





User	password_file
Runzhi	$r, H(r, pw)$
Tom	$r_2, H(r_2, pw_2)$
...	...

# TLS + Salted Hashes of Passwords

- TLS + salted & hashed passwords
  - Use TLS to protect the transmission of pw
  - No TLS handshake key => Cannot launch offline dictionary attacks

Account = "Runzhi"  
password =  $pw$   
where  $pw$  is some string





User	password_file
Runzhi	$r, H(r, pw)$
Tom	$r_2, H(r_2, pw_2)$
...	...

If the database is compromised,  
then one can launch offline dictionary attack...

# TLS + Salted Hashes of Passwords

- TLS + salted & hashed passwords
  - Use TLS to protect the transmission of pw
  - No TLS handshake key => Cannot launch offline dictionary attacks

Account = "Runzhi"  
password =  $pw$   
where  $pw$  is some string



User	password_file
Runzhi	$r, H(r, pw)$
Tom	$r_2, H(r_2, pw_2)$
...	...

If the database is compromised,  
then one can launch offline dictionary attack...

Is it possible to increase the  
difficulty of offline attacks?

# The SCRAM protocol

- Salted Challenge Response Authentication Mechanism
- Main idea:
  1. Add iteration in computing salted & hashed password
  2. Challenge-response Mechanism
  3. Run over TLS
- Other Important Features:
  - Inherent Resistance to Replay Attacks

(TLS + salted & hashed passwords resists replay attacks because of TLS, while SCRAM resists replay attacks inherently, independent of the transport layer.)
  - Mutual Authentication

# The SCRAM protocol

- Add iteration in computing salted & hashed password:

`password_file = [  $r$ ,  $H(pw, r)$  ]`

Offline dictionary  
attacks

$pw$

Running time:  $T$

# The SCRAM protocol

- Add iteration in computing salted & hashed password:

`password_file = [  $r, H(pw, r)$  ]`

Offline dictionary  
attacks

$pw$

Running time:  $T$

`password_file = [  $r, H^2(pw, r)$  ]`  
where  $H^2(pw, r) = H(pw, H(pw, r))$

# The SCRAM protocol

- Add iteration in computing salted & hashed password:

`password_file = [  $r$ ,  $H(pw, r)$  ]`

Offline dictionary  
attacks

$pw$

Running time:  $T$

`password_file = [  $r$ ,  $H^2(pw, r)$  ]`  
where  $H^2(pw, r) = H(pw, H(pw, r))$

Offline dictionary  
attacks

$pw$

Running time:  $2 \cdot T$



# The SCRAM protocol

- Add iteration in computing salted & hashed password:

```
Iterate_hash_with_salt(password, salt, num_of_iteration):
```

```
    // salt can be 16- or 32-byte
```

```
    // num_of_iteration can be 4096 or even 100,000
```

```
    // All variable are bytes with big-endian order
```

```
    pw = password
```

```
    padded_salt = salt || b'\x00\x00\x00\x01' // Append a 4-byte string 0x00000001 (in hex)
```

```
    hash1 = HMAC(pw, padded_salt) // We use keyed HMAC, where the key to HMAC is the password
```

```
    For i from 2 to num_of_iteration: // Iteratively evaluate the HMAC of pw and previous HMAC
```

```
        hashi = HMAC(pw, hashi-1)
```

```
    Password_file = hash1 ⊕ hash2 ⊕ ... ⊕ hashnum_of_iteration // One integrate this part into the loop
```

```
    return Password_file
```

# The SCRAM protocol

- Add iteration in computing salted & hashed password:

**A simpler description:**

(using the notation  $H^n(pw, r) = \text{Iterate\_hash\_with\_salt}(pw, r, n)$ )

Given  $r, n, pw$ :

$$U_1 = \text{HMAC}(pw, r \parallel \text{b}'\backslash\text{x00}\backslash\text{x00}\backslash\text{x00}\backslash\text{x01}')$$

$$U_2 = \text{HMAC}(pw, U_1)$$

$\vdots$

$$U_{n-1} = \text{HMAC}(pw, U_{n-2})$$

$$U_n = \text{HMAC}(pw, U_{n-1})$$

We compute  $H^n(pw, r) = U_1 \oplus U_2 \oplus \dots \oplus U_{n-1} \oplus U_n$

# The SCRAM protocol

- Add iteration in computing salted & hashed password:

`password_file = [  $r$ ,  $H(pw, r)$  ]`

Offline dictionary  
attacks

$pw$

Running time:  $T$

# The SCRAM protocol

- Add iteration in computing salted & hashed password:

**password\_file** = [  $r$ ,  $H(pw, r)$  ]

Offline dictionary  
attacks

$pw$

Running time:  $T$

**password\_file**  
= [  $r$ ,  $n$ ,  $H^n(pw, r)$  ]  
where  $H^n(pw, r) = \text{Iterate\_hash\_with\_salt}(pw, r, n)$

Offline dictionary  
attacks

$pw$

Running time:  $n \cdot T$

# The SCRAM protocol

- Add iteration in computing salted & hashed password:

**password\_file** = [  $r$ ,  $H(pw, r)$  ]

Offline dictionary attacks

$pw$

Running time:  $T$

**password\_file**  
= [  $r$ ,  $n$ ,  $H^n(pw, r)$  ]  
where  $H^n(pw, r) = \text{Iterate\_hash\_with\_salt}(pw, r, n)$

Offline dictionary attacks


$pw$

Running time:  $n \cdot T$


Significantly increase  
the cost of offline  
dictionary attacks

# The SCRAM protocol

- Challenge-response paradigm




$pw$



$r, n, H^n(r, pw)$


# The SCRAM protocol

- Challenge-response paradigm



$pw$

I want to prove  
that I have  $pw$




$r, n, H^n(r, pw)$

OK, let me  
'challenge' you.


# The SCRAM protocol

- Challenge-response paradigm



$pw$

Request



$r, n, H^n(r, pw)$


ServerChallenge:  $r, n, ch_2$

1. sample a challenge  $ch_2$  uniformly at random




# The SCRAM protocol

- Challenge-response paradigm



$r, n, pw$

Request



$r, n, H^n(r, pw)$


ServerChallenge: $r, n, ch_2$

1. sample a challenge  $ch_2$  uniformly at random

2.  $Salted\_pw = H^n(r, pw)$
3.  $Client\_key = \text{HMAC}(Salted\_pw, \text{'Client key'})$
4.  $Auth\_msg = [\text{Client's Name}] || r, n, ch_2$
5.  $Client\_sign = \text{HMAC}(H(Client\_key), Auth\_msg)$  // Here **H** is the hash function used in **HMAC**
6.  $Client\_proof = Client\_key \oplus Client\_sign$


# The SCRAM protocol

- Challenge-response paradigm



$r, n, pw$

Request



$r, n, H^n(r, pw)$

ServerChallenge:  $r, n, ch_2$

1. sample a challenge  $ch_2$  uniformly at random


2.  $Salted\_pw = H^n(r, pw)$
3.  $Client\_key = \text{HMAC}(Salted\_pw, \text{'Client key'})$
4.  $Auth\_msg = [\text{Client's Name}] || r, n, ch_2$
5.  $Client\_sign = \text{HMAC}(H(Client\_key), Auth\_msg)$  // Here **H** is the hash function used in **HMAC**
6.  $Client\_proof = Client\_key \oplus Client\_sign$

ClientProof: **Client\_proof**

6. Verify **Client\_proof**


# The SCRAM protocol

- Challenge-response paradigm



# The SCRAM protocol


- Challenge-response paradigm



$r, n, pw$

1. sample a challenge  $ch_1$   
uniformly at random


ClientChallenge:  $ch_1$




$r, n, H^n(r, pw)$

# The SCRAM protocol

- Challenge-response paradigm



$r, n, pw$



$r, n, H^n(r, pw)$

1. sample a challenge  $ch_1$   
uniformly at random


ClientChallenge:  $ch_1$

2.  $Salted\_pw = H^n(r, pw)$
3.  $Server\_key = \text{HMAC}(Salted\_pw, \text{'Client key'})$
4.  $Auth\_msg = [\text{Client's Name}] || ch_1$
5.  $Server\_sign = \text{HMAC}(Server\_key, Auth\_msg)$


ServerSign:  $Server\_sign$

# The SCRAM protocol

- Challenge-response paradigm



$r, n, pw$



$r, n, H^n(r, pw)$

1. sample a challenge  $ch_1$   
uniformly at random

ClientChallenge:  $ch_1$

2.  $Salted\_pw = H^n(r, pw)$
3.  $Server\_key = \text{HMAC}(Salted\_pw, \text{'Client key'})$
4.  $Auth\_msg = [\text{Client's Name}] || ch_1$
5.  $Server\_sign = \text{HMAC}(Server\_key, Auth\_msg)$

ServerSign:  $Server\_sign$


6. Verify  $Server\_sign$

# The SCRAM protocol



Account = [ClientName]  
password =  $pw$   
where  $pw$  is some string

Run TLS handshake to share  
a handshake key  $K$  and  
some channel binding info **TLS\_INFO**



User	password_file
Runzhi	$r, n, H^n(r, pw)$
Tom	$r_2, n, H^n(r_2, pw_2)$
...	...

1. Pick a random  
client challenge " $ch_1$ "

ClientFirst: [ClientName],  $ch_1$

3. Compute **Client\_proof**  
using **Auth\_msg**

ServerFirst:  $ch_1 || ch_2, r, n$

ClientFinal: **TLS\_INFO**,  $ch_1 || ch_2$ , **Client\_proof**

5. Verify **Server\_sign**

ServerFinal: **Server\_sign**

**Auth\_msg** = [ClientName] ||  $ch_1 || ch_2 || r || n ||$  **TLS\_INFO**

2. Pick a random  
server challenge " $ch_2$ "

4. Verify **Client\_proof**.  
If valid:  
Compute **Server\_sign**  
using **Auth\_msg**

# The SCRAM protocol

- Main idea:
  1. Add iteration in computing salted & hashed password
  2. Challenge-response Mechanism
  3. Run over TLS
- Used in some systems that require higher security guarantees...
  - IMAP / POP / SMTP / ...
  - Database Authentication (e.g., MongoDB)...



# Password-based Authenticated Key Exchange

- Previous protocols: TLS + salted & hashed (& iterated) passwords
  - Advantages: Simple, rely on known constructions

# Password-based Authenticated Key Exchange


- Previous protocols: TLS + salted & hashed (& iterated) passwords
  - Advantages: Simple, rely on known constructions
- **Not entirely satisfactory:**
  - If the handshake protocol is not secure, then they can be trivially broken (leads to offline attacks immediately).

# Password-based Authenticated Key Exchange

- Previous protocols: TLS + salted & hashed (& iterated) passwords
  - Advantages: Simple, rely on known constructions
- **Not entirely satisfactory:**
  - If the handshake protocol is not secure, then they can be trivially broken (leads to offline attacks immediately).
- **An alternative solution: Password-based Authenticated Key Exchange (PAKE)**


# Password-based Authenticated Key Exchange

- (Symmetric) PAKE:




# Password-based Authenticated Key Exchange

- (Symmetric) PAKE:



# Password-based Authenticated Key Exchange

- (Symmetric) PAKE:



## Primary Goals:

- (1) Resistance to Offline Dictionary attacks    (2) The shared key  $SK$  is *pseudorandom*

# Password-based Authenticated Key Exchange


- **Encrypted-Key-Exchange DH (EKE-DH) protocols:**
  - **Main idea:** Use pw to encrypt the underlying DH key exchange



*pw*

$Enc(H(pw), g^x)$

$Enc(H(pw), g^y)$



*pw*


$$SK = KDF(H(g^{xy}), \dots)$$

$$SK = KDF(H(g^{xy}), \dots)$$

- Is it secure?

# Password-based Authenticated Key Exchange

- **Encrypted-Key-Exchange DH (EKE-DH) protocols:**
  - **Main idea:** Use pw to encrypt the underlying DH key exchange



$$SK = KDF(H(g^{xy}), \dots)$$


$$SK = KDF(H(g^{xy}), \dots)$$

- Is it secure? **Depends on the encryption!**



# Password-based Authenticated Key Exchange


- EKE-DH protocols **based on AEAD**:



- Is it secure? (Hint: On invalid input key/ciphertext, AEAD may output “reject”)

# Password-based Authenticated Key Exchange


- EKE-DH protocols **based on AEAD**:



- Is it secure? (Hint: On invalid input key/ciphertext, AEAD may output "reject")

# Password-based Authenticated Key Exchange

- EKE-DH protocols **based on an “ideal” encryption**:




$$SK = KDF(H(g^{xy}), \dots)$$

$$SK = KDF(H(g^{xy}), \dots)$$

- The **ideal encryption** has the following properties:
  - Outputs of encryption and decryption **are (pseudo)random even if the key has low entropy**
  - Namely, if the adversary does not have the correct  $pw$ , the outputs of encryption/decryption are some random group elements.

# Password-based Authenticated Key Exchange


- EKE-DH protocols **based on an “ideal” encryption**:



- The **ideal encryption** has the following properties:
  - Outputs of encryption and decryption **are (pseudo)random even if the key has low entropy**
  - Namely, if the adversary does not have the correct  $pw$ , the outputs of encryption/decryption are some random group elements.


# Password-based Authenticated Key Exchange

- EKE-DH protocols **based on an “ideal” encryption**:




# Password-based Authenticated Key Exchange

- Asymmetric PAKE (aPAKE):



# Password-based Authenticated Key Exchange


- Secure Remote Password (SRP) Protocol



- Based on module integer groups / Not directly compatible with Elliptic Curves
- Apple ID Authentication / Blizzard Entertainment

# Password-based Authenticated Key Exchange

- Secure Remote Password (SRP) Protocol (version 6a)



$pw$


## Public Parameters:

$q$  a large prime  
 $N = 2q + 1$  a prime (we call it as safe prime)  
 $\mathbb{G}$  a sub-group of  $\mathbb{Z}_N$  with order  $q$   
 $g$  the generator of  $\mathbb{G}$

## Notations:

Let  $h$  be an integer in  $\mathbb{Z}_N$ .

If  $h \in \mathbb{G}$  and  $x \in \mathbb{Z}_q$ , then we denote  $h^x := h^x \bmod N$



Password file:

$r, v = g^{H(r, [user\_name], pw)}$




# Password-based Authenticated Key Exchange

- SRP-v6a: (1) Key Exchange phase (2) Key Confirmation phase



*pw*

“user\_name”, login\_request



*r, v*

# Password-based Authenticated Key Exchange


- SRP-v6a: (1) Key Exchange phase (2) Key Confirmation phase



$pw$

“user\_name”, login\_request

$r, B$




$r, v$

$$\begin{aligned} k &= H_5(p, g) \\ b &\leftarrow_{\$} \mathbb{Z}_{p-1} \\ B &= k \cdot v + g^b \end{aligned}$$


# Password-based Authenticated Key Exchange

- **SRP-v6a: (1) Key Exchange phase** (2) Key Confirmation phase




# Password-based Authenticated Key Exchange

- **SRP-v6a: (1) Key Exchange phase** (2) Key Confirmation phase




# Password-based Authenticated Key Exchange

- **SRP-v6a:** (1) Key Exchange phase (2) Key Confirmation phase




# Password-based Authenticated Key Exchange

- **SRP-v6a:** (1) Key Exchange phase (2) Key Confirmation phase




# Password-based Authenticated Key Exchange

- **SRP-v6a:** (1) Key Exchange phase (2) Key Confirmation phase



# Password-based Authenticated Key Exchange


- **SRP-v6a:** (1) Key Exchange phase (2) Key Confirmation phase






# Password-based Authenticated Key Exchange

- SRP-v6a:



# Password-based Authenticated Key Exchange

- **TLS + SRP-v6a:**



# Homework

- Implement the SCRAM protocol (You do not need to use sockets, but your program should draw the message flows)
- **Bonus:** Try arguing that, even though SRP-v6a is run without using TLS encrypted channel, the adversary still cannot “easily” launch offline dictionary attacks on it. Just write a simple pdf to argue it. (Hint: Using specific example is better than providing abstract explanations)

(You can ask AI, but then you should learn its answer and write a human-friendly answer by yourself, since it is not hard to detect that a solution is written from AI)

# Further Reading

- RFC document of SRCAM: <https://datatracker.ietf.org/doc/html/rfc5802>
- Password-Based Key Derivation Function:  
<https://datatracker.ietf.org/doc/html/rfc8018#page-11>
- Analysis on SRP: *Provable Security Analysis of the Secure Remote Password Protocol*,  
<https://eprint.iacr.org/2023/1457>
- Matthew Green's blog: *Should you use SRP?*  
<https://blog.cryptographyengineering.com/should-you-use-srp/>