# K. Scalability with respect to Dimension and Constraints

1101

1102

1103

1104

1105

1107

1111

1112

1113

1115

1117

1118

1119

1120

1121

1122

1123

1124

1125

1126

1127

1128

1129

1130

1144 1145 1146

1147

1148

1149

1150

1151

1152

1153

1154

We first present the results of exact sampling, computing closed-form loss, and gradient estimator with respect to varying dimensions. The number of constraints is half of the dimension (n). All results are averaged over 100 runs and conducted on a Nvidia A800 80GB GPU. All numbers are measured in seconds. We highlight that even though increasing dimension slows down the algorithm, the additional computational cost can be mitigated by choosing a larger batch size. For example, the additional time taken to run with batch\_size=16 and batch\_size=32 is almost negligible for n=32,64, and 128. In the challenging n=2048 case, using batch\_size=32 only takes 1.5 times more time to run compared to batch\_size=16. Larger batch sizes can significantly reduce computation time per sample thanks to the parallelization of our method.

Table 11. Runtime (in seconds) for varying dimensions and batch sizes.

n <u>zeo.</u>					
	16	32	64	128	256
n = 32	0.00249	0.00250	0.00252	0.00253	0.00255
n = 64	0.00348	0.00348	0.00348	0.00352	0.00366
n = 128	0.00467	0.00473	0.00479	0.00483	0.00498
n = 256	0.00760	0.00769	0.00806	0.00916	0.01052
n = 512	0.00760	0.01770	0.02159	0.02921	0.04500
n = 1024	0.04843	0.06266	0.09138	0.13943	0.23699
n = 2048	0.20515	0.31654	0.46224	0.78970	1.24126

#### Algorithm 2 Varying Dimensions

```
1131
        1: for each n \in ls\_n do
1132
              num\_constraints \leftarrow n/2
1133
              Total\ time \leftarrow 0
        3:
1134
        4:
              for i \leftarrow 1 to repeat\_num do
1135
        5:
                 Generate unconstrained parameters and constraints
1136
                 Conduct exact sampling
        6:
1137
                 Compute closed-form loss
        7:
1138
                 Compute gradient estimator
        8:
1139
        9:
                 Total \ time \leftarrow Total \ time + time
1140
       10:
              end for
1141
       11:
              Total\_time \leftarrow Total\_time/repeat\_num
1142
              print(Total time)
       12:
1143
       13: end for
```

We next investigate the impact of the number of constraints (num\_k). We conduct experiments on the challenging n=2048 setting. Similar to the findings in scaling the number of dimensions, using larger batch sizes significantly reduces computation time per sample. Additionally, we also found that increasing the number of constraints does not significantly increase the computational time. For example, under batch\_size = 64, increasing the number of con-

straints from 256 to 512 only increases computational time by 32%.

Table 12. Runtime (in seconds) for varying number of constraints and batch sizes at n=2048.

	16	32	64	128	256
$\texttt{num\_k} = 32$	0.05109	0.09899	0.19531	0.29093	0.47706
${\tt num\_k}=64$	0.05343	0.10259	0.20241	0.30316	0.48106
$\texttt{num\_k} = 128$	0.05894	0.11060	0.21666	0.32456	0.50057
$\mathtt{num\_k} = 256$	0.07336	0.13211	0.24871	0.38556	0.52001
$\texttt{num\_k} = 512$	0.10885	0.18119	0.32935	0.52796	0.84375
$\texttt{num\_k} = 1024$	0.20515	0.31654	0.46224	0.78970	1.24126

## **Algorithm 3** Exact Sampling and Gradient Estimation over Varying Number of Constraints

```
1: for each num \ k \in ls \ k do
      Total\ time \leftarrow 0
 3:
      for i \leftarrow 1 to repeat\_num do
 4:
         Generate unconstrained parameters and constraints
         Conduct exact sampling
 5:
         Compute closed-form loss
 6:
         Compute gradient estimator
 7:
 8:
         Total\_time \leftarrow Total\_time + time
 9:
      end for
10:
      Total\_time \leftarrow Total\_time/repeat\_num
      print(Total_time)
11:
12: end for
```

#### L. Additional Metrics for DDPM and DDIM

	Table 13	. CIFAR	
Model	Precision	Recall	Coverage
DDPM Ours DDIM Ours	0.538 <b>0.543</b> 0.567 <b>0.570</b>	0.483 <b>0.485</b> 0.433 <b>0.439</b>	0.965 <b>0.979</b> 0.986 <b>0.992</b>

Table 14	. CelebA	
Precision	Recall	Coverage
0.812	0.488	0.996
0.826	0.498	0.998
0.872	0.391	0.998
0.886	0.406	0.998
	0.812 <b>0.826</b> 0.872	0.812 0.488 <b>0.826 0.498</b> 0.872 0.391

1	1	55
1	1	56

1	1	58
1	1	59
1	1	60
1	1	61
1	1	62
1	1	63
1	1	64
1	1	65
1	1	66

Table 15. LSUN Church			
Model	Precision	Recall	Coverage
DDPM	0.453	0.488	0.930
Ours	0.468	0.494	0.936
DDIM	0.594	0.307	0.995
Ours	0.598	0.336	0.997

Table 16. LSUN Cat			
Model	Precision	Recall	Coverage
DDPM	0.409	0.429	0.942
Ours	0.434	0.432	0.957
DDIM	0.554	0.307	0.992
Ours	0.559	0.311	0.993

### M. Additional Experiment on CL and **Constrained Reparametrization**

Additional experiment results on CL and Constrained Reparametrization are highlighted with gray.

#### M.1. Constrained Generation using VAE

#### M.2. Constrained Generation using Diffusion Models

Table 18. Comparison of constrained and unconstrained models across datasets under DDPM. We report FID (Fréchet Inception Distance), IS (Inception Score), and Violation metrics.

DATASET	MODEL	FID $\downarrow$	IS ↑	VIOLATION $\downarrow$
	Ours	3.811	$9.223 \pm 0.130$	0
CIFAR	Constr Layer	4.234	$8.535 \pm 0.157$	0
	Constr Reparam	3.881	$9.126\pm0.122$	0
	DDPM	4.173	$\textbf{9.278} \pm \textbf{0.116}$	0.999
	Ours	10.193	$\textbf{2.360} \pm \textbf{0.016}$	0
CelebA	Constr Layer	12.067	$2.345\pm0.039$	0
	Constr Reparam	10.305	$2.334\pm0.028$	0
	DDPM	10.345	$2.358 \pm 0.030$	0.999
	Ours	4.779	$\textbf{2.471} \pm \textbf{0.020}$	0
LSUN Church	Constr Layer	6.695	$2.319\pm0.028$	0
	Constr Reparam	4.895	$2.431\pm0.032$	0
	DDPM	4.945	$2.460 \pm 0.028$	1.0
	Ours	12.489	$4.711 \pm 0.054$	0
LSUN Cat	Constr Layer	13.472	$4.642 \pm 0.081$	0
	Constr Reparam	12.696	$4.707 \pm 0.062$	0
	DDPM	12.913	$4.705 \pm 0.047$	1.0

#### M.3. Charge-Neutral Predictions

Table 19. Performances of different methods for estimating partial charges on metal ions are presented. Compared to the baseline MPNN (variance), both the closed-form loss function and likelihood objective yield superior mean absolute deviation (MAD) results. The same holds for their ensemble counterpart. We find that ensemble methods (second block) notably boost the predictive performance in general.

perrormance in general.		
Метнор	MAD ↓	NLL↓
neutrality enforcement	mean $\pm$ std	mean $\pm$ std
Constrained Layer	$0.327 \pm 0.004$	$103.522 \pm 3.018$
Constant Prediction	$0.324 \pm 0.007$	_
Element-mean (uniform)	$0.154 \pm 0.002$	_
Element-mean (variance)	$0.153 \pm 0.002$	_
MPNN (KKThPINN)	$0.0260 \pm 0.0008$	$109.8 \pm 6.9$
MPNN (Constr Reparam)	$0.0256 \pm 0.0007$	$3340.03 \pm 2398$
MPNN (variance)	$0.0251 \pm 0.0010$	$-19.9 \pm 71.1$
Closed-form (ours)	$0.0245 \pm 0.0009$	>1e+7
Likelihood (ours)	$0.0248 \pm 0.0008$	$-252 \pm 24.7$
Constrained Layer (ens)	$0.319 \pm 0.002$	$99.236 \pm 2.3$
MPNN (ens, KKThPINN)	$0.0244 \pm 0.0006$	$57.29 \pm 12.8$
MPNN (ens, Constr Reparam)	$0.0242 \pm 0.0006$	$4883.46 \pm 1695$
MPNN (ens, variance)	$0.0238 \pm 0.0007$	$-45.2 \pm 55.8$
Closed-form (ens, ours)	$0.0230 \pm 0.0008$	>1e+7
Likelihood (ens, ours)	$0.0231 \pm 0.0007$	$-180 \pm 38.3$

#### M.4. Chemical Process Units and Subsystems

Table 20. Comparison of models across CSTR, plant, and distillation tasks. The mean and standard deviation of MSE scaled by  $10^{-4}$  are reported. All experiments are averaged for 10 times.

MODEL	CSTR	PLANT	DISTILLATION
ECNN	$20.6 \pm 27.0$	$0.31 \pm 0.23$	$1.94 \pm 0.70$
KKThPINN	$11.7\pm20.3$	$0.11 \pm 0.04$	$2.02 \pm 0.94$
NN	$18.3 \pm 20.8$	$0.34 \pm 0.64$	$1.99 \pm 0.67$
PINN	$260.8 \pm 20.4$	$3.62 \pm 1.94$	$40.9 \pm 10.7$
CL	$9.28 \pm 3.56$	$0.58 \pm 0.64$	$2.26\pm1.19$
Constr Reparam	$7.13\ \pm\ 3.22$	$0.14\ \pm\ 0.07$	$2.22\ \pm\ 0.94$
Ours	$\textbf{4.31} \pm \textbf{1.58}$	$\textbf{0.09} \pm \textbf{0.05}$	$\textbf{1.73} \pm \textbf{0.70}$

#### M.5. Stock Investment

Table 21. Comparison of models based on Sharpe ratio. We report the mean and standard deviation averaged across 10 runs.

MODEL	Sharpe ratio $\uparrow$
StemGNN	$1.5576 \pm 0.3405$
StemGNN-KKThPINN	$1.8092 \pm 0.7055$
StemGNN-CL	$1.5018 \pm 0.3318$
StemGNN-Constr Reparam	$1.8162 \pm 0.2966$
Ours	$1.9041 \pm 0.2329$

*Table 17.* Comparison on VAE generative performance. The constrained VAE models achieve similar or better generative ability while strictly satisfying the constraints, whereas the unconstrained counterparts have a high constraint violation rate.

MODEL	$\mathbf{LL}\uparrow$		<b>ELBO</b> ↑		$\mathbf{RL}\downarrow$		Violation $\downarrow$
VAE	-22.42 ±	0.29	-23.41 ±	0.22	$15.00 \pm$	0.46	$0.30 \pm 0.06$
VAE + Constr Layer	-34.45 $\pm$	2.64	-40.89 $\pm$	9.37	$37.11\pm$	9.35	$\textbf{0.00}  \pm  \textbf{0.00}$
VAE + Constr Reparam	-22.33 ±	0.48	-23.83 ±	0.49	$14.54 \pm$	0.58	$0.00 \pm 0.00$
ours	-21.48 $\pm$	0.18	-22.62 $\pm$	0.07	$\textbf{12.79} \pm$	0.11	$\textbf{0.00} \pm \textbf{0.00}$
Ladder VAE	-24.25 ±	0.07	-30.84 ±	0.51	23.06 ±	0.54	$0.38 \pm 0.02$
Ladder VAE + Constr Layer	-36.83 $\pm$	0.56	-39.59 $\pm$	0.56	$37.46 \pm$	0.55	$\textbf{0.00}  \pm  \textbf{0.00}$
Ladder VAE + Constr Reparam	-25.27 ±	0.19	-31.56 ±	0.48	$25.20 \pm$	0.62	$0.00 \pm 0.00$
ours	-23.86 $\pm$	0.06	-30.78 $\pm$	0.08	23.40 $\pm$	0.16	$\textbf{0.00}  \pm    \textbf{0.00}$
Graph VAE	-22.74 $\pm$	0.11	-23.54 $\pm$	0.18	15.45 $\pm$	0.41	$0.29 \pm 0.09$
Graph VAE + Constr Layer	-33.27 $\pm$	3.60	-33.27 $\pm$	5.84	$28.29 \pm$	6.40	$\textbf{0.00}  \pm  \textbf{0.00}$
Graph VAE + Constr Reparam	-22.96 ±	0.80	-23.55 ±	0.86	$16.08 \pm$	1.38	$0.00 \pm 0.00$
ours	-21.61 $\pm$	0.20	-22.53 $\pm$	0.06	12.73 $\pm$	0.21	$0.00 \pm 0.00$