Real-world driving cycles and energy consumption informed by large-sized vehicle trajectory data

Ruoyun Ma^{1, #}, Xiaoyi He^{2, #}, Yali Zheng³, Boya Zhou⁴, Sheng Lu¹, Ye Wu^{1,5*}

- ¹ School of Environment, and State Key Joint Laboratory of Environment Simulation and Pollution Control, Tsinghua University, Beijing 100084, China
- ² School for Environment and Sustainability, University of Michigan, Dana Bldg. 440 Church, Ann Arbor, MI 48109-1041
- ³ China Society of Automotive Engineers, 4F Tianlian Building, Lianhuachi East Rd., Xicheng District, Beijing 100084, China
- ⁴ China Automotive Technology & Research Center Co., Ltd., 68 Xianfeng East Rd, Dongli, Tianjin 300300, China
- ⁵ State Environmental Protection Key Laboratory of Sources and Control of Air Pollution Complex, Beijing 100084, China
- # These authors contributed equally.

*Corresponding authors: Ye Wu (www@tsinghua.edu.cn)

Abstract

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

The inadequate representativeness of driving cycles used by regulatory lab tests is one significant factor leading to the large discrepancy between real-world fuel consumption and type-approval levels. On-board measurement devices have been used in previous researches to collect vehicle activity data but the amount of data is sometimes limited. With second-by-second GPS trajectory data of 459 private passenger cars, covering over 17,000 sampling days, we used big-data mining techniques to study the variations in real-world driving cycles. A Markov chain method was developed to generate typical driving cycles that have representative features of real-world driving. As a case study, two typical cycles, Off-peak cycle and Peak cycle, are constructed from six sub-cycles representing different road types and travel periods, which could depict fine-scale discrepancies of driving characteristics among different situations. The simulation results of vehicle fuel consumption showed that different driving cycles could lead to different lab-to-road gaps when comparing with the NEDC type-approval levels. For example, the fuel consumption (median value) of Off-peak cycle and Peak cycle were higher than the NEDC type-approval level by 29.3% and 37.5%, respectively. This study highlights the importance of realworld vehicle activity data in improving future fuel economy regulations.

19

20

21

Keywords

- 22 Driving cycle; second-by-second GPS trajectories; Markov Chain process; Light-duty
- vehicles; Real-world energy consumption