



Master algorithms together on [Binary Search!](#) Create a room, invite your friends, and race to finish the problems.

Daily Coding Problem

[Blog](#)

Daily Coding Problem #218

Problem

This problem was asked by Yahoo.

Write an algorithm that computes the reversal of a directed graph. For example, if a graph consists of $A \rightarrow B \rightarrow C$, it should become $A \leftarrow B \leftarrow C$.

Solution

Our first instinct might be to traverse the graph, finding all the edges. For each edge, we can swap its vertices and add the updated edge to a new graph.

For example, if we find an edge directed from A to B, with a weight of 5, we would add a corresponding edge to our transposed graph with the same weight, but from B to A. Traversing the graph can be done with depth-first search.

```
from collections import defaultdict

def helper(graph, node, visited, transpose):
    if node not in visited:
```

```

        visited.add(node)

    for n, weight in graph[node]:
        transpose[n] += [(node, weight)]
        helper(graph, n, visited, transpose)

    return transpose

def reverse(graph):
    start = graph.keys()[0]
    transpose = helper(graph, start, set(), defaultdict(list))
    return transpose

```

This will take $O(|V| + |E|)$ time, and building up the reversed graph will use $O(|V| + |E|)$ space.

However, there is a simpler approach. If we already have our graph represented as an adjacency list, all we need to do is generate a new adjacency list with swapped keys and values.

In other words, suppose we our graph is represented as $\{0: [2, 3], 1: [3, 4], 2: [1]\}$. We iterate through each key k , and every value v . If v is not a key in our transposed graph, we add it, along with the value k . Otherwise, we append v to the existing list of k 's edges. In this example the first few edges would be $\{2: 0, 3: 0, 3: 1, \dots\}$.

```

def reverse(graph):
    transpose = defaultdict(list)

    for node in graph:
        for neighbor, weight in graph[node]:
            transpose[neighbor].append((node, weight))

    return transpose

```

The time and space complexity is unchanged from above.

© Daily Coding Problem 2019

[Privacy Policy](#)

[Terms of Service](#)

[Press](#)