



Spectral Clustering




General ideas




Dataset

General ideas



Construction of a graph

General ideas



Cut in the graph

Plan

1 Introduction

2 Generalities on graphes

- Definition
- Caracterisation
- General case
- Spectral theory on graphes

3 Clustering with graphs

- Generalities
- Graph construction
- Graph cut
 - Minimal cut
 - RatioCut
 - MinMaxCut

4 Variations

Definition of a simple graph

A finite **graph** $G = \{V, E\}$ is defined as a set of :

- **Vertices** $V = \{v_1, v_2, \dots, v_n\}$
- **Edges** $E = \{e_1, e_2, \dots, e_n\}$
 - The number of vertices and edges is in general different
 - Vertices are composed of pairs $e = (x, y)$ of edges

Definition of a simple graph

A finite **graph** $G = \{V, E\}$ is defined as a set of :

- **Vertices** $V = \{v_1, v_2, \dots, v_n\}$
- **Edges** $E = \{e_1, e_2, \dots, e_n\}$
 - The number of vertices and edges is in general different
 - Vertices are composed of pairs $e = (x, y)$ of edges

Definition of a simple graph

A finite **graph** $G = \{V, E\}$ is defined as a set of :


- **Vertices** $V = \{v_1, v_2, \dots, v_n\}$
- **Edges** $E = \{e_1, e_2, \dots, e_n\}$
 - The number of vertices and edges is in general different
 - Vertices are composed of pairs $e = (x, y)$ of edges

Definition of a simple graph

A finite **graph** $G = \{V, E\}$ is defined as a set of :

- **Vertices** $V = \{v_1, v_2, \dots, v_n\}$
- **Edges** $E = \{e_1, e_2, \dots, e_n\}$
 - The number of vertices and edges is in general different
 - Vertices are composed of pairs $e = (x, y)$ of edges

Example : How is defined the following graph ?



Definition of a simple graph


A finite **graph** $G = \{V, E\}$ is defined as a set of :

- **Vertices** $V = \{v_1, v_2, \dots, v_n\}$
- **Edges** $E = \{e_1, e_2, \dots, e_n\}$
 - The number of vertices and edges is in general different
 - Vertices are composed of pairs $e = (x, y)$ of edges

Example : How is defined the following graph ?

Caracterisation

$$G = \{V, E\}$$



Definition of a simple graph

A finite **graph** $G = \{V, E\}$ is defined as a set of :


- **Vertices** $V = \{v_1, v_2, \dots, v_n\}$
- **Edges** $E = \{e_1, e_2, \dots, e_n\}$
 - The number of vertices and edges is in general different
 - Vertices are composed of pairs $e = (x, y)$ of edges

Example : How is defined the following graph ?

Caracterisation

$$G = \{V, E\}$$

$$V = \{A, B, C, D, E, F\}$$




Definition of a simple graph

A finite **graph** $G = \{V, E\}$ is defined as a set of :

- **Vertices** $V = \{v_1, v_2, \dots, v_n\}$
- **Edges** $E = \{e_1, e_2, \dots, e_n\}$
 - The number of vertices and edges is in general different
 - Vertices are composed of pairs $e = (x, y)$ of edges

Example : How is defined the following graph ?



Caracterisation

$$G = \{V, E\}$$

$$V = \{A, B, C, D, E, F\}$$

$$E =$$


$$\{(A, B), (A, E), (A, F), (B, E), (B, D), (B, C), (C, E), (C, D), (D, E)\}$$

Definition of a simple graph

A finite **graph** $G = \{V, E\}$ is defined as a set of :

- **Vertices** $V = \{v_1, v_2, \dots, v_n\}$
- **Edges** $E = \{e_1, e_2, \dots, e_n\}$
 - The number of vertices and edges is in general different
 - Vertices are composed of pairs $e = (x, y)$ of edges

Example : How is defined the following graph ?




Important note

Here we focus only on **simple graphs** (vertices connect only 2 edges) but we can have **multiple graphs** (one edge can be connect with himself) and **ordered** (vertices can connect only in one direction – directed multigraph)

Characterisation

- Two edges (X, Y) are **adjacents** if there exists a vertex (X, Y) in E . They are **neighbors**
- One edge that joints X and Y is **incident** to X and Y
- The **degree** $d(X)$ of a vertex X is the number of incident edges to X




Example for B

- Degree $d(B) = 4$
- Incident edges are $(B, A), (B, E), (B, D), (B, C)$

Note : a vertex of 0 degree is **isolated**. A simple graph with n vertex has degrees $\in [0, n - 1]$. If all vertices have a $n - 1$ -degree, the associated graph is **complete**.

Characterisation

- Two edges (X, Y) are **adjacents** if there exists a vertex (X, Y) in E .
They are **neighbors**
- One edge that joints X and Y is **incident** to X and Y
- The **degree** $d(X)$ of a vertex X is the number of incident edges to X




Example for B

- Degree $d(B) = 4$
- Incident edges are $(B, A), (B, E), (B, D), (B, C)$

Note : a vertex of 0 degree is **isolated**. A simple graph with n vertex has degrees $\in [0, n - 1]$. If all vertices have a $n - 1$ -degree, the associated graph is **complete**.

Characterisation

- Two edges (X, Y) are **adjacents** if there exists a vertex (X, Y) in E .
They are **neighbors**
- One edge that joints X and Y is **incident** to X and Y
- The **degree** $d(X)$ of a vertex X is the number of incident edges to X




Example for B

- Degree $d(B) = 4$
- Incident edges are $(B, A), (B, E), (B, D), (B, C)$

Note : a vertex of 0 degree is **isolated**. A simple graph with n vertex has degrees $\in [0, n - 1]$. If all vertices have a $n - 1$ -degree, the associated graph is **complete**.

Characterisation

- Two edges (X, Y) are **adjacents** if there exists a vertex (X, Y) in E .
They are **neighbors**
- One edge that joints X and Y is **incident** to X and Y
- The **degree** $d(X)$ of a vertex X is the number of incident edges to X




Example for B

- Degree $d(B) = 4$
- Incident edges are $(B, A), (B, E), (B, D), (B, C)$

Note : a vertex of 0 degree is **isolated**. A simple graph with n vertex has degrees $\in [0, n - 1]$. If all vertices have a $n - 1$ -degree, the associated graph is **complete**.

Characterisation

- Two edges (X, Y) are **adjacents** if there exists a vertex (X, Y) in E .
They are **neighbors**
- One edge that joints X and Y is **incident** to X and Y
- The **degree** $d(X)$ of a vertex X is the number of incident edges to X




Example for B

- Degree $d(B) = 4$
- Incident edges are $(B, A), (B, E), (B, D), (B, C)$

Note : a vertex of 0 degree is **isolated**. A simple graph with n vertex has degrees $\in [0, n - 1]$. If all vertices have a $n - 1$ -degree, the associated graph is **complete**.

Characterisation

- Two edges (X, Y) are **adjacents** if there exists a vertex (X, Y) in E .
They are **neighbors**
- One edge that joints X and Y is **incident** to X and Y
- The **degree** $d(X)$ of a vertex X is the number of incident edges to X




Example for B

- Degree $d(B) = 4$
- Incident edges are $(B, A), (B, E), (B, D), (B, C)$

Note : a vertex of 0 degree is **isolated**. A simple graph with n vertex has degrees $\in [0, n - 1]$. If all vertices have a $n - 1$ -degree, the associated graph is **complete**.

Characterisation

- Two edges (X, Y) are **adjacents** if there exists a vertex (X, Y) in E .
They are **neighbors**
- One edge that joints X and Y is **incident** to X and Y
- The **degree** $d(X)$ of a vertex X is the number of incident edges to X




Example for B

- Degree $d(B) = 4$
- Incident edges are $(B, A), (B, E), (B, D), (B, C)$

Note : a vertex of 0 degree is **isolated**. A simple graph with n vertex has degrees $\in [0, n - 1]$. If all vertices have a $n - 1$ -degree, the associated graph is **complete**.


Characterization matrices

Let $G = \{V, E\}$ be a graph with n vertices. We call :



Characterization matrices


Let $G = \{V, E\}$ be a graph with n vertices. We call :



- The **adjacency matrix** A , of dimension $(n \times n)$, the binary matrix where a_{ij} is 1 if one edge connects the i^{th} et j^{th} vertices of V .

Characterization matrices

Let $G = \{V, E\}$ be a graph with n vertices. We call :




- The **adjacency matrix** A , of dimension $(n \times n)$, the binary matrix where a_{ij} is 1 if one edge connects the i^{th} et j^{th} vertices of V . Ex :

$$A = \begin{bmatrix} 0 & 1 & 0 & 0 & 1 & 1 \\ 1 & 0 & 1 & 1 & 1 & 0 \\ 0 & 1 & 0 & 1 & 1 & 0 \\ 0 & 1 & 1 & 0 & 1 & 0 \\ 1 & 1 & 1 & 1 & 0 & 0 \\ 1 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}$$

Characterization matrices


Let $G = \{V, E\}$ be a graph with n vertices. We call :



- The **degree matrix** D , of dimension $(n \times n)$, a diagonal matrix where d_{ii} is the number of incident edges of i^{th} vertex.

Characterization matrices

Let $G = \{V, E\}$ be a graph with n vertices. We call :




- The **degree matrix** D , of dimension $(n \times n)$, a diagonal matrix where d_{ii} is the number of incident edges of i^{th} vertex. Ex :

$$D = \begin{bmatrix} 3 & 0 & 0 & 0 & 0 & 0 \\ 0 & 4 & 0 & 0 & 0 & 0 \\ 0 & 0 & 3 & 0 & 0 & 0 \\ 0 & 0 & 0 & 3 & 0 & 0 \\ 0 & 0 & 0 & 0 & 4 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 \end{bmatrix}$$

Characterization matrices

Let $G = \{V, E\}$ be a graph with n vertices. We call :



- The **Laplacian matrix** L , of dimension $(n \times n)$, such that $L = D - A$ (bilan)

$$L = \begin{bmatrix} 3 & -1 & 0 & 0 & -1 & -1 \\ -1 & 4 & -1 & -1 & -1 & 0 \\ 0 & -1 & 3 & -1 & -1 & 0 \\ 0 & -1 & -1 & 3 & -1 & 0 \\ -1 & -1 & -1 & -1 & 4 & 0 \\ -1 & 0 & 0 & 0 & 0 & 1 \end{bmatrix}$$

Normalized Laplacian matrix

Définition : **Normalized Laplacian matrix**

$$L' = D^{-1/2} L D^{-1/2} = I - D^{-1/2} A D^{-1/2}$$

We get it from the graph

$$L' = \begin{cases} 1 & \text{on the diagonal if } \deg(v_i) \neq 0 \\ -\frac{1}{\sqrt{d(i)d(j)}} & \text{if } i \neq j \text{ and } v_i \text{ and } v_j \text{ are adjacent} \\ 0 & \text{else} \end{cases}$$

Normalized Laplacian matrix

Définition : **Normalized Laplacian matrix**


$$L' = D^{-1/2} L D^{-1/2} = I - D^{-1/2} A D^{-1/2}$$

We get it from the graph

$$L' = \begin{cases} 1 & \text{on the diagonal if } \deg(v_i) \neq 0 \\ -\frac{1}{\sqrt{d(i)d(j)}} & \text{if } i \neq j \text{ and } v_i \text{ and } v_j \text{ are adjacent} \\ 0 & \text{else} \end{cases}$$


In general

- Each edge connects 2 vertices through an **incidence function** $\gamma(x_i, x_j)$
 - \Rightarrow A graph is defined by $G = \{V, E, \gamma\}$ but we often omit γ and note $G = \{V, E\}$




In general

- Each edge connects 2 vertices through an **incidence function** $\gamma(x_i, x_j)$
 \Rightarrow A graph is defined by $G = \{V, E, \gamma\}$ but we often omit γ and note $G = \{V, E\}$



In general


- Each edge connects 2 vertexes through an **incidence function** $\gamma(x_i, x_j)$
 \Rightarrow A graph is defined by $G = \{V, E, \gamma\}$ but we often omit γ and note $G = \{V, E\}$



- The **adjacency matrix** W is now the value a_{ij} that links the i^{th} and j^{th} vertexes of V .

In general

- Each edge connects 2 vertexes through an **incidence function** $\gamma(x_i, x_j)$
 \Rightarrow A graph is defined by $G = \{V, E, \gamma\}$ but we often omit γ and note $G = \{V, E\}$




- The **adjacency matrix** W is now the value a_{ij} that links the i^{th} and j^{th} vertexes of V . Ex :

$$W = \begin{bmatrix} 0 & 0.6 & 0 & 0 & 0.2 & 1 \\ 0.6 & 0 & 0.1 & 0.7 & 0.8 & 0 \\ 0 & 0.1 & 0 & 0.3 & 0.4 & 0 \\ 0 & 0.7 & 0.3 & 0 & 0.9 & 0 \\ 0.2 & 0.8 & 0.4 & 0.9 & 0 & 0 \\ 1 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}$$

In general


- Each edge connects 2 vertexes through an **incidence function** $\gamma(x_i, x_j)$
 \Rightarrow A graph is defined by $G = \{V, E, \gamma\}$ but we often omit γ and note $G = \{V, E\}$



- For **degree matrix** D : each element is the sum of weights

In general

- Each edge connects 2 vertexes through an **incidence function** $\gamma(x_i, x_j)$
 \Rightarrow A graph is defined by $G = \{V, E, \gamma\}$ but we often omit γ and note $G = \{V, E\}$




- For **degree matrix** D : each element is the sum of weights. Ex :

$$D = \begin{bmatrix} 1.8 & 0 & 0 & 0 & 0 & 0 \\ 0 & 2.2 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0.8 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1.9 & 0 & 0 \\ 0 & 0 & 0 & 0 & 2.3 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 \end{bmatrix}$$

In general

- Each edge connects 2 vertexes through an **incidence function** $\gamma(x_i, x_j)$
 \Rightarrow A graph is defined by $G = \{V, E, \gamma\}$ but we often omit γ and note $G = \{V, E\}$



- The **Laplacian matrix** L , of dimension $(n \times n)$, is such that $L = D - W$

$$L = \begin{bmatrix} 1.8 & -0.6 & 0 & 0 & -0.2 & -1 \\ -0.6 & 2.2 & -0.1 & -0.7 & -0.8 & 0 \\ 0 & -0.1 & 0.8 & -0.3 & -0.4 & 0 \\ 0 & -0.7 & -0.3 & 1.9 & -0.9 & 0 \\ -0.2 & -0.8 & -0.4 & -0.9 & 2.3 & 0 \\ -1 & 0 & 0 & 0 & 0 & 1 \end{bmatrix}$$

Spectral theory on graphs

Main idea : analyze the **spectra** of associated matrices

⇒ If one vertex is permuted, associated matrix change but not their spectra

With **adjacency matrix**, we get informations on :

- Cycles, regularity, ...

With **Laplacian matrix**, we get informations on :

- number of trees inside the graph, shapes (with eigenvalues, ...)

Many **Applications**

- Network traffic, space optimization, microbiology, image processing, data analysis, ...

Spectral theory on graphs

Main idea : analyze the **spectra** of associated matrices

⇒ If one vertex is permuted, associated matrix change but not their spectra

With **adjacency matrix**, we get informations on :

- Cycles, regularity, ...

With **Laplacian matrix**, we get informations on :

- number of trees inside the graph, shapes (with eigenvalues, ...)

Many **Applications**

- Network traffic, space optimization, microbiology, image processing, data analysis, ...

Spectral theory on graphs

Main idea : analyze the **spectra** of associated matrices

⇒ If one vertex is permuted, associated matrix change but not their spectra

With **adjacency matrix**, we get informations on :

- Cycles, regularity, ...

With **Laplacian matrix**, we get informations on :

- number of trees inside the graph, shapes (with eigenvalues, ...)

Many **Applications**

- Network traffic, space optimization, microbiology, image processing, data analysis, ...

Spectral theory on graphs

Main idea : analyze the **spectra** of associated matrices

⇒ If one vertex is permuted, associated matrix change but not their spectra

With **adjacency matrix**, we get informations on :

- Cycles, regularity, ...

With **Laplacian matrix**, we get informations on :

- number of trees inside the graph, shapes (with eigenvalues, ...)

Many **Applications**

- Network traffic, space optimization, microbiology, image processing, data analysis, ...

Outline

- 1 Introduction
- 2 Generalities on graphes
 - Definition
 - Characterisation
 - General case
 - Spectral theory on graphes
- 3 Clustering with graphs**
 - Generalities
 - Graph construction
 - Graph cut
 - Minimal cut
 - RatioCut
 - MinMaxCut
- 4 Variations

Spectral clustering

Reminder : main families

- Centroid : create several clusters and evaluate their quality depending on some centroids (k-means, k-medoids, PAM, ...)
- Hierarchical : group in a hierarchical way data (AGNES, DIANA, ...)
- Density : rely on the adequacy of data with respect to a certain density (DBSCAN)
- Model-based : one model for each cluster
- Spectral : based on a graph-representation of data

Spectral clustering

Reminder : main families

- **Centroid** : create several clusters and evaluate their quality depending on some centroids (k-means, k-medoids, PAM, ...)
- **Hierarchical** : group in a hierarchical way data (AGNES, DIANA, ...)
- **Density** : rely on the adequacy of data with respect to a certain density (DBSCAN)
- **Model-based** : one model for each cluster
- **Spectral** : based on a graph-representation of data

Spectral clustering

Reminder : main families

- **Centroid** : create several clusters and evaluate their quality depending on some centroids (k-means, k-medoids, PAM, ...)
- **Hierarchical** : group in a hierarchical way data (AGNES, DIANA, ...)
- **Density** : rely on the adequacy of data with respect to a certain density (DBSCAN)
- **Model-based** : one model for each cluster
- **Spectral** : based on a graph-representation of data

⇒ Graph partition

Spectral clustering : generalities

Interesting methods since

- Simple & fast implementation

Spectral clustering : generalities


Interesting methods since

- Simple & fast implementation
- In general efficient in cpu-time


Spectral clustering : generalities

Interesting methods since

- Simple & fast implementation
- In general efficient in cpu-time
- No prior on clusters



General principle 1 – Graph construction (1/2)




From the dataset, construct a graph

Several possibilities :

- 1 **Complete** graph : all vertices connected, all edges $\neq 0$
- 2 **r-neighbour** : vertices are connected only to “close” vertexes $< r$
 \implies Radius r to be defined
- 3 **k-nn** graph : vertices are connected to k nearest neighbours
 \implies Number k to be defined
- 4 One can combine r-neighbour and knn

General principle 1 – Graph construction (1/2)




From the dataset, construct a graph

Several possibilities :

- 1 **Complete** graph : all vertices connected, all edges $\neq 0$
- 2 **r-neighbour** : vertices are connected only to “close” vertexes $< r$
 \implies Radius r to be defined
- 3 **k-nn** graph : vertices are connected to k nearest neighbours
 \implies Number k to be defined
- 4 One can combine r-neighbour and knn

General principle 1 – Graph construction (1/2)




From the dataset, construct a graph

Several possibilities :

- 1 **Complete** graph : all vertices connected, all edges $\neq 0$
- 2 **r-neighbour** : vertices are connected only to “close” vertexes $< r$
 \Rightarrow Radius r to be defined
- 3 **k-nn** graph : vertices are connected to k nearest neighbours
 \Rightarrow Number k to be defined
- 4 One can combine r-neighbour and knn

General principle 1 – Graph construction (1/2)




From the dataset, construct a graph

Several possibilities :

- 1** **Complete** graph : all vertices connected, all edges $\neq 0$
- 2** **r-neighbour** : vertices are connected only to “close” vertexes $< r$
 \Rightarrow Radius r to be defined
- 3** **k-nn** graph : vertices are connected to k nearest neighbours
 \Rightarrow Number k to be defined
- 4** One can combine r-neighbour and knn

General principle 1 – Graph construction (1/2)



From the dataset, construct a graph

Several possibilities :

- 1 **Complete** graph : all vertices connected, all edges $\neq 0$
- 2 **r-neighbour** : vertices are connected only to “close” vertexes $< r$
 \Rightarrow Radius r to be defined
- 3 **k-nn** graph : vertices are connected to k nearest neighbours
 \Rightarrow Number k to be defined
- 4 One can combine r-neighbour and knn

General principle 1 – Graph partition (2/2)

From data matrix X (of dimension $N \times P$: N points of dimension P), **how to affect edge values?**

- Definition of a **similarity matrix**. This can be :
 - Covariance (between each pair of points x_i, x_j)
 - Cosinus of the angle formed by x_i, x_j
 - ...
 - Gaussian kernel

$$K(x_i, x_j) = \exp\left(-\frac{\|x_i - x_j\|^2}{2\sigma^2}\right)$$

Important note : for spatial data (images, ...), one can add spatial coordinates (x, y) to the data

General principle 1 – Graph partition (2/2)

From data matrix X (of dimension $N \times P$: N points of dimension P), **how to affect edge values?**

- Definition of a **similarity matrix**. This can be :
 - Covariance (between each pair of points x_i, x_j)
 - Cosinus of the angle formed by x_i, x_j
 - ...
 - Gaussian kernel

$$K(x_i, x_j) = \exp\left(-\frac{\|x_i - x_j\|^2}{2\sigma^2}\right)$$

Important note : for spatial data (images, ...), one can add spatial coordinates (x, y) to the data

General principle 1 – Graph partition (2/2)

From data matrix X (of dimension $N \times P$: N points of dimension P), **how to affect edge values ?**

- Definition of a **similarity matrix**. This can be :
 - Covariance (between each pair of points x_i, x_j)
 - Cosinus of the angle formed by x_i, x_j
 - ...
 - Gaussian kernel

$$K(x_i, x_j) = \exp\left(-\frac{\|x_i - x_j\|^2}{2\sigma^2}\right)$$

Important note : for spatial data (images, ...), one can add spatial coordinates (x, y) to the data

General principle 1 – Graph partition (2/2)

From data matrix X (of dimension $N \times P$: N points of dimension P), **how to affect edge values?**

- Definition of a **similarity matrix**. This can be :
 - Covariance (between each pair of points x_i, x_j)
 - Cosinus of the angle formed by x_i, x_j
 - ...
 - Gaussian kernel

$$K(x_i, x_j) = \exp\left(-\frac{\|x_i - x_j\|^2}{2\sigma^2}\right)$$

Important note : for spatial data (images, ...), one can add spatial coordinates (x, y) to the data

General principle 1 – Graph partition (2/2)

We aim at partitioning graph $G = (V, E, \gamma)$ into two disjoint ensembles A and B such as

$$\begin{cases} A \cup B = V \\ A \cap B = \emptyset \end{cases}$$

Several possibilities : MinCut, RatioCut, NCut, MinMaxCut, ... We define :

- The **sum of connections between two clusters** (A et B) :

$$Cut(A, B) = \sum_{x_i \in A, x_j \in B} \gamma(x_i, x_j) = \frac{1}{4} q^T (D - W) q$$

with $q = \{-1, 1\}$

- The **sum of connections inside one clusters** A :

$$Cut(A) = \sum_{x_i \in A, x_j \in A} \gamma(x_i, x_j)$$

- The **total weights** embed in cluster A :

$$Vol(A) = \sum_{x_i \in A} D(x_i) \text{ avec } D(x_i) \text{ (from the degree matrix)}$$

General principle 1 – Graph partition (2/2)

We aim at partitioning graph $G = (V, E, \gamma)$ into two disjoint ensembles A and B such as

$$\begin{cases} A \cup B = V \\ A \cap B = \emptyset \end{cases}$$

Several possibilities : MinCut, RatioCut, NCut, MinMaxCut, ... We define :

- The **sum of connections between two clusters** (A et B) :

$$Cut(A, B) = \sum_{x_i \in A, x_j \in B} \gamma(x_i, x_j) = \frac{1}{4} q^T (D - W) q$$

with $q = \{-1, 1\}$

- The **sum of connections inside one clusters** A :

$$Cut(A) = \sum_{x_i \in A, x_j \in A} \gamma(x_i, x_j)$$

- The **total weights** embed in cluster A :

$$Vol(A) = \sum_{x_i \in A} D(x_i) \text{ avec } D(x_i) \text{ (from the degree matrix)}$$

General principle 1 – Graph partition (2/2)

We aim at partitioning graph $G = (V, E, \gamma)$ into two disjoint ensembles A and B such as

$$\begin{cases} A \cup B = V \\ A \cap B = \emptyset \end{cases}$$

Several possibilities : MinCut, RatioCut, NCut, MinMaxCut, ... We define :

- The **sum of connections between two clusters** (A et B) :

$$Cut(A, B) = \sum_{x_i \in A, x_j \in B} \gamma(x_i, x_j) = \frac{1}{4} q^T (D - W) q$$

with $q = \{-1, 1\}$

- The **sum of connections inside one clusters** A :

$$Cut(A) = \sum_{x_i \in A, x_j \in A} \gamma(x_i, x_j)$$

- The **total weights** embed in cluster A :

$$Vol(A) = \sum_{x_i \in A} D(x_i) \text{ avec } D(x_i) \text{ (from the degree matrix)}$$

General principle 1 – Graph partition (2/2)

We aim at partitioning graph $G = (V, E, \gamma)$ into two disjoint ensembles A and B such as

$$\begin{cases} A \cup B = V \\ A \cap B = \emptyset \end{cases}$$

Several possibilities : MinCut, RatioCut, NCut, MinMaxCut, ... We define :

- The **sum of connections between two clusters** (A et B) :

$$Cut(A, B) = \sum_{x_i \in A, x_j \in B} \gamma(x_i, x_j) = \frac{1}{4} q^T (D - W) q$$

with $q = \{-1, 1\}$

- The **sum of connections inside one clusters** A :

$$Cut(A) = \sum_{x_i \in A, x_j \in A} \gamma(x_i, x_j)$$

- The **total weights** embed in cluster A :

$$Vol(A) = \sum_{x_i \in A} D(x_i) \text{ avec } D(x_i) \text{ (from the degree matrix)}$$

General principle 1 – Graph partition (2/2)

We aim at partitioning graph $G = (V, E, \gamma)$ into two disjoint ensembles A and B such as

$$\begin{cases} A \cup B = V \\ A \cap B = \emptyset \end{cases}$$

Several possibilities : MinCut, RatioCut, NCut, MinMaxCut, ... We define :

- The **sum of connections between two clusters** (A et B) :

$$Cut(A, B) = \sum_{x_i \in A, x_j \in B} \gamma(x_i, x_j) = \frac{1}{4} q^T (D - W) q$$

with $q = \{-1, 1\}$

- The **sum of connections inside one clusters** A :


$$Cut(A) = \sum_{x_i \in A, x_j \in A} \gamma(x_i, x_j)$$

- The **total weights** embed in cluster A :

$$Vol(A) = \sum_{x_i \in A} D(x_i) \text{ avec } D(x_i) \text{ (from the degree matrix)}$$


General principle 1 – Graph partition (2/2)

Example




General principle 1 – Graph partition (2/2)

Example



General principle 1 – Graph partition (2/2)


Example



Compute parameters associated with each cluster

General principle 1 – Graph partition (2/2)


Example



- $Cut(A, B) = \sum_{x_i \in A, x_j \in B} \gamma(x_i, x_j)$
- $Cut(A) = \sum_{x_i \in A, x_j \in A} \gamma(x_i, x_j)$
- $Cut(B) = \sum_{x_i \in B, x_j \in B} \gamma(x_i, x_j)$
- $Vol(A) = \sum_{x_i \in A} D(x_i)$
- $Vol(B) = \sum_{x_i \in B} D(x_i)$

General principle 1 – Graph partition (2/2)

Example



- $Cut(A, B) = \sum_{x_i \in A, x_j \in B} \gamma(x_i, x_j) = 0.3$
- $Cut(A) = \sum_{x_i \in A, x_j \in A} \gamma(x_i, x_j) = 2.6$
- $Cut(B) = \sum_{x_i \in B, x_j \in B} \gamma(x_i, x_j) = 2.4$
- $Vol(A) = \sum_{x_i \in A} D(x_i) = 5.5$
- $Vol(B) = \sum_{x_i \in B} D(x_i) = 5.1$

Outline

- 1 Introduction
- 2 Generalities on graphes
 - Definition
 - Characterisation
 - General case
 - Spectral theory on graphes
- 3 Clustering with graphs**
 - Generalities
 - Graph construction
 - Graph cut**
 - Minimal cut
 - RatioCut
 - MinMaxCut
- 4 Variations

General principle 2 – Graph cut

- Principles of **MinCut (minimal cut)** method is to search for two clusters A and B that have minimal connection sums ($Cut(A, B)$)
- Minimize a **cost function** :

$$\{A^*, B^*\} = \arg \min_{A, B} Cut(A, B)$$

- We define

$$q = \begin{cases} 1 & \text{if } i \in A \\ -1 & \text{if } i \in B \end{cases}$$

- this is equivalent to find q^* that minimize :

$$q^* = \arg \min_q q^T (D - W)q$$

General principle 2 – Graph cut

- Principles of **MinCut (minimal cut)** method is to search for two clusters A and B that have minimal connection sums ($Cut(A, B)$)
- Minimize a **cost function** :

$$\{A^*, B^*\} = \arg \min_{A, B} Cut(A, B)$$

- We define

$$q = \begin{cases} 1 & \text{if } i \in A \\ -1 & \text{if } i \in B \end{cases}$$

- this is equivalent to find q^* that minimize :

$$q^* = \arg \min_q q^T (D - W)q$$

General principle 2 – Graph cut

- Principles of **MinCut (minimal cut)** method is to search for two clusters A and B that have minimal connection sums ($Cut(A, B)$)
- Minimize a **cost function** :

$$\{A^*, B^*\} = \arg \min_{A, B} Cut(A, B)$$

- We define

$$q = \begin{cases} 1 & \text{if } i \in A \\ -1 & \text{if } i \in B \end{cases}$$

- this is equivalent to find q^* that minimize :

$$q^* = \arg \min_q q^T (D - W)q$$

General principle 2 – Graph cut

- Principles of **MinCut (minimal cut)** method is to search for two clusters A and B that have minimal connection sums ($Cut(A, B)$)
- Minimize a **cost function** :

$$\{A^*, B^*\} = \arg \min_{A, B} Cut(A, B)$$

- We define

$$q = \begin{cases} 1 & \text{if } i \in A \\ -1 & \text{if } i \in B \end{cases}$$

- this is equivalent to find q^* that minimize :

$$q^* = \arg \min_q q^T (D - W) q$$

General principle 2 – Graph cut

- **Reminder** We search for q^* that minimize :

$$q^* = \arg \min_q q^T (D - W)q$$

with the constraint $q_i = \{1, -1\}$

- This is a **discrete optimization** problem
- A continuous formulation gives a **trivial solution** ($q = 1$) but not satisfactory (all points in the same cluster)
- In practice : **eigen vector/value** problem :

$$(D - W)q = \lambda q$$

General principle 2 – Graph cut

- **Reminder** We search for q^* that minimize :

$$q^* = \arg \min_q q^T (D - W)q$$

with the constraint $q_i = \{1, -1\}$

- This is a **discrete optimization** problem
- A continuous formulation gives a **trivial solution** ($q = 1$) but not satisfactory (all points in the same cluster)
- In practice : **eigen vector/value** problem :

$$(D - W)q = \lambda q$$

General principle 2 – Graph cut

- **Reminder** We search for q^* that minimize :

$$q^* = \arg \min_q q^T (D - W)q$$

with the constraint $q_i = \{1, -1\}$

- This is a **discrete optimization** problem
- A continuous formulation gives a **trivial solution** ($q = 1$) but not satisfactory (all points in the same cluster)
- In practice : **eigen vector/value** problem :

$$(D - W)q = \lambda q$$

General principle 2 – Graph cut

- **Reminder** We search for q^* that minimize :

$$q^* = \arg \min_q q^T (D - W)q$$

with the constraint $q_i = \{1, -1\}$

- This is a **discrete optimization** problem
- A continuous formulation gives a **trivial solution** ($q = 1$) but not satisfactory (all points in the same cluster)
- In practice : **eigen vector/value** problem :

$$(D - W)q = \lambda q$$

Analysis of Laplacian matrix

- Matrix $L = D - W$ **symmetric** (if non oriented graph)
- Immediate eigen vector : $q_1 = (1, 1, 1, 1, 1, 1, 1, \dots, 1)^T$ (cf demo)
 - ⇒ Not satisfactory since **all points in the same cluster**. **Associated eigen value** : $\lambda_1 = 0$
- Other eigen vectors give other possible partitions. The second eigen vector (in growing order), named **Fiedler-vector**, is used for the graph partition
 - ⇒ The smaller λ_2 , the more interesting the partition is
 - ⇒ The assignation can be done with the sign of the eigenvector

cf example on matlab

⇒ No guarantee to have homogeneous clusters

Analysis of Laplacian matrix

- Matrix $L = D - W$ **symmetric** (if non oriented graph)
- Immediate eigen vector : $q_1 = (1, 1, 1, 1, 1, 1, 1, \dots, 1)^T$ (cf demo)
 - ⇒ Not satisfactory since **all points in the same cluster**. **Associated eigen value** : $\lambda_1 = 0$
- Other eigen vectors give other possible partitions. The second eigen vector (in growing order), named **Fiedler-vector**, is used for the graph partition
 - ⇒ The smaller λ_2 , the more interesting the partition is
 - ⇒ The assignation can be done with the sign of the eigenvector

cf example on matlab

⇒ No guarantee to have homogeneous clusters

Analysis of Laplacian matrix

- Matrix $L = D - W$ **symmetric** (if non oriented graph)
- Immediate eigen vector : $q_1 = (1, 1, 1, 1, 1, 1, 1, \dots, 1)^T$ (cf demo)
 - ⇒ Not satisfactory since **all points in the same cluster**. **Associated eigen value** : $\lambda_1 = 0$
- Other eigen vectors give other possible partitions. The second eigen vector (in growing order), named **Fiedler-vector**, is used for the graph partition
 - ⇒ The smaller λ_2 , the more interesting the partition is
 - ⇒ The assignation can be done with the sign of the eigenvector

cf example on matlab

⇒ No guarantee to have homogeneous clusters

Analysis of Laplacian matrix

- Matrix $L = D - W$ **symmetric** (if non oriented graph)
- Immediate eigen vector : $q_1 = (1, 1, 1, 1, 1, 1, 1, \dots, 1)^T$ (cf demo)
 - ⇒ Not satisfactory since **all points in the same cluster**. **Associated eigen value : $\lambda_1 = 0$**
- Other eigen vectors give other possible partitions. The second eigen vector (in growing order), named **Fiedler-vector**, is used for the graph partition
 - ⇒ The smaller λ_2 , the more interesting the partition is
 - ⇒ The assignation can be done with the sign of the eigenvector

cf example on matlab

⇒ No guarantee to have homogeneous clusters

Analysis of Laplacian matrix

- Matrix $L = D - W$ **symmetric** (if non oriented graph)
- Immediate eigen vector : $q_1 = (1, 1, 1, 1, 1, 1, 1, \dots, 1)^T$ (cf demo)
 - ⇒ Not satisfactory since **all points in the same cluster**. **Associated eigen value** : $\lambda_1 = 0$
- Other eigen vectors give other possible partitions. The second eigen vector (in growing order), named **Fiedler-vector**, is used for the graph partition
 - ⇒ The smaller λ_2 , the more interesting the partition is
 - ⇒ The assignation can be done with the sign of the eigenvector

cf example on matlab

⇒ No guarantee to have homogeneous clusters

Analysis of Laplacian matrix

- Matrix $L = D - W$ **symmetric** (if non oriented graph)
- Immediate eigen vector : $q_1 = (1, 1, 1, 1, 1, 1, 1, \dots, 1)^T$ (cf demo)
 - ⇒ Not satisfactory since **all points in the same cluster**. **Associated eigen value : $\lambda_1 = 0$**
- Other eigen vectors give other possible partitions. The second eigen vector (in growing order), named **Fiedler-vector**, is used for the graph partition
 - ⇒ The smaller λ_2 , the more interesting the partition is
 - ⇒ The assignation can be done with the sign of the eigenvector

cf example on matlab

⇒ No guarantee to have homogeneous clusters

Analysis of Laplacian matrix

- Matrix $L = D - W$ **symmetric** (if non oriented graph)
- Immediate eigen vector : $q_1 = (1, 1, 1, 1, 1, 1, 1, \dots, 1)^T$ (cf demo)
 - ⇒ Not satisfactory since **all points in the same cluster**. **Associated eigen value : $\lambda_1 = 0$**
- Other eigen vectors give other possible partitions. The second eigen vector (in growing order), named **Fiedler-vector**, is used for the graph partition
 - ⇒ The smaller λ_2 , the more interesting the partition is
 - ⇒ The assignation can be done with the sign of the eigenvector

cf example on matlab

⇒ No guarantee to have homogeneous clusters

Minimal cut : coins

- No guarantee to have **homogeneous clusters**
 - ⇒ One can use the second eigenvector and cut it
- **Multi-class partitioning**
 - ⇒ One can use other eigenvectors
 - ⇒ One can use recursive cuts
 - ⇒ Packages : Scikit learn, Chaco, PaToH, Party, METIS
- **Packages**
 - ⇒ Scikit learn, Chaco, PaToH, Party, METIS, ...

Minimal cut : coins

- No guarantee to have **homogeneous clusters**
 - ⇒ One can use the second eigenvector and cut it
- **Multi-class partitioning**
 - ⇒ One can use other eigenvectors
 - ⇒ One can use recursive cuts
 - ⇒ Packages : Scikit learn, Chaco, PaToH, Party, METIS
- **Packages**
 - ⇒ Scikit learn, Chaco, PaToH, Party, METIS, ...

Minimal cut : coins

- No guarantee to have **homogeneous clusters**
 - ⇒ One can use the second eigenvector and cut it
- **Multi-class partitioning**
 - ⇒ One can use other eigenvectors
 - ⇒ One can use recursive cuts
 - ⇒ Packages : Scikit learn, Chaco, PaToH, Party, METIS
- **Packages**
 - ⇒ Scikit learn, Chaco, PaToH, Party, METIS, ...

Plan

- 1 Introduction
- 2 Generalities on graphes
 - Definition
 - Characterisation
 - General case
 - Spectral theory on graphes
- 3 Clustering with graphs**
 - Generalities
 - Graph construction
 - Graph cut
 - Minimal cut
 - RatioCut
 - MinMaxCut
- 4 Variations


RatioCut method

- Idea : impose in the cost function **homogeneous clusters**

RatioCut method

- Idea : impose in the cost function **homogeneous clusters**
- Cost function :

$$\{A^*, B^*\} = \arg \min_{A, B} Cut(A, B) \left(\frac{1}{|A|} + \frac{1}{|B|} \right)^2$$



RatioCut method

- Idea : impose in the cost function **homogeneous clusters**
- One can replace **cardinals** by **volumes**. Cost-function :

$$\{A^*, B^*\} = \arg \min_{A, B} Cut(A, B) \left(\frac{1}{Vol(A)} + \frac{1}{Vol(B)} \right)^2$$

RatioCut method

- Similar system based on eigen vectors
- Until now, the cost function is composed of
 - Information about **distances** between clusters
 - Information about **size** of clusters
 - Need also **internal informations** inside clusters

RatioCut method

- Similar system based on eigen vectors
- Until now, the cost function is composed of
 - Information about **distances** between clusters
 - Information about **size** of clusters
 - Need also **internal informations** inside clusters

RatioCut method

- Similar system based on eigen vectors
- Until now, the cost function is composed of
 - Information about **distances** between clusters
 - Information about **size** of clusters
 - Need also **internal informations** inside clusters

Plan

- 1 Introduction
- 2 Generalities on graphes
 - Definition
 - Characterisation
 - General case
 - Spectral theory on graphes
- 3 Clustering with graphs**
 - Generalities
 - Graph construction
 - Graph cut
 - Minimal cut
 - RatioCut
 - MinMaxCut
- 4 Variations

MinMaxCut method

- Idea : compromise between clusters of homogeneous sizes, “far-away” from each others and hemegeneous

1 **Constraint 1** : minimize inter-connections :

$$\{A^*, B^*\} = \arg \min_{A, B} Cut(A, B)$$

2 **Constraint 2** : maximize intra-connections :

$$\max_A Cut(A) \text{ et } \max_B Cut(B)$$

- joint minimization of

$$\begin{cases} \{A^*, B^*\} = \arg \min_{A, B} Cut(A, B) \left(\frac{1}{Vol(A)} + \frac{1}{Vol(B)} \right) \\ \{A^*, B^*\} = \arg \min_{A, B} Cut(A, B) \left(\frac{1}{Cut(A)} + \frac{1}{Cut(B)} \right) \end{cases}$$

- This also leads to an eigen vector/value problem on Laplacian matrix L , with different constraints on q

MinMaxCut method

- Idea : compromise between clusters of homogeneous sizes, “far-away” from each others and heterogeneous

1 **Constraint 1** : minimize inter-connections :

$$\{A^*, B^*\} = \arg \min_{A, B} \text{Cut}(A, B)$$

2 **Constraint 2** : maximize intra-connections :

$$\max_A \text{Cut}(A) \text{ et } \max_B \text{Cut}(B)$$

- joint minimization of

$$\begin{cases} \{A^*, B^*\} = \arg \min_{A, B} \text{Cut}(A, B) \left(\frac{1}{\text{Vol}(A)} + \frac{1}{\text{Vol}(B)} \right) \\ \{A^*, B^*\} = \arg \min_{A, B} \text{Cut}(A, B) \left(\frac{1}{\text{Cut}(A)} + \frac{1}{\text{Cut}(B)} \right) \end{cases}$$

- This also leads to an eigen vector/value problem on Laplacian matrix L , with different constraints on q

MinMaxCut method

- Idea : compromise between clusters of homogeneous sizes, "far-away" from each others and heterogeneous

1 Constraint 1 : minimize inter-connections :

$$\{A^*, B^*\} = \arg \min_{A, B} Cut(A, B)$$

2 Constraint 2 : maximize intra-connections :

$$\max_A Cut(A) \text{ et } \max_B Cut(B)$$

- joint minimization of

$$\begin{cases} \{A^*, B^*\} = \arg \min_{A, B} Cut(A, B) \left(\frac{1}{Vol(A)} + \frac{1}{Vol(B)} \right) \\ \{A^*, B^*\} = \arg \min_{A, B} Cut(A, B) \left(\frac{1}{Cut(A)} + \frac{1}{Cut(B)} \right) \end{cases}$$

- This also leads to an eigen vector/value problem on Laplacian matrix L , with different constraints on q

MinMaxCut method

- Idea : compromise between clusters of homogeneous sizes, “far-away” from each others and heterogeneous

1 **Constraint 1** : minimize inter-connections :

$$\{A^*, B^*\} = \arg \min_{A, B} \text{Cut}(A, B)$$

2 **Constraint 2** : maximize intra-connections :

$$\max_A \text{Cut}(A) \text{ et } \max_B \text{Cut}(B)$$

- joint minimization of

$$\begin{cases} \{A^*, B^*\} = \arg \min_{A, B} \text{Cut}(A, B) \left(\frac{1}{\text{Vol}(A)} + \frac{1}{\text{Vol}(B)} \right) \\ \{A^*, B^*\} = \arg \min_{A, B} \text{Cut}(A, B) \left(\frac{1}{\text{Cut}(A)} + \frac{1}{\text{Cut}(B)} \right) \end{cases}$$

- This also leads to an eigen vector/value problem on Laplacian matrix L , with different constraints on q

MinMaxCut method

- Idea : compromise between clusters of homogeneous sizes, “far-away” from each others and heterogeneous

1 Constraint 1 : minimize inter-connections :

$$\{A^*, B^*\} = \arg \min_{A, B} Cut(A, B)$$

2 Constraint 2 : maximize intra-connections :

$$\max_A Cut(A) \text{ et } \max_B Cut(B)$$

- joint minimization of

$$\begin{cases} \{A^*, B^*\} = \arg \min_{A, B} Cut(A, B) \left(\frac{1}{Vol(A)} + \frac{1}{Vol(B)} \right) \\ \{A^*, B^*\} = \arg \min_{A, B} Cut(A, B) \left(\frac{1}{Cut(A)} + \frac{1}{Cut(B)} \right) \end{cases}$$

- This also leads to an eigen vector/value problem on Laplacian matrix L , with different constraints on q

Generalities

On methods

- If clusters are well separables, the 3 approaches are almost identical
- Otherwise, MinMaxCut is the most efficient

Extension to k classes

- MinCut :

$$A_I^* = \arg \min_{A_i} \sum_{i=1}^k \text{Cut}(A_i, \overline{A_i})$$

- RatioCut :

$$A_I^* = \arg \min_{A_i} \sum_{i=1}^k \frac{\text{Cut}(A_i, \overline{A_i})}{|A_i|}$$

- MinMaxCut

$$\begin{cases} A_I^* = \arg \min_{A_i} \sum_{i=1}^k \frac{\text{Cut}(A_i, \overline{A_i})}{\text{Vol}(A_i)} \\ A_i^* = \arg \min_{A_i} \sum_{i=1}^k \frac{\text{Cut}(A_i, \overline{A_i})}{\text{Cut}(A_i)} \end{cases}$$

Generalities

On methods

- If clusters are well separables, the 3 approaches are almost identical
- Otherwise, MinMaxCut is the most efficient

Extension to k classes

- MinCut :

$$A_I^* = \arg \min_{A_i} \sum_{i=1}^k \text{Cut}(A_i, \overline{A_i})$$


- RatioCut :

$$A_I^* = \arg \min_{A_i} \sum_{i=1}^k \frac{\text{Cut}(A_i, \overline{A_i})}{|A_i|}$$

- MinMaxCut

$$\begin{cases} A_I^* = \arg \min_{A_i} \sum_{i=1}^k \frac{\text{Cut}(A_i, \overline{A_i})}{\text{Vol}(A_i)} \\ A_i^* = \arg \min_{A_i} \sum_{i=1}^k \frac{\text{Cut}(A_i, \overline{A_i})}{\text{Cut}(A_i)} \end{cases}$$

Example in image processing



Source : *Diffusion Maps, Spectral Clustering and Eigenfunctions of Fokker-Planck Operators* Boaz Nadler,
 Stephane Lafon, Ronald R. Coifman

Outline

- 1 Introduction
- 2 Generalities on graphes
 - Definition
 - Characterisation
 - General case
 - Spectral theory on graphes
- 3 Clustering with graphs
 - Generalities
 - Graph construction
 - Graph cut
 - Minimal cut
 - RatioCut
 - MinMaxCut
- 4 Variations

Clustering with Laplacian matrix

We can directly use the Laplacian matrix without cut

1 Step 1 : pre-processing

- Graph construction and computation of adjacency, degree and Laplacian matrices

2 Step 2 : spectral analysis

- Computation of eigenvectors and eigenvalues of Laplacian matrix
- Change of variables in the eigen-vector space

3 Step 3 : clustering

- Apply a simple clustering technique (k-means, ...) on this representation