

Random Numbers

Random numbers are ubiquitous in physics – thermodynamics, radioactivity, particle collision and everything in between

Two basic methods to generate random number with varying degree of randomness

- *True* RNG

True RNG : uses natural phenomenon like coin flipping, dice rolling, radioactive decay, thermal noise, atmospheric radio-noise etc.

Requires post-processing, slow $\Rightarrow$ not useful for regular usage

- *Pseudo* RNG

Pseudo RNG : based on algorithms, generated iteratively

Deterministic, finite sequence length, correlated but extremely fast and portable

Sequence length can be made veryyy long by proper choice of parameters




Basic goal : Write your own pRNG and use it for all assignments, exams and DIY

Example : a quick and dirty pRNG




$$x_{i+1} = c x_i (1 - x_i)$$

x_0 is the seed which defines the random sequence.

An exercise with $x_0 = 0.1$ and $c = 3.2, 3.7, 3.98$



Plots of x_i vs. x_{i+5} show correlatedness (how to measure / quantify it?)



Bad pRNG for many choices of c and seed x_0 – settles down into regular pattern. However, no specific pattern for $c = 3.98, x_0 = 0.1$

Quantifying good and bad pRNG : Need mathematical tests for determining randomness $\Rightarrow$ if pRNG fails test, then don't use

Eyes are good at discerning patterns but can fool us too!

Basic test : correlation, moments

Advanced test : chi-square, Kolmogorov-Smirnov

Ideally random numbers generated have have no correlations and error statistical i.e. scale as $1/\sqrt{N}$

Correlations test :

$$\epsilon(n, N) = \frac{1}{N} \sum_{i=1}^N x_i x_{i+n} - \left(\frac{1}{N} \sum_{i=1}^N x_i \right)^2$$

Connected Correlations test :

$$\epsilon(n, N) = \frac{1}{N} \sum_{i=1}^N x_i x_{i+n} - \frac{1}{N} \sum_{i=1}^N x_i \frac{1}{N} \sum_{i=1}^N x_{i+n}$$

If tuplets of RN not correlated, $\epsilon(n, N) \rightarrow 0$ with statistical error $1/\sqrt{N}$.

Linear Congruential Generator

One of the oldest and most common choice of **pRNG** having a uniform distribution,

$$x_{i+1} = (ax_i + c) \bmod m \equiv x_{i+1} = \text{remainder} \left(\frac{ax_i + c}{m} \right)$$

The m determines the period of the generator *i.e.* produces random numbers between 0 and $m - 1$, whereas x_i/m yields randoms in the interval $[0,1]$.

- ▶ m is typically chosen to be 2^{32}
- ▶ a is *multiplier* and usually $0 < a < m$. **Numerical Recipes** uses $a = 1664525$ and **gcc** uses $a = 1103515245$
- ▶ c is *increment* and usually $0 < c < m$. **Numerical Recipes** uses $c = 1013904223$ and **gcc** uses $c = 12345$

Not all rosy with **LCG**

- $a, c, m, x_0 = 6, 7, 5, 2$: 4,1,2,0,2,4,1,2,0,2, ...
- $a, c, m, x_0 = 27, 11, 54, 2$: 11,38,11,38, ...

LCG : Hull-Dobell theorem

LCG is extremely sensitive to a, c, x_0, m . Particularly, a has to be chosen with great care else short / very short periodicity will set in.

Hull-Dobell theorem : LCG has a period m iff $c \neq 0$ and

1. c is coprime to m ,
2. $a - 1$ is a multiple of p for every prime p dividing m
3. $a - 1$ is a multiple of 4, if m is a multiple of 4.

LCG works well for m having many repeated prime factors p , such as power of 2. But if m are square-free integer (having no n^2 factor for any n), then only $a = 1$ is allowed and it is a very bad pRNG.

LCG is extremely fast, least memory footprint but period severely limited by choice of m : for $m \sim 10^{32} \rightarrow 10^9$ pRN. Gets exhausted in seconds!!

$c = 0$ corresponds to Lehmer, Park-Miller pRNG

$$x_{i+1} = ax_i \cdot \text{mod } m$$



m can be a prime or a prime just less than a power of 2 (Mersenne primes $2^{31} - 1, 2^{61} - 1$ etc.) or can be a simple power of 2.

A few exercise in **LCG**



$a = 27, c = 11, m = 54, x_0 = 10$ (Ugly choice) :

0.204, 0.704, 0.204, 0.704, ...

$a = 57, c = 1, m = 256, x_0 = 10$ (Bad choice)



$a = 1103515245, c = 12345, m = 32768, x_0 = 10$ (Good choice)




Application : Determination of π

Consider a **unit circle** $r = 1$ centered at origin $\Rightarrow$ area = π .




Put unit circle in a square of side $2r = 2$.

Confine to first quadrant and randomly generate points (x, y) and check for inside points $x^2 + y^2 \leq 1$. $\Rightarrow$ area = $\pi/4$.



Then over LARGE number of trials

$$\frac{\text{circle area}}{\text{square area}} \approx \frac{\text{total inside}}{\text{total trials}} \Rightarrow \pi \approx 4 \times \frac{\text{total inside}}{\text{total trials}}$$



Application : Radioactivity



Radioactive decay is intrinsically random at atomic level – cannot predict when one particular atom will decay.

But, a large collection of atoms decay at predictable rate proportional to the decay rate λ . Decay probability, over a time Δt is given by

$$P = \lambda \Delta t$$

To simulate radiative decay, e.g. $A \rightarrow B$ or $A \rightarrow B \rightarrow C$

- ▶ Choose a random number $r \in [0, 1]$
- ▶ If $r < P_A$ change $A \rightarrow B$ i.e. $N_A \rightarrow N_A - 1$ and $N_B \rightarrow N_B + 1$
- ▶ Cycle over all N_A atoms in given time interval.
- ▶ For the process $A \rightarrow B \rightarrow C$, iterate the above steps over all the N_B , generated this far, by comparing $r < P_B$ and changing N_B and N_C accordingly.



Different pRNG distribution

Standard **pRNG** generates uniform random integers $\ell \in [0, INT_MAX]$ or floating point numbers $x = (\ell / INT_MAX) \in [0, 1)$.

- **pRNG** uniformly distributed $u \in [a, b)$ from $x \in [0, 1)$

$$u = a + (b - a) x$$

Suppose $p(x)$ is **pdf** of a uniform RN x and target **pdf** is $q(y)$.

$$|q(y) dy| = |p(x) dx| \rightarrow q(y) = p(x) \left| \frac{dx}{dy} \right|$$

For uniform RN $x \in [0, 1) \Rightarrow p(x) = 1$.

- Exponentially distributed RN

$$q(y) = a e^{-ay} \text{ for } y \geq 0, a > 0$$

From the transformation law

$$a e^{-ay} = \left| \frac{dx}{dy} \right| \rightarrow x = \int_0^y q(y) dy = 1 - e^{-ay} \Rightarrow y = -\frac{1}{a} \ln(1-x) \equiv -\frac{1}{a} \ln x$$

because $(1-x) \in [0, 1)$ as well.

How to histogram random numbers

An example program in Python

```
import matplotlib.pyplot as plt
import numpy as np
from mylib import *

# Main execution block
if __name__ == "__main__":

    myexprn=[]
    myrn=mylib.my_exprand(1234) # seed the pRNG
    for i in range(2000):      # 2K randoms for histogram
        myrn=mylib.my_exprand()
        myexprn.append(myrn)

    # plotting basic histogram
    plt.hist(myexprn, bins=40, color='skyblue', edgecolor='black')
    plt.show()

# end of python code
```

How to call random numbers?

An example program in C

```
#include <stdio.h>
#include <stdlib.h>

int main(int argc, char *argv[]){

srand(1234);    // seeding pRNG only once
for (int=0; i < 20; i++){
    float myrand=(float)rand()/(float)RAND_MAX;    // call RNG
    printf("Random-#-%d-: -%.4f\n", i, myrand);
}

} // end of main
```

An example program in Python

```
import random

random.seed(12345)    // seeding pRNG only once
for _ in range(0,20)
    myrand=random.uniform(0,1)
    print(myrand)

# end of python code
```

Here is what you should do

An example program in C

```
#include <stdio.h>

float myrand(int seed = 0){
    static int x0,x1;
    static int a=1103515245;           // static int c,m etc.
    float rn;

    if(seed) x0=seed;
    x1=(a*x0+c)%m;
    rn=(float)x1/(float)m;             // converting to [0.0,1.0]
    x0=x1;
    return(rn);
} // end of myrand()

int main(int argc, char *argv[]){

    float myrn=myrand(1234);
    for(int i=0; i<20; i++){
        printf("Random-#-%d-: -%.4f\n", i, myrand());
    }

} // end of main
```

Here is what you should do

An example program in Python

```
def myrand(seed=0):
    if not hasattr(myrand, "x0"):
        myrand.x0 = 0
    a = 1103515245
    c = 12345
    m = 2**31

    if seed:
        myrand.x0 = seed
    x1 = (a * myrand.x0 + c) % m
    rn = x1 / m # converting to [0.0,1.0]
    myrand.x0 = x1
    return rn

# Main execution block
if __name__ == "__main__":
    myrn = myrand(1234) # seed the pRNG
    for i in range(20):
        print(f"Random-#{i}-:-{myrand():.4f}")
```