

# Contabo VPS + OpenClaw Setup Guide

Audience: non-technical PC users. Goal: buy a cheap VPS, secure it, install OpenClaw, and connect it to Telegram and Claude (subscription).

This guide is written for **Contabo VPS 10 (8 GB RAM)** on **Ubuntu 24.04**.

---

## What you will achieve

- A private server (VPS) running Ubuntu 24.04.
  - Secure access using **Tailscale** (no public admin ports).
  - OpenClaw installed and running as a background service.
  - Telegram bot connected.
  - Claude connected via your subscription.
  - Browser automation working on the VPS.
- 

## Preparation (do this first, on your own PC)

Complete these steps before buying the VPS. This way you can paste tokens directly during setup without switching context.

### 1. Create a Telegram bot and save the token

1. Open Telegram and find `@BotFather`.
2. Send `/newbot`.
3. Choose a name and a username.
4. BotFather will give you a **Bot Token** (looks like `123456:ABC...` ).

Save the Bot Token somewhere safe.

### 2. Install Tailscale on your PC

1. Go to [tailscale.com](https://tailscale.com) and download the app for your computer.

2. Install it and sign in.
3. Confirm Tailscale is running (you'll see its icon in your system tray/menu bar).

### 3. Ensure you have a Claude subscription

You need an active Claude subscription at [claude.ai](https://claude.ai).

---

## Part 1: Buy and Access VPS

### Step 1. Buy the VPS on Contabo

1. [Go to Contabo](#) and choose **VPS 10 (8 GB RAM)**.
2. Choose:
3. **Operating system:** Ubuntu **24.04 LTS**
4. **Server location:** pick the closest region
5. Set the **root password** option.
6. Finish checkout.
7. After the VPS is ready, find **Server IP address** (looks like `123.45.67.89`) in your email.

Write it down.

---

### Step 2. Connect to the server

1. Open Terminal (macOS/Linux) or Windows Terminal (Windows).
2. Type this command, replacing YOUR\_SERVER\_IP with your actual IP:

```
ssh root@YOUR_SERVER_IP
```

1. Type `yes` when asked about unknown host.
2. Paste the root password and press Enter.

If you see a prompt like `root@...`, you're connected.

---

## Part 2: Secure the Server

### Step 3. Update and create a user

Copy and paste each block. Wait for each to finish before running the next.

#### **Update system and create user "remote":**

```
apt update && apt upgrade -y  
adduser remote  
usermod -aG sudo remote
```

It will ask you to create a password. Save it. Then allow this user to login:

```
mkdir -p /home/remote/.ssh && cp -r /root/.ssh/* /home/remote/.ssh/ 2>/dev/null
```

#### **Now disconnect and reconnect as the new user:**

```
exit
```

Then:

```
ssh remote@YOUR_SERVER_IP
```

---

## Step 4. Install Tailscale on the server

Tailscale creates a private network between your PC and the server.

```
curl -fsSL https://tailscale.com/install.sh | sh  
sudo tailscale up
```

After running, it shows a login link. Copy it, open in your browser, and approve the server. Then get your server's Tailscale IP:

```
tailscale ip -4
```

It returns something like `100.x.y.z`. Write this down as **TS\_IP**.

---

## Step 5. Lock down the server

After this step, you'll only access the server through Tailscale (more secure).

**First, test that Tailscale works.** On your PC, open a new terminal and run:

```
ssh remote@TS_IP
```

(Replace TS\_IP with the 100.x.y.z address from Step 4.)

If this works, continue. If not, check that Tailscale is running on both your PC and server.

**Enable the firewall:**

```
sudo apt install -y ufw && sudo ufw default deny incoming && sudo ufw default a
```

Type `y` when asked.

**Disable root login:**

```
sudo sed -i 's/^#*PermitRootLogin.*/PermitRootLogin no/' /etc/ssh/sshd_config
```

From now on, always connect using `ssh remote@TS_IP`.

---

## Part 3: Install OpenClaw

### Step 6. Install Claude Code CLI

```
curl -fsSL https://claude.ai/install.sh | bash  
echo 'export PATH="$HOME/.local/bin:$PATH"' >> ~/.bashrc && source ~/.bashrc  
claude setup-token
```

It shows a URL. Copy it and open it in your PC's browser. Log in to Claude and approve. You'll get a short code.

Go back to the server terminal and paste the code. Press Enter.

You'll see a token like `sk-ant-xxxxxxxx`. This is saved automatically.

---

### Step 7. Install OpenClaw

#### Install Node.js 22:

```
curl -fsSL https://deb.nodesource.com/setup_22.x | sudo -E bash -  
sudo apt install -y nodejs
```

**Install Homebrew** (follow the prompts, then run the second block):

```
/bin/bash -c "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/
```

```
echo 'eval "$(/home/linuxbrew/.linuxbrew/bin/brew shellenv)"' >> ~/.bashrc && e
```

## Install pnpm and OpenClaw:

```
curl -fsSL https://get.pnpm.io/install.sh | sh - && source ~/.bashrc  
pnpm i -g openclaw
```

## Step 8. Onboarding

Run the interactive setup wizard:

```
openclaw onboard --install-daemon
```

The wizard guides you through configuration. Follow each screen:

Screen	What to select
Security confirmation	<b>Yes</b>
Gateway configuration	<b>Local</b> (unless you need remote access)
Model / auth provider	<b>Anthropic</b>
Authentication	Paste your <code>sk-ant-...</code> token from Step 6
Channel selection	<b>Telegram</b> → paste your Telegram bot token
Daemon installation	<b>Yes</b> (runs as background service)
Security defaults	<b>Enable</b> pairing approvals

After onboarding, OpenClaw starts running automatically as a background service.

## Step 9. Install browser support

This lets the bot browse websites.

```
sudo apt update && sudo apt install -y chromium xvfb fonts-liberation libnss3 l
```

Restart OpenClaw:

```
systemctl --user restart openclaw-gateway.service
```

---

## Part 4: Connect and Verify

### Step 10. Pair your Telegram account

1. Open your bot in Telegram.
2. Send `/start`.
3. The bot replies with a pairing code.
4. On the server, run (replace CODE with your actual code):

```
openclaw pairing approve telegram CODE
```

**Note:** Pairing codes expire after 1 hour. If the code doesn't work, send `/start` again to get a new one.

---

### Step 11. Open the Dashboard

The dashboard lets you manage OpenClaw from your browser.

**On your PC**, open Terminal/Windows Terminal and run:

```
ssh -L 18789:127.0.0.1:18789 remote@TS_IP
```

Keep this window open.

**On the server**, run:

```
openclaw dashboard --no-open
```

It prints a link like `http://127.0.0.1:18789/?token=...`

Copy the full link and open it in your PC's browser.

---

## Step 12. Test the bot

1. Open your bot in Telegram.
2. Send `hi`.
3. You should get a response.

**Verify everything is healthy:**

```
openclaw status
```

This shows if all services are running correctly.

**Done!** Your OpenClaw is running.

---

## Troubleshooting

### Bot doesn't respond

Check if OpenClaw is running:

```
systemctl --user status openclaw-gateway.service
```

View logs:

```
journalctl --user -u openclaw-gateway.service -n 100 --no-pager
```

Restart it:

```
systemctl --user restart openclaw-gateway.service
```

## Can't open dashboard

Make sure the SSH tunnel command is still running on your PC.

## Browser tool fails

Run the browser install command from Step 9 again, then restart OpenClaw.

---

## Security notes

- Keep your tokens in a password manager.
  - Always use Tailscale to connect to your server.
  - Don't share your dashboard link.
- 

## Appendix A: WhatsApp setup

In the Dashboard:

1. Go to Channels
  2. Add WhatsApp
  3. Scan the QR code with your phone (WhatsApp → Settings → Linked Devices)
- 

## Appendix B: Skills and Gemini API

After the bot works, you can add extra features:

```
openclaw configure
```

Some skills need a Gemini API key. Get one at <https://aistudio.google.com/app/api-keys>, then:

```
echo 'export GEMINI_API_KEY="YOUR_KEY"' >> ~/.bashrc && source ~/.bashrc
```

---

## Appendix C: Useful commands

```
# Check if OpenClaw is running  
systemctl --user status openclaw-gateway.service  
  
# Restart OpenClaw  
systemctl --user restart openclaw-gateway.service  
  
# View logs  
journalctl --user -u openclaw-gateway.service -n 100 --no-pager  
  
# Check Tailscale  
tailscale status  
  
# Reconfigure OpenClaw  
openclaw configure
```

---

## Get a VPS

[Buy a VPS at Contabo](#)