

Word Sense Disambiguation using localized RNNs

CS498A - UGP Presentation

Rushab Munot (14405)
CSE, IITK

Supervisor
Prof. Harish Karnick
CSE, IITK

November 20, 2017

Word Sense Disambiguation

- WSD addresses the task of classifying the sense of a word in use depending on its usage.

Example

- 1 It was in my interest to do so.
- 2 The bank's new policy boosted the interest rates on deposits.
- 3 The play was interesting.

Word Sense Disambiguation

- WSD addresses the task of classifying the sense of a word in use depending on its usage.

Example

- 1 It was in my interest to do so.
 - 2 The bank's new policy boosted the interest rates on deposits.
 - 3 The play was interesting.
- A more subtle example - *public-interest* vs *self-interest*

Example

- 1 In the people's interest - *public-interest*
- 2 My interest in the field - *self-interest*

Word Sense Disambiguation

- WSD addresses the task of classifying the sense of a word in use depending on its usage.

Example

- ① It was in my interest to do so.
 - ② The bank's new policy boosted the interest rates on deposits.
 - ③ The play was interesting.
- A more subtle example - *public-interest* vs *self-interest*

Example

- ① In the people's interest - *public-interest*
 - ② My interest in the field - *self-interest*
- The context of a word is its immediate neighbourhood. In our approach, we model contexts using LSTM networks.

Wordnet Senses

- To disambiguate a word we do not need to know the complete meaning of the senses
- Only a certain number of characteristics are required

Wordnet Senses

- To disambiguate a word we do not need to know the complete meaning of the senses
- Only a certain number of characteristics are required
- For example, to disambiguate the word *set* in the following examples

Example

- 1 A *set* of rules - Noun
- 2 To *set* the volume - Verb

To distinguish between these two senses, we only need to know the POS tags

Wordnet Senses

- To disambiguate a word we do not need to know the complete meaning of the senses
- Only a certain number of characteristics are required
- For example, to disambiguate the word *set* in the following examples

Example

- 1 A *set* of rules - Noun
- 2 To *set* the volume - Verb

To distinguish between these two senses, we only need to know the POS tags

- However, to disambiguate between two verb senses of the same word, we need more informative tags

Example

- 1 To *set* fire - Verb \Rightarrow To *start* a fire
- 2 To *set* the volume - Verb \Rightarrow To *adjust* the volume

These two senses *cannot* be distinguished only with POS tags

WordNet Senses

- **WordNet Sense** \Rightarrow `sense_key = lemma % lex_sense`
`lex_sense = ss_type:lex_filenum:lex_id:head_word:head_id`

Reference: <https://wordnet.princeton.edu/man/senseidx.5WN.html>

WordNet Senses

- **WordNet Sense** \Rightarrow `sense_key = lemma % lex_sense`
`lex_sense = ss_type:lex_filenum:lex_id:head_word:head_id`
- **ss_type** is a 1-digit number between 1 and 5.
It denotes the Synset type which is one of *Noun*, *Verb*, *Adjective*, *Adverb*, *Adjective Satellite* respectively

Reference: <https://wordnet.princeton.edu/man/senseidx.5WN.html>

WordNet Senses

- **WordNet Sense** \Rightarrow `sense_key = lemma % lex_sense`
`lex_sense = ss_type:lex_filenum:lex_id:head_word:head_id`
- **ss_type** is a 1-digit number between 1 and 5.
It denotes the Synset type which is one of *Noun*, *Verb*, *Adjective*, *Adverb*, *Adjective Satellite* respectively
- **lex_filenum** is the file number of the WordNet file (00 to 44) corresponding to the sense.
 - Based on syntactic category and logical groupings
 - For example, file 04 represents nouns denoting acts or actions; file 39 denotes perception related verbs (seeing, hearing, feeling)

WordNet Senses

- **WordNet Sense** \Rightarrow `sense_key = lemma % lex_sense`
`lex_sense = ss_type:lex_filenum:lex_id:head_word:head_id`
- **ss_type** is a 1-digit number between 1 and 5.
It denotes the Synset type which is one of *Noun*, *Verb*, *Adjective*, *Adverb*, *Adjective Satellite* respectively
- **lex_filenum** is the file number of the WordNet file (00 to 44) corresponding to the sense.
 - Based on syntactic category and logical groupings
 - For example, file 04 represents nouns denoting acts or actions; file 39 denotes perception related verbs (seeing, hearing, feeling)
- **lex_id** along with the lemma differentiate between senses within a lexicographer file

WordNet Senses

- **WordNet Sense** \Rightarrow `sense_key = lemma % lex_sense`
`lex_sense = ss_type:lex_filenum:lex_id:head_word:head_id`
- **ss_type** is a 1-digit number between 1 and 5.
It denotes the Synset type which is one of *Noun*, *Verb*, *Adjective*, *Adverb*, *Adjective Satellite* respectively
- **lex_filenum** is the file number of the WordNet file (00 to 44) corresponding to the sense.
 - Based on syntactic category and logical groupings
 - For example, file 04 represents nouns denoting acts or actions; file 39 denotes perception related verbs (seeing, hearing, feeling)
- **lex_id** along with the lemma differentiate between senses within a lexicographer file
- **head_word** is present only if `ss_type=5`.
Satellite adjectives are basic adjectives like *dry* which when appended with a context enhance the meaning.
"arid" = "dry" + "climate"; "thirsty" = "dry" + "throat"; etc
- **head_id** is similar to `lex_id`

Reference: <https://wordnet.princeton.edu/man/senseidx.5WN.html>

The model

- The model is a (backward directional) LSTM network (with attention) for generating context embeddings
- The model is localized at the word level i.e. one LSTM network per word

The model

- The model is a (backward directional) LSTM network (with attention) for generating context embeddings
- The model is localized at the word level i.e. one LSTM network per word
- The attention mechanism is word dependent but context independent i.e. fixed for every word.

The model

- The model is a (backward directional) LSTM network (with attention) for generating context embeddings
- The model is localized at the word level i.e. one LSTM network per word
- The attention mechanism is word dependent but context independent i.e. fixed for every word.
- The context windows have a fixed size (may vary for different words). In our experiments the optimum size was observed to be 10.

The model

- The model is a (backward directional) LSTM network (with attention) for generating context embeddings
- The model is localized at the word level i.e. one LSTM network per word
- The attention mechanism is word dependent but context independent i.e. fixed for every word.
- The context windows have a fixed size (may vary for different words). In our experiments the optimum size was observed to be 10.
- We observed that self attention mechanisms tend to have a fixed profile, with little deviations depending on the contexts.

The Model




Figure: The Model and the Attention Mechanism

The Model




Figure: One model per word

Image taken from my UGP titled WSD using RNNs for context embedding (CS396A, II Semester, 2016-17)

Generating Data

- For the OMSTI dataset, more data is generated by gathering all examples have the same sense as the given sense.
- This helps to have more data with varied sentences.

Generating Data

- For the OMSTI dataset, more data is generated by gathering all examples have the same sense as the given sense.
- This helps to have more data with varied sentences.
- This approach does not always work with the Lexical Sample Task where the data is scarce (200 sentences per word with many words having 6-7 senses). The data is also highly unbalanced.

- Senseval-2 dataset of 4 words - hard, line, interest, serve
About 4000 sentences for hard, line, serve; 2000 for interest
Only those senses with more than 300 senses

- Senseval-2 dataset of 4 words - hard, line, interest, serve
About 4000 sentences for hard, line, serve; 2000 for interest
Only those senses with more than 300 senses
- Certain words from the One-million word corpus interest = 4 senses (500 each), position = 5 senses (500 each), serve = 8 senses (6 senses 500, remaining 2 have lesser instances)

- Senseval-2 dataset of 4 words - hard, line, interest, serve
About 4000 sentences for hard, line, serve; 2000 for interest
Only those senses with more than 300 senses
- Certain words from the One-million word corpus interest = 4 senses (500 each), position = 5 senses (500 each), serve = 8 senses (6 senses 500, remaining 2 have lesser instances)
- Senseval-2 English Lexical Sample Task

Accuracy

Word	#Senses	BLSTM Embedding		Attention Mechanism	
		Accuracy	F1	Accuracy	F1
hard	3	90.90	79.28	91.55	79.99
interest	4	87.67	80.42	91.85	84.11
serve	4	84.79	81.76	86.8	83.705
line	6	79.05	70.65	83.5	77.21

Table: Accuracy and F1(macro) score on the Senseval-2 dataset

- Accuracy not a good measure, as data is unbiased (for Senseval-2), F1 is a better measure

Accuracies - Senseval-2, English Lexical Sample Task

Word	#Instances	#Senses	Score*
art	196	8	60.2
authority	184	9	62.5
bar	304	13	51.7
blind	108	9	80.0*
bum	92	6	75.6
chair	138	4	81.7*
channel	145	9	41.7
child	129	8	59.4
church	128	5	62.5
colorless	67	3	60.0*
cool	106	7	50.0
day	289	9	71.0

Table: Accuracy (as evaluated by their scorer)* on the Senseval-2, English Lexical Sample Task

Here we have predicted only one sense (instead of multiple senses). We have precision = recall and fine grained = coarse grained)

CAUSE - OMSTI - Accuracy Plots




Figure: *cause*: OMSTI dataset - Comparison between different methods

SERVE- OMSTI - Accuracy Plots




Figure: *serve*: OMSTI dataset - Comparison between different methods

HARD: 4 Words Dataset - Accuracy Plots




Figure: *hard*: Four word dataset - Comparison between different methods

SERVE- 4 Words Dataset - Accuracy Plots




Figure: serve: Four word dataset - Comparison between different methods

- The model can be used for sense vector generation. One such approach would be to modify the WSD layer in - *Efficient Non-parametric Estimation of Multiple Embeddings per Word in Vector Space* (Neelakantan et Al., 2014).
- To develop a model that inherently uses the hierarchical nature of senses.

Acknowledgements

- Datasets from Senseval-2 and One million word corpus (Kaveh Taghipour and Hwee Tou Ng, 2015 - One Million Sense-Tagged Instances for Word SenseDisambiguation and Induction)
- Word Sense Disambiguation: A Survey - R. Navigli, 200
- WordNet 3.1 - <https://wordnet.princeton.edu/>

THANK YOU