K. C. COLLEGE OF ENGINEERING AND MANAGEMENT STUDIES AND RESEARCH THANE (EAST).

Department of Computer Engineering

Subject : FSJP **Semester-III** **Academic Year: 2025-26**

Programs for Practical Exam

1. **Write Programs on classes and objects with Looping and Branching in java**
2. **Programs on method and constructor overloading in java**
3. **Programs on various types of inheritance and Exception handling in java**
4. **Program to Implement Java Script Animation**
5. **Program on java script Document Object Model (DOM)**
6. **JSP implicit and explicit objects programs**

   6.1 dispDate.jsp
   6.2 greetings.jsp
   6.3 userinfo1.jsp

Note: Java script program can be implemented with Html or node js
Program 1 to 3 are there in your manual and 4,5, 6 are given here for reference.

Examples for reference:

Exp:4 Program to Implement Java Script Animation

```
<!DOCTYPE html>
<html>
<style>
#container {
  width: 400px;
  height: 400px;
  position: relative;
  background: yellow;
}
#animate {
  width: 50px;
  height: 50px;
  position: absolute;
  background-color: red;
}
</style>
<body>

<p><button onclick="myMove()">Click Me</button></p>

<div id ="container">
  <div id ="animate"></div>
</div>

<script>
function myMove() {
  let id = null;
  const elem = document.getElementById("animate");
  let pos = 0;
  clearInterval(id);
  id = setInterval(frame, 5);
  function frame() {
    if (pos == 350) {
      clearInterval(id);
    } else {
      pos++;
```

```
      elem.style.top = pos + "px";
      elem.style.left = pos + "px";
    }
  }
}
</script>

</body>
</html>
```

Exp 5: Program on java script Document Object Model (DOM)

```
<html>
<body>
  <h2>Document Object Model (DOM)</h2>
  <p id='targetText'>This is the original text.</p>
  <div id='output'></div>
  <script type="text/javascript">
    // Get the element by its ID
    const element = document.getElementById("targetText");

    // Change the text content
    element.textContent = "The DOM has changed me!";

    // Update the output div to confirm the change
    document.getElementById("output").innerHTML = "The text of the paragraph above has
been changed by JavaScript.";
  </script>
  <p>The JavaScript code located the paragraph above and changed its text.</p>
</body>
</html>
```

Exp: 6.1 dispDate.jsp

```
<%@page language="java" isThreadSafe= "false" import="java.io.*,java.util.*" %>
<html>
   <body bgcolor="white">
<%
          Date now = new Date();
          out.println(now.toString());
          out.println(now.toGMTString());
%>
          </body>
</html>
```

Exp: 6.2 greetings.jsp

```
<html>
   <body bgcolor="white">
   <% java.util.Date clock = new java.util.Date( ); %>
   <% if (clock.getHours( ) < 12) { %>
     <h1>Good morning!</h1>
   <% } else if (clock.getHours( ) < 18) { %>
     <h1>Good afternoon!</h1>
   <% } else { %>
     <h1>Good evening!</h1>
   <% } %>
   Welcome to our site, open 24 hours a day.
   </body>
</html>
```

Exp: 6.3 userinfo1.jsp

```
<%@page language="java" isThreadSafe= "false" import="java.io.*" %>
<html>
   <body bgcolor="white">
<%
          String name, bdate, email;
          int lucky;
          name = request.getParameter("userName");
          bdate = request.getParameter("birthDate");
          email = request.getParameter("emailAddr");
          lucky = Integer.parseInt(request.getParameter("luckyNo"));
```

```
%>
                <ul>
                        <li> Name : <%= name %> </li>
                        <li> BirthDate : <%= bdate %> </li>
                        <li> EMail : <%= email %> </li>
                        <li> Lucky : <%= lucky %> </li>
                </ul>
        </body>
</html>
```