

# Experiment No. 5

---

## Aim

To implement the **8 Queen's Problem** using the **Depth-First Search (DFS)** approach in C++.

---

## Theory

The **8 Queen's Problem** is a classic problem in the field of Artificial Intelligence and combinatorial optimization. The problem statement is:

Place 8 queens on a standard 8×8 chessboard such that no two queens attack each other.

A queen in chess can move:

- Vertically
- Horizontally
- Diagonally

Thus, the constraint is that **no two queens should share the same row, column, or diagonal**.

## Key Concepts:

- **Depth-First Search (DFS):**  
DFS is a graph/tree traversal method where the search goes deep along one branch before backtracking. For the N-Queens problem, DFS explores possible queen placements column by column, row by row, backtracking when conflicts arise.
- **Backtracking in DFS:**  
If placing a queen in a particular row/column leads to an invalid configuration (conflict), DFS backtracks to the previous step and tries the next possible option.
- **State Space Representation:**
  - Each level (depth) of DFS corresponds to placing a queen in a column.
  - Each node represents a partial solution.
  - A goal state is reached when 8 queens are placed without conflict.

## Complexity:

- **Time Complexity:**  $O(N!)$  in the worst case, since we may need to explore all row placements for  $N$  queens.
  - **Space Complexity:**  $O(N)$  for recursion stack and placement storage.
- 

## Algorithm

1. Start with an empty chessboard of size  $8 \times 8$ .
  2. Begin with the first column ( $col = 0$ ).
  3. For the current column, try placing a queen in each row one by one:
    - a. Check if placing the queen is safe (no other queen in the same row, column, or diagonals).
    - b. If safe, place the queen and recursively attempt to place the next queen in the next column.
    - c. If not safe, move to the next row in the same column.
  4. If a placement leads to a solution where all 8 queens are placed:
    - Print/display the configuration as a solution.
  5. If no placement works in the current column, backtrack to the previous column and try the next possible row.
  6. Repeat until all possible solutions are found.
- 

## Code (C++ Implementation)

```
#include <iostream>
using namespace std;

#define N 8

int board[N][N];

bool safe(int r, int c){
    for(int i=0; i<c; i++) if(board[r][i]) return false;
    for(int i=r, j=c; i>=0&&j>=0; i--, j--) if(board[i][j]) return false;
    for(int i=r, j=c; i<N&&j>=0; i++, j--) if(board[i][j]) return false;
    return true;
}

bool solve(int c){
    if(c==N){
        for(int i=0; i<N; i++){
            for(int j=0; j<N; j++) cout<<(board[i][j]?"Q ":". ");
            cout<<"\n";
        }
    }
}
```

```

        }
        cout<<"\n";
        return true;
    }
    bool res=false;
    for(int i=0;i<N;i++){
        if(safe(i,c)){ board[i][c]=1; res=solve(c+1)||res; board[i][c]=0; }
    }
    return res;
}

int main(){
    if(!solve(0)) cout<<"No solution\n";
}

```

---

## Input/Output Examples

### Sample Output (One of the Possible Solutions)

```

. Q . . . . .
. . . Q . . .
. . . . . Q .
. . . . . . Q
Q . . . . . .
. . Q . . . .
. . . . Q . .
. . . . . Q .

```

- Multiple valid outputs exist, as there are **92 distinct solutions** to the 8 Queen's Problem.
- 

## Analysis of Code and Algorithm

- **Algorithm Used:** Depth-First Search with Backtracking.
- **Logic Flow:**
  - Recursively try each row for every column.
  - Place a queen if safe, else backtrack.
  - Continue until all queens are placed or no solution exists.
- **Time Complexity:**  $O(N!)$  in the worst case.
- **Space Complexity:**  $O(N)$  for recursion stack +  $O(N^2)$  for board storage.

- **Efficiency:** Although exponential, backtracking prunes many invalid states, making it practical for  $N=8$ .
- 

## Real-Life Applications

1. **Constraint Satisfaction Problems (CSPs):**

Used in scheduling, time-tabling, and resource allocation problems.

2. **Artificial Intelligence Search Problems:**

Demonstrates DFS with backtracking, which is fundamental in pathfinding, puzzle-solving, and game playing.

3. **Circuit Design and Parallel Processing:**

Avoiding conflicts (like queen conflicts) is analogous to avoiding overlaps in circuits and processor tasks.

---

## Conclusion

In this experiment, the **8 Queen's Problem** was successfully implemented using the **Depth-First Search (DFS) with backtracking** approach in C++. The program systematically explored the solution space, backtracked when conflicts occurred, and generated valid solutions.

This demonstrates the effectiveness of **DFS and backtracking** in solving combinatorial problems and provides insight into constraint satisfaction techniques in Artificial Intelligence.

---