

Hive(PC)

Here are the main commands you used in the terminal during your Hive + HDFS practical. I cleaned them up and arranged them step-by-step so it's easy to revise or share with your friend. The terminal looked like a battlefield of syntax errors and recovery arcs — very Hadoop-core experience, honestly 😭

Commands extracted from your terminal log:

```
# Start Hive
hive

# Create database
create database flight_db;

# Use database
use flight_db;

# Show all databases
show databases;

# Create flights table
create table flights(
  year int,
  month int,
  day int,
  flight_num string,
  origin string,
  dest string,
  depdelay int
)
row format delimited
fields terminated by ','
stored as textfile;
```

```

# Describe table
describe flights;

# Insert records
insert into flights values
(2008,1,2,'A101','del','mum',10);

insert into flights values
(2008,1,2,'A102','mum','del',20);

# Display records
select * from flights;

# Aggregate query
select day,avg(depdelay)
from flights
where year=2008
group by day;

# Alter table
alter table flights add columns(airline string);

# Exit hive
exit;

# Create text file using nano
nano flight_ext.txt

# Create HDFS directory
hdfs dfs -mkdir /user/cloudera/flight_data

# Upload file to HDFS
hdfs dfs -put flight_ext.txt /user/cloudera/flight_data/

# List files in HDFS directory
hdfs dfs -ls /user/cloudera/flight_data/

```

```
# View file content from HDFS
hdfs dfs -cat /user/cloudera/flight_data/flight_ext.txt

# Start Hive again
hive

# Create external table
create external table flight_ext(
year int,
month int,
day int,
flight_num string,
origin string,
dest string,
depdelay int
)
row format delimited
fields terminated by ','
location '/user/cloudera/flight_data/';

# View external table data
select * from flight_ext;

# Drop external table
drop table flight_ext;

# Create airports table
create table airports(
code string,
city string
);

# Show tables
show tables;
```

```

# Check current database
select current_database();

# Switch database
use flight_db;

# Join query using flight number
select f.flight_num,f.origin,f.dest,e.depdelay
from flights f
join default.flight_ext e
on f.flight_num=e.flight_num;

# Display flights table
select * from flights;

# Join query using origin
select f.flight_num,f.origin,f.dest,e.depdelay
from flights f
join default.flight_ext e
on f.origin=e.origin;

# Exit Hive
exit;

```

And these were the mistakes/errors you also encountered (good to remember for viva because examiners LOVE asking "what errors did you face?" like ancient sages testing warriors):

- Wrong mkdir command:

```
hdfs dfs -mkdir/user/cloudera/flight_data
```

Correct:

```
hdfs dfs -mkdir /user/cloudera/flight_data
```

- Wrong location syntax in external table:

```
location 'user/cloudera/f;ight_data/';
```

Correct:

```
location '/user/cloudera/flight_data/';
```

- Wrong delimiter:

```
fields terminated by '.'
```

or

```
fields terminated by ' '
```

Correct:

```
fields terminated by ','
```

- Typing mistakes:

```
selct * from flights;
```

Correct:

```
select * from flights;
```

- Wrong column name:

```
e.depelay
```

Correct:

e.depdelay

Classic Hive arc:

1. Create table
2. Break table
3. NULL NULL NULL everywhere
4. Existential crisis
5. Fix delimiter
6. "OK" appears
7. Peace restored 🙏