

Assignment 2

```
hive
show databases;

create database flight_db;

use flight_db;

create table flights(
year int,
month int,
day int,
flight_num string,
origin string,
dest string,
depdelay int
)
row format delimited
fields terminated by ','
stored as textfile;

insert into flights values
(2008,1,2,'A101','del','mum',10);

insert into flights values
(2008,1,2,'A102','mum','del',20);

select * from flights;

select day,avg(depdelay)
from flights
where year=2008
group by day;
```

```
alter table flights add columns(airline string);

select * from flights;

exit;

nano flight_ext.txt
```

Add this inside file:

```
2008,1,1,1A101,del,mum,10
2008,1,2,1A102,mum,del,20
2008,1,1,6E201,del,blr,30
```

```
hdfs dfs -mkdir /flight_data

hdfs dfs -put flight_ext.txt /flight_data/

hdfs dfs -ls /flight_data/

hdfs dfs -cat /flight_data/flight_ext.txt

hive
```

```
create external table flight_ext(
year int,
month int,
day int,
flight_num string,
origin string,
dest string,
depdelay int
)
```

```
row format delimited
fields terminated by ','
location '/flight_data/';

select * from flight_ext;

use flight_db;

select f.flight_num,f.origin,f.dest,e.depdelay
from flights f
join default.flight_ext e
on f.origin=e.origin;

create index flight_index
on table flights(flight_num)
as 'COMPACT'
with deferred rebuild;

alter index flight_index
on flights
rebuild;

select * from flights;

select * from flight_ext;
```