CPP CCEE Practice Quiz 2

Total points 21/30

The respondent's email (**rushikesh.sambare.cmfeb26@gmail.com**) was recorded on submission of this form.

0 of 0 points

Form_no *

251100559

Name *

Rushikesh Bhagwat Sambare

MCQ

21 of 30 points

✓ What is the output of the following code snippet * 1/1

```
void fun(int x) { cout << "int"; }
void fun(double x) { cout << "double"; }

int main() {
    fun(10.5f);
}
```

- ○ A. int
- ◉ B. double ✓
- ○ C. float
- ○ D. Error

✓ What must be used with malloc? * 1/1

- ○ A. delete
- ○ B. delete[]
- ◉ C. free() ✓
- ○ D. destructor manually

✗ Initialization happens at _____, while assignment happens at _____. * 0/1

- ◉ A. Compile time, run time ✗
- ○ B. Run time, compile time
- ○ C. Object creation, after object creation
- ○ D. Function call, return time

Correct answer

- ◉ C. Object creation, after object creation

✓ Why does C++ perform name mangling? * 1/1

- ○ A. To reduce code size
- ○ B. To support OOP
- ◉ C. To support function overloading ✓
- ○ D. For memory optimization

✕ What is the rule for default arguments? * 0/1

- (●) A. They must be on left side ✕
- ( ) B. They must be on right side
- ( ) C. They can be anywhere
- ( ) D. Default values must be constants only

Correct answer

- (●) B. They must be on right side

✓ What happens if two namespaces contain the same function name and you use both with using? *1/1

```
namespace A { void show() { cout << "A"; } }
namespace B { void show() { cout << "B"; } }

using namespace A;
using namespace B;

int main() {
 show();
}
```

- ( ) A. Prints A
- ( ) B. Prints B
- (●) C. Ambiguity error ✓
- ( ) D. Depends on compiler

✓ int a = 20; * 1/1

```
int &ref = a;
ref = ref + 5;

std::cout << a << " " << ref;
```

- ○ A. 20 25
- ◉ B. 25 25 ✓
- ○ C. 20 20
- ○ D. Compile-time error

✓ Which is NOT valid about this? * 1/1

- ◉ A. It is available in static functions ✓
- ○ B. It stores address of calling object
- ○ C. It helps resolve naming conflicts
- ○ D. It can be used to return current object

✓ Which call type allows function to modify original variable? * 1/1

- ○ A. Call by value
- ○ B. Call by address
- ○ C. Call by reference
- ◉ D. Both B & C ✓

✓ **Which is TRUE for reference variables?** * 1/1

- (●) A. A reference must be initialized when declared ✓
- ( ) B. Reference can be reseated to another variable
- ( ) C. References store actual data, not addresses
- ( ) D. References take no memory

✗ int* p = new int(30); * 0/1

```
int& r = *p;

r = 50;
delete p;

std::cout << r;
```

- ( ) A. Prints 30
- (●) B. Prints 50 ✗
- ( ) C. Runtime error
- ( ) D. Undefined behavior

Correct answer

- (●) D. Undefined behavior

✓ What happens in the following code? * 1/1

```
extern "C" void test() { }
void test(int) { }

int main() { test(); }
```

- (●) A. Calls C version ✓
- ( ) B. Compile error
- ( ) C. Ambiguous
- ( ) D. Undefined behavior

✗ What is true about enum class (strong enum)? * 0/1

- (●) A. Implicitly converts to int ✗
- ( ) B. Values must be qualified
- ( ) C. Cannot set underlying type
- ( ) D. Cannot overload operators

Correct answer

- (●) B. Values must be qualified

✓ What is true about namespaces? * 1/1

- (●) A. They can be nested ✓
- ( ) B. They cannot contain classes
- ( ) C. They must end with semicolon
- ( ) D. They cannot be extended later

✗ Which is TRUE? * 0/1

- ( ) A. malloc calls constructor
- ( ) B. new calls constructor
- (●) C. Both call constructor ✗
- ( ) D. Neither call constructor

Correct answer

- (●) B. new calls constructor

✓ int a = 5; *
int &r = a;
r = 10;
cout << a;

1/1

- A. 5
- B. 10 ✓
- C. Compilation error
- D. Undefined

✗ What is the default underlying type of enum in C++? *

0/1

- A. char
- B. int
- C. long
- D. compiler dependent ✗

Correct answer

- B. int

✕ **What is wrong?** * 0/1

```
int *p = new int(10);
delete p;
cout << *p;
```

- ○ A. Prints 10
- ◉ B. Prints garbage ✕
- ○ C. Undefined behavior
- ○ D. Compile error

Correct answer

- ◉ C. Undefined behavior

✓ What is required to initialize a const data member? * 1/1

- ○ A. Assignment inside constructor
- ◉ B. Initializer list ✓
- ○ C. Static block
- ○ D. It cannot be initialized

✓ output? *

1/1

```
class B {
public:
   int x;
   B(int v) { x = v; }
};

int main() {
   B obj(30);
   cout << obj.x;
}
```

- ○ A. 0
- ◉ B. 30 ✓
- ○ C. Garbage
- ○ D. Error

✓ What will be the Output? * 1/1

```
class A {
public:
   int x;
   A() : x(10) {}      // initialization
};

int main() {
   A obj;
   obj.x = 20;         // assignment
   cout << obj.x;
}
```

- ○ 10
- ◉ 20 ✓
- ○ Garbage
- ○ Error

✗ Problem? * 0/1

```
void f(int x = 0, int y);
```

- ○ A. Valid
- ○ B. Invalid
- ○ C. Ambiguous
- ◉ D. Works only in C++11 ✗

Correct answer

- ◉ B. Invalid

✓ Identify the error * 1/1

```
class A {
public:
   const int x;
   A() { x = 50; }
};
```

- ○ A. No error
- ○ B. Logical error
- ◉ C. const must be initialized in initializer list ✓
- ○ D. const cannot exist in class

✗ **Which statement is true? *** 0/1

- ○ A. A reference can be NULL
- ◉ B. A pointer cannot be changed once assigned ✗
- ○ C. A pointer stores address, reference is an alias
- ○ D. Pointer is safer than reference

Correct answer

- ◉ C. A pointer stores address, reference is an alias

What is the output of following code? * 1/1

```
void fun(int x, int y = 20) {
    cout << x + y;
}

int main() { fun(10); }
```

- 10
- 20
- 30 ✓
- error

```
class A {
public:
    int x;
    void set(int x) {
        this->x = x;
    }
};

int main() {
    A obj;
    obj.set(25);
    cout << obj.x;
}
```

*

1/1

- A. 0
- B. 25 ✓
- C. Garbage
- D. Compile error

Which is the correct way to access a function inside a namespace? *

1/1

- A. namespace.function()
- B. namespace::function() ✓
- C. ns->function()
- D. using function()

What is the Output? * 1/1

```
int a = 10;
int *p = &a;
int &r = a;
*p = 20;
cout << r;
```

- A. 10
- B. 20 ✓
- C. Garbage
- D. Error

What is the output ? * 1/1

```
enum Color { RED = 5, BLUE, GREEN = 10 };

int main() {  cout << BLUE;  }
```

- A. 5
- B. 6 ✓
- C. 10
- D. Undefined

What is the output? *

1/1

```
void fun(int &x) { x = x + 5; }

int main() {
   int a = 10;
   fun(a);
   cout << a;
}
```

- A. 10
- B. 5
- C. 15 ✓
- D. Error

This content is neither created nor endorsed by Google. - Contact form owner - Terms of Service - Privacy Policy

Does this form look suspicious? Report

Google Forms