Faculty of Science and Technology
Department of Computing & Informatics

Blockchain and Digital Futures (COMP7058)

Topic - Blockchain Based Anti-Counterfeiting Measures in the Supply Chain

Submitted By – Rushikesh Temghare

Table of Contents

Abstract 3

Introduction 3

Problem Definition 4

Contribution 5

- System Design 7
  - Assignment of Decentralised Identity (DID) 8
  - Validation and Data Input 8
  - Enforcement of Smart Contracts 8
  - Unchangeable Document Storage 8
  - Responsibility and Trackability 8
  - Fraud Identification and Human Monitoring 8
- System Components 9
  - Nodes 9
  - The Blockchain Network 9
  - Smart Contracts 9
  - Mechanism of Consensus 10
  - Layer of Traceability 10
- Working of System 10
- Smart Contract 13
- Consensus Mechanism 16
  - Why POA? 16
- Theoretical Evaluation 17
  - Data Authenticity and Trustworthiness 17
  - Automated Validation with Smart Contracts 17
  - Immutability and Security 17
  - Effectiveness and Expandability 17
- Technical Evaluation 18
  - Openness and Traceability 19
  - Combining Automation with IOT 19
  - Obstacles and Restrictions 19

Conclusion 20

Future Scope 21

References 22

Abstract

This study introduces a blockchain-based supply chain anti-counterfeiting system that integrates smart contracts, decentralised identities (DIDs), and Internet of Things (IoT) devices to guarantee data integrity and authenticity. Before data is posted to the blockchain, it is digitally signed and validated using a cryptographic DID that is assigned to each supply chain participant and device. The system guarantees immutability, traceability, and accountability by using Proof of Authority (POA) for consensus. This system increases supply chain security, lowers fraud, and guarantees product authenticity throughout its whole lifespan by utilising the transparency of blockchain technology and the real-time data capturing capabilities of the Internet of Things.

Introduction

Globally, counterfeiting is still a major problem that damages businesses billions of dollars every year and erodes customer confidence. Counterfeit goods permeate supply chains, threatening consumer health, safety, and brand reputation in everything from electronics and medicines to luxury goods and food items. In an increasingly intricate and linked global supply chain, conventional anti-counterfeiting techniques like physical seals and barcodes have proven insufficient. By improving supply chain security, transparency, and traceability, blockchain technology has become a game-changing answer to these problems.

Blockchain is a distributed ledger system that records transactions across several nodes. It is especially well-suited to fight counterfeiting because of its three main characteristics: immutability, transparency, and security. Blockchain guarantees the validity of goods as they go through the supply chain by producing an unchangeable and verifiable record of each transaction. Every product may be given a distinct digital identity that is stored on the blockchain, allowing stakeholders to follow the product's path from point of origin to point of destination.

Smart contracts, IoT devices, and advanced cryptographic techniques form the backbone of a blockchain-based anti-counterfeiting system. Smart contracts automate tasks like verifying product origins before progressing in the supply chain. IoT devices, such as RFID tags and QR codes, enable real-time data collection on product location, temperature, and handling, ensuring accurate records. This integrated ecosystem significantly reduces counterfeiting risks.

Blockchain ensures only authentic products reach customers, enhancing brand protection and building trust. Retailers benefit from reduced repetitional risks, while blockchain-based apps enable customers to verify product authenticity, fostering informed purchases. Tamper-proof records also support regulatory agencies in ensuring compliance with quality and safety standards.

Blockchain tackles supply chain inefficiencies in addition to fighting counterfeiting. It improves stakeholder cooperation, lowers administrative expenses, and simplifies processes. For instance, blockchain reduces mistakes and delays by enabling smooth information exchange between merchants, shipping companies, and manufacturers.

Implementing blockchain-based supply chain solutions faces challenges such as interoperability issues, high costs, and stakeholder resistance. It also requires robust infrastructure, including reliable internet and widespread IoT adoption. Collaboration among governments, businesses, and tech firms is essential to create scalable and cost-effective solutions.

To sum up, supply chain management is undergoing a paradigm change thanks to blockchain-based anti-counterfeiting methods. Industries can successfully fight counterfeiting, improve transparency, and foster customer trust by utilising blockchain's special characteristics. Although there are certain difficulties, implementing blockchain has long-term advantages that much exceed the early difficulties, making it an essential weapon in the battle against counterfeiting in the contemporary global supply chain.

Problem Definition

Assuring the correctness and legitimacy of the data uploaded into the blockchain is a crucial obstacle in the implementation of blockchain-based anti-counterfeiting measures in the supply chain. Blockchain cannot automatically confirm the accuracy of the data being recorded, despite the fact that it is extremely safe and impenetrable. Due to the "garbage in, garbage out" issue, inaccurate or fraudulent data entered into the blockchain becomes unchangeable and may compromise the integrity of the system.

This issue often arises during the early stages of the supply chain when product data is entered manually or via IoT devices like RFID tags or QR codes. Blockchain cannot differentiate between genuine and fraudulent entries, so counterfeit products tagged with valid IDs are accepted as authentic. In regions with limited supply chain transparency, reliance on external systems and human input increases the risks of fraud, errors, and manipulation.

Reliance on IoT devices for data collection presents another challenge. While critical for automating data entry, these devices can malfunction or be hacked. For instance, inaccurate temperature readings for perishable items may be recorded on the immutable blockchain, leading to misunderstandings and poor decisions.

Strong verification procedures must be incorporated at the data entry sites in order to overcome this difficulty. Risks can be reduced by combining blockchain with cutting-edge authentication technologies like digital watermarks, secure hardware, or AI-based fraud detection systems. The potential of blockchain-based anti-counterfeiting technologies to improve supply chain security is limited in the absence of such protections.

Contribution

Integrating decentralised identity (DID) solutions for supply chain actors is a practical way to handle data integrity and input authenticity challenges in blockchain-based anti-counterfeiting systems. By giving all supply chain participants—manufacturers, distributors, and Internet of Things devices—cryptographic IDs, this method makes sure that only authenticated users may enter data into the blockchain. This approach increases confidence in the data entry process and offers accountability by fusing DIDs with digital signatures.

Each participant in the supply chain is assigned a unique cryptographic identity tied to their responsibilities. For example, manufacturers have a DID to authenticate product data before it's recorded on the blockchain. Similarly, IoT devices collecting data are equipped with cryptographic keys to verify and sign their outputs. This ensures that only data from authenticated identities is added to the blockchain, reducing the risk of tampered or fraudulent entries.

Rules for data validation can also be enforced via the blockchain smart contracts. Smart contracts, for instance, may ensure that inputs satisfy certain standards, including comparing manufacturing timestamps with shipping records or using metrics provided by the Internet of Things to certify the physical integrity of commodities. Any inconsistencies that the smart contracts identify are either immediately rejected or forwarded for human examination.

Additionally, by allowing mistakes or fraudulent activities to be traced back to the accountable party, this method fosters responsibility. The digital signatures enable prompt action to be taken in the event that a counterfeit product is discovered later on.

Data input procedures may be made much more reliable by integrating DIDs into blockchain-based anti-counterfeiting solutions. This technique increases the overall effectiveness of anti-counterfeiting measures by guaranteeing that the immutable entries on the blockchain represent correct and reliable data.

Background and Related Work

High-end, rare, and costly goods are known as luxury goods around the world. These goods, which are marketed by well-known labels like Chanel, Gucci, and Louis Vuitton, fall into a number of categories, including jewellery, watches, bags, and apparel. However, the luxury sector has become a prominent target for counterfeiters because to its fast expansion. The luxury sector accounted for 60–70% of all counterfeit transactions in 2019, with the worldwide counterfeit trade valued at $4.5 trillion (Harvard Business Review, 2019). Customers, companies, and governments have suffered large financial losses as a result, and brands have suffered harm to their reputations. Despite modern anti-counterfeiting strategies like RFID chips, QR codes, and specialised detection teams, a significant portion of the market is still dominated by counterfeit luxury items (Wang, Lin and Choi, 2020) and (Chen et al., 2020).

There are inherent problems with current anti-counterfeiting technology. The trustworthiness of QR code-based solutions is undermined by their vulnerability to replication, database manipulation, and phishing websites (Qi, Chen and Chen, 2018), (Puthal et al., 2019), (Mohit et al., 2017) and (Schmidt and Wagner, 2019). Despite providing some automation, RFID-based systems have drawbacks such high installation costs, centralised administration weaknesses, and data manipulation (Singh et al., 2020). Customers are also unable to independently confirm the legitimacy of items due to the absence of transparency and real-time tracking in many systems.

This work suggests a blockchain-based anti-counterfeiting management system to address these problems by utilising smart contract automation and non-interference, as well as the tamper-resistance, traceability, and decentralisation characteristics of blockchain technology (Chen et al., 2020), (Deepa et al., 2022), (Stamatellis et al., 2020) and (Chen et al., 2021). The solution securely stores manufacturing, logistics, and sales data by integrating the supply chain with a consortium blockchain using the Hyper-ledger Fabric platform. By doing this, dependence on centralised authority is removed, reducing the possibility of data breaches and manipulation. Customers may obtain thorough product histories thanks to the system's integration of IoT technology for real-time tracking. Smart contracts provide accuracy and transparency in the supply chain by enforcing present criteria automatically.

Proposed Model

System Design

To guarantee data authenticity and integrity in blockchain-based anti-counterfeiting solutions for supply chains, the suggested system architecture combines blockchain technology with digital signatures, decentralised identification (DID) solutions, and Internet of Things (IoT) devices. The following crucial steps are how the system functions:



Figure 1: System Design

Assignment of Decentralised Identity (DID)

A distinct cryptographic identity is assigned to every supply chain member, including producers, distributors, and Internet of Things devices. The identity of the entity submitting data onto the blockchain is verified by these DIDs. For example, before registering product information, a manufacturer verifies its accuracy using their DID. Cryptographic keys connected to their DIDs enable IoT devices, including RFID tags and QR scanners, to sign and validate the data they produce.

Validation and Data Input

Data submitted by an IoT device or participant is digitally signed with their DID. The digital signature guarantees that the data source is authenticated and can be linked to the appropriate organisation. This procedure lessens the possibility of fraudulent or illegal data entry. After then, the information is sent to a blockchain smart contract.

Enforcement of Smart Contracts

As the blockchain's guardians, smart contracts enforce preset guidelines for validating data. These guidelines can involve comparing production timestamps with shipping records, confirming IoT device measurements, or employing extra technologies for product authentication, such as digital watermarks. If the data satisfies the requirements, it is added to the blockchain; if not, it is discarded or marked for human examination.

Unchangeable Document Storage

The data is permanently stored on the blockchain after validation, guaranteeing its immutability. This ensures that the data that has been captured cannot be changed or tampered with. This safe and unchangeable record may be consulted for any follow-up questions on the validity of a product or its supply chain history.

Responsibility and Traceability

Digital signatures and DIDs work together to guarantee responsibility for every data entry. The responsible party's cryptographic signature can be used to identify them if a fake product or inaccurate data is found at any time. Participants in the supply chain are encouraged to be more accountable and trustworthy by this traceability system.

Fraud Identification and Human Monitoring

Data entries can be examined by hand when smart contracts identify discrepancies. At this point, AI-based fraud detection technologies might also be included to find trends that could point to mistakes or possible fraud.

System Components

Nodes

The fundamental units of the blockchain network are called nodes. Manufacturers, distributors, merchants, and Internet of Things devices are just a few examples of the devices or participants that each node represents in the supply chain. Data uploading, verification, and storage on the blockchain are handled by these nodes.

- IoT Nodes: IoT nodes are gadgets such as temperature sensors, RFID scanners, and QR code readers. They gather information on items in real time, including timestamps, temperature, and location, and they authenticate this information by signing it with their cryptographic keys.
- Participant Nodes: Manufacturers, distributors, and other supply chain participants are examples of nodes. To verify their submissions and guarantee the authenticity of the supplied data, they employ decentralised identification (DID) credentials.

The Blockchain Network

All verified data inputs are permanently kept in the blockchain network, which functions as a decentralised ledger.

- Decentralisation: The blockchain's distributed structure lowers the possibility of fraud and manipulation by preventing any one party from controlling the whole network.
- Immutability: Data becomes unchangeable when it has been uploaded and validated, guaranteeing a permanent and impenetrable record.
- Accessibility: Transparent access to the data by authorised parties promotes confidence across the supply chain and makes tracing easier.

Smart Contracts

Self-executing scripts called smart contracts are incorporated into the blockchain to automate procedures and enforce preset regulations.

- Data Validation Rules: Smart contracts use preset criteria, including comparing production and shipping timestamps or evaluating IoT sensor readings, to confirm the accuracy of incoming data.
- Automation: For example, the smart contract can reject this data input completely or flag it for additional inspection if an IoT device indicates a temperature anomaly in a perishable commodity.
- Handling Exceptions: Data entries that don't fit the requirements are either discarded or sent to a fraud detection system for human examination.

Mechanism of Consensus

Before the data is posted to the blockchain, the consensus process makes sure that everyone in the network agrees that it is legitimate.

- Proof Of Authority (POA): In this situation, a POA system that restricts data validation and signing to confirmed individuals with DIDs may be employed. This preserves the legitimacy of the data while reducing processing overhead.
- Verification Procedure: Nodes in the network check a data entry against the standards specified in the smart contracts once it is submitted. When the majority of nodes concur on its validity, consensus is reached.

Layer of Traceability

To ensure responsibility, the traceability layer offers a way to pinpoint the origin of every data input.

- Cryptographic Signatures: The DID of the accountable node, be it an Internet of Things device or a human participant, is used to sign each data entry.
- Audit Trails: The traceability layer enables investigators to identify the source of the error or fraud in the event that a counterfeit product is found. This is essential for taking corrective action and keeping the guilty party accountable.
- Transparency: The traceability layer increases trust and discourages harmful action by making it possible to follow each product's path across the supply chain.

To solve issues with data authenticity in blockchain-based anti-counterfeiting systems, the solution smoothly combines these elements. The blockchain network guarantees safe storage, while nodes offer the interface for data input. Together, the traceability layer imposes responsibility, the consensus mechanism guarantees agreement, and smart contracts automate validation, improving supply chain security and transparency.

Working of System

1. Decentralised Identity Assignment (DID)
   Every IoT device and supply chain participant has an own cryptographic identity. When submitting data, these identities provide responsibility and authenticity. The acquired data is signed by IoT devices (such as RFID scanners) using their private keys.

2. Information Gathering and Submission
   IoT devices collect data in real time, including product position, temperature, and timestamps. Before being transferred to the blockchain for additional verification, this data is signed using the device's DID.



Figure 2: System Diagram

3. Validation of Smart Contracts
   Smart contracts use pre-established rules, like these, to automatically verify incoming data:
   a. Comparing shipment data with manufacture timestamps.
   b. Evaluating IoT sensor data against permissible limits.
      Data is added to the blockchain if it passes validation. Either invalid data is rejected or marked for manual examination.
4. Mechanism of Consensus
   Data validity is guaranteed using a Proof Of Authority (POA) consensus method. Before a data input is permanently saved on the blockchain, verified nodes with DIDs collectively concur on its legitimacy.
5. Storage That Is Unchangeable
   The blockchain provides a safe and impenetrable record by storing validated data in an immutable manner. This guarantees that once the data is submitted, it cannot be changed or removed.
6. Layer of Traceability
   Through audit trails and cryptographic signatures, each data entry is traced back to its original source. In the event of fraud or inconsistencies, this permits complete traceability, which makes it possible to identify the accountable parties.

Sequence Diagram

To improve the legitimacy and integrity of supply chain data, the suggested approach combines blockchain technology with Decentralised Identity (DID), Internet of Things devices, and smart contracts. Decentralised Identity Assignment is the first step in the process, in which every participant—including Internet of Things devices—is given a distinct cryptographic DID. Data is digitally signed using these DIDs to guarantee its legitimacy prior to submission.

IoT devices gather real-time data, including timestamps and environmental indicators, and sign it with their DIDs during the Information Gathering and Submission stage. After being signed, the data is sent to the blockchain network for additional processing. The next step is Smart Contract Validation, where data is verified by pre-established rules in the smart contracts. Smart contracts, for example, verify that timestamps are consistent and that environmental limits are being met. On the blockchain, verified data is permanently saved, whereas invalid data is marked or removed.

Prior to being permanently saved on the blockchain, the Consensus Mechanism, which is implemented using Proof Of Authority (POA), guarantees that all validated data inputs are accepted by authorised nodes. Data integrity is guaranteed by this decentralised method, which also removes the potential for a single point of failure.

Blockchain's Storage That Is Unchangeable feature ensures that verified records cannot be altered, creating a permanent and impenetrable supply chain data repository. Last but not least, the Layer of Traceability makes it possible to use audit trails and cryptographic signatures to track each data input back to its original source. Accountability is guaranteed, fraudulent activity is deterred, and in the event of inconsistencies, this traceability helps identify the people at fault.



Figure 3: Sequence Diagram

Smart Contract

Overview of the Contract: Written in Solidity, the contract manages the essential functions of the supply chain, including data validation, storage, and DID management.

Node Authorisation: The contract can only be accessed by approved nodes, such as manufacturers or Internet of Things devices. By using the authorise Node and revoke Node capabilities, the administrator may add or remove nodes, guaranteeing that only reliable participants provide data.

Data Submission: The submit Data method is used by authorised nodes to submit data. The data payload, the sender's DID (address), and the current timestamp are all included in the sent data. To ascertain whether the data is legitimate, the contract applies validation logic (a placeholder here).

Validation logic: Rules that confirm the accuracy of the data, including examining timestamp ranges or IoT sensor restrictions, are contained in the validate Data function. It is possible to modify this function to meet certain supply chain needs.

Immutable Storage: The data Entries array contains a permanent record of every data entry. Data cannot be altered once it has been verified and saved thanks to the blockchain's immutability.

Complete traceability is made possible by data entries being connected to the sender's timestamp and DID (address). This allows audit trails and guarantees responsibility.

This agreement establishes the framework for a strong supply chain anti-counterfeiting mechanism based on blockchain technology.

```
// SPDX-License-Identifier: MIT
pragma solidity ^0.8.0;

contract SupplyChainAntiCounterfeit {

    struct DataEntry {
        string data; // Data submitted (e.g., temperature, timestamp)
        address sender; // DID of the sender
        uint256 timestamp; // Time of submission
        bool isValid; // Validation status
    }

    address public admin;
    mapping(address => bool) public authorizedNodes; // Stores authorized DIDs
    DataEntry[] public dataEntries;

    event DataSubmitted(address indexed sender, uint256 indexed timestamp, string data, bool isValid);
    event NodeAuthorized(address indexed node);
    event NodeRevoked(address indexed node);

    modifier onlyAdmin() {
        require(msg.sender == admin, "Only admin can perform this action");
        _;
    }

    modifier onlyAuthorizedNode() {
        require(authorizedNodes[msg.sender], "Node not authorized");
        _;
    }

    constructor() {    924198 gas 899000 gas
        admin = msg.sender; // Assign contract deployer as admin
    }

    function authorizeNode(address node) external onlyAdmin {    28152 gas
        authorizedNodes[node] = true;
        emit NodeAuthorized(node);
    }
```

Figure 4: Smart Contract 1

```
    }

    function revokeNode(address node) external onlyAdmin {    28173 gas
        authorizedNodes[node] = false;
        emit NodeRevoked(node);
    }

    function submitData(string memory data) external onlyAuthorizedNode {    infinite gas
        uint256 currentTime = block.timestamp;
        bool valid = validateData(data, currentTime);

        dataEntries.push(DataEntry({
            data: data,
            sender: msg.sender,
            timestamp: currentTime,
            isValid: valid
        }));

        emit DataSubmitted(msg.sender, currentTime, data, valid);
    }

    function validateData(string memory /*data*/, uint256 /*timestamp*/) internal pure returns (bool) {    undefined gas
        // Placeholder for validation logic: Assume all data is valid
        return true;
    }

    function getAllData() external view returns (DataEntry[] memory) {    infinite gas
        return dataEntries;
    }
}
```

Figure 5: Smart Contract 2



Figure 6: Debugging



Figure 7: Output

Consensus Mechanism

With Proof Of Authority (POA), a consensus method, a group of pre-approved organisations known as "validators" are given the power to validate and add data to the blockchain. POA makes guarantee that only reliable parties with confirmed Decentralised Identities (DIDs), such producers, distributors, and Internet of Things (IoT) devices, are able to authenticate and submit data in the suggested blockchain-based anti-counterfeiting model for supply chains. The DIDs of these individuals function as cryptographic evidence of their identification and authority, and they operate as nodes.

Data is digitally signed by the participant or IoT device using its DID before being transferred to the blockchain. Validators, working under POA, check the data against smart contract rules to verify its authenticity. They may, for example, validate IoT sensor readings, compare shipping and manufacturing data, or verify timestamps. If most validators agree the data is correct, it is added to the blockchain. Otherwise, it is either discarded or flagged for human review. This process ensures data integrity and confidentiality while keeping validation efficient and low-cost.

Why POA?

POA is a more energy-efficient cryptographic system than Proof of Work (POW), using fewer computational resources. This makes it ideal for supply chains, where low latency and high throughput are crucial. POA handles multiple data submissions quickly and suits real-time inputs from IoT devices and trusted supply chain participants. Unlike POW or POS, which focus on trust-less environments, POA works well in permissioned supply chains. It also reduces operational costs and enhances trust and traceability through Digital Identity Identifiers (DIDs), unlike the pseudonymous validators in POW and POS.

The suggested approach strikes a balance between security, efficiency, and accountability by utilising POA, which makes it a good option for a supply chain blockchain-based anti-counterfeiting solution.

Evaluation

Theoretical Evaluation

The suggested blockchain-based anti-counterfeiting system provides a strong answer to supply chain management's problems with data integrity and authenticity. Decentralised Identity (DID), IoT devices, smart contracts, and blockchain technology are all integrated to provide a smooth and safe data flow across the supply chain. This creative strategy increases stakeholder confidence while reducing the possibility of fake goods.

Data Authenticity and Trustworthiness

Every data entry is traceable and connected to a verified source thanks to the assignment of distinct cryptographic IDs to each participant and IoT device. Strong cryptographic guarantees are offered by DIDs and digital signatures, which guarantee that data is impenetrable and stop unwanted inputs. By lowering manual intervention and related mistakes, the use of IoT sensors to gather real-time environmental and logistical data offers an additional layer of authenticity.

Automated Validation with Smart Contracts

Smart contracts automate data validation by enforcing predefined rules, reducing human bias and the risk of fraud. For example, when verifying timestamps or checking IoT sensor readings against set thresholds, this system ensures consistency and reliability. It also flags invalid or suspicious entries for further review, enhancing fraud detection.

Immutability and Security

Because blockchain technology is immutable, data cannot be changed or removed once it has been verified and saved, resulting in a permanent, impenetrable record. This creates a single source of truth that can be cited in the event of disagreements or audits and offers a high degree of data protection. Because the blockchain is decentralised, there isn't a single point of failure, making the system more resilient to hackers.

Effectiveness and Expandability

The system's Proof Of Authority (POA) consensus process works effectively in permissioned networks, such as supply chains, where members are entities that have already been confirmed. Compared to energy-intensive processes like Proof Of Work (POW), POA lowers computing overhead, enabling speedier transaction processing. Because of this, the system is scalable and able to manage high amounts of real-time data inputs from supply chain participants and IoT devices.

Responsibility and Traceability

Every data entry may be traced back to its source using cryptographic signatures thanks to the traceability layer. This promotes moral behaviour and increases responsibility among stakeholders. Audit trails make it possible to quickly identify the offending party in the case of a counterfeit or discrepancy, guaranteeing timely remedial action and reducing interruptions.

The proposed approach is a significant advancement in preventing counterfeiting and ensuring data integrity in supply chains. By integrating blockchain, DIDs, IoT, and smart contracts, it offers a secure, efficient, and transparent system for monitoring and verifying supply chain data. Its potential to enhance traceability, accountability, and trust makes it a promising solution to current supply chain challenges. However, overcoming interoperability issues and fostering collaboration among stakeholders is essential for successful implementation.

Technical Evaluation

Key issues with supply chain data integrity and authenticity are successfully addressed by the suggested blockchain-based anti-counterfeiting solution, which integrates cutting-edge technology including Decentralised Identity (DID), Internet of Things (IoT) devices, and smart contracts. The system is made to be efficient and scalable while improving security, accountability, and transparency.

Data Integrity and Security

By guaranteeing a decentralised, unchangeable record, blockchain technology dramatically lowers the possibility of data manipulation or illegal changes. The system ensures that every data submission is verified and connected to its source by allocating DIDs to all participants and IoT devices. Data integrity is further improved with cryptographic signatures, which guarantee that data cannot be changed after it has been sent. By automating data validation procedures according to pre-established standards, smart contract integration reduces the likelihood of fraud or human mistake and adds an extra layer of protection.

Performance and Scalability

A high-performance substitute for more resource-intensive protocols like Proof Of Work (POW) is the Proof Of Authority (POA) consensus method. POA is perfect for real-time data submission and validation in supply chain contexts since it allows for quicker transaction validation with less computing overhead. This scalability guarantees that the system can manage the large amount of data produced by several supply chain actors and IoT devices without sacrificing functionality.

Openness and Traceability

Transparency and traceability, which are essential for fostering confidence among supply chain partners, are highlighted in the system's architecture. Every data entry can be tracked back to its source thanks to audit trails and cryptographic signatures, guaranteeing accountability. This function is very helpful for spotting fraudulent activities, settling conflicts, and making sure regulations are followed. Transparency is further increased by the blockchain's immutable data storage, which offers an unchangeable record of transactions.

Combining Automation with IOT

The granularity and accuracy of supply chain monitoring are improved by the integration of IoT devices, which allows real-time data gathering and reporting. IOT nodes, including temperature sensors and RFID scanners, are essential for making sure that important product data is recorded and verified. By automating the implementation of validation requirements, smart contracts increase operational efficiency and lessen the need for manual interventions.

Flexibility and Adaptability

The system's modular architecture, which integrates blockchain, IOT, and DIDs, guarantees adaptation to different supply chain scenarios and sectors. Smart contracts' rules may be tailored to meet the demands of various product categories, legal regulations, and business operations. Additionally, because the system is expandable, cutting-edge technologies like AI-based fraud detection for improved anomaly detection and predictive analytics may be included.

Obstacles and Restrictions

Notwithstanding its advantages, the method has many drawbacks. Concerns with centralisation and trust in validator selection may arise from POA's dependence on pre-approved validators. Furthermore, even if the system takes care of a lot of data authenticity issues, the correctness of the initial data is dependent on the participants' data submissions and the integrity of IOT devices. Data dependability may be jeopardised by IoT device vulnerabilities or DID abuse. Lastly, smaller supply chain enterprises may find it difficult to afford the expense of implementing IoT devices and maintaining blockchain infrastructure.

The suggested method provides a reliable, scalable, and secure way to deal with supply chain issues related to data integrity and authenticity. It maintains efficiency while improving accountability, traceability, and transparency by utilising blockchain, DIDs, IoT, and POA. Although there are still some issues, the system's extensible and modular architecture allows it to be adjusted to changing supply chain requirements and technology developments, making it a useful instrument for preventing counterfeiting and boosting supply chain security.

Conclusion

The suggested blockchain-based supply chain anti-counterfeiting solution shows a strong and creative method for guaranteeing data integrity, authenticity, and transparency. The system tackles the serious problems of fraud and counterfeiting, which are common in contemporary supply chains, by combining blockchain technology with decentralised identification (DID), Internet Of Things (IOT) devices, and smart contracts. While IOT devices provide real-time data gathering and identification, the use of decentralised identities improves accountability and guarantees the authenticity of data sources. This combination strengthens stakeholder confidence by establishing a safe framework in which each data entry can be tracked back to its source.

Smart contracts reduce mistakes and human involvement by introducing an automatic data validation method. These contracts make sure that only legitimate entries are put to the blockchain by enforcing pre-established restrictions, such as validating timestamps and sensor data. The integrity of the supply chain records is further maintained by the blockchain's immutability, which guarantees that data cannot be changed or tampered with once it has been recorded. This is enhanced by the traceability layer, which permits audit trails that can spot irregularities and hold people responsible.

The system is appropriate for supply chains with several stakeholders as it adopts a Proof Of Authority (POA) consensus approach, which balances efficiency and security. The system ensures data validity while maintaining high throughput by restricting validation rights to certified organisations. This method lowers computing overhead, which makes it an affordable option for practical uses.

In summary, the suggested solution is a big step toward improving supply chain security and thwarting counterfeiting. Its use of cutting-edge technology provides stakeholders with a scalable and reliable framework. As the system develops, its efficacy and worldwide applicability may be further enhanced by adding AI-driven fraud detection and expanding interoperability across supply chains.

Future Scope

Future developments of the suggested blockchain-based supply chain anti-counterfeiting system are quite promising. Integrating machine learning (ML) and artificial intelligence (AI) to improve fraud detection skills is one important area for study. Large amounts of supply chain data may be analysed by AI algorithms to find trends and abnormalities that can point to fraud, enhancing the system's real-time monitoring and prediction power.

Future improvements should aim at enhancing compatibility with other blockchain networks. Enabling seamless data exchange between different platforms will boost the system's scalability and global reach, as supply chains often span multiple sectors and regions. Implementing cross-chain protocols will allow more stakeholders to participate and benefit from the system.

Additionally, adding more sophisticated IOT devices—like drones and sensors with blockchain capabilities—could enhance real-time data collection and monitoring. More exact data validation may result from these devices' even higher tracking accuracy of product motions and conditions.

Lastly, future research may concentrate on using privacy-preserving technologies like zero-knowledge proofs (ZKPs) to safeguard sensitive data while keeping transparency, as privacy concerns in decentralised systems continue to develop. This would guarantee the system's security while complying with data protection laws.

By taking care of these issues, the suggested system may develop into a complete, flexible solution for international supply chains that guarantees security, trust, and authenticity.

References

Chen, C.-L., Deng, Y.-Y., Li, C.-T., Zhu, S., Chiu, Y.-J. and Chen, P.-Z. (2020) 'An IoT-based traceable drug anti-counterfeiting management system', *IEEE Access: Practical Innovations, Open Solutions*, 8, pp. 224532–224548. Available from: https://doi.org/10.1109/ACCESS.2020.3036832 [Accessed 10 January 2025].

Chen, C.-L. et al. (2021) 'Based on consortium blockchain to design a credit verifiable cross university course learning system', *Security and Communication Networks*, 2021, pp. 1–18. Available at: https://doi.org/10.1155/2021/8241801.

Deepa, N., Pham, Q.-V., Nguyen, D.C., Bhattacharya, S., Prabadevi, B., Gadekallu, T.R., Maddikunta, P.K.R., Fang, F. and Pathirana, P.N. (2022) 'A survey on blockchain for big data: Approaches, opportunities, and future directions', *Future Generations Computer Systems: FGCS*, 131, pp. 209–226. Available at: https://linkinghub.elsevier.com/retrieve/pii/S0167739X22000243.

Harvard Business Review (2019) 'How luxury brands can beat counterfeiters', *Harvard Business Review* [online]. Available from: https://hbr.org/2019/05/how-luxury-brands-can-beat-counterfeiters [Accessed 14 January 2025].

Mohit, P., Amin, R. and Biswas, G.P. (2017) 'Design of authentication protocol for wireless sensor network-based smart vehicular system', *Vehicular Communications*, 9, pp. 64–71. Available at: https://linkinghub.elsevier.com/retrieve/pii/S2214209616301127.

Puthal, D., Ranjan, R., Nanda, A., Nanda, P., Jayaraman, P. P. and Zomaya, A. Y. (2019) 'Secure authentication and load balancing of distributed edge datacenters', *Journal of Parallel and Distributed Computing*, 124, pp. 60–69. Available from: https://doi.org/10.1016/j.jpdc.2018.10.007 [Accessed 10 January 2025].

Qi, M., Chen, J. and Chen, Y. (2018) 'A secure biometrics-based authentication key exchange protocol for multi-server TMIS using ECC', *Computer Methods and Programs in Biomedicine*, 164, pp. 101–109. Available from: https://doi.org/10.1016/j.cmpb.2018.07.008 [Accessed 10 January 2025].

Schmidt, C.G. and Wagner, S.M. (2019) 'Blockchain and supply chain relations: A transaction cost theory perspective', *Journal of Purchasing and Supply Management*, 25(4), p. 100552. Available at: https://doi.org/10.1016/j.pursup.2019.100552.

Singh, R., Dwivedi, A.D. and Srivastava, G. (2020) 'Internet of Things based blockchain for temperature monitoring and counterfeit pharmaceutical prevention', *Sensors (Basel, Switzerland)*, 20(14), 3951. Available at: https://www.mdpi.com/1424-8220/20/14/3951 [Accessed 10 January 2025].

Stamatellis, C., Papadopoulos, P., Pitropakis, N., Katsikas, S. and Buchanan, W. (2020) 'A privacy-preserving healthcare framework using Hyperledger Fabric', *Sensors (Basel, Switzerland)*, 20(22), 6587. Available at: https://www.mdpi.com/1424-8220/20/22/6587 [Accessed 10 January 2025].

Wang, Y., Lin, J. and Choi, T.-M. (2020) 'Gray market and counterfeiting in supply chains: A review of the operations literature and implications to luxury industries', *Transportation Research Part E: Logistics and Transportation Review*, 133(101823), p. 101823. Available from: https://doi.org/10.1016/j.tre.2019.101823 [Accessed 10 January 2025].