


# GRAPHS

# Definitions


- A graph,  $G=(V, E)$ , consists of two sets:
  - a finite set of *vertices*( $V$ ), and
  - a finite, possibly empty set of edges( $E$ )
  - $V(G)$  and  $E(G)$  represent the sets of vertices and edges of  $G$ , respectively
- Undirected graph
  - The pairs of vertices representing any edge is *unordered*
  - e.g.,  $(v_0, v_1)$  and  $(v_1, v_0)$  represent the same edge  $(v_0, v_1) = (v_1, v_0)$
- Directed graph
  - Each edge as a directed pair of vertices  $\langle v_0, v_1 \rangle \neq \langle v_1, v_0 \rangle$
  - e.g.  $\langle v_0, v_1 \rangle$  represents an edge,  $v_0$  is the tail and  $v_1$  is the head

# Examples for Graph




$G_1$

complete graph



$G_2$

incomplete graph



$G_3$

$$V(G_1) = \{0, 1, 2, 3\}$$

$$E(G_1) = \{(0, 1), (0, 2), (0, 3), (1, 2), (1, 3), (2, 3)\}$$

$$V(G_2) = \{0, 1, 2, 3, 4, 5, 6\}$$

$$E(G_2) = \{(0, 1), (0, 2), (1, 3), (1, 4), (2, 5), (2, 6)\}$$

$$V(G_3) = \{0, 1, 2\}$$

$$E(G_3) = \{<0, 1>, <1, 0>, <1, 2>\}$$

complete undirected graph:  $n(n-1)/2$  edges

complete directed graph:  $n(n-1)$  edges

# Complete Graph


A complete graph is a graph that has the maximum number of edges

- for **undirected graph** with  $n$  vertices, the maximum number of edges is  $n(n-1)/2$
- for **directed graph** with  $n$  vertices, the maximum number of edges is  $n(n-1)$
- example:  $G_1$  (previous slide) is a complete graph

# Adjacent and Incident

- If  $(v_0, v_1)$  is an edge in an undirected graph,
  - $v_0$  and  $v_1$  are **adjacent**
  - The edge  $(v_0, v_1)$  is incident on vertices  $v_0$  and  $v_1$
- If  $\langle v_0, v_1 \rangle$  is an edge in a directed graph
  - $v_0$  is **adjacent to**  $v_1$ , and  $v_1$  is **adjacent from**  $v_0$
  - The edge  $\langle v_0, v_1 \rangle$  is incident on  $v_0$  and  $v_1$


**\*Figure 6.3:**Example of a graph with feedback loops and a multigraph (p.260)




# Subgraph and Path

- A **subgraph** of  $G$  is a graph  $G'$  such that  $V(G')$  is a subset of  $V(G)$  and  $E(G')$  is a subset of  $E(G)$
- A **path** from vertex  $v_p$  to vertex  $v_q$  in a graph  $G$ , is a sequence of vertices,  $v_p, v_{i1}, v_{i2}, \dots, v_{in}, v_q$ , such that  $(v_p, v_{i1}), (v_{i1}, v_{i2}), \dots, (v_{in}, v_q)$  are edges in an undirected graph
- The **length of a path** is the number of edges on it


**Figure 6.4: subgraphs of  $G_1$  and  $G_3$  (p.261)**




$G_1$




(i)



(ii)



(iii)



(iv)


(a) Some of the subgraph of  $G_1$



$G_3$




(i)



(ii)



(iii)



(iv)


(b) Some of the subgraph of  $G_3$




# Simple Path and Cycle

- A **simple path** is a path in which all vertices, except possibly the first and the last, are distinct
- A **cycle** is a simple path in which the first and the last vertices are the same
- In an undirected graph  $G$ , two vertices,  $v_0$  and  $v_1$ , are **connected** if there is a path in  $G$  from  $v_0$  to  $v_1$
- An undirected graph is **connected** if, for every pair of distinct vertices  $v_i$ ,  $v_j$ , there is a path from  $v_i$  to  $v_j$

connected



$G_1$



$G_2$

tree (acyclic graph)

# Degree of an undirected graph

- The degree  $d_i$  of vertex  $i$  is the number of edges incident on vertex  $i$ .
- In an undirected graph, if  $d_i$  is the degree of a vertex  $i$ ,  $n$  is the number of vertices and  $e$  is the number of edges, then number of edges  $e$  is

$$e = \left( \sum_{i=0}^{n-1} d_i \right) / 2$$

# Degree of a directed graph


in – degree of vertex i: Let  $G$  be a digraph. The in-degree  $d_i^{\text{in}}$  of vertex  $i$  is the number of edges incident to  $i$ .


Out – degree of vertex i: The out- degree  $d_i^{\text{out}}$  of vertex  $i$  is the number of edges incident from this vertex.

$$e = \sum_{i=1}^n d_i^{\text{in}} = \sum_{i=1}^n d_i^{\text{out}}$$

# Undirected graph


degree






# Graph representations


- Adjacency matrices
- Adjacency lists



**G1**




**G3**




**G2**

# Graph representation – undirected



(a)

graph



(b)

Adjacency list


	1	2	3	4	5
1	0	1	0	0	1
2	1	0	1	1	1
3	0	1	0	1	0
4	0	1	1	0	1
5	1	1	0	1	0

(c)

Adjacency matrix




# Graph representation – directed



(a)

graph



(b)

Adjacency list

	1	2	3	4	5	6
1	0	1	0	1	0	0
2	0	0	0	0	1	0
3	0	0	0	0	1	1
4	0	1	0	0	0	0
5	0	0	0	1	0	0
6	0	0	0	0	0	1


(c)

Adjacency matrix

# Adjacency Matrix

- Let  $G=(V,E)$  be a graph with  $n$  vertices.
- The **adjacency matrix** of  $G$  is a two-dimensional  $n$  by  $n$  array, say `adj_mat`
- If the edge  $(v_i, v_j)$  is in  $E(G)$ , `adj_mat[i][j]=1`
- If there is no such edge in  $E(G)$ , `adj_mat[i][j]=0`
- The adjacency matrix for an undirected graph is symmetric; the adjacency matrix for a digraph need not be symmetric

# Examples for Adjacency Matrix





$$\begin{bmatrix} 0 & 1 & 1 & 1 \\ 1 & 0 & 1 & 1 \\ 1 & 1 & 0 & 1 \\ 1 & 1 & 1 & 0 \end{bmatrix}$$

$G_1$



$$\begin{bmatrix} 0 & 1 & 0 \\ 1 & 0 & 1 \\ 0 & 0 & 0 \end{bmatrix}$$

$G_2$




$$\begin{bmatrix} 0 & 1 & 1 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 0 & 1 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 \end{bmatrix}$$

$G_4$


symmetric

undirected:  $n^2/2$   
directed:  $n^2$

# Adjacency lists



# Adjacency lists



# Graph Operations

- Traversal

Given  $G=(V,E)$  and vertex  $v$ , find all  $w \in V$ , such that  $w$  connects  $v$ .

- Depth First Search (DFS)  
preorder tree traversal

- Breadth First Search (BFS)  
level order tree traversal

# Graph Traversals: DFS BFS

# Some Graph Operations

- Traversal

Given  $G=(V,E)$  and vertex  $v$ , find all  $w \in V$ , such that  $w$  connects  $v$ .

- Depth First Search (DFS)  
preorder tree traversal

- Breadth First Search (BFS)  
level order tree traversal




**DFS**



**BFS**



# Depth-first search



- A depth-first search (DFS) explores a path all the way to a leaf before backtracking and exploring another path
- For example, after searching A, then B, then D, the search backtracks and tries another path from B
- Node are explored in the order  
A B D E H L M N I O P C F G J  
K Q

# DFS Algorithm

Mark all the  $n$  vertices as not visited.

insert source into stack and mark it visited

**while(Stack is not empty)**

**{**

**delete Stack element into variable  $u$**

**place all the adjacent (not visited) vertices of  $u$  into Stack and also mark them visited**

**print  $u$**

**}**


```
void dfs(int a[20][20],int n, int source)
{
    int visited[10],u,v,i;
    for(i=1;i<=n;i++)        visited[i]=0;
    int S[20],top=-1;
    S[++top]=source;
    visited[source]=1;
    while(top>=0)
    {
        u=S[top--];
        for(v=1;v<=n;v++)
        {
            if(a[u][v]==1 && visited[v]==0)
            {
                visited[v]=1;        S[++top]=v;
            }
        }
        printf(" %d ",u);
    }
}
```

# Breadth first search

It is so named because

It discovers all vertices at distance  $k$  from  $s$  before discovering vertices at distance  $k+1$ .

# Breadth-first search



- A breadth-first search (BFS) explores nodes nearest the root before exploring nodes further away
- For example, after searching A, then B, then C, the search proceeds with D, E, F, G
- Node are explored in the order  
A B C D E F G H I J K L M N O  
P Q

# Algorithm BFS

Mark all the  $n$  vertices as not visited.

insert source into  $Q$  and mark it visited

**while**( $Q$  is not empty)

{

    delete  $Q$  element into variable  $u$

    place all the adjacent (not visited) vertices of  $u$   
into  $Q$  and also mark them visited

    print  $u$

}

```

void bfs(int a[20][20],int n,int source)
{
    int visited[10],u,v,i;

    for(i=1;i<=n;i++)    visited[i]=0;
    int Q[20],f=-1,r=-1;
    Q[++r]=source;    visited[source]=1;
    while(f<r)
    {
        u=Q[++f];
        for(v=1;v<=n;v++)
        {    if(a[u][v]==1 && visited[v]==0)
            {
                visited[v]=1;
                Q[++r]=v;
            }
        }
        printf(" %d ",u);
    }
}

```



```
int main()
{
    int a[20][20],source, n,i,j;
    printf("Enter the no of vertices: ");
        scanf("%d",&n);


    printf("Enter the adjacency matrix: ");
    for(i=1;i<=n;i++)
        for(j=1;j<=n;j++)
            scanf("%d",&a[i][j]);

    printf("Enter the source vertex: ");
        scanf("%d",&source);


    printf("\n BFS: ");    bfs(a,n,source);
    printf("\n DFS: ");    dfs(a,n,source);
    return 1;
}
```

# Spanning Tree (ST)


- A spanning tree is a minimal subgraph  $G'$ , such that  $V(G')=V(G)$  and  $G'$  is connected. Spanning Tree is always acyclic.



**ST1(G)**



**ST2(G)**



**G1**

