

# XdagJ Node 0.8.0 Run Document

---

## System Environment

---

JDK : v21

Maven : v3.9.1

MySQL : Above v8.0

**Notice:** The JDK version has been updated from `JDK 17` to `JDK 21`.

## Operation Steps

---

### 1. Clone Code

- *If the XdagJ project does not exist:*

```
$ git clone https://github.com/XDagger/xdagj.git
```

- *If the XdagJ project already exists:*

```
$ cd xdagj  
$ git pull
```

- *Make sure the XdagJ project is in the master branch:*

- *View the current branch*

```
$ git branch
```

- *Perform this operation when the current branch is not master*

```
$ git checkout master
```

### 2. Configure MySQL

- *If you are configuring MySQL for the first time:*

- *Install MySQL*

```
# install MySQL.  
$ sudo apt install mysql-server
```

- *Change password*

- Log in to the MySQL database as the root user

```
$ sudo mysql -u root
```

- Change password

```
mysql> ALTER USER 'root'@'localhost' IDENTIFIED WITH  
mysql_native_password BY 'your_new_password';  
mysql> FLUSH PRIVILEGES;  
mysql> EXIT;
```

- *Create a database for saving transaction history*

- Log in to MySQL as the root user, using the password you just set

```
$ mysql -u root -p
```

- Create a database named `your_store_transaction_history_database_name`

```
mysql> CREATE DATABASE your_store_transaction_history_database_name;
```

- Check if the database was created successfully

```
mysql> SHOW DATABASES;
```

- *Create a table*

- Select the database you just created

```
mysql> USE your_store_transaction_history_database_name;
```

- Locate the `mysql_create_table.sql` script in the `xdagj/script` folder. Create table `t_transaction_history` under this database

```
mysql> source absolute_path_of_your mysql_create_table.sql script;  
  
# For example: "source  
/home/ubuntu/xdagj/script/mysql_create_table.sql;"
```

- Check whether the table is created successfully

```
mysql> SHOW TABLES;
```

- ***If you have already configured MySQL and have run nodes before, please perform the following steps:***

- *Login to MySQL*

```
$ mysql -u root -p
```

- *Back up previous versions of transaction history*

- Select the database where you previously stored transaction history

```
mysql> USE your_store_transaction_history_database_name;
```

- Back up previous versions of transaction history data

```
mysql> RENAME TABLE t_transaction_history TO  
transaction_history_v_0_7_2;
```

- Re-create an empty `t_transaction_history` table

- Select the database where you previously stored transaction history

```
mysql> USE your_store_transaction_history_database_name;
```

- Locate the `mysql_create_table.sql` script in the `xdagj/script` folder. Create table `t_transaction_history` under this database

```
mysql> source absolute_path_of_your mysql_create_table.sql script;  
  
# For example: "source  
/home/ubuntu/xdagj/script/mysql_create_table.sql;"
```

- Check whether the table is created successfully

```
mysql> SHOW TABLES;
```

### 3. Execute mvn

```
$ cd xdagj  
$ mvn clean package -Dmaven.test.skip=true
```

### 4. Create "run" Folder and Modify the Configuration Files

- *If you have not created a "run" folder before, please follow the steps below:*

- Create a "run" folder:

```
# Create a run folder, which is usually in the same directory as the  
xdagj.  
$ mkdir run
```

- Copy the necessary files to the "run" folder:

Copy "xdag-mainnet.conf", "druid.properties", "log4j2.xml", "xdag.sh", "xdagj-0.8.0-shaded.jar" to "run" folder.

- "xdag-mainnet.conf", "druid.properties", "log4j2.xml" are located in the xdagj/src/main/resources
- "xdag.sh" is located in the xdagj/script
- "xdagj-0.8.0-shaded.jar" is located in the xdagj/target

◦ *Modify the configuration files:*

■ Modify druid.properties

- Modify the url in the druid.properties file to:  
jdbc:mysql://localhost:3306/your\_store\_transaction\_history\_database\_name?  
autoReconnect=true&useUnicode=true&characterEncoding=utf-8&serverTimezone=UTC
- The user name is root, and the password is the password (your\_new\_password) set in the mysql configuration before.

■ Modify xdag-mainnet.conf

- "node.whiteIPs": Determines which nodes, under which IP addresses, can communicate with this node (Please ask the community if "node.whiteIPs" needs to be updated, added or deleted).
- "fund.address": Set fund.address = "PKCBtHWDSnAwfZntqWPBLedqBShuKSTzS" (Required: Without this address, miner rewards cannot be distributed).
- "node.generate.block.enable": Set node.generate.block.enable = true for mining nodes and node.generate.block.enable = false for exchanges.
- "randomx.flags.fullmem": Please set randomx.flags.fullmem = false.
- "fund.ration" and "node.ration" are the ratios of foundation reward and block node reward, respectively.
- node.reject.transaction.address is the address to be denied service.
- pool.whiteIPs is the pool whitelist. If set to ["0.0.0.0"], any pool can access the node. Otherwise, only specified IPs are allowed.

■ Modify xdag.sh

- XDAG\_VERSION: Modify XDAG\_VERSION to "0.8.0".

- ***If you have already created the "run" folder and run the node before, follow these steps:***

- Copy xdagj-0.8.0-shaded.jar to the run folder.
- Modify the XDAG\_VERSION in xdag.sh to XDAG\_VERSION="0.8.0".
- In xdag-mainnet.conf, set randomx.flags.fullmem = false.
- Please ask the community if "node.whiteIPs" needs to be updated, added or deleted.

## 5. Download the SNAPSHOT File

1. Create the /main/rocksdb/xdagdb directory under the run folder.
2. SNAPSHOT download address: <https://storage.xdagpool.com/>.
3. Unzip the compressed package to get a SNAPSHOT folder.
4. Delete all files except SNAPSHOT files in the run/mainnet/rocksdb/xdagdb directory.
5. Copy the unzipped SNAPSHOT file to mainnet/rocksdb/xdagdb in the root directory, overwriting the existing SNAPSHOT folder.

## 6. Make Snapshot (Developer node steps: Ignore if not relevant)

```
###
Notice:
  1. Please make sure to update file "xdagj-0.8.0-shaded.jar" before
performing this step.
  2. Snapshot file "SNAPSHOT" will be generated in directory
mainnet/rocksdb/xdagdb.
###

# Run the following command to make the snapshot.
$ cd run
$ sh xdag.sh --makesnapshot
```

## 7. Verify the Version of xdag.sh

```
# Run this command in the /run path to verify the version.
$ sh xdag.sh --version    // return: 0.8.0
```

## 8. Start Xdagj

###

Notice:

1. If there is no wallet folder under the current mainnet directory, it will be created automatically when the node starts.
2. The node and pool wallet addresses must be different; otherwise, rewards will not be issued.

###

# Run the following command to start the xdagj node.

```
$ cd run
```

```
$ sh xdag.sh --enablesnapshot true [Snapshot Height] [Timestamp] // Check with the community for the correct command.
```

# For example: "sh xdag.sh --enablesnapshot true 3140605 19a15630000" (Check with the community for the correct command).

**Notice:** If an exception occurs when starting the snapshot, delete the loaded data from `t_transaction_history` in MySQL. Ensure the table is empty before restarting. Also, delete all non-SNAPSHOT files in `rocksdb/xdagdb`.

## 9. Verify MySQL Data and SNAPSHOT Data

- *Verify MySQL data:*

# Login to MySQL.

```
$ mysql -u root -p
```

###

1. Run the following command to verify whether the data is successfully written to MySQL.
2. If the data amount is greater than 0, it means that it has been successfully written to MySQL.

###

```
mysql> USE you_database_name;
```

```
mysql> SELECT COUNT(*) FROM t_transaction_history;
```

## 10. Check the Node State

- *This is an example of a successful node startup result:*

```
ubuntu@xxx-xxx-xxx-xxx:~/XdagJNode/run$ sh xdag.sh --enablesnapshot true 3140605 19a15630000
xdag.sh: 3: ulimit: error setting limit (Operation not permitted)
enable snapshot:true
Please Enter wallet Password:
init snapshot...
amount in address: 631490160.480122105
amount in blocks: 615276623.519882021
```

```
init snapshotJ done
time: 179815ms
Our balance: 0.000000000
All amount: 1246766784.000004126
telnetd is running on 127.0.0.1:6001
Mar 09, 2025 3:10:05 AM org.jline.builtins.telnet.PortListener run
INFO: Listening to Port 6,001 with a connectivity queue size of 10.
```

- **Check the node status by using the telnet:**

- *Start telnet*

- Run the following command to use telnet

```
$ telnet 127.0.0.1 6001
```

- Enter the password, the password is admin.telnet.password in xdag-mainnet.conf

```
Enter Admin password>[Your password]
```

- *List all methods in telnet*

```
xdag> help
```

- *Check the state of the node*

```
xdag> state
```

**Notice:** If the returned result is `Synchronized with the main network. Normal operation.`, it indicates that synchronization is complete and block generation is functioning normally. At this point, your node has been successfully set up and synchronized with the mainnet.