
Rust and GraphQL for backend Schema creation and basic features

Maciek Zwoliński

June 2022

Graphql Schema



```
struct User {
    id: usize,
    name: String,
    surname: String,
    age: u32,
    car_id: Optional<usize>, // references car.id
enum Brand {
    Fiat,
    Ford,
    Opel,
struct Car {
    id: usize,
    brand: Brand,
    model: String,
    year: u32,
    owner_id: usize, // references user.id
```

REST API

Overfetching

Users:

- ▶ Will Smith, 32 years

REST API

Underfetching

```
GET /users -> [
    "name": "Will",
    "car_id": 1,
    ... // unused
  },
    "name": "Agnieszka",
    "car id": 3.
    ... // unused
  },
GET /cars/1 -> {
  "brand": "Opel",
  "model": "Astra",
  "year": 1999 // unused
}
GET /cars/3 -> {
  "brand": "Ford",
  "model": "Focus",
  "year": 2010 // unused
```

Users:

- Will, Opel Astra
- Agnieszka, Ford Focus
- **...**

GraphQL API

Declarative fetching

```
query {
                   "users": [
  users {
    name,
                      "name": "Will",
                       "surname": "Smith",
    surname,
                       "age": 32,
    age
                     },
}
query {
                   "users": [
  users {
                      "name": "Will",
    name,
                       "car": {
    car {
                         "brand": "Opel"
      brand,
      model
                         "model": "Astra"
                     . . .
```

Users:

- ▶ Will Smith, 32 years
- **...**

Users:

- Will, Opel Astra
- •

REST API

Overfetching/Underfetching

Server side crates:

- async-graphql
- juniper

both integrates well with popular backend crates like actix-web, axum, rocket, warp...

Client side crates:

- graphql_client
- cynic

you can choose from different designs of strong typing but subscriptions are not quite there yet