API / Contracts

This is the contract reference for `candex-api`. It builds on Back-end (how the API is built) and lists the endpoints per resource. The **live, exhaustive contract** — request/response schemas, examples, and try-it-out — is **Swagger UI** at `/swagger-ui.html`; this page is the stable map around it.

Conventions

- **Envelope** — every response is a `Result<T>`: `{ success, data, error }` (see Back-end).
- **Status codes** — come from typed exceptions (`404` / `400` / `409` / `422`…); see Back-end error handling.
- **Headers** — list responses carry `X-Total-Count`; creations return `201` with a `Location` header.
- **Authentication** — send a Firebase ID token as `Authorization: Bearer <token>`.
- **Access** — per endpoint, in the tables below: `USER_OR_ADMIN` = any authenticated user, `ADMIN` = admin only, `PUBLIC` = no auth, **own** = the authenticated user may only act on their own records.
- **Base path** — resources are served under the API base (for example `/api/drinks`).

Catalogue

Drinks — `/drinks`

Method	Path	Access	Purpose
GET	/drinks	USER_OR_ADMIN	List drinks
GET	/drinks/{id}	USER_OR_ADMIN	A single drink
POST	/drinks	ADMIN	Create a drink
POST	/drinks/import	ADMIN	Bulk import drinks
POST	/drinks/import/diff	ADMIN	Preview an import against the current catalogue
POST	/drinks/import/sync	ADMIN	Apply an import
PUT	/drinks/{id}/shift	ADMIN	Move the drink's World Dex position
PUT	/drinks/{id}/swap	ADMIN	Swap two World Dex positions
DELETE	/drinks/{id}	ADMIN	Delete a drink

Cans — /cans

Method	Path	Access
GET	/cans • /cans/{id}	USER_OR_ADMIN
POST	/cans	ADMIN
DELETE	/cans/{id}	ADMIN

Reference data (reads)

Catalogue reference resources expose list and by-id reads: **Brands** /brands, **Flavors** /flavors and **Flavor categories** /flavor-categories, **Colors** /colors (+

`/colors/extract`), **Drink categories** `/drink-categories`, **Can formats** `/can-formats`, and **App versions** `/app-versions` (+ `/app-versions/current`).

World Dex — `/world-dex`

Method	Path	Access	Purpose
GET	`/world-dex/drinks/{id}/history`	USER_OR_ADMIN	A drink's position history
GET	`/world-dex/drinks/{id}/stats`	USER_OR_ADMIN	A drink's Dex stats
GET	`/world-dex/snapshot`	USER_OR_ADMIN	Current Dex snapshot
GET	`/world-dex/movers`	USER_OR_ADMIN	Recent movers
GET	`/world-dex/positions/{position}/occupants`	USER_OR_ADMIN	Who sits at a position

Users & collection

Users — `/users`

Method	Path	Access	Purpose
GET	/users	ADMIN	List users
GET	/users/{id}	own	A user
GET	/users/firebase/{firebaseUid}	own	A user by Firebase UID
GET	/users/{id}/drinks	own	A user's unlocked drinks
GET	/users/exists	PUBLIC	Existence check
POST	/users	PUBLIC	Register
PUT • PATCH	/users/{id}	own	Update a user
DELETE	/users/{id}	own	Delete a user

Unlocked drinks — `/user-unlocked-drinks`

Method	Path	Access	Purpose
GET	/user-unlocked-drinks/{userId}	own	A user's unlocks
POST	/user-unlocked-drinks	own	Unlock a drink
DELETE	/user-unlocked-drinks/{userId}/{drinkId}	own	Remove an unlock

Admin & operations

- **SQL console** — `POST /admin/...` (ADMIN): run a read-only query through the console role (see Database & Model).
- **Reports** — `POST /reports`: generate a report.

The bulk-import flow

Importing a batch of drinks is a three-step, admin-only pipeline:

1. `POST /drinks/import` — submit the payload.
2. `POST /drinks/import/diff` — preview the changes against the current catalogue.
3. `POST /drinks/import/sync` — apply them.

Where to go next

- How the API is built → Back-end
- Live schemas & try-it-out → **Swagger UI** (`/swagger-ui.html`)