
Security

Security is enforced in the **API**. Authentication decides *who* is calling; authorization decides *what* they may do. The HTTP layer stays deliberately thin — it sets the authentication mechanism and a few public routes — while the real business rules live in method security, next to the endpoints they protect.

Request authentication at a glance



Authentication

Two mechanisms coexist.

Firebase ID tokens are the primary path, for app users. A request carries `Authorization: Bearer <token>`; the `FirebaseAuthenticationFilter` verifies it (`FirebaseAuth.verifyIdToken`) and, on success, sets a Spring Security authentication whose **principal is the Firebase UID** and whose authority is `ROLE_USER`. Verification is non-blocking: if the token is missing, invalid, expired, or revoked, the filter simply clears the

context and lets authorization reject the request downstream. Firebase is the source of truth for app identity.

Interim HTTP Basic Auth covers the administrator. An in-memory user store (`InMemoryUserDetailsManager`) holds two accounts loaded from environment variables — a standard `user` (`ROLE_USER`) and an `admin` (`ROLE_ADMIN`) — with BCrypt-hashed passwords. The code documents this as a temporary bridge, intended to be replaced by JWT-based authentication later.

The filter chain is **stateless** (`SessionCreationPolicy.STATELESS`), **CSRF is disabled** (there are no server sessions or cookies to protect), and **CORS** is handled by a dedicated `CorsFilter` with a fixed allow-list of origins (`CorsOrigins`).

Roles

There are two authorities — `ROLE_USER` and `ROLE_ADMIN` (`SecurityRoles`).

Authorization

Authorization runs in two layers.

At the HTTP layer (`SecurityConfig`), only a handful of rules are declared:

- **Public** — `/error`, `/actuator/health`, user registration (`POST /users`), and the existence check (`GET /users/exists`).
- **Admin only** — Swagger UI and the OpenAPI docs (`/swagger-ui/**`, `/v3/api-docs/**`) and the actuator (`/actuator/**`).
- **Everything else** — authenticated.

At the method layer (`@EnableMethodSecurity`), each endpoint carries a `@PreAuthorize` rule, built from reusable `SecurityExpressions`:

- `USER_OR_ADMIN` — any authenticated user or admin.
- `ADMIN_ONLY` — admin authority required (catalogue writes, imports, admin operations).
- `PERMIT_ALL` — explicitly open.

Ownership-scoped endpoints go through the `@securityAccess` bean (`SecurityAccess`) rather than a role alone, e.g. `@PreAuthorize("@securityAccess.canAccessUserId(authentication, #id)")`. The rule is consistent: an **admin bypasses ownership**, otherwise the caller's Firebase UID (or user id) must match the resource's owner. The same bean also guards Firebase-UID access (`canAccessFirebaseUid`) and unlocked-drink management (`canManageUserUnlockedDrink`).

Secrets

No credential or key is committed. The Firebase service account is loaded at runtime from a configured file path (`candex.firebase.config-path`), never from the repository. The Basic-auth accounts (`candex.security.*`) and the database credentials come from environment variables, per Spring profile — the repositories ship only `.env.example` files with placeholders. See Local Installation for setting them locally and Deployment for the deployed environments.

On the client side

The mobile app signs users in with **Firebase Authentication** and calls the API with the resulting ID token in the `Authorization` header; the API trusts Firebase to have authenticated the user and derives identity from the verified token. See Architecture for how the pieces connect.

Where to go next

- The endpoints these rules protect → API / Contracts
- The layers behind them → Back-end
- The big picture → Architecture