

CANDEX HANDBOOK

Releasing

How the three Candex projects are versioned and shipped — the mobile app to the stores, the API via its deploy pipeline, and the admin dashboard.

Written by
Eliott Barbet

Version 0.23.0
November 2026
candex.app

Releasing

Candex is three deployable projects, each versioned and released on its own: the mobile app (`candex-app`), the API (`candex-api`), and the admin dashboard (`candex-dashboard`). For the runtime and infrastructure side, see Deployment.

Mobile app (`candex-app`)

The app carries one version across web, Android, and iOS. A release is cut with the release script:

```
npm run release 1.2.0
```

`scripts/release.js` bumps the version everywhere it lives — `package.json`, the Android `build.gradle` (`versionName` and `versionCode`), and the iOS `project.pbxproj` — updates `CHANGELOG.md`, commits the change, and creates an **annotated git tag** whose message is that version's changelog section. If any step fails it rolls back (restores the files, deletes the tag). It then prints the push command:

```
git push && git push origin 1.2.0
```

Pushing the tag triggers **`github-release.yml`** ("Create GitHub Release"), which publishes the GitHub Release. Shipping to the stores is a separate, manual step: the **"Deploy to Stores"** workflow (`deploy.yml`, `workflow_dispatch`) takes an already-released tag and, via **Fastlane**, builds and submits **Android → Google Play** (an AAB) and **iOS → App Store** (an IPA to App Store Connect).

(Current app version: 1.1.4.)

API (`candex-api`)

The API is a Maven project; its version lives in `pom.xml` (currently 1.1.10). It is released by deploying its Docker image: the **Deployment Development** (`deploy-dev.yml`) and **Deployment Production** (`deploy-prod.yml`) workflows run automatically after CI completes successfully (`workflow_run`), or manually (`workflow_dispatch`). The image build and the Compose stacks are covered in Deployment.

Admin dashboard (`candex-dashboard`)

The dashboard follows the same release-script style: `npm run release` bumps `package.json` and `CHANGELOG.md` and tags the version (web only, no mobile files). Its version is currently 1.0.0. CI runs on every change; there is no store or deploy workflow in the repository, so its deployment is handled elsewhere *(to confirm)*.

Versioning

Each project has its own semantic version and its own `CHANGELOG.md` — the app, the API, and the dashboard move independently.

Where to go next

- The runtime, images, and infrastructure → Deployment
- The checks that gate a release → Testing • Software Quality