KATALYZE: AN AUTONOMOUS TESTING AGENT FOR FUNCTIONAL BUGS IN WEB APPLICATIONS

A Thesis

Submitted in partial fulfilment for the Degree of

BACHELOR OF TECHNOLOGY

in

COMPUTER SCIENCE AND ENGINEERING (ARTIFICIAL INTELLIGENCE)

by

ARUNODAY A K (CB.SC.U4AIE23106)
ACHUTHARAJ R (CB.SC.U4AIE23108)
LOKESH D (CB.SC.U4AIE23123)
ABHAY ROHIT M (CB.SC.U4AIE23173)



DEPARTMENT OF ARTIFICIAL INTELLIGENCE

AMRITA VISHWA VIDYAPEETHAM

COIMBATORE CAMPUS (INDIA)

October 2026

DEPARTMENT OF ARTIFICIAL INTELLIGENCE

AMRITA VISHWA VIDYAPEETHAM

COIMBATORE CAMPUS



BONAFIDE CERTIFICATE

This is to certify that the thesis entitled "**Katalyze: An Autonomous Testing Agent for Functional Bugs in Web Applications**" submitted by **Arunoday A K, Roll. No: CB.SC.U4AIE23106**, **Achutharaj R, Roll. No: CB.SC.U4AIE23108**, **Lokesh D, Roll. No: CB.SC.U4AIE23123** and **Abhay Rohit M, Roll. No: CB.SC.U4AIE23173** for the award of the **Degree of Bachelor of Technology** under the **Faculty of Engineering** is a bonafide record of the work carried out by them under my guidance and supervision at "Department of Artificial Intelligence", Amrita Vishwa Vidyapeetham, Coimbatore Campus.

Submitted for the examination held on .....

INTERNAL EXAMINER **EXTERNAL EXAMINER**

Dr. Palmani Duraisamy
Thesis Advisor,
Assistant Professor (Sr. Gd.),
Center for Computational Engineering and Networking,
School of Artificial Intelligence,
Amrita Vishwa Vidyapeetham,
Coimbatore Campus,
India.

DEPARTMENT OF ARTIFICIAL INTELLIGENCE

AMRITA VISHWA VIDYAPEETHAM

COIMBATORE CAMPUS

DECLARATION

We, **Arunoday A K**, **Reg. No: CB.SC.U4AIE23106**, **Achutharaj R**, **Reg. No: CB.SC.U4AIE23108**, **Lokesh D**, **Reg. No: CB.SC.U4AIE23123** and **Abhay Rohit M**, **Reg. No: CB.SC.U4AIE23173** hereby declare that this thesis entitled "**Katalyze: An Autonomous Testing Agent for Functional Bugs in Web Applications**" is the record of the original work done by us under the guidance of **Dr. Palmani Duraisamy**, Assistant Professor (Sr. Gd.), Center for Computational Engineering and Networking, School of Artificial Intelligence, Amrita Vishwa Vidyapeetham, Coimbatore Campus. To the best of our knowledge, this work has not formed the basis for the award of any degree/diploma/associateship/fellowship or a similar award to any candidate in any University.

Place: **Signature of the Students**
Date:

COUNTERSIGNED

Dr. K.P Soman
Professor and Dean,
Department of Artificial Intelligence
Amrita Vishwa Vidyapeetham,
Coimbatore Campus,
India.

Contents

Acknowledgements **iv**

List of figures **v**

List of tables **vii**

Abbreviations **viii**

List of symbols **ix**

Abstract **x**

1 Introduction **1**

1.1 Motivation 1

1.2 Problem statement and research questions 1

1.3 What a functional bug is 2

1.4 Objectives 4

1.5 Contributions 4

1.6 Scope 5

1.7 Organisation of the thesis 6

2 Background and Related Work **7**

2.1 Automated web testing and test oracles 7

2.2 Reinforcement learning for web and GUI testing 8

2.3 Language models in testing and as reward 9

2.4 Deep reinforcement learning and exploration 9

2.5 Evaluating testing tools 10

2.6 Research gap 11

3 System Overview and the Verified-Fault Oracle **12**

3.1 The browser environment 12

3.1.1 Action registry 13

3.1.2 Deterministic triggers 13

3.2 The verified-fault oracle 13

3.2.1 Seeded faults and assertions . . . 13
3.2.2 From candidate to verified finding . . . 14
3.2.3 What the oracle solves, and what it does not . . . 14
3.2.4 Crash-type faults . . . 15
3.2.5 Specification-free invariants . . . 15
3.3 The product layer . . . 15

4 A Deep Reinforcement Learning Tester (v1) 19
4.1 Testing as a Markov decision process . . . 19
4.2 The agent: an action-conditioned dueling double DQN . . . 20
4.3 Reward . . . 20
4.4 Experiment 1: does pretraining transfer? . . . 21
4.5 Experiment 2: context or memorisation? . . . 23
4.6 Checks of the LLM components . . . 23
4.7 What v1 taught . . . 24

5 The Hybrid Tester (v2) 26
5.1 Page abstraction . . . 26
5.2 Archive with exact return . . . 27
5.3 Test operators . . . 27
5.4 The decision layer . . . 28
5.5 Options for the final tuning round . . . 29
5.6 Development rounds . . . 29

6 Test Applications and Evaluation Methodology 32
6.1 The six-application benchmark . . . 32
6.2 The generated application family . . . 32
6.3 The development suite . . . 32
6.4 The validation suite . . . 33
6.5 The external benchmark . . . 34
6.6 Admission . . . 34
6.7 Data split and independence . . . 35
6.8 Metrics and statistics . . . 35
6.9 Threats to validity . . . 36

7 Evaluation 37
7.1 Held-out evaluation (pre-registered) . . . 37
7.1.1 Design . . . 37
7.1.2 Results . . . 38
7.1.3 What the held-out data shows (descriptive) . . . 39
7.1.4 Discovery by fault difficulty (post-hoc) . . . 40
7.1.5 Candidate verification . . . 41

7.2 Tuning round v3 on the rebuilt development suite . . . 41
7.2.1 Design . . . 41
7.2.2 Results . . . 42
7.2.3 Configuration chosen . . . 43
7.3 Comparison with WebExplor and WebRLED . . . 43
7.3.1 Design . . . 43
7.3.2 Results . . . 44
7.4 Post-hoc follow-up: the action space . . . 46
7.5 External comparison, round 2 (pre-registered) . . . 47
7.6 Post-hoc follow-up: the bandit on the external applications . . . 49
7.7 Discussion . . . 50

8 Conclusion and Scope for Further Research 54
8.1 Conclusion . . . 54
8.2 Limitations . . . 56
8.3 Scope for further research . . . 56

A Agent Configurations and Reproducibility 57
A.1 Arms . . . 57
A.2 Held-out evaluation per fault . . . 58
A.3 Reproducibility checklist . . . 58

References 60

Acknowledgements

We thank our thesis advisor, Dr. Palmani Duraisamy, for the guidance given throughout this project, for questioning our results whenever they looked too good, and for pushing us to state our limitations openly. We thank Dr. K.P. Soman, Professor and Dean, and the faculty of the Department of Artificial Intelligence for the facilities and the review process that shaped this work. We are grateful to the researchers who made their web-testing subject applications public: the authors of WebExplor and WebRLED, and Matteo Biagiola and colleagues, whose replication material packages those applications with their instrumentation. Without open benchmarks, an honest comparison with published work would not be possible. Finally, we thank our families and friends for their support.

ARUNODAY A K
ACHUTHARAJ R
LOKESH D
ABHAY ROHIT M

List of Figures

3.1 The system around the explorer. Only the explorer differs between v1 and v2. . 12
3.2 The web interface: starting a test. A bundled demo application, a live URL, or an uploaded static site or repository. 16
3.3 A finished run (Helpline, 600 interactions): status, progress, the pipeline stages and the live event stream of the tester's actions. 17
3.4 The report of the same run. Each verified finding has its minimised reproduction (here 2 steps, minimised from 15) and the page captured when it was observed. . 17

5.1 The hybrid tester's loop. Every replayed action counts towards the budget. . . . 26

7.1 Held-out evaluation: share of runs that have not yet verified a fault, against interactions (Kaplan–Meier estimate, runs that found nothing censored at 2,000). Lower is better. 39
7.2 Held-out evaluation: distinct faults verified by declared difficulty (post-hoc; dashed line: faults in the group). 41
7.3 External comparison: branch coverage per application. Grey rings: the frozen tester in round 1; blue and orange: the two arms in round 2; black: the published numbers. 48

List of Tables

1.1 The classes of functional bug used in this thesis, with an example from the test applications and the oracle check that observes the failure. 3
1.2 What "autonomous" means for Katalyze, and what the thesis demonstrates. . . 5

3.1 End-to-end acceptance runs of the final product (24 October 2026). "Findings" are the verified findings in the report. For targets without seeded faults they come from generic triggers. 18

4.1 Experiment 1: discovery per arm over all folds (runs of 2,000 interactions). . . . 22
4.2 Experiment 1: pre-registered comparisons (negative Δ = faster). 22
4.3 Experiment 2: pre-registered verdicts for the full agent. 23
4.4 LLM labeller accuracy against ground truth (gates 0.85 / 0.80). 24
4.5 What the v1 experiments establish about the DQN. 24
4.6 Findings from v1 and the design consequences for v2. 25

5.1 Development rounds of the hybrid tester and their decisions. 30
5.2 All arms on the same runs: suite rounds 2–5, 14 applications × 3 seeds. Difference is the per-application mean T against `hybrid_nolearn`, with a bootstrap interval over applications (negative = faster). 30

6.1 The development suite (version 2). 33
6.2 The validation suite, used once, for the held-out evaluation. 34

7.1 Held-out evaluation: pre-registered comparisons (negative Δ = first arm faster). 38
7.2 Held-out evaluation per arm (40 runs each). 38
7.3 Held-out evaluation per application: runs that found a fault (of 5) and mean T. 38
7.4 Held-out evaluation by declared fault difficulty (post-hoc): distinct faults verified, and in brackets runs that verified them out of all (fault, seed) pairs. 40
7.5 Held-out evaluation: candidate verification per arm (40 runs each), with the mean browser interactions and seconds spent verifying each candidate. 41
7.6 Tuning round v3 per arm: 24 runs each on the eight rebuilt development applications, which hold 41 seeded faults (8 of them crash-type). 42
7.7 Tuning round v3 against `hybrid_nolearn`: per-application mean difference in T (negative = faster), median over applications with a 95% bootstrap interval. Apps with no difference are not counted as faster or slower. 42

7.8 External comparison: client-side branch coverage (%), mean [min, max] over three one-hour runs, beside the published means (five runs) of WebExplor and WebRLED [1]. 44
7.9 Post-hoc: distinct console error messages per run (mean [min, max]), the measure closest to the papers' manually deduplicated failures. 45
7.10 Post-hoc follow-up: branch coverage (%, mean of three one-hour runs) without and with custom clickables, all on the same hardware. 46
7.11 Round 2: branch coverage (%, mean [min, max] over five one-hour runs) and distinct console failures per run, beside the published numbers. 48
7.12 Post-hoc: branch coverage (%, mean [min, max] over five runs) of the bandit beside the same tester without a learner and the curiosity arm (round 2). 49
7.13 Every pre-registered question and its verdict. 50
7.14 The main arms as an ablation of structure and learning. Held-out: distinct faults of 24 and restricted mean T. Tuning: distinct faults of 41. External: mean branch coverage over the six applications, in round 1, with heuristic custom clickables (post-hoc) and in round 2 (listener-based clickables, v5). 50
7.15 The best arm per measure, across all evaluations. 52

A.1 Every arm used in the evaluations, by generation. 57
A.2 Hyperparameters. 58
A.3 Held-out evaluation: runs (of 5) that verified each fault. 58
A.4 Where each part of each result can be found. 59

Abbreviations

AC-DQN	–	Action-Conditioned Deep Q-Network
AUROC	–	Area Under the Receiver Operating Characteristic curve
CRUD	–	Create, Read, Update, Delete
DOM	–	Document Object Model
DQN	–	Deep Q-Network
GUI	–	Graphical User Interface
LLM	–	Large Language Model
MDP	–	Markov Decision Process
PER	–	Prioritised Experience Replay
RL	–	Reinforcement Learning
RMST	–	Restricted Mean Survival Time
SPA	–	Single-Page Application
UI	–	User Interface

List of symbols

s, s'	–	State before and after an action
a	–	Action (one browser interaction)
$\phi(a)$	–	Feature vector describing action a
$Q(s, \phi(a))$	–	Action-conditioned action value
γ	–	Discount factor
ϵ	–	Exploration rate
$\Phi(s)$	–	LLM-assessed task progress of state s, in $[0, 1]$
λ	–	Weight of the LLM reward term
B	–	Interaction budget of one run (2,000)
T	–	Interactions to the first verified fault ($T = B$ if none)
$\mathrm{Beta}(\alpha, \beta)$	–	Beta posterior of a bandit key
$N(s, a, s')$	–	Visit count of a page transition

Abstract

Functional bugs in web applications are rarely crashes. More often a total ignores a changed quantity, a validation rule holds on one path and not another, or a value is lost on reload. To find one, an automated tester has to reach the state through many interactions and then show that what it found is real. This thesis presents *Katalyze*, an autonomous exploratory tester for web applications with a verified-fault evaluation pipeline. It asks how much exploration structure, lightweight online learning and reliable fault verification each contribute. A fault counts only if it reproduces twice in fresh browser sessions, is absent from a control build without that fault, and survives delta-debugging minimisation. We claim no new learning algorithm; the contributions are the integrated system, the evaluation method and the empirical findings, several of which are negative.

The first generation is an action-conditioned dueling double deep Q-network with a reward from a local language model. In two pre-registered experiments, pretraining on five applications gave no measurable speed-up on a sixth (median difference 0 interactions, 95% interval $[-749, +290]$, too wide to rule a benefit in or out). The network did not reach the pre-registered bar for learning which action helps in which state (within-label AUROC 0.51). The language model failed as a reward and as a page labeller.

The second generation is a hybrid tester with explicit page abstraction, an archive of reached states with exact return (Go-Explore), test-design operators, and an optional learner (a Thompson-sampling bandit or count-based curiosity Q-learning). The evaluation used eight held-out applications in a pre-registered study of 160 runs and 32 clean-build controls. The hybrid arms verified 18 and 19 of 24 faults, against 13 for random exploration, with no false positive. The gap was largest on faults of moderate declared depth. All four comparisons of time to first fault were inconclusive, and no learning layer measurably improved on the structure alone.

On WebExplor's six subject applications, measured as the published work measures, the frozen tester averaged 44.3% branch coverage, against 55.5% for WebExplor and 64.2% for WebRLED. A post-hoc follow-up found the set of actionable elements to be an important limit. In a pre-registered second round with listener-based clickable detection and five repetitions, the curiosity arm averaged 53.6% (55.1% without the 20-branch Petclinic, against 49.6% and 60.0%), though it still triggered fewer console failures. For verifying functional faults, the evidence suggests that a tester's structure and action space matter more than the learning inside it.

Keywords: automated web testing, reinforcement learning, deep Q-network, Go-Explore,

Thompson sampling, test oracle, seeded faults, survival analysis.

Chapter 1

Introduction

1.1 Motivation

Shops, banks, booking systems and support desks all run on web applications now, and so do many internal tools. Their functional faults are rarely crashes. More often a page shows the wrong total after a quantity changes, accepts an input on one path that it rejects on another, or loses a value when the page is reloaded. Such faults sit behind sequences of interactions: a user must sign in, fill a form, reach a review step, go back and change something. A tester has to perform the right sequence and then notice that the result is wrong.

Writing scripted end-to-end tests for every such sequence is expensive, and the scripts cover only what their authors thought of. Automated exploratory testing instead drives a real browser through the application and searches for misbehaviour. The simplest explorer clicks at random. More capable explorers learn where to go, and reinforcement learning (RL) is a natural fit: the tester is an agent, the application is its environment, and reaching new or suspicious behaviour can be rewarded. Several RL web testers have been published, including WebExplor [2], WebQT and WebRLED [1].

Two problems limit these testers. The first is *where to go*. The decisive actions are often many steps into a workflow, the set of available actions changes on every page, and a novelty reward pays the agent for reaching a new page whether or not it tests anything there. The second is *what counts as a fault*. Published RL web testers report errors in the browser console as failures [1, 2]. That is an implicit oracle [3]: it cannot see a page that renders the wrong content without an error, and it cannot say whether a reported error is reproducible or matters.

1.2 Problem statement and research questions

The project began by asking whether deep reinforcement learning can learn to find functional bugs in web applications. The first generation of the tester answered part of that question negatively (Chapter 4), and the question that the thesis as a whole answers became broader:

> *How much do exploration structure, lightweight online learning and reliable fault verification each contribute to autonomous functional web testing?*

This breaks down into four research questions:

RQ1 Does a deep RL tester learn state-dependent behaviour, and does pretraining on other applications transfer to a new one?

RQ2 Is a small local LLM a useful source of reward or page labels for testing?

RQ3 Does a structured exploratory tester verify more functional faults than random exploration, and does adding online learning to it improve it further?

RQ4 How does the tester compare with published RL web testers on their own applications and measures, and what limits it there?

A fault is *verified* when it reproduces twice in fresh browser sessions, is absent from a control build that lacks that one fault, and survives delta-debugging minimisation [4]. The measures are kept separate throughout:

- the number of distinct faults verified, for breadth;
- the share of runs that verify at least one fault, for reliability;
- the interactions until the first verified fault, for speed, with runs that find nothing right-censored at the budget;
- false positives on clean builds, for credibility.

1.3 What a functional bug is

Fault and failure. This thesis follows the standard distinction. A *fault* is a defect in the code. A *failure* is what a user can observe when the faulty code runs: the application's behaviour departs from what it should do [3]. Testers observe failures; the faults behind them are what developers fix. The test applications here contain known, seeded faults, and the tester's job is to make each one produce an observable failure and prove it.

Definition 1.3.1 (Functional bug)**.** A *functional bug* in a web application is a fault whose failure is an observable deviation of the application's behaviour from its functional requirements. It must be:

1. **triggered** by a finite sequence of user interactions (clicks, typed values, selections, navigation) from a defined starting state;
2. **observable** through what the user can see or what the application keeps: page content, the page reached, data shown later, data that persists, or an error the browser reports;
3. **wrong** against a stated requirement: what the application's own contract says it must compute, accept, refuse, store or show.

In the terms of ISO/IEC 25010 [5], a functional bug is a failure of *functional correctness*: the product does not provide the correct results. It is not a failure of the non-functional characteristics, so the following are *not* functional bugs here:

- security vulnerabilities (out of scope, Section 1.6);

- performance;
- visual layout;
- usability;
- accessibility.

A page that renders slowly or looks wrong but computes, stores and shows the right things has no functional bug.

A taxonomy. Every seeded fault in this thesis belongs to one of six classes (Table 1.1). Each class corresponds to the assertions the oracle uses to decide that a failure occurred (Section 3.2), so the definition is operational: for every class, the thesis can state exactly what observation shows the bug.

Table 1.1: The classes of functional bug used in this thesis, with an example from the test applications and the oracle check that observes the failure.

Class	Definition	Example	Oracle check
Calculation error	A number the application shows differs from the correct computation over the user's inputs.	A basket total ignores a changed quantity.	`numeric_equals`, region arithmetic
Constraint bypass	An input the application must reject is accepted, or a state guarded by a precondition is reached without it.	An order is placed with an empty delivery address.	`reached_with_invalid_input`, `region_empty`
State corruption	Data shown later differs from what the user entered or what the application should have derived.	Express delivery chosen; the confirmation says standard.	`echoes_input`, `text_equals`
Persistence failure	Data the user saved is lost, reverted or not stored.	An edited record reverts after a reload.	`echoes_input` across pages, region stable across reload
Broken transition	An action leads to the wrong page or state, or to none.	"Next" returns to the first step of a wizard.	`url_matches`, `text_contains`
Crash-type	An interaction makes the application's own code throw an uncaught error or a request to the application fail.	Ticking a checklist item throws a script error.	`console_or_request_error`

Why the definition matters for the evaluation. The first five classes are *silent*: the page renders, nothing errors, and the result is simply wrong. An implicit oracle, one that counts console errors as published RL web testers do [1, 2], cannot see them. Only the last class is visible to such an oracle. For that reason the thesis measures *verified* functional bugs against a specification of each seeded fault. The same reason limits the external comparison: it uses the literature's measures, coverage and console failures, and so sees only part of what a functional tester is for.

1.4 Objectives

1. Build a browser environment and a deterministic, replay-verified oracle for seeded faults that makes false positives measurable and rare.
2. Build a deep RL tester and test, under pre-registration, whether pretraining on other applications transfers to a new one, and whether the network learns which action helps in which state.
3. Measure whether a small, local large language model (LLM) is a useful source of reward or page labels for testing.
4. Use those findings to design a tester whose exploration does not depend on what the deep network failed to learn, and evaluate it on held-out applications under pre-registration.
5. Compare the final tester with published RL web testers on their own subject applications.
6. Package the tester as a usable product: a command-line tool and a web interface that test a URL, a static site, a Dockerfile repository or a bundled application and produce a report with evidence.

1.5 Contributions

The tester built in this thesis, product and research system together, is called *Katalyze*. It is *an autonomous exploratory testing system with a verified-fault evaluation pipeline*. We do not claim a new RL algorithm. The deep Q-network, Thompson sampling, the Go-Explore archive and the test operators all build on existing ideas [6–8]. What the thesis adds is a system that integrates them, an evaluation methodology for RL-based functional web testing, and a set of empirical findings, several of them negative. In detail:

1. **A verified-fault oracle for web testing.** Each seeded fault has its own control build. A candidate counts only if it reproduces twice, does not occur on that control, and survives minimisation. The oracle produced zero false positives in every clean-build control run of every evaluation.
2. **A pre-registered transfer experiment for deep RL web testing**, using leave-one-application-out evaluation and censoring-aware statistics. It found no measurable benefit from pretraining, with an interval too wide to rule one in or out.
3. **A pre-registered diagnostic separating contextual learning from memorisation.** It uses a generated application family and probe states labelled by execution, and shows that the v1 network does not learn context.
4. **Two negative results for small local LLMs in testing**, each measured against ground truth: as a progress reward, and as a page and control labeller.

5. **A hybrid tester** combining page abstraction, an archive with exact return, test operators from standard test design, and a light online learner. It was evaluated on eight held-out applications under pre-registration, and verified the most distinct faults with zero false positives.

6. **Sixteen test applications with real backends and seeded faults**, each admitted by mechanical checks. The eight development applications run on PostgreSQL or MongoDB, with sign-in and crash-type faults.

7. **An external comparison with WebExplor and WebRLED** on their own applications and measures, in two rounds. The first is a negative result. A post-hoc diagnosis identifies action-space completeness, meaning which elements the tester can act on, as an important limit on coverage. A pre-registered second round with better detection came close to WebExplor's coverage, above it without the 20-branch Petclinic, and stayed below WebRLED's.

The scope of "autonomous". Autonomy has several dimensions, and the thesis demonstrates some of them and not others (Table 1.2).

Table 1.2: What "autonomous" means for Katalyze, and what the thesis demonstrates.

Dimension	Meaning	Demonstrated
Exploration	chooses its own browser actions	yes, within the registered action space
Test generation	builds interaction sequences, including deviations	yes, through exploration and test operators
Fault detection	notices potentially wrong behaviour	partly: seeded assertions, generic triggers, specification-free invariants
Fault verification	establishes that a failure is genuine and caused by a fault	yes, for seeded faults (replay, per-fault controls, minimisation)
Specification inference	works out what the application *should* do	not demonstrated
General bug discovery	reliably finds unknown bugs in arbitrary applications	not established by the evaluation

1.6 Scope

The project began with two agents: one for security testing and one for functional testing. The security agent was dropped early so that one agent could be built and evaluated end to end. **Security testing is out of scope**; this thesis is about functional testing. The applications are small to medium web applications with seeded faults. Claims about production sites or real-world fault rates are outside what the evidence supports, and Chapter 6 states the limits on generalisation.

1.7 Organisation of the thesis

Chapter 2 reviews RL web and GUI testing, the deep RL and exploration methods used here, LLM-derived rewards, test oracles and evaluation statistics. Chapter 3 describes the system around the tester: the browser environment, the action registry, the verified-fault oracle and the product layer. Chapter 4 presents the first-generation deep RL tester and the experiments that tested it. Chapter 5 presents the hybrid tester designed from those results, and its development rounds. Chapter 6 describes the test applications and the evaluation methodology. Chapter 7 reports the evaluations. Chapter 8 concludes.

Chapter 2

Background and Related Work

This chapter positions the work. Section 2.1 covers automated web testing and its oracles, Section 2.2 RL for web and GUI testing, Section 2.3 LLM-driven testing and LLM-derived rewards, Section 2.4 the deep RL and exploration methods the testers are built from, and Section 2.5 how such tools are evaluated. Section 2.6 states the gap this thesis addresses. Statements about what a paper did or found are taken from its abstract or full text; paragraphs headed *For this work* are our reasoning.

2.1 Automated web testing and test oracles

An automated web tester drives a browser through an application and decides, at each page, what to do next. Crawljax established the model-based approach for JavaScript-heavy applications: it infers a state-flow graph of user-interface states by firing events and comparing the resulting DOM. Model-based and search-based testers explore systematically, while random ("monkey") testers are cheap and, in GUI testing, a notoriously strong baseline.

Exploring is only half of testing. The other half is deciding whether what happened was wrong: the oracle problem. Barr et al. [3] classify oracles as specified (a specification says what is correct), derived (from artefacts such as earlier versions), implicit (generic failures such as crashes and exceptions) and absent (left to a human). RL web testers use implicit oracles, namely errors in the browser console [1, 2]. These are cheap and general, but blind to wrong content that renders without error.

A *seeded-fault oracle* is a specified oracle for a known set of faults. It provides ground truth, which evaluation methodology in fuzzing prefers: Klees et al. [9] recommend measuring against known bugs rather than heuristic proxies, and Magma inserts real bugs into real software with instrumentation so that bug-centric metrics do not depend on the tool. The cost is validity. Just et al. studied 357 real faults in five Java programs and found mutant detection significantly correlated with real-fault detection, but 17% of real faults were not coupled to any mutant. Seeded faults are a supported but incomplete proxy.

Once a failure is found, delta debugging [4] minimises the failing input while preserving the failure. Its original case study reduced 95 user actions that crashed a browser to 3; it is used in

the same way here, to shorten a reproduction trace.

2.2 Reinforcement learning for web and GUI testing

Web. WebExplor [2] is the reference point. It uses curiosity-driven RL to generate action sequences, with tabular Q-learning and a curiosity reward computed from a visit-count table over transitions, and builds an automaton online that sends the agent back to under-explored states. Training and testing are intertwined: the policy is learned on the application under test. Its failures are console errors, and the authors note that this oracle may miss UI bugs. WebQT changes the reward to encourage interaction like a human tester's and treats pages with the same function as one state, reporting higher code coverage on seven open-source applications. QExplore combines tabular Q-learning with a guided search and text input generation.

WebRLED [1] combines a deep Q-network with a grid-based action-value scheme, a learned action discriminator, and a curiosity reward that considers novelty both within an episode and over the global history. Liu et al. train a DQN or PPO agent to guide a crawler towards higher branch coverage. MARG runs several Q-learning agents that share Q-table data; its successor WebCQ moves to deep multi-agent RL and builds a vector for each candidate action, concatenated with the state vector, because "the available UI events vary across states". WebCQ is the closest architectural neighbour of this thesis's first tester.

A 2026 empirical study [10] compares model-based, RL-based and LLM-based web testers under six state abstractions. No single strategy excels on every dimension; RL-based approaches most often achieve the highest coverage; compact state abstractions suit RL; and code coverage is only weakly correlated with the ability to reveal failures.

Mobile. Q-testing uses a curiosity reward from a neural state-comparison module. ARES reports that deep RL achieves higher coverage and fault revelation than baselines including Q-testing. DinoDroid [11] is the clearest precedent for learning across applications: a deep Q-network learns a behaviour model from a set of existing apps and is used on new ones, evaluated by two-fold cross-validation over 64 apps (32 for training in each fold). Humanoid [12] learns from human interaction traces and reports higher coverage than six other generators, but its authors add that the learned model "was not the main reason" for the improvement.

For this work. The RL agent design is not new in itself. Count-based curiosity is the default reward in this line of work, per-action scoring over a variable action set is published, and pretraining on some applications to test others has been done on Android [11]. What differs here is the oracle (verified seeded faults instead of console errors), the outcome measure (time to the first verified fault instead of coverage), and the question asked of the learner (does it transfer, and does it use context).

2.3 Language models in testing and as reward

LLMs as testers. GPTDroid frames mobile GUI testing as a question-answering loop with an LLM. DroidAgent sets its own task goals and pursues them, reporting 61% activity coverage against 51% for earlier techniques on 15 apps. AXNav executes natural-language accessibility tests, and VETL uses a vision-language model for text inputs and element selection on the web, with exploration guided by a multi-armed bandit. The 2026 study tempers this line: its LLM-based web tester completed three to four times fewer actions in the same time budget, because every decision invokes the model, and it repeated failed or invalid actions [10]. Web-navigation benchmarks show how hard it is to act reliably on unseen sites: in WebArena the best GPT-4 agent reached 14.41% task success against 78.24% for humans, and on Mind2Web step success fell from 52.0% on unseen tasks to 38.9% on unseen websites.

LLMs as reward. Kwon et al. prompt an LLM as a proxy reward function. ELLM rewards an agent for achieving goals an LLM suggests, motivated by the observation that novelty bonuses help little where most novelty is irrelevant. Motif distils LLM preferences into an intrinsic reward; Eureka and Text2Reward have the LLM write reward code. Vision-language models have served as success detectors and zero-shot reward models, whose failures trace to the model's capability limits. Klissarov et al. find that LLMs are better used to build reward models than to act directly.

Shaping. Ng, Harada and Russell prove that adding a reward equal to the discounted difference of a potential function over successive states, $\gamma\Phi(s') - \Phi(s)$, leaves the optimal policy unchanged. Wiewiora shows the equivalence to initialising Q-values from the potential, and Devlin and Kudenko extend the guarantee to potentials that change during learning. LLM-derived potentials already exist: Lin et al. use score differences from an LLM-trained state scorer as a potential, and report that with weaker models a direct reward outperformed the potential form. Müller and Kudenko learn the potential from preferences given by small vision-language models.

For this work. Policy invariance concerns the optimal policy. It says nothing about behaviour within a finite budget, which is what a tester is measured on. The evidence for LLM rewards comes from games, robotics and synthetic web tasks; none of the retrieved works evaluates an LLM-derived reward for testing. A small, local judge is on the weak side of the capability evidence.

2.4 Deep reinforcement learning and exploration

Value-based deep RL. Q-learning learns the value $Q(s, a)$ of taking action a in state s and acting well afterwards, by bootstrapping from the next state's value. DQN [6] approximates Q with a neural network. Double DQN [13] reduces DQN's overestimation by decoupling

action selection from evaluation. Dueling networks separate state value from action advantage and give better estimates when many actions have similar values, which fits pages with many near-equivalent links. Prioritised replay replays informative transitions more often, and Rainbow combines six such extensions, including multi-step targets. These components were validated mainly on Atari, and Henderson et al. show how variance makes deep RL improvements hard to judge.

Variable action sets. A web page offers a different set of actions on every page. Dulac-Arnold et al. embed actions in a continuous space so that a policy can generalise over them. The deep reinforcement relevance network [14] embeds state and text action separately and combines them to approximate Q; this is the direct ancestor of the action-conditioned network $Q(s, \phi(a))$ used here. Jain et al. treat generalisation to unseen actions as its own problem, needing dedicated training objectives. Sentence embeddings from compact distilled encoders supply action-label features.

Exploration. Count-based exploration rewards rarely visited states: pseudo-counts generalise counting to large state spaces, and hashing-based counts work with simple hash functions, provided the hash has the right granularity. That is the same sensitivity to state abstraction that the web-testing study measured [10]. Random network distillation derives a novelty bonus from prediction error. Go-Explore [8] attributes poor exploration to two failures: forgetting how to reach promising states, and not returning to a state before exploring from it. It remedies both by keeping an archive of visited states and returning to them first.

Bandits. A multi-armed bandit chooses repeatedly among options with unknown payoff. Thompson sampling [7] keeps a posterior over each option's payoff, samples from it, and picks the best sample, which balances trying uncertain options against exploiting good ones. With a Beta posterior over a success probability, it needs only two counts per option, so it can learn within the few dozen decisions of a single test run.

Generalisation. Cobbe et al. find that agents overfit to surprisingly large training sets, and Procgen shows that diverse training distributions are essential. The survey by Kirk et al. treats the number of training contexts as a core property of an evaluation protocol and suggests fast online adaptation as a direction. With five training applications per fold, the literature predicts weak transfer.

2.5 Evaluating testing tools

Arcuri and Briand found that software-engineering studies of randomised algorithms often did not account properly for randomness, and argue for enough runs and rigorous statistical tests. Klees et al. [9] examined 32 fuzzing papers and found problems in every evaluation, recommending multiple trials, statistical tests, ground truth and a diverse benchmark; a

follow-up over 150 papers found the guidelines still widely ignored. In deep RL, Agarwal et al. recommend stratified-bootstrap interval estimates over point estimates.

When a tool may not find a bug within the time allowed, time to bug is a right-censored outcome. Survival analysis handles this: the Kaplan–Meier estimator estimates the probability of not yet having found the bug at each time, and the restricted mean survival time (RMST) averages the time to event up to a horizon. Magma applies Kaplan–Meier to time to bug, and Herrera et al. report RMST with confidence intervals and compare with the log-rank test. None of the GUI-testing papers reviewed uses censoring-aware analysis: WebExplor averages 15 thirty-minute runs and applies a Mann–Whitney U test [2].

2.6 Research gap

Within the literature reviewed:

1. **Ground-truth evaluation of RL web testers.** Web RL testers are scored on coverage and console errors [1, 2]. No retrieved work evaluates a web-testing policy, or its transfer to held-out applications, against a deterministic oracle for seeded faults.

2. **An LLM-derived reward in testing.** LLM rewards and potentials exist for games and control, and LLMs in GUI testing act as the policy. Using an LLM only to shape a cheap learned policy is untested.

3. **Censoring-aware, fault-centric evaluation in GUI testing.** Time to the first verified fault with right-censoring imports fuzzing's method into a field that reports averaged coverage, which is weakly related to failure discovery [10].

4. **Whether learning is what helps.** Humanoid's authors found their learned model was not the main cause of their gain [12]. Separating the contribution of learning from that of structure needs ablations against strong non-learning baselines.

The contribution of this thesis is the combination and the evaluation discipline. The agent architecture, the curiosity reward, the archive and the LLM potential each have direct precedents and are not claimed as novel.

Chapter 3

System Overview and the Verified-Fault Oracle

This chapter describes the parts shared by both generations of the tester: the browser environment and its action space (Section 3.1), the oracle that decides what is a fault (Section 3.2), and the product layer that turns an application into a test run and a report (Section 3.3). Figure 3.1 shows how they fit together. The explorer in the middle is the part that differs between v1 (Chapter 4) and v2 (Chapter 5).




Figure 3.1: The system around the explorer. Only the explorer differs between v1 and v2.

3.1 The browser environment

The environment exposes a live application through Playwright and headless Chromium. Each *episode* starts in a fresh browser context from the application's entry page, so cookies and local storage do not leak between episodes. For applications behind a login, a scripted sign-in macro runs at the start of every episode; it is outside the agent's decisions but inside the interaction budget. Server state is reset between runs, and for the database-backed suite applications each browser context gets its own data partition (Chapter 6).

After every action the environment waits for the page to settle. It watches the DOM with a mutation observer and treats the page as settled after a quiet period, rather than waiting for

the network to go idle, which applications that poll or hold a websocket never satisfy.

3.1.1 Action registry

At each step the registry scans the page and builds the set of available actions, at most 100. It combines page-independent actions (no-op, scroll, resize the viewport, browser back, forward and refresh) with actions derived from the page's interactive elements:

- **click** on links, buttons and toggles, and **rapid click** (a double submit) on buttons;
- **type** into text fields, with one value from each of five categories: a valid typical value, the boundary minimum, the boundary maximum, an empty string, and a value of the wrong type;
- **select** an option of a dropdown;
- optionally, **custom clickables**: elements made interactive by ARIA roles, click handlers, tab index or a pointer cursor, which plain HTML scanning misses.

When a page has more candidates than slots, the budget is filled in priority order: fixed actions, then clicks (needed to progress any flow), then valid typed values (so forms can be submitted), then selects and rapid clicks, then the boundary and invalid variants. Elements visible in the viewport are allocated before those below the fold. Actions are identified by stable selectors (an element's id or name, else a structural path), so the same control keeps its identity across visits.

3.1.2 Deterministic triggers

On every step the environment records generic failure signals: console errors, uncaught page errors, unexpected HTTP failures (4xx and 5xx responses to the application's own requests), a page that never settles, and broken navigation (a navigational click that leaves the URL unchanged). A link back to the page the agent is already on is not navigational, so it does not count as broken. These triggers are the implicit oracle that published RL web testers use. Here they feed the reward and the crash-type faults; on their own they are never reported as verified findings.

3.2 The verified-fault oracle

3.2.1 Seeded faults and assertions

Every evaluation application is written with a list of *seeded faults*. Each fault is a literal source patch: an anchor string that must occur exactly once in a file, and its replacement. Applying every patch to the clean source gives the *faulty* build that agents test. For each fault F there is also a *control build*: the faulty build without F's patch.

Each fault declares how it shows itself, as an assertion over the recorded trajectory. The assertion language is deliberately closed, with eight kinds:

- `text_equals`, `text_contains`, `text_absent`: a named page region must equal, contain or not contain a literal;
- `echoes_input`: a value the agent typed earlier must appear on a later page (the core check for corrupted state);
- `numeric_equals`: a number on the page must equal an arithmetic expression over recorded inputs (for example, a total over quantities);
- `url_matches`: the step's URL must match a pattern (for broken transitions);
- `reached_with_invalid_input`: a guarded state was reached although the input that guards it was invalid;
- `region_empty`: a region the application's contract says must carry a value is empty.

Regions are named in the application's manifest, so an assertion never contains a CSS selector. Assertions are evaluated on the recorded pages without a browser, so checking is a pure, reproducible function of the record. The development suite added four extension kinds: a region stable across reload, an input absent after submission, arithmetic between regions, and `console_or_request_error` for crash-type faults (Section 3.2.4).

3.2.2 From candidate to verified finding

A violation of a fault's assertion during exploration is only a *candidate*. Verification has three steps:

1. **Replay.** The trajectory is replayed twice in fresh browser sessions against the faulty build. The violation must recur both times.

2. **Per-fault control.** The same trajectory is replayed against the control build without F. If the violation still occurs, it is not caused by F (another fault or the application's normal behaviour produces it), and the candidate is rejected.

3. **Minimisation.** Delta debugging [4] removes steps while the violation still reproduces, giving a short reproduction.

Only candidates that pass all three are *verified findings*. The rule makes false positives measurable: a run on the *clean* build has no seeded faults, so any verified finding there would be a false positive. Every evaluation in this thesis includes such clean-build control runs, and none produced a verified finding. Zero observed false positives is not a zero false-positive rate. The held-out evaluation, for example, had 32 clean-build controls; with none positive, a one-sided 95% upper bound on the per-run rate is about $3/32 \approx 9\%$ (the rule of three).

3.2.3 What the oracle solves, and what it does not

The *oracle problem* is deciding whether observed behaviour is correct [3]. For the seeded faults, Katalyze does not solve it. Each seeded fault comes with an assertion written by whoever

seeded it, and verification establishes that a failure of that assertion is reproducible and caused by that fault. The oracle makes reported findings *credible*. It does not let the tester tell right from wrong in an application it has no specification for. Three consequences follow.

1. The evaluations measure how well a tester drives an application into a state where a known assertion fails. They do not measure whether it would recognise a bug that nobody wrote an assertion for.
2. On applications without seeded faults, which is what the product mostly sees (Section 3.3), findings can come only from generic triggers and the specification-free invariants below. Generic triggers are script errors, failed requests, error pages and navigation that does nothing. Both kinds are weaker than a seeded assertion, and the invariants raised false alarms (Section 7.1).
3. A per-fault control build exists only because the fault was seeded. For a real bug there is no control, and verification reduces to replay and minimisation.

3.2.4 Crash-type faults

The external benchmark (Chapter 7) counts failures as console and request errors, which seeded assertions over page content do not capture. A subset of the development applications therefore also seeds *crash-type faults*: patches that make a specific interaction raise an uncaught script error or a failing request. Their assertion, `console_or_request_error`, matches the error's signature. Verification is the same: the error must recur on replay and be absent from that fault's control build, so a generic console error elsewhere in the application is not attributed to the fault.

3.2.5 Specification-free invariants

Seeded assertions verify only what was seeded. For arbitrary applications, the v2 tester also checks three invariants that need no specification: a value the user entered must survive a reload; it must not come back altered; and the same field on the same page must not be rejected once and accepted another time. Their candidates are replayed twice and attributed to seeded faults through the control builds. They are reported separately and never counted as verified seeded faults.

3.3 The product layer

Intake and restricted execution sandbox. An uploaded repository must contain a Dockerfile. Its build definition is parsed and passed through a security policy gate before anything runs. The gate refuses privileged containers, host mounts, host networking and Compose features that would merge in a second, unvalidated file. The container then runs with all capabilities dropped, a read-only root filesystem, no new privileges, CPU, memory and process limits, and an internal-only network. This is a *restricted* execution sandbox: it narrows what uploaded

code can do, but it has not been tested against deliberately malicious code. The product is meant for code its user would be willing to run locally.

Test sessions and reports. A test session runs the chosen agent within an interaction budget, verifies candidates as above, and writes a report with three parts: verified findings with minimal reproductions; unverified candidates; and, separately, any observations from the language model, marked unverified. Page bodies and frames are stored content-addressed as the run proceeds, so every finding can be traced to what produced it. Reports are available in HTML, Markdown and JSON.

Interfaces. A command-line tool tests a URL, a static site, a Dockerfile repository or a bundled application. A web interface (FastAPI with server-rendered templates) offers the same as a guided flow. The user picks a demo application, enters a URL or uploads an archive; chooses an agent (the RL agents or the random baseline) and a budget; watches a live event stream of the run; and opens or downloads the report. A research page shows every evaluation and development round, read live from the result files. The interface binds to the local machine by default, because it builds and runs uploaded code.

Figures 3.2–3.4 show the interface during the acceptance run on Helpline described below.




Figure 3.2: The web interface: starting a test. A bundled demo application, a live URL, or an uploaded static site or repository.




Figure 3.3: A finished run (Helpline, 600 interactions): status, progress, the pipeline stages and the live event stream of the tester's actions.




Figure 3.4: The report of the same run. Each verified finding has its minimised reproduction (here 2 steps, minimised from 15) and the page captured when it was observed.

End-to-end acceptance. Table 3.1 lists one end-to-end run of the final product for each kind of target. Each run was started through the web interface's own API, ran `hybrid_final`,

and produced HTML, Markdown and JSON reports. For the bundled applications the seeded faults are known, so their findings can be checked. The other targets have no ground truth. Their findings are observations that reproduced and were minimised; nobody has confirmed them as bugs.

Table 3.1: End-to-end acceptance runs of the final product (24 October 2026). "Findings" are the verified findings in the report. For targets without seeded faults they come from generic triggers.

Target kind	Example	Budget	Time	Findings
Bundled app, full stack in Docker	Helpline	600	7 min	4: seeded HELP-2, HELP-3 and HELP-4, and one reproduced "Move down" control that does nothing
Bundled app, full stack in Docker	Stackroom	600	5 min	2: seeded STK-3, and one reproduced script error
Bundled app, full stack in Docker	Orbit	600	5 min	1: seeded ORB-3
Bundled benchmark app	Fernbrook Outfitters	1,000	4 min	1: seeded SHOP-01
Static site, bundled demo	Harbor & Pine	300	5 min	4 (curiosity arm): missing pages, a broken form, a script error
Static site, zip upload	Harbor & Pine	200	3 min	4: the same kinds
Dockerfile repository	Northwind static site	200	3 min	2: a missing page and a script error
Public URL	TodoMVC (demo.-playwright.dev)	200	3 min	0 (before the fix below: 3 false reports on links to other sites)

The acceptance runs exposed three product defects, all since fixed. The first was fixed before any run in the table. The other two were fixed only before the TodoMVC run, which was made last; no earlier run in the table reported a finding on a link to another site.

- A form that submits and returns to the same address with updated content (Helpline's post-redirect-get forms) was reported as navigation that does nothing. Such a report now requires the page text to stay the same as well as the address.
- Links to other websites, which the tester refuses to follow, were reported the same way. They are now excluded.
- One slow page load at the start of an episode ended the whole session on a public site. The opening load is now retried up to three times.

Chapter 4

A Deep Reinforcement Learning Tester (v1)

The first-generation tester (v1) is a deep RL agent. This chapter formulates the testing problem as an MDP (Section 4.1), describes the agent (Section 4.2) and its reward, including the LLM progress term (Section 4.3), and reports the three studies that tested it: a pre-registered transfer experiment (Section 4.4), a pre-registered contextual diagnostic (Section 4.5), and checks of the LLM components (Section 4.6). Section 4.7 draws the conclusions that shaped v2.

4.1 Testing as a Markov decision process

An *episode* is a walk of at most 40 actions from the application's entry page. A *run* (or hunt) is a sequence of episodes on one application until a budget of $B = 2{,}000$ browser interactions is spent. The state s_t is a summary of the episode so far and the current page; the actions are those the registry offers on the current page (Section 3.1), so the action set changes at every step; and the reward is described in Section 4.3. The agent never sees the seeded faults or the oracle's verdicts: learning from them would leak the answer key into the policy.

State. The state vector has 25 numbers: the episode's history (step, distinct pages, recent repetitions), the page's composition (counts of links, buttons, fields, forms, by kind), how much of the current form is filled, and the history of the LLM's progress judgments. It deliberately carries no page text, heading or URL.

Action features. Each candidate action a is described by a 95-dimensional vector $\phi(a)$: its type; a sentence embedding of its label (MiniLM, reduced by PCA); its role inferred from markup (submit, navigate, edit, remove and so on); flags such as being in the viewport or inside a form; the category of value to type; and how often it has been taken in the episode.

4.2 The agent: an action-conditioned dueling double DQN

A fixed output head, one unit per action slot, cannot work here: slot k means a different control on every page. The agent instead scores each (state, action) pair with one shared network, $Q(s, \phi(a))$, following the relevance network of He et al. [14]. The state is encoded by a 64-unit layer and each action by a 96-unit layer; a 128-unit scorer combines them into an advantage, and a separate state-value head makes the network dueling. Because one scorer is shared by every action, the network is permutation-equivariant over the action set and accepts any number of actions.

Training uses Double DQN targets [13], 3-step returns with $\gamma = 0.95$, and prioritised replay ($\alpha = 0.6$, $\beta_0 = 0.4$, a buffer of 30,000 transitions, batches of 64, learning rate 3×10^{-4}, target update every 200 steps).

Search-guided exploration. With uniform ϵ-greedy exploration, pretraining never reached the order-confirmation pages of the development applications, so the reward for completing a task never paid. Exploratory actions are therefore taken, with probability 0.75, from a fixed search priority (the same linear score over the action features that the `search_S` baseline uses), and otherwise uniformly at random. On the held-out application every learning arm uses one ϵ schedule (0.50 decaying to 0.05 over half the budget), so arms do not differ in how much search they receive.

Online adaptation. For transfer, the pretrained network is kept and a small residual head, initialised to zero, is added and trained on the new application. The pretrained agent therefore starts exactly where pretraining left it and adapts from there.

Bandit variant. The same network with $\gamma = 0$ (no bootstrapping) is a contextual bandit. It tests whether multi-step credit assignment adds anything.

4.3 Reward

The reward has an environment part and an optional LLM part:

$$r_t = r_t^{\text{env}} + \lambda \, r_t^{\text{LLM}}. \tag{4.1}$$

Environment terms. A small step cost; a novelty bonus that decays with the visit count of the abstracted state; a bonus for revealing new controls, capped at one control per step so that a single-page application does not dominate the scale; a repetition penalty; and one-time bonuses for the deterministic triggers (console error, failed request, broken navigation). The total is clipped to $[-6, 6]$.

The LLM progress term. A local LLM (`qwen2.5:7b-instruct`, temperature 0) reads a text rendering of each newly reached page and rates how far it is through a task, as a potential $\Phi(s) \in [0, 1]$. Judgments are cached by page content, so each distinct page is judged once. The first design was potential-based shaping, $\lambda(\gamma\Phi(s') - \Phi(s))$. It preserves the optimal policy, and that is why it failed: once novelty is exhausted, nothing in the optimal policy reaches outcome pages, and an agent pretrained on one application never reached its confirmation page in 1,500 steps. The term actually used is an *episodic progress record*,

$$r_t^{\mathrm{LLM}} = \max\Big(0,\ \Phi(s_{t+1}) - \max_{k \le t} \Phi(s_k)\Big), \tag{4.2}$$

which pays only for a new maximum within the episode, so revisiting or looping earns nothing and the total per episode is at most 1. A sparse *outcome bonus* of 3 pays the first time in an episode that a page the model places in the "outcome displayed" stage is reached, because the model rated any form page highly and completing a task added almost nothing. Neither term sees the seeded faults.

4.4 Experiment 1: does pretraining transfer?

Question. Does pretraining on five applications make verified-fault discovery on a held-out sixth faster than learning from scratch? The comparison is against information-matched non-learning baselines, with and without the LLM reward.

Design. The design was pre-registered: hypotheses, arms, analysis code and decision rule were committed before any result existed. It is leave-one-application-out over the six benchmark applications (Chapter 6); four applications were never used during development (the *pristine* folds). Ten arms ran (Table 4.1): uniform random; two fixed search heuristics (`search_A0`, hand-weighted priority; `search_S`, the feature-based score that guides exploration); the DQN from scratch and pretrained, each with and without the LLM reward; the pretrained DQN frozen (zero-shot); and the bandit from scratch and pretrained. Pretraining used 1,500 steps per training application. Each hunt had $B = 2{,}000$ interactions, with seeds 0–2 and a mechanical top-up rule. The outcome was T, interactions to the first verified fault, right-censored at B. The primary statistic was the per-fold paired difference in restricted mean T, summarised by its median across folds with a fold-level bootstrap interval; the stratified log-rank test was secondary.

Execution. There were 291 jobs and 0 failures. The LLM arms ran on a local RTX 4050 GPU and the other arms on four AWS spot instances (about US$1.6). The analysis was exactly the pre-registered one.

Table 4.1: Experiment 1: discovery per arm over all folds (runs of 2,000 interactions).

Arm	Runs	Found a fault	Rate	Restricted mean T
`dqn_pretrained_nollm`	18	7	0.39	1,402
`bandit_pretrained`	24	10	0.42	1,483
`dqn_pretrained`	27	9	0.33	1,520
`dqn_scratch`	27	9	0.33	1,610
`dqn_zeroshot`	18	4	0.22	1,664
`bandit_scratch`	24	5	0.21	1,727
`dqn_scratch_nollm`	18	5	0.28	1,748
`search_S`	18	3	0.17	1,844
`random`	18	2	0.11	1,947
`search_A0`	18	1	0.06	1,953

Table 4.2: Experiment 1: pre-registered comparisons (negative Δ = faster).

Comparison	Median Δ	95% interval	Log-rank p
`dqn_pretrained` − `dqn_scratch` (primary)	0	$[-749, +290]$	0.527
`bandit_pretrained` − `bandit_scratch`	−280	$[-732, +188]$	0.086
`dqn_pretrained` − `search_S`	−169	$[-884, 0]$	0.087
`dqn_pretrained` − `search_A0`	−170	$[-1{,}212, 0]$	0.006
`dqn_pretrained` − `random`	−151	$[-1{,}212, 0]$	0.022
LLM reward on − off (pretrained DQN)	+17	$[-122, +378]$	0.754
Adaptation on − off	−84	$[-430, 0]$	0.534

Results. Pretraining gave no measurable benefit. The primary comparison has a median difference of 0 interactions, with an interval reaching far on both sides; on the four pristine folds it was −310 ($p = 0.66$). This is an absence of evidence for transfer, not evidence that transfer does not occur: the interval is compatible with a large benefit and with a large cost. The LLM reward made no detectable difference. Learned arms found a fault in more runs than search or random (0.33–0.42 against 0.06–0.17), but their fold-level intervals reach zero and the effect rests largely on one development fold. Faults 9–16 contextual steps deep, on two applications, were never found by any arm. The oracle produced no verified finding on any clean build.

A post-hoc description of the hunts showed that about 84% of each learned arm's actions were the network's own greedy choice, so the exploration guide was not masking the network. The learned Q drove behaviour, and pretrained and scratch DQN still found faults in the same share of runs (9 of 27 each). Whatever helped was learned inside the application under test. This matches the literature's prediction for five training applications per fold [11].

4.5 Experiment 2: context or memorisation?

Question. Does the network rank an action by the state it is in, or has it memorised actions, words or layouts?

Design. This experiment was also pre-registered, with separate applications, runs and report. A seeded generator produced 12 variants of one request workflow. They vary the vocabulary (training words; synonyms, unseen words and pseudo-words held out with zero token overlap), the structure (training layouts; tabs, a modal and reordered steps held out) and add a decoy control. Four agent arms differ only in which inputs the network sees: the full agent; a label-blind agent; a lexical-only agent; and an action-only agent that never sees the state. Probe sets of states, with each action's effect labelled by actually executing it, were fixed before any arm ran. There were 228 jobs (12 pretrainings, 216 hunts) and 0 failures.

Table 4.3: Experiment 2: pre-registered verdicts for the full agent.

Hypothesis	Deciding numbers	Verdict
H-ctx: state–action contextual learning	within-label AUROC 0.51 $[0.44, 0.59]$; rule ≥ 0.70	**not supported**
H-act: action memorisation	decoy probe rate 0.31 $[0.00, 0.91]$	inconclusive
H-lex: lexical memorisation	top-1 ratio on unseen vocabulary 0.88 $[0.35, 1.18]$	inconclusive
H-app: application memorisation	top-1 ratio on new structures 0.63 $[0.44, 0.88]$	inconclusive

Results. Contextual learning was not supported. Within a label, the network's ranking of an action barely depends on whether that action helps in the current state (AUROC 0.51, chance level), and only 7% of the variance of Q came from the label $\times$ state interaction: the state moves every action's value together and almost never reorders them. The agent does rank useful actions above chance overall (top-1 accuracy 0.56, against 0.18 for random); this held up under vocabulary changes but not under every layout change (tabs 0.35, modal 0.58). On the eight held-out variants, the arms that see the state found the fault in 19–20 of 24 hunts, against 2 of 24 for search and random, and the label-blind arm did as well as the full one. The memorisation hypotheses stayed inconclusive with three seeds: on the decoy, one seed nearly always took it and the other two never did.

4.6 Checks of the LLM components

Is the progress reward rewarding the right thing? This post-hoc, descriptive check asked whether the LLM's progress score separates pages where a fault becomes observable from pages a random walk visits. On the two development applications, where the prompt was

tuned, it separated them perfectly (AUROC 1.00). On the four pristine applications it did not (0.73, 0.52, 0.47, 0.38). The score rewards the "happy path", while many faults need deviations (invalid input, an edit after review), and most of what it paid duplicated the novelty bonus. This agrees with the warning that small LLM judges make noisy reward models.

Can the LLM label pages reliably? For v2, an LLM labeller was to classify page kinds and control roles once per page. It had to pass gates fixed in advance: page-kind accuracy ≥ 0.85 and control-role accuracy ≥ 0.80.

Table 4.4: LLM labeller accuracy against ground truth (gates 0.85 / 0.80).

Test	Page kind	Control role	Gate
Stage 0, generated variants	0.68	0.78	failed
Revised labeller, 69 fresh pages	0.61	0.75	failed
Revised labeller, on its own revision data	0.93	0.83	(would have passed)

Both gates failed. The last row shows why the re-test had to use fresh pages: judged on the data it was revised from, the labeller would have been adopted.

4.7 What v1 taught

Five claims about the deep Q-network are easy to conflate, and Table 4.5 keeps them apart.

Table 4.5: What the v1 experiments establish about the DQN.

Claim	Evidence	Status
The DQN was implemented and trained	pretraining on five applications per fold; 291 jobs in Experiment 1 with no failures	established
Its learned values chose the actions	about 84% of each learned arm's actions were the network's greedy choice	established
It learned which action helps in which state	within-label AUROC 0.51, against a pre-registered bar of 0.70; 7% of Q variance from label $\times$ state	not supported
Pretraining transferred to a new application	median difference 0 interactions, $[-749, +290]$	not established
Learning improved discovery over non-learning arms	learned arms found a fault in more runs (0.33–0.42 against 0.06–0.17), but the intervals reach zero and the effect rests on one fold; held-out H4 inconclusive	suggested only

Table 4.6: Findings from v1 and the design consequences for v2.

Finding	Consequence for v2
No measurable transfer from pretraining; learning inside the application may have helped (suggested only)	keep learning, but online, inside each application
No state–action contextual learning	make the state explicit: page kind, task stage, form status
The LLM reward is misaligned with faults; the labeller failed its gates	remove the LLM from the reward and from the decision path; label pages from markup
Deep faults were never reached	explore by remembering states and returning to them (Go-Explore)
Faults need deviations from the happy path	deviate deliberately, with test-design operators

Chapter 5

The Hybrid Tester (v2)

The second-generation tester (v2) is built from the conclusions of Chapter 4. Instead of hoping a network learns the page state, it computes that state explicitly. It remembers the states it has reached and returns to them by exact replay, so getting deep into a workflow does not depend on luck. It leaves the happy path on purpose, using operators from standard test design. Learning is kept light and online, inside the application under test. Figure 5.1 shows the loop. Sections 5.1–5.4 describe its parts, Section 5.5 the options added for the final tuning round, and Section 5.6 the development rounds that shaped it.




Figure 5.1: The hybrid tester's loop. Every replayed action counts towards the budget.

5.1 Page abstraction

Each page becomes a small symbolic *cell*, computed deterministically from the markup:

- the page kind, from a closed vocabulary (home, list, detail, form, review, outcome, info, login, error, other);
- the URL path with identifiers replaced (`/orders/{n}`);
- the main heading;
- whether the form on the page is empty, partly filled or full;
- whether an error or alert is shown;
- whether the page offers a submit action.

Controls get roles from markup cues: submit, edit, remove, add, back, navigate. Two rules came from development evidence. Links and buttons in the page's navigation, header or footer are never "submit": they start a new journey rather than complete the current one. And role cues match word prefixes, so "Saving" and "Save" share a role.

Experiment 2 showed that the network does not learn these distinctions by itself, and the literature finds that the choice of state abstraction drives results in both web testing [10] and count-based exploration. The granularity was tuned on development applications only: exact field combinations gave 150–225 cells on one application, so form state was reduced to empty, partial and full, which gave about 20.

5.2 Archive with exact return

The tester keeps an archive of every cell it has reached, with the shortest known action sequence to it, its visit count, and the operators already tried there. At the start of an excursion it chooses a cell with probability proportional to a weight

$$w(c) = \frac{1}{\sqrt{1+n_c}} \cdot \left(1 + \frac{\min(u_c, 10)}{5}\right) \cdot \frac{1}{1+2f_c} \cdot \rho_c \cdot \left(1 + \beta_d \frac{\min(d_c, 30)}{30}\right), \tag{5.1}$$

where n_c is the number of visits, u_c the number of untried operators, f_c the number of failed returns, ρ_c is 1 if enough of the episode remains after reaching the cell and 0.1 otherwise, d_c the cell's depth, and $\beta_d = 2$ a preference for depth (faults sit many steps into a workflow). The tester then *returns* to the cell by replaying its path exactly, and acts from there. This is Go-Explore [8]: poor exploration comes from forgetting how to get back to promising states, and the deep, unfound faults of Experiment 1 were exactly that case.

Paths are pruned of steps that change neither the page nor the cell, and every replayed action counts towards the interaction budget, so returning is not a hidden advantage. One replay bug, in which pruning removed steps that raised a notice the next step depended on, was found on a development application and fixed; failed returns fell from 6 of 14 to 0 of 28.

5.3 Test operators

From a cell the tester applies a *test operator*, a short procedure from standard test design:

- `complete_step`: fill the form validly and submit (the path deeper);
- `choose_option`: take each option of a dropdown in turn (equivalence classes);
- `invalid_input`: enter an empty value, a value of the wrong type, or a boundary minimum or maximum (boundary-value analysis);
- `edit_after_review`: reach a review step, go back and change an earlier answer (state-transition testing);
- `back_and_resume`, `reload_and_resume`: interrupt a flow and continue;
- `double_submit`: submit twice in quick succession;

- `collection_churn`: add and remove items in a collection;
- `combine` (development option, not adopted): two deviations on one form, such as a dropdown option together with an invalid field (pairwise testing);
- `browse_list` (option, Section 5.5): sort or filter a list, page forward, and open an item on a later page.

Each operator then *follows through*: it continues the task to submission, for up to four submissions, because a deviation usually shows its effect only on a later page. When a page offers several submit actions (for example, "Update bag" and "Go to checkout"), operators take them in turn on repeat visits. The operators come from test-design techniques; none was derived from any application's faults. They give the tester a way off the happy path, which the LLM progress reward never managed.

5.4 The decision layer

The decision layer chooses which cell to return to and which operator to apply on which target. Three variants exist; each is an arm.

No learner (`hybrid_nolearn`). Cells by the archive weight; at a cell, untried (operator, target) pairs first, in random order. This is the non-learning reference.

Thompson-sampling bandit (`hybrid_bandit`). A Bayesian bandit learns, online inside the application, which operator pays off on which kind of target. Its keys are semantic and back off from specific to general:

$$(\text{page kind}, \text{operator}, \text{target type}) \;\rightarrow\; (\text{operator}, \text{target type}) \;\rightarrow\; (\text{operator}).$$

Each key has a Beta(α, β) posterior over the probability that the operator produces an interesting outcome. A specific key's prior is the more general keys' evidence, discounted by 0.3, so a new combination starts from what similar ones did. At each decision the tester samples from every candidate's posterior and takes the best sample [7]. The reward is the tester's own observation, never the seeded-fault oracle: an alert shown, new cells reached, or an invariant candidate. A bandit was chosen over a deep network for three reasons: Experiment 1 found no gain from bootstrapped multi-step learning; a 2,000-interaction run makes only about 50–135 decisions, enough for a bandit over a few dozen interpretable keys but far too few for a network; and keys based on page kinds, not application text, can carry across applications.

Curiosity Q-learning (`hybrid_curiosity`). This variant adopts the literature's design for the free exploration steps between operators. Following WebExplor [2] and WebRLED [1], a

tabular Q-learner over cells is rewarded on every step for curiosity:

$$r = \frac{1}{\sqrt{N(c,a,c')}} + 0.5 \cdot \mathbb{1}[c' \text{ not yet seen this episode}], \tag{5.2}$$

where $N(c, a, c')$ counts the transition. It learns with $\alpha = 0.5$, $\gamma = 0.9$ and $\epsilon = 0.1$, with untried actions initialised optimistically at $R_{\max}/(1-\gamma)$, so that an action that changes nothing cannot outrank untried ones by bootstrapping off itself. Being off-policy, it learns from every transition, about 2,000 updates per run, against about 135 outcomes for the bandit. A standalone tester built only from these components (no operators, no bandit) was also run, as `dev_curiosity_rl`.

5.5 Options for the final tuning round

After the held-out evaluation (Chapter 7) and the rebuild of the development applications, three options were added, each switched on in its own tuning arm:

- `browse_list` (`dev_v3_browse`). The held-out evaluation exposed a blind spot: the operators work on forms, and no operator pages through a list. This operator applies a sort or filter control, presses "next" or "load more" up to twice, and opens an item on the later page.
- **Custom clickables** (`dev_v3_clickables`). The registry also offers elements made clickable by ARIA roles, click handlers or styling, such as kanban cards and tab strips.
- **Failure feedback** (`dev_v3_failfeedback`). Cells where a browser error followed an action get extra archive weight (up to $\times 3$), since code that already misbehaves is likelier to misbehave again nearby.

The curiosity variant (`dev_v3_curiosity`) is the fourth tuning arm.

5.6 Development rounds

The design was tuned on development data only: the six benchmark applications, a generated application family, Gitea, and the eight development suite applications (Chapter 6). Each round compared arms on the same applications and seeds, and ended with a recorded decision. Table 5.1 lists them.

Table 5.1: Development rounds of the hybrid tester and their decisions.

Round	Tested	Decision
Benchmark 1	bandit, no learner, random (4 apps)	discarded (code changed mid-round); replay bug found and fixed
Benchmark 2	bandit vs no learner, with clean builds (6 apps)	validation invariant narrowed; form fixes
Benchmark 3	free-exploration variants	depth preference and weighted exploration adopted
Benchmark 4–5	which submit actions a cell records	cells record *whether* a submit is offered
Benchmark 6–7	whole-word vs prefix matching of role cues	prefix matching adopted
Suite 1	bandit vs no learner, 8 suite apps	site navigation never submits; submit actions taken in turn
Suite 2	the same after the fix, 14 apps	kept; learner not ahead
Suite 3	two corrected bandit rewards (novelty, surprise)	no difference: reward not the bottleneck
Suite 4	pairwise operator + technique-first choice	worse; not adopted
Suite 5	curiosity Q-learning, in the hybrid and standalone	neither adopted

Table 5.2: All arms on the same runs: suite rounds 2–5, 14 applications × 3 seeds. Difference is the per-application mean T against `hybrid_nolearn`, with a bootstrap interval over applications (negative = faster).

Arm	Found a fault	Median T	Mean T	Difference [95% interval]
`hybrid_nolearn`	32 / 42	742	889	reference
`hybrid_bandit`	30 / 42	335	840	-49 $[-279, +190]$
`dev_bandit_surprise`	31 / 42	586	844	-46 $[-257, +143]$
`dev_bandit_novelty`	31 / 42	486	854	-35 $[-252, +190]$
`dev_pairwise_bandit`	27 / 42	757	943	$+53$ $[-121, +227]$
`dev_hybrid_curiosity`	29 / 42	612	978	$+89$ $[-38, +202]$
`dev_pairwise_nolearn`	26 / 40	1,069	1,046	$+119$ $[-37, +281]$
`dev_curiosity_rl`	17 / 42	2,000	1,313	$+423$ $[+142, +744]$
`random`	18 / 42	2,000	1,355	$+465$ $[+178, +790]$

Is the learner helping? The top four arms in Table 5.2 are statistically tied. `hybrid_nolearn` verified a fault in the most runs, and `hybrid_bandit` was fastest when it found one. No learner variant improved on no learner: three bandit reward signals, the pairwise operator, and curiosity Q-learning. The standalone curiosity tester was fast on shallow faults but never found the deep ones, and was significantly worse than the hybrid, level with random. It is a tester built from

the published components, not a reproduction of WebExplor or WebRLED; their published results (coverage and crash-type failures over long runs) are not contradicted by it.

The design leaves the learner little to decide, for four reasons. On about 5 of the 14 applications a fault is found within the first few decisions, before learning can matter. The faults no arm finds need two deviations in one walk (for example, express delivery *and* an empty address), which choosing one operator more cleverly cannot produce. The option space is small: about 28 cells times 8 operators can mostly be covered in about 135 decisions, so trying untried options systematically already does most of the work. And operators with many targets crowd out the rest: invalid input took 30% of all decisions because pages have many fields. This agrees with the Humanoid authors' observation that their learned model was not the main reason for their gains [12]. On functional faults, most of the work is done by the structure: the abstraction, the archive with exact return and the operators.

Chapter 6

Test Applications and Evaluation Methodology

A tester can only be evaluated on applications whose faults are known. This chapter describes the four sets of test applications (Sections 6.1–6.5), how an application is admitted before any agent touches it (Section 6.6), how applications were split between development and evaluation (Section 6.7), and the metrics and statistics (Section 6.8). Section 6.9 states the threats to validity.

6.1 The six-application benchmark

Six small web applications were built to one design contract for the v1 experiments: an account hub, an admin records system, a booking desk, a media library, a shop catalogue and a support portal. Each carries two seeded faults, 12 in total, in five classes: calculation error, constraint bypass, persistence failure, state corruption and broken transition. Some faults sit 9–16 contextual steps deep. Two applications (the shop catalogue and the booking desk) were used during development; the other four stayed pristine until the transfer experiment.

6.2 The generated application family

For Experiment 2, a seeded generator produced twelve variants of one loan-request workflow. They differ in vocabulary, structure and decoys, and each was admitted by the same validator as the benchmark (Section 4.5).

6.3 The development suite

Eight applications were built to differ from each other and from the benchmark in domain, architecture and stack (Table 6.1). They started as zero-dependency applications and were later rebuilt as full-stack ones. Each now has its own database (PostgreSQL or MongoDB), a sign-in page and a richer data model. The five rebuilt last were also enlarged to at least 12

views, 3 entities with full create, read, update and delete, 5 interaction patterns, and 2 new faults that are not about forms.

Table 6.1: The development suite (version 2).

App	Domain and architecture	Server	Database	Faults	Crash
tidewater	personal banking; single-page app over a JSON API	Python	PostgreSQL	3	–
clinicflow	clinic front desk; server-rendered branching wizard	Python	PostgreSQL	5	–
stackroom	stockroom inventory; data grid with server-side paging, sorting, bulk actions	Python	PostgreSQL	5	2
ledgerly	expense claims with multi-role approval; server-rendered forms	Node.js	PostgreSQL	5	–
bagstreet	small shop; server-rendered pages and HTML forms	Python	MongoDB	5	–
helpline	broadband care desk; pages with HTML fragment updates	Python	MongoDB	7	2
orbit	kanban boards; modal-heavy single-page app	Node.js	MongoDB	5	2
wayfarer	trip itinerary builder; client drafts and sealed server versions	Node.js	MongoDB	6	2
				41	8

Isolation between sessions. Every signed-in browser context gets its own data partition: a schema per session in PostgreSQL, a database per session in MongoDB. This resets the application between episodes and keeps parallel runs independent. The database drivers are vendored and pinned, so a build needs no network.

Crash-type faults. Four applications also carry two crash-type faults each (Section 3.2.4), so that the tuned tester is exercised on the kind of failure the external benchmark counts. The other four have none. All four were admitted with every check passing, the Docker build included: 40 checks for orbit, 44 for helpline, 40 for stackroom and 41 for wayfarer.

6.4 The validation suite

Eight further applications were planned by an independent agent working only from the suite's design contract, without access to the tester's code or results, and built for the held-out evaluation (Table 6.2). Each has three seeded faults, 24 in total, and each was admitted with 20 of 20 checks. They were evaluated in their first version (without a database server or sign-in) and have not been changed since.

Table 6.2: The validation suite, used once, for the held-out evaluation.

App	Domain	Stack	Faults
dutyday	a food bank's volunteer rota	Python, SQLite	3
fosterly	an application to become a foster carer, saved section by section	Node.js, JSON files	3
larder	a personal recipe box with scaling and unit conversion	Node.js, JSON files	3
markbook	a teacher's markbook with a student view	Python, SQLite	3
quizcraft	a survey editor with undo, redo and a respondent preview	Python, SQLite	3
sideline	a football league's results, confirmations and table	Python, SQLite	3
skylark	a nature group's bird-sightings register with a paged feed	Node.js, JSON files	3
tally	a club election by ranked ballot	Node.js, JSON files	3

6.5 The external benchmark

To compare with published RL web testers on their own ground, the final evaluation uses the six subject applications of WebExplor [2], which WebRLED's first benchmark [1] also uses:

- Dimeshift, an expense tracker;
- Pagekit, a content management system, tested in its admin area;
- Splittypie, which splits bills;
- Phoenix, a Trello clone;
- Retroboard, a retrospective board;
- Petclinic, the Spring demonstration application.

They are open-source applications not written by this project. They run from the Docker images of the DIG replication material [15], which instrument the client JavaScript with Istanbul, so branch coverage is measured the way the papers measured it. To keep the comparison honest, nobody looked at these applications before the re-tuned tester was frozen and the comparison pre-registered (Section 7.3).

6.6 Admission

Before any agent runs on an application, a harness must admit it mechanically. For each fault, a scripted *witness* trace must trigger the fault's assertion on the faulty build and not on that fault's control build. The witness must replay deterministically and minimise to a short reproduction. Benign traces must trigger nothing. A random walk on the clean build must produce no candidate. The faulty build must differ from the clean build *only* by the declared patches; a diff audit checks this. The development suite adds a data-model contract (seeded record counts per entity), a breadth contract (views, entities, interaction patterns), sign-in checks, crash checks and a Docker build. An application that fails any check is not used. A

diversity check also confirms that the suite's applications do not share code (the largest overlap was 3.2%).

6.7 Data split and independence

- **Development** (used for tuning and design decisions): the six benchmark applications, the generated family, Gitea (a real open-source application, as a non-admin user), and the eight development suite applications.
- **Held-out**: the eight validation applications, used once, by the pre-registered evaluation of Chapter 7.
- **External**: the WebExplor and WebRLED subject applications, used once, by the final comparison.

The split was fixed before any agent ran on the suites. Development results are tuning data. They are never presented as evidence of generalisation, and the held-out result belongs to the version of the tester frozen before it ran.

6.8 Metrics and statistics

Outcome. For a run with budget B, T is the number of interactions until the first verified fault. Every browser action counts, including replays and returns. A run that finds nothing is right-censored at $T = B$.

Per arm. The *discovery rate* is the share of runs that verified at least one fault. The *restricted mean* of T (RMST) averages T over runs with censored runs at B. *Distinct faults* counts how many of the seeded faults an arm verified in at least one run. Clean-build control runs give the false-positive count. For the tuning round two descriptive metrics were added. *Unique failures* counts distinct browser-error signatures (console, page and failed-request errors). *JavaScript coverage* is the share of the application's client-side code executed, measured with V8's precise coverage through the Chrome DevTools Protocol, attached before the first navigation.

Comparisons. Applications differ far more than seeds do, so the *application* is the unit of inference. For two arms, the per-application difference in restricted mean T is computed on matched (application, seed) pairs; the median across applications summarises it, with a 95% bootstrap interval resampling applications. The stratified log-rank test is secondary. The pre-registered decision rule:

- *supported* if the median difference is negative (faster) and its interval excludes zero;
- *refuted* if it is positive and the interval excludes zero;
- otherwise *inconclusive*.

Pre-registration. For every pre-registered experiment, the hypotheses, arms, applications, budget, seeds, analysis code and decision rule were committed to the repository, and the commit was tagged before any agent ran on the evaluation applications [9]. Deviations, such as rerunning a job lost to an infrastructure failure, follow rules written in advance and are reported.

6.9 Threats to validity

- **Same developer.** The test applications and their seeded faults were built by the same project as the tester. Independent planning of the validation suite and the external benchmark reduce, but do not remove, this threat.
- **Seeded faults.** Seeded faults are an incomplete proxy for real faults, and the oracle sees only what was seeded.
- **Scale.** Eight applications per evaluation leave wide intervals at the application level. Small effects cannot be told apart from noise.
- **Fault difficulty.** If the held-out faults are shallow, every arm finds them and differences compress. Chapter 7 reports that this happened.
- **Tuning leakage.** Decisions made on development data can overfit it; the held-out and external evaluations exist to measure that.

Chapter 7

Evaluation

This chapter reports the evaluations of the hybrid tester: the pre-registered held-out evaluation on the validation suite (Section 7.1), the final tuning round on the rebuilt development suite (Section 7.2), the external comparison with WebExplor and WebRLED (Section 7.3), its post-hoc follow-up (Section 7.4) and its pre-registered second round (Section 7.5).

7.1 Held-out evaluation (pre-registered)

7.1.1 Design

The pre-registration was frozen and its commit tagged before any agent ran on any validation application.

- **Applications**: the eight validation applications (Table 6.2), 24 seeded faults.
- **Arms**:
  - `random`, uniform over the page's valid actions;
  - `hybrid_nolearn`, the primary arm;
  - `hybrid_bandit`;
  - `v1_dqn_pretrained`, v1's best AC-DQN arm from Experiment 1: pretrained without the LLM reward and adapting online, using that experiment's own checkpoints. Seed s loads the checkpoint of fold s mod 6, pretraining seed s mod 3.
- **Runs**: seeds 0–4, $B = 2{,}000$ interactions, 160 hunts, plus 32 clean-build control runs (one per arm and application). The run took about seven and a half hours with four workers and no other workload.
- **Hypotheses** (difference in restricted mean T, decision rule of Section 6.8):
  - H1 (primary): the hybrid tester is faster than random;
  - H2: the bandit makes the hybrid faster;
  - H3: the hybrid with the bandit is faster than random;

– H4: the hybrid is faster than v1's best AC-DQN.

One of 192 jobs failed for an infrastructure reason: Windows held a file lock while the temporary build folder of a clean-build control was being deleted. As pre-registered, the job was rerun unchanged; it completed with no finding.

7.1.2 Results

Table 7.1: Held-out evaluation: pre-registered comparisons (negative Δ = first arm faster).

	Comparison	Median Δ	95% interval	Apps favouring	Log-rank p	Verdict
H1	`hybrid_nolearn` − `random`	−324	$[-665, +148]$	6/8	0.159	inconclusive
H2	`hybrid_bandit` − `hybrid_nolearn`	+86	$[-304, +285]$	4/8	0.781	inconclusive
H3	`hybrid_bandit` − `random`	−191	$[-801, +67]$	5/8	0.180	inconclusive
H4	`hybrid_nolearn` − `v1_dqn_pretrained`	+42	$[-196, +574]$	4/8	0.276	inconclusive

Table 7.2: Held-out evaluation per arm (40 runs each).

Arm	Found a fault	RMST	Faults per run	Distinct faults	Clean false positives
`v1_dqn_pretrained`	34 (0.85)	**595**	1.18	17 / 24	0 / 8
`hybrid_nolearn`	30 (0.75)	737	1.15	18 / 24	0 / 8
`hybrid_bandit`	34 (0.85)	769	**1.23**	**19** / 24	0 / 8
`random`	32 (0.80)	978	1.00	13 / 24	0 / 8

Table 7.3: Held-out evaluation per application: runs that found a fault (of 5) and mean T.

App	`random`	`v1_dqn_pretrained`	`hybrid_nolearn`	`hybrid_bandit`
dutyday	4/5 · 1,217	**5/5 · 281**	4/5 · 788	4/5 · 778
fosterly	5/5 · 1,262	4/5 · 763	4/5 · 681	**5/5 · 370**
larder	5/5 · 411	5/5 · 407	**5/5 · 211**	5/5 · 393
markbook	1/5 · 1,805	**4/5 · 567**	3/5 · 1,141	4/5 · 1,442
quizcraft	5/5 · 299	5/5 · 97	**5/5 · 81**	5/5 · 366
sideline	2/5 · 1,623	1/5 · 1,759	**4/5 · 620**	3/5 · 822
skylark	5/5 · 980	**5/5 · 614**	0/5 · 2,000	3/5 · 1,696
tally	5/5 · **229**	5/5 · 276	5/5 · 376	5/5 · 284




Figure 7.1: Held-out evaluation: share of runs that have not yet verified a fault, against interactions (Kaplan–Meier estimate, runs that found nothing censored at 2,000). Lower is better.

Figure 7.1 shows the same runs over time. All four pre-registered comparisons are inconclusive (Table 7.1). As the pre-registration anticipated, eight applications give the median rule wide intervals, and no comparison was supported or refuted. The per-fault counts are in Appendix A.2.

7.1.3 What the held-out data shows (descriptive)

1. **The held-out faults were easier for random exploration than the development ones.** Random verified a fault in 80% of runs, against 43% (18 of 42) on the development suite. Several faults sit one or two interactions from a page that random visits constantly. Three faults were verified in 5 of 5 runs by every arm, which compresses every difference.

2. **The hybrid arms reached the deeper faults.** 22 of the 24 faults were verified by at least one arm; two by none. Of the 16 faults random verified in at most one of five runs, the two hybrid arms together verified 14 at least once, and `v1_dqn_pretrained` 9. Nine faults were verified by a hybrid arm and by no random run. This is where test operators help: completing forms validly, invalid input, edits after review.

3. **One clear blind spot: list paging.** All three skylark faults sit behind its feed's "Load more" button. Random presses it often by chance. The hybrid's operators work on forms and none pages through a list, so `hybrid_nolearn` reached the right pages in every run but never repeated the paging (0 of 5). This cost H1 one of its eight applications. It was reported, not fixed, because the code was frozen; it motivated the `browse_list` operator (Section 5.5).

4. **v1's pretrained AC-DQN did better here than on its own benchmark**: discovery 0.85 and the lowest mean time, especially on dutyday and markbook. Whether that reflects the method or the applications' shallower faults cannot be separated with eight applications (H4 inconclusive).

5. **The learner (H2).** `hybrid_bandit` found a fault in more runs than `hybrid_nolearn` (34 against 30) and more distinct faults (19 against 18), with a slightly higher mean time (769 against 737). As in development, the learner is not distinguishable from no learner.

6. **Zero false positives.** No clean-build control verified a seeded fault (0 of 32 runs).

Specification-free invariants. As pre-registered, they are reported separately. They flagged no seeded fault for any arm. On clean builds they produced three reproduced candidates (two for `hybrid_nolearn`, one for `hybrid_bandit`), all on quizcraft's editor, all of the form "an entered value is gone after reload". On inspection, quizcraft keeps its working copy in page memory until the user saves, so losing unsaved edits on reload is intended. They are false alarms: the reload invariant cannot tell saved state from unsaved state.

7.1.4 Discovery by fault difficulty (post-hoc)

The statement that the hybrid arms reached deeper faults rests on how often random found each fault, so it partly defines difficulty by the arms' own results. A criterion that does not depend on any agent is each fault's declared shortest trigger path. It was written into the application's manifest when the fault was designed, before any agent ran. Faults are *shallow* with at most 4 interactions, *moderate* with 5–6, and *deep* with 7 or more. Table 7.4 applies it to the frozen held-out results. The analysis was defined after the results (`scripts/analyze_difficulty.py`).

Table 7.4: Held-out evaluation by declared fault difficulty (post-hoc): distinct faults verified, and in brackets runs that verified them out of all (fault, seed) pairs.

Group	Faults	`random`	`v1_dqn_pretrained`	`hybrid_nolearn`	`hybrid_bandit`
Shallow (≤ 4)	8	6 (26/40)	7 (24/40)	6 (22/40)	**8** (28/40)
Moderate (5–6)	10	5 (12/50)	7 (15/50)	**9** (20/50)	7 (16/50)
Deep (≥ 7)	6	2 (2/30)	3 (8/30)	3 (4/30)	**4** (5/30)
Observed on the same visit	18	9 (30/90)	12 (37/90)	13 (35/90)	**14** (40/90)
Needs a reload or a revisit	6	4 (10/30)	5 (10/30)	5 (11/30)	5 (9/30)

On shallow faults every arm found most of them. The gap opens at moderate depth, where `hybrid_nolearn` verified 9 of 10 faults and random 5. On deep faults no arm found more than 4 of 6, and random found 2. Faults that need a reload or a revisit were found about equally by every arm. With 6 to 10 faults per group, this is descriptive. It agrees with the claim that structure helps most where a fault needs a deliberate sequence of steps. Figure 7.2 shows the distinct-fault counts of Table 7.4.




Figure 7.2: Held-out evaluation: distinct faults verified by declared difficulty (post-hoc; dashed line: faults in the group).

7.1.5 Candidate verification

Table 7.5 shows what the oracle did with the candidates each arm submitted. Verification runs in separate browser sessions and is not charged to the exploration budget B, so its cost is reported here separately.

Table 7.5: Held-out evaluation: candidate verification per arm (40 runs each), with the mean browser interactions and seconds spent verifying each candidate.

Arm	Candidates	Verified	Rejected	Steps each	Seconds each
`random`	40	40	0	76	88
`v1_dqn_pretrained`	65	47	18	79	84
`hybrid_nolearn`	46	46	0	99	116
`hybrid_bandit`	49	49	0	100	126

No candidate failed to reproduce on replay. All 18 rejections concern one fault, TALLY-3, in runs of `v1_dqn_pretrained`. The trajectories violated TALLY-3's assertion on the control build without TALLY-3 as well, so the failure was not caused by that fault. A replay-only oracle would have reported all 18 as TALLY-3; the per-fault control caught them.

7.2 Tuning round v3 on the rebuilt development suite

7.2.1 Design

After the held-out evaluation, the development suite was rebuilt (Section 6.3) and the tester re-tuned on it before the external comparison. Eight arms ran on the eight development

applications with seeds 0–2, 192 runs of 2,000 interactions:

- the references: `random`, `hybrid_nolearn`, `hybrid_bandit` and `v1_dqn_pretrained`;
- one option each (Section 5.5):
  - `dev_v3_browse`,
  - `dev_v3_clickables`,
  - `dev_v3_curiosity`,
  - `dev_v3_failfeedback`.

Each run records verified faults (including crash-type faults), unique failures and JavaScript coverage. These are development data: they choose the configuration to freeze, and are not evidence of generalisation.

7.2.2 Results

All 192 runs completed, none failed. Table 7.6 summarises each arm. Table 7.7 compares each arm with `hybrid_nolearn` on matched (application, seed) pairs.

Table 7.6: Tuning round v3 per arm: 24 runs each on the eight rebuilt development applications, which hold 41 seeded faults (8 of them crash-type).

Arm	Found a fault	RMST	Distinct faults	Crash faults	Unique failures / run	JS coverage
`dev_v3_failfeedback`	21 / 24	**450**	19 / 41	3 / 8	3.79	0.893
`random`	**23** / 24	498	19 / 41	1 / 8	5.38	0.861
`dev_v3_browse`	20 / 24	545	19 / 41	3 / 8	3.12	0.885
`hybrid_nolearn`	21 / 24	560	19 / 41	**4** / 8	2.88	0.896
`v1_dqn_pretrained`	20 / 24	564	19 / 41	2 / 8	4.75	**0.909**
`dev_v3_clickables`	19 / 24	638	17 / 41	3 / 8	2.50	0.891
`dev_v3_curiosity`	20 / 24	650	16 / 41	2 / 8	**5.67**	0.894
`hybrid_bandit`	19 / 24	692	16 / 41	3 / 8	2.83	0.896

Table 7.7: Tuning round v3 against `hybrid_nolearn`: per-application mean difference in T (negative = faster), median over applications with a 95% bootstrap interval. Apps with no difference are not counted as faster or slower.

Arm	Median	95% interval	Apps faster / slower
`dev_v3_browse`	−20	$[-79, 0]$	6 / 1
`dev_v3_failfeedback`	0	$[-379, 0]$	3 / 1
`random`	−18	$[-285, +186]$	5 / 3
`v1_dqn_pretrained`	−45	$[-182, +265]$	5 / 3
`dev_v3_clickables`	0	$[0, +286]$	0 / 3
`dev_v3_curiosity`	+43	$[-248, +549]$	4 / 4
`hybrid_bandit`	+140	$[+112, +416]$	1 / 7

Reading. The `browse_list` operator helped consistently but modestly: it was faster on six of seven applications, slower on one, and lost no fault. Failure feedback gave the best restricted mean time (450). Custom clickables did not help; they were never faster and verified fewer distinct faults. The bandit was slower than no learner on seven of eight applications, and its interval excludes zero. Curiosity Q-learning triggered the most unique browser errors (5.67 per run) but verified fewer seeded faults. Random exploration was strong here, finding a fault in 23 of 24 runs and triggering many errors, yet it verified only one crash-type fault. The rebuilt applications are also hard: no arm verified 15 of the 41 faults.

7.2.3 Configuration chosen

The two options that did not hurt any measure, `browse_list` and failure feedback, were combined (`dev_v3_combined`) and checked in 24 further runs on the same applications and seeds before freezing. The combination found a fault in 22 of 24 runs, with restricted mean T 465. It verified 22 of the 41 faults, more than any single arm, and 4 of the 8 crash-type faults. Against `hybrid_nolearn` it was faster on six of seven applications (median -52, interval $[-145, 0]$). It was frozen as `hybrid_final`, and the commit was tagged before anyone looked at the external benchmark's applications. Custom clickables and the bandit were not adopted.

7.3 Comparison with WebExplor and WebRLED

7.3.1 Design

The WebRLED paper [1] reports results on WebExplor's six subject applications (Dimeshift, Pagekit, Splittypie, Phoenix, Retroboard and Petclinic), with one-hour runs and five repetitions. WebExplor averaged 55.54% client-side branch coverage and 3.1 failures; WebRLED averaged 64.18% and 4.1. Coverage was measured with Istanbul on the instrumented client code. Failures were console errors, deduplicated by hand.

The comparison was pre-registered when `hybrid_final` was frozen, before anyone looked at the subject applications.

- **Applications.** The same six applications, from the Docker images of the DIG replication material [15], which WebExplor's benchmark reuses. Each image instruments its client JavaScript with Istanbul before the application starts.
- **Arms.** `hybrid_final`; the hybrid with curiosity Q-learning, the RL arm closest to WebExplor and WebRLED; and random.
- **Runs.** One hour of wall-clock time per run, three repetitions (seeds 0–2), and a fresh application instance per run, so $3 \times 6 \times 3 = 54$ runs.
- **Measures.** Branch coverage of the instrumented client code, read from Istanbul's counters after every step and unioned over the run; and unique failures, meaning console errors,

page errors and failed requests, deduplicated automatically by kind, page and normalised message.

- **Analysis.** A descriptive comparison with the published averages, with no significance test against numbers from other machines and runs, and a per-application comparison between our arms.

Two decisions were made during set-up and recorded before any run. First, Pagekit and Phoenix start with a sign-in macro using their documented accounts. Second, requests to a development live-reload server and to web analytics, which the images' pages make, are answered with an empty response. Left alone, they would add the same console failure to every run of every arm. Two differences from the published protocol remain and are reported: three repetitions instead of five, and automatic instead of manual deduplication of failures.

To finish in time, the runs were split across two machines, decided and recorded before any result existed. Dimeshift, Pagekit and Splittypie ran on the development laptop; Phoenix, Retroboard and Petclinic ran on four AWS spot instances (2 vCPU, 8 GB). Every run of a given application used the same machine type, so arms are compared on equal hardware within each application. The AWS applications also ran on GitHub Actions as a replication. Which runs count was fixed in advance by completion, never by result. After launch, Phoenix's sign-in was found to complete about a second after the macro ended, so episodes began on a stale page. The macro was fixed, and every earlier Phoenix run was discarded unread.

7.3.2 Results

All 54 counted runs completed, 27 on the laptop and 27 on AWS. The GitHub Actions replication also completed all 27 of its runs. Phoenix runs made before the sign-in fix were discarded on every platform without being read, as recorded in the pre-registration. Table 7.8 gives branch coverage per application.

Table 7.8: External comparison: client-side branch coverage (%), mean [min, max] over three one-hour runs, beside the published means (five runs) of WebExplor and WebRLED [1].

App	Branches	`hybrid_final`	`hybrid_curiosity`	`random`	WebExplor	WebRLED
Dimeshift	1,080	49.2 [47.5, 52.4]	47.8 [46.9, 48.7]	45.0 [44.4, 45.8]	54.2	55.4
Pagekit	555	32.4 [32.1, 32.8]	33.9 [30.8, 39.0]	34.2 [32.1, 35.5]	25.8	39.8
Splittypie	130	35.7 [32.6, 40.8]	42.9 [38.4, 49.1]	37.5 [32.7, 42.4]	36.2	44.6
Phoenix	76	48.7 [48.7, 48.7]	48.7 [48.7, 48.7]	46.9 [43.4, 48.7]	71.8	82.9
Retroboard	171	53.2 [53.2, 53.2]	53.2 [53.2, 53.2]	53.2 [53.2, 53.2]	60.2	77.4
Petclinic	20	46.7 [20.0, 75.0]	41.7 [20.0, 85.0]	25.0 [15.0, 40.0]	85.0	85.0
Average		44.3	44.7	40.3	55.5	64.2

Failures. The pre-registered failure count averaged 21.9 per run for `hybrid_final`, 31.8 for `hybrid_curiosity` and 19.2 for random. These numbers cannot be compared with the papers'

3.1 and 4.1. The pre-registered count includes failed requests as well as console errors. It counts a message once per page. And it includes requests the applications make to other websites: Pagekit's Gravatar images, Splittypie's geo-location service, and external links. The papers counted console errors and merged by hand those that "differ only in parameters". A post-hoc count closer to theirs keeps console errors only, drops messages naming another host, and replaces ids, numbers, quoted values and codes with placeholders before counting distinct messages.

Table 7.9: Post-hoc: distinct console error messages per run (mean [min, max]), the measure closest to the papers' manually deduplicated failures.

App	`hybrid_final`	`hybrid_curiosity`	`random`	WebExplor	WebRLED
Dimeshift	3.0 [1, 4]	2.7 [2, 3]	1.3 [1, 2]	3.0	5.4
Pagekit	2.0 [1, 3]	4.0 [1, 7]	2.7 [2, 3]	6.6	7.4
Splittypie	1.0 [1, 1]	1.0 [1, 1]	1.0 [1, 1]	4.0	5.0
Phoenix	3.0 [3, 3]	3.0 [3, 3]	3.0 [3, 3]	0.0	2.0
Retroboard	0.0 [0, 0]	0.0 [0, 0]	0.0 [0, 0]	1.0	1.0
Petclinic	2.0 [2, 2]	2.7 [2, 4]	0.7 [0, 1]	3.8	3.8
Average	1.8	2.2	1.4	3.1	4.1

Between our arms. Both hybrid arms reached more code than random on average (44.3% and 44.7% against 40.3%). The per-application difference is small and its interval includes zero, for `hybrid_final` (median +0.9 points, $[-1.8, +12.9]$) and for `hybrid_curiosity` (+2.3, $[-0.2, +11.1]$). The curiosity arm triggered more distinct failures than random on every application where they differed (post-hoc count: median +0.7, three applications higher, none lower), consistent with its development-round behaviour. With six applications these comparisons are descriptive.

Replication. On GitHub's runners (4 vCPU, 16 GB), Phoenix and Retroboard gave exactly the same coverage as on AWS for every arm, and the same post-hoc failure counts. Petclinic, which has only 20 branches, varied as much between platforms as between seeds: for `hybrid_final`, 35.0% against 46.7%.

Against the published numbers. The frozen tester does not reach the published averages. It is comparable on Pagekit and Splittypie, below WebExplor and WebRLED on Dimeshift, Phoenix, Retroboard and Petclinic, and below both on average (44.3% against 55.5% and 64.2%; 1.8 failures against 3.1 and 4.1).

Why the gap: the action space (exploratory). On Phoenix and Retroboard, no run of any arm, random included, went beyond the same coverage: 48.7% and 53.2%. Both hybrid arms reached exactly that in every run. If three different exploration strategies, one of them

random, all stop at the same branch, the limit is more likely to be what they can act on than how they choose. Phoenix is a React application whose controls are mostly clickable `div` elements. The frozen tester offers only standard HTML controls, because the custom-clickables option (Section 5.5) was not adopted in tuning. The post-hoc follow-up in Section 7.4 tests this directly. WebRLED learns which elements are actionable with a trained discriminator [1], and on these applications that part of its design may matter more than its choice of policy.

7.4 Post-hoc follow-up: the action space

The external result suggested that the tester's action space, not its policy, limited coverage. To measure this, all three external arms were run again with custom clickables in the action space. That is the only change; tag `v4-clickables` marks it. Every run of this follow-up, with and without clickables, ran on GitHub's runners. For Dimeshift, Pagekit and Splittypie the arms without clickables were run there anew; for the other three, the replication runs serve. This version was defined after the external result. It is a diagnosis and does not replace the pre-registered result.

Table 7.10: Post-hoc follow-up: branch coverage (%, mean of three one-hour runs) without and with custom clickables, all on the same hardware.

App	`hybrid_final`	`hybrid_curiosity`	`random`	WebExplor	WebRLED
Dimeshift	47.5 → 49.3	48.0 → 48.6	45.4 → 45.2	54.2	55.4
Pagekit	33.2 → 33.3	35.1 → 34.5	34.2 → 37.1	25.8	39.8
Splittypie	33.1 → 34.9	45.6 → 43.2	37.5 → 37.7	36.2	44.6
Phoenix	48.7 → **82.0**	48.7 → **83.3**	46.9 → **74.6**	71.8	82.9
Retroboard	53.2 → 53.2	53.2 → 53.2	53.2 → 53.2	60.2	77.4
Petclinic	35.0 → 20.0	85.0 → 61.7	28.3 → 26.7	85.0	85.0
Average, 6 apps	41.8 → 45.5	52.6 → 54.1	40.9 → 45.7	55.5	64.2
Average, without Petclinic	43.1 → 50.6	46.1 → 52.6	43.5 → 49.5	49.6	60.0

Reading.

- **Phoenix.** With clickables, every arm rose by 28 to 35 points. The hybrid arms reached 82–83%, level with WebRLED's 82.9% and above WebExplor's 71.8%. Random reached 74.6%. On Phoenix, then, the gap was the action space.
- **Retroboard.** The ceiling (53.2% for every arm and run) did not move. Its cause is not the clickable elements and was not identified.
- **Dimeshift, Pagekit and Splittypie.** Small changes of a few points in either direction. Clickables were not what limited them.

- **Petclinic.** With only 20 branches, one branch is 5 points. Results varied between platforms and seeds as much as between conditions; the three-run means cannot be read as an effect of clickables.
- **Failures.** Distinct console failures did not change (about two per run for every arm).

Against the published numbers. Over all six applications, the arms with clickables averaged 45.5–54.1%, still below WebExplor's 55.5% and WebRLED's 64.2%. Petclinic, where WebExplor and WebRLED both report 85%, weighs heavily on that average. Without Petclinic, a post-hoc view, the arms with clickables averaged 49.5–52.6%. That matches or exceeds WebExplor (49.6%) and remains below WebRLED (60.0%).

What it shows about policy. The gains were similar for the frozen tester, the curiosity arm and random. Next to the set of actions available, the choice of policy made little difference.

7.5 External comparison, round 2 (pre-registered)

Design. The first round was below the published numbers, and its diagnosis pointed at clickable-element detection. A second round measured an improved tester under a protocol closer to the papers'. It was pre-registered and the code tagged (`v5-freeze`) before any run. Because it is informed by round 1, it is not an independent test, and it is reported beside round 1, not in its place.

- **Tester (v5).** The two hybrid arms with *listener-based* clickable detection. A script injected before the page's own code records every element that receives a click-type event listener. It also reads the handlers of React, Vue and jQuery, AngularJS and Ember action attributes, and links without an address. It was developed and checked only on the project's own applications.
- **Arms.** `hybrid_final_v5` and `hybrid_curiosity_v5`. We chose not to include a random arm in this round.
- **Protocol.** The same six applications, images, sign-in macros and stubs as round 1; one-hour runs; **five repetitions**, as in the papers; every run on the same hardware (GitHub-hosted runners, 4 vCPU, 16 GB).

All 60 runs completed; none failed.

Table 7.11: Round 2: branch coverage (%, mean [min, max] over five one-hour runs) and distinct console failures per run, beside the published numbers.

App	`hybrid_final_v5`	`hybrid_curiosity_v5`	WebExplor	WebRLED
Dimeshift	48.6 [45.6, 55.0] / 3.0	48.9 [47.2, 50.9] / 3.6	54.2 / 3.0	55.4 / 5.4
Pagekit	35.0 [33.3, 35.7] / 1.8	**41.0** [34.7, 49.4] / 2.8	25.8 / 6.6	39.8 / 7.4
Splittypie	37.7 [30.8, 44.6] / 1.0	**47.0** [40.1, 52.6] / 1.2	36.2 / 4.0	44.6 / 5.0
Phoenix	82.4 [76.3, 84.2] / 2.6	**84.7** [82.9, 85.5] / 2.6	71.8 / 0.0	82.9 / 2.0
Retroboard	54.0 [53.8, 54.4] / 1.0	54.0 [53.8, 54.4] / 1.0	60.2 / 1.0	77.4 / 1.0
Petclinic	51.0 [20.0, 75.0] / 1.8	46.0 [20.0, 85.0] / 2.4	85.0 / 3.8	85.0 / 3.8
Average, 6 apps	51.4 / 1.9	53.6 / 2.3	55.5 / 3.1	64.2 / 4.1
Average, without Petclinic	51.5	55.1	49.6	60.0
Round 1 on the same hardware, 6 apps	41.8	52.6		




Figure 7.3: External comparison: branch coverage per application. Grey rings: the frozen tester in round 1; blue and orange: the two arms in round 2; black: the published numbers.

Reading.

- **Against the published numbers.** Over all six applications, both arms remain below WebExplor (55.5%) and WebRLED (64.2%). The curiosity arm reached 53.6%. Without Petclinic, it reached 55.1%: above WebExplor's 49.6%, below WebRLED's 60.0%. Per application, the curiosity arm was above both published testers on Pagekit, Splittypie and Phoenix, and below both on Dimeshift, Retroboard and Petclinic.
- **Against round 1 on the same hardware.** `hybrid_final` rose from 41.8% to 51.4%, higher on all six applications (median +3.2 points). The curiosity arm rose on five of six (median +1.1); its round-1 average is lifted by one Petclinic run at 85%. Against the

heuristic clickables of the follow-up, both arms were higher on five of six applications (median about +1.2 points).

- **Failures.** Distinct console failures did not change: about two per run, below the papers' 3.1 and 4.1.
- **Retroboard** stayed at 54% in every run. Its limit is not the clickable elements and was not identified.

The curiosity arm was ahead of `hybrid_final` again on coverage, as in every coverage measurement in this thesis. All comparisons here are descriptive: our runs and the papers' ran on different machines, and the failure counts were deduplicated differently.

7.6 Post-hoc follow-up: the bandit on the external applications

Neither external round included the bandit. To complete the comparison of learners, it was run afterwards. A tuning sweep of its back-off weight and of evidence forgetting was planned on the development applications, then cancelled for time before any result was read. The bandit therefore ran at its existing settings: back-off 0.3, no forgetting. It ran on `hybrid_final_v5`'s base, so the learner was the only difference (arm `hybrid_bandit_v5`, tag `bandit-v5`). The protocol matched round 2: six applications, five one-hour runs each, on the same hardware. All 30 runs completed. This follow-up is post-hoc and the bandit untuned.

Table 7.12: Post-hoc: branch coverage (%, mean [min, max] over five runs) of the bandit beside the same tester without a learner and the curiosity arm (round 2).

App	`hybrid_bandit_v5`	`hybrid_final_v5`	`hybrid_curiosity_v5`
Dimeshift	**51.3** [48.4, 54.1]	48.6	48.9
Pagekit	34.8 [34.1, 35.7]	35.0	**41.0**
Splittypie	34.8 [19.9, 43.8]	37.7	**47.0**
Phoenix	82.9 [81.6, 85.5]	82.4	**84.7**
Retroboard	53.9 [53.8, 54.4]	54.0	54.0
Petclinic	42.0 [20.0, 80.0]	**51.0**	46.0
Average, 6 apps	50.0	51.4	**53.6**
Average, without Petclinic	51.5	51.5	**55.1**

The bandit was level with the same tester without a learner. The median difference per application was −0.1 points, with 2 applications higher and 4 lower, and without Petclinic both averaged 51.5%. It reached the best Dimeshift coverage of our arms (51.3%), and it triggered about two distinct console failures per run, like the other arms. It stayed below the curiosity arm and the published numbers. This matches its behaviour on our own applications: the

bandit learns which operator produces an interesting outcome, not which page is new, so it should not be expected to widen coverage.

7.7 Discussion

All results in one place. Table 7.13 lists every pre-registered question and its verdict. Table 7.14 arranges the main arms as an ablation of structure and learning, so that the contribution of each can be read directly.

Table 7.13: Every pre-registered question and its verdict.

Evaluation	Question	Verdict
Experiment 1	Does pretraining on five applications speed up discovery on a sixth?	inconclusive (median 0)
Experiment 2	Does the DQN rank actions by state (H-ctx)?	not supported
Experiment 2	Does it memorise actions, words or layouts?	inconclusive
Held-out H1, H3	Is the hybrid, with or without the bandit, faster than random?	inconclusive
Held-out H2	Does the bandit make the hybrid faster?	inconclusive
Held-out H4	Is the hybrid faster than v1's best DQN?	inconclusive
External, round 1	Coverage and failures against WebExplor and WebRLED (descriptive)	below both
External, round 2	The same, with listener-based clickables and five runs (descriptive; without Petclinic, coverage above WebExplor)	below both

Table 7.14: The main arms as an ablation of structure and learning. Held-out: distinct faults of 24 and restricted mean T. Tuning: distinct faults of 41. External: mean branch coverage over the six applications, in round 1, with heuristic custom clickables (post-hoc) and in round 2 (listener-based clickables, v5).

Arm	Structure	Learning	Held-out faults	RMST	Tuning faults	Round 1	Clickables	Round 2
`random`	–	–	13	978	19	40.3	45.7	–
`v1_dqn_pretrained`	–	deep Q-network	17	**595**	19	–	–	–
`hybrid_nolearn`	yes	–	18	737	19	–	–	–
`hybrid_bandit`	yes	Thompson bandit	**19**	769	16	–	–	50.0†
`hybrid_curiosity`	yes	curiosity Q-learning	–	–	16	**44.7**	**54.1**	**53.6**
`hybrid_final`	yes, tuned	–	–	–	**22***	44.3	45.5	51.4

* from the 24-run check of the combined configuration before freezing (Section 7.2).

† post-hoc, untuned, on `hybrid_final_v5`'s base (Section 7.6).

Reading across: adding structure to random raised the distinct faults verified on the held-out applications from 13 to 18. Adding a learner to the structure changed it by at most one fault in either direction, and in tuning it lowered it. The deep Q-network without the structure

was fastest to a first fault on the held-out applications, but no comparison of speed reached a verdict.

What the structure contributes. Across every evaluation, the parts of the hybrid tester that are not learned did the measurable work. Remembering states and returning to them exactly, abstracting pages, and applying test-design operators let it verify deep faults that random exploration did not reach: nine faults no random run found on the held-out applications, and the most distinct faults of any configuration in the final tuning round (22 of 41). The verified-fault oracle produced no false positive in any clean-build control.

What learning contributes.

- **Deep RL (v1).** Pretraining gave no measurable benefit, and the network did not reach the pre-registered bar for learning which action helps in which state.
- **Bandit layer.** Thompson sampling over operators was never better than trying untried options systematically, and in the final round it was slower.
- **Curiosity Q-learning.** It reliably triggered more distinct browser errors, on the development applications and on the external benchmark, but verified fewer seeded faults.

This agrees with the observation from Humanoid that a learned model may not be the main reason for a tester's gains [12]. It also agrees with the web-testing study that found coverage only weakly related to failure revelation [10]: the arm that causes the most errors is not the one that verifies the most faults.

How the tester compares with the literature. On WebExplor's own applications and measures, the frozen tester did not reach WebExplor's or WebRLED's published coverage or failure counts. The post-hoc follow-up located a large part of the gap in the action space, not the exploration policy. With custom clickables, Phoenix coverage rose to WebRLED's level for every arm, and over the five applications other than Petclinic the arms matched or exceeded WebExplor's average, though not WebRLED's. The pre-registered second round, with listener-based detection and five repetitions, gave the same picture: the curiosity arm averaged 53.6% over six applications, just below WebExplor, and 55.1% without Petclinic, between WebExplor and WebRLED. It still triggered fewer console failures than either. Whatever policy a tester uses, it can act only on the elements it detects. The comparison has its own limits: three repetitions instead of five in the first round, different machines, automatic instead of manual failure deduplication, and published numbers we could not re-run.

Verified faults and coverage disagree. The project's own evaluations measure verified seeded faults; the literature measures coverage and console errors. The hybrid was designed and tuned for the first, and is strongest there. On the second it is close to random on coverage and below the published testers on failures. A tester for real use needs both: deep, verified functional faults, and broad reach over the interface.

Which arm is best depends on the measure. Table 7.15 gathers, for each measure, the arm that did best and whether it learns.

Table 7.15: The best arm per measure, across all evaluations.

Measure	Best arm	Reinforcement learning?
Distinct verified faults, final tuning round	`hybrid_final` (22 of 41)	no
Distinct verified faults, held-out evaluation	`hybrid_bandit` (19 of 24)	bandit only
Restricted mean time to first fault, held-out	`v1_dqn_pretrained` (595)	yes, deep Q-learning
Client-side coverage, final tuning round	`v1_dqn_pretrained` (0.91)	yes, deep Q-learning
Branch coverage, WebExplor's applications	`hybrid_curiosity` (44.7%; 53.6% in round 2)	yes, Q-learning
Distinct failures triggered (all evaluations)	`hybrid_curiosity`	yes, Q-learning

Arms that learn to explore, curiosity Q-learning and the deep Q-network, do best on the literature's measures: breadth of coverage and errors triggered. The structure without a learner does best on verified seeded faults, which require deliberate test actions rather than novelty. No learning layer added on top of the structure verified clearly more faults than the structure alone: at best one more on the held-out applications (19 against 18), and fewer in tuning. On the external applications the bandit matched the same tester without a learner (50.0% against 51.4%; 51.5% each without Petclinic). Since WebExplor and WebRLED are both RL testers, the like-for-like comparison is with `hybrid_curiosity`. It reached 44.7% branch coverage; with custom clickables it reached 54.1% over all six applications, and 53.6% in the pre-registered second round: close to WebExplor (55.5%) and below WebRLED (64.2%).

Limits of the evidence.

- **Scale.** Every evaluation used six to eight applications, which leaves wide intervals; all four held-out comparisons were inconclusive.
- **Same developer.** The development and validation applications were built within the project. The external applications were not, and there the tester did worse.
- **Seeded faults.** Seeded faults stand in for real ones only partially.
- **Post-hoc analyses.** The failure measure comparable with the papers, the clickables follow-up and the view without Petclinic were defined after the results and are reported as such.

- **Phoenix cold start.** On a freshly started container, Phoenix's first sign-in redirect can complete after the macro's wait, so a run's first episode may begin on the sign-in page. This affects at most one episode per run, equally for every arm.

Chapter 8

Conclusion and Scope for Further Research

8.1 Conclusion

Katalyze set out to find out how much exploration structure, lightweight online learning and reliable fault verification each contribute to autonomous functional web testing. The four research questions have these answers.

RQ1 The deep RL tester did not reach the pre-registered bar for learning which action helps in which state. The transfer experiment found no statistically established benefit from pretraining. Given the uncertainty in the estimate, the results do not establish whether pretraining helps or has no effect.

RQ2 No. A small local LLM failed as a progress reward and as a page labeller; neither generalised beyond the data it was tuned on.

RQ3 Structure, yes, descriptively: a structured tester verified more distinct faults than random, mostly faults that need a deliberate sequence of steps. No learning layer on top of the structure was shown to improve it.

RQ4 The frozen tester did not reach WebExplor's or WebRLED's published coverage or failure counts. A post-hoc follow-up found the set of actionable elements to be an important limit. With better clickable detection, a pre-registered second round came close to WebExplor's coverage and exceeded it without Petclinic, but stayed below WebRLED and below both on failures.

The evidence is kept in three grades below. *Established* means decided by a pre-registered test or measured directly. *Suggested* means consistent across evaluations but not confirmed by a pre-registered test. *Not established* lists claims that the evidence does not support, including some that a reader might assume.

Established

- The verified-fault oracle reported no false positive in any clean-build control run, and its per-fault controls rejected 18 candidates that replay alone would have misattributed.
- The v1 deep Q-network did not reach the pre-registered bar for state-dependent action values (within-label AUROC 0.51, interval $[0.44, 0.59]$, against a bar of 0.70).
- The local LLM failed both of its pre-set gates, as a reward and as a labeller.
- On WebExplor's six applications, measured as the published work measures, the frozen tester averaged 44.3% branch coverage and 1.8 console failures, against 55.5% and 3.1 for WebExplor and 64.2% and 4.1 for WebRLED. In the pre-registered second round (five runs, listener-based clickables) the curiosity arm averaged 53.6% and 2.3.

Suggested

- **Structure verifies more faults than random exploration.** On the held-out applications, the hybrid arms verified 18 and 19 of 24 faults against 13 for random. Of the 10 faults of moderate declared depth, `hybrid_nolearn` verified 9 and random 5.
- **No learning layer measurably improved on the structure.** The bandit changed distinct faults by at most one on held-out applications, was slower in tuning, and matched the same tester without a learner on the external applications (post-hoc). Curiosity Q-learning triggered more browser errors but verified fewer seeded faults.
- **The action space bounds coverage.** With custom clickables, Phoenix coverage rose from 49% to 75–83% for every arm, random included. With listener-based detection, `hybrid_final` rose from 41.8% to 51.4% on the same hardware, higher on all six applications.

Not established

- That any arm finds a first fault faster than another: every pre-registered comparison of speed was inconclusive.
- That pretraining helps on a new application, or that it has no effect: the interval ($[-749, +290]$ interactions) allows a large benefit and a large cost.
- That Katalyze finds unknown bugs in arbitrary applications. Every quantitative evaluation used seeded faults with known assertions (Section 3.2.3).
- That the false-positive rate is zero. None was observed; with 32 held-out controls the per-run rate is bounded only below about 9%.
- That the product's sandbox resists malicious code. It was not tested against it.

Taken together, the evidence suggests that for verifying functional faults, how a tester is structured and what it can act on matter more than the learning methods tested here. That is a narrower claim than "reinforcement learning does not help". With these learners, in these experiments, learning was not what made the difference. The per-fault verification is what lets

the counts be trusted: without it, 18 misattributed candidates would have been reported as TALLY-3.

8.2 Limitations

- **The oracle problem.** The oracle verifies only seeded faults whose assertions were written by hand. On other applications, findings come from generic triggers and specification-free invariants, which are weaker and raised false alarms on unsaved state.
- **Scale.** Each evaluation used six to eight applications, so most comparisons are inconclusive and the claims are descriptive.
- **Same developer.** The development and validation applications and their seeded faults were built within the project. The external applications were not, and there the tester did worse.
- **Action space.** How many of an application's actionable elements the tester detects (its recall) was not measured independently. The follow-up shows it matters, not how complete it is.
- **External comparison.** The first round used three repetitions instead of five. Both rounds ran on different machines from the papers and deduplicated failures automatically, against published numbers that could not be re-run. WebExplor's code is not public.
- **Product.** Repository intake requires a Dockerfile, and the sandbox is a restricted environment, not one hardened against hostile code.

8.3 Scope for further research

- **Action space.** Measure detection recall against an independent reference, such as event listeners recorded in the browser. Evaluate listener-based detection under pre-registration, or learn which elements are actionable as WebRLED does. Find what bounds Retroboard.
- **Two deviations in one walk.** Operators that combine two deviations in one walk, for the faults no single deviation reaches.
- **Learning across applications.** At the scale the literature suggests (tens of applications), with page semantics in the state.
- **Specification-free oracles** that distinguish saved from unsaved state.
- **LLMs off the decision path.** Use them offline, to propose test operators or assertions for an application.

Appendix A

Agent Configurations and Reproducibility

A.1 Arms

Table A.1: Every arm used in the evaluations, by generation.

Arm	Configuration
Baselines	
`random`	uniform choice among the page's valid actions
`search_A0`	fixed hand-weighted action priority; no learning
`search_S`	fixed linear score over the action features; no learning
v1: action-conditioned DQN (Chapter 4)	
`dqn_scratch`	learns on the target only; LLM reward on
`dqn_scratch_nollm`	as above, LLM reward off
`dqn_pretrained`	pretrained on the other five applications with the LLM reward; residual head adapts
`dqn_pretrained_nollm`	pretrained without the LLM reward; residual head adapts (`v1_dqn_pretrained` in v2 evaluations)
`dqn_zeroshot`	pretrained network frozen; no adaptation
`bandit_scratch`, `bandit_pretrained`	the same network with $\gamma = 0$
v2: hybrid tester (Chapter 5); all with depth preference $\beta_d = 2$	
`hybrid_nolearn`	untried (operator, target) pairs first, at random
`hybrid_bandit`	Thompson-sampling bandit over semantic keys
`dev_bandit_novelty`, `dev_bandit_surprise`	bandit rewarded only for new pages / for unexpected responses
`dev_pairwise_bandit`, `dev_pairwise_nolearn`	pairwise operator and technique-first choice
`dev_hybrid_curiosity`	curiosity Q-learning chooses the free exploration
`dev_curiosity_rl`	standalone curiosity Q-learning tester (no operators)
`dev_v3_browse`	with the `browse_list` operator
`dev_v3_clickables`	with custom clickables in the action registry
`dev_v3_curiosity`	curiosity Q-learning for free exploration (rebuilt suite)
`dev_v3_failfeedback`	archive weight for cells where errors followed actions

Table A.2: Hyperparameters.

Component	Values
Run	budget 2,000 interactions; episodes of at most 40 actions
v1 network	state encoder 64, action encoder 96, scorer 128 units; dueling
v1 learning	Double DQN, 3-step returns, $\gamma = 0.95$, learning rate 3×10^{-4}, batch 64, buffer 30,000, target update 200, PER $\alpha = 0.6$, $\beta_0 = 0.4$
v1 exploration	guide probability 0.75; target ϵ 0.50 $\rightarrow$ 0.05 over half the budget; pretraining 1,500 steps per application
v1 reward	LLM weight $\lambda = 1$ (LLM arms), outcome bonus 3, reveal cap 1.5, clip ± 6
Hybrid archive	weight of Section 5.2; depth preference $\beta_d = 2$
Bandit	Beta posteriors; back-off weight 0.3
Curiosity Q-learning	$\alpha = 0.5$, $\gamma = 0.9$, $\epsilon = 0.1$, episodic bonus 0.5, optimistic initialisation $R_{\max}/(1-\gamma)$

A.2 Held-out evaluation per fault

Table A.3: Held-out evaluation: runs (of 5) that verified each fault.

Fault	R	V1	HN	HB	Fault	R	V1	HN	HB
DUTY-1	3	3	0	3	QUIZ-1	5	5	5	5
DUTY-2	4	3	4	4	QUIZ-2	0	2	1	2
DUTY-3	0	1	1	0	QUIZ-3	0	1	2	0
FOST-1	5	3	4	5	SIDE-1	0	0	1	1
FOST-2	0	0	0	0	SIDE-2	1	1	2	2
FOST-3	0	2	1	1	SIDE-3	1	0	4	3
LARD-1	1	0	3	4	SKY-1	0	3	0	1
LARD-2	5	5	5	5	SKY-2	3	1	0	1
LARD-3	1	0	2	1	SKY-3	5	5	0	2
MARK-1	0	0	2	2	TALLY-1	5	5	5	5
MARK-2	0	1	2	1	TALLY-2	0	2	1	0
MARK-3	1	4	1	1	TALLY-3	0	0	0	0

R = `random`, V1 = `v1_dqn_pretrained`, HN = `hybrid_nolearn`, HB = `hybrid_bandit`.

A.3 Reproducibility checklist

Every result in this thesis can be traced to a tagged version of the code, a pre-registration written before the run, one result file per job, and the analysis code that turned them into the tables (Table A.4). Paths are relative to the project repository.

Table A.4: Where each part of each result can be found.

Item	Location
Frozen code	tags `v2-eval-freeze` (held-out), `v3-freeze` (tuned tester and external comparison), `v4-clickables` (follow-up), `v5-freeze` (external round 2)
Pre-registrations	Experiments 1 and 2 and the held-out evaluation: `docs/methodology/` at tag `docs-archive-2026-10-22`; external comparison: `PROJECT_CONTEXT.md`, section 0.8
Run records	one JSON file per job under `runs/<evaluation>/results/`, e.g. `runs/v2-eval`, `runs/v3-tune`, `runs/ext-eval*`, `runs/ext-v4-gha`
Analysis code	`scripts/analyze_transfer.py` (Experiment 1), `ctxbench/analyze.py` (Experiment 2), `hybrid/analyze.py` (held-out), `scripts/summarize_tuning.py`, `scripts/analyze_external.py`, `scripts/analyze_difficulty.py`
Derived results	`reports/*.json`; the web interface's research page reads them live
Applications	manifests with every fault's patches, assertion and declared shortest path: `validation_suite/apps/*/app.json`, `e2e_suite/apps/`; external: DIG Docker images `dockercontainervm/<app>` with `configs/external_apps.json`
Seeds and budgets	stated with each evaluation; seeds 0–4 (held-out), 0–2 (Experiment 1, tuning, external round 1)
Environment	Python 3.11, Playwright with Chromium, dependencies pinned in `requirements.txt` and `requirements-ci.txt`
Cloud runs	`cloud/aws/launch_external.sh` (AWS spot instances) and `.github/workflows/external-comparison.yml` (GitHub Actions)
Tests	1,291 unit tests (5 skipped without optional dependencies), `pytest tests/unit`
Deviations	recorded with each evaluation: the rerun held-out job, the discarded Phoenix runs

References

[1] Z. Gu, C. Liu, G. Wu, Y. Zhang, C. Yang, Z. Liang, W. Chen, and J. Wei, "Deep reinforcement learning for automated web GUI testing," 2025. arXiv preprint; introduces WebRLED. A journal article on WebRLED by an overlapping author list is registered at doi:10.1145/3843235 (ACM TOSEM, 2026).

[2] Y. Zheng, Y. Liu, X. Xie, Y. Liu, L. Ma, J. Hao, and Y. Liu, "Automatic web testing using curiosity-driven reinforcement learning," in *2021 IEEE/ACM 43rd International Conference on Software Engineering (ICSE)*, pp. 423–435, 2021.

[3] E. T. Barr, M. Harman, P. McMinn, M. Shahbaz, and S. Yoo, "The oracle problem in software testing: A survey," *IEEE Transactions on Software Engineering*, vol. 41, no. 5, pp. 507–525, 2015.

[4] A. Zeller and R. Hildebrandt, "Simplifying and isolating failure-inducing input," *IEEE Transactions on Software Engineering*, vol. 28, no. 2, pp. 183–200, 2002.

[5] ISO/IEC, "ISO/IEC 25010:2011 systems and software engineering – systems and software quality requirements and evaluation (SQuaRE) – system and software quality models." International Organization for Standardization, 2011.

[6] V. Mnih, K. Kavukcuoglu, D. Silver, A. A. Rusu, J. Veness, M. G. Bellemare, A. Graves, M. Riedmiller, A. K. Fidjeland, G. Ostrovski, S. Petersen, C. Beattie, A. Sadik, I. Antonoglou, H. King, D. Kumaran, D. Wierstra, S. Legg, and D. Hassabis, "Human-level control through deep reinforcement learning," *Nature*, vol. 518, no. 7540, pp. 529–533, 2015.

[7] D. J. Russo, B. V. Roy, A. Kazerouni, I. Osband, and Z. Wen, "A tutorial on Thompson sampling," *Foundations and Trends in Machine Learning*, vol. 11, no. 1, pp. 1–96, 2018.

[8] A. Ecoffet, J. Huizinga, J. Lehman, K. O. Stanley, and J. Clune, "First return, then explore," *Nature*, vol. 590, no. 7847, pp. 580–586, 2021. The Go-Explore family of algorithms.

[9] G. Klees, A. Ruef, B. Cooper, S. Wei, and M. Hicks, "Evaluating fuzz testing," in *Proceedings of the ACM Conference on Computer and Communications Security (CCS)*, 2018.

[10] C. Liu, W. Yang, Y. Zhang, and T. Xie, "Understanding automated web GUI testing: An empirical study across exploration strategies and state abstractions," 2026. arXiv preprint.

[11] Y. Zhao, B. Harrison, and T. Yu, "DinoDroid: Testing Android apps using deep Q-networks," *ACM Transactions on Software Engineering and Methodology*, vol. 33, no. 5, 2024.

[12] Y. Li, Z. Yang, Y. Guo, and X. Chen, "Humanoid: A deep learning-based approach to automated black-box Android app testing," in *2019 34th IEEE/ACM International Conference on Automated Software Engineering (ASE)*, pp. 1070–1073, 2019.

[13] H. van Hasselt, A. Guez, and D. Silver, "Deep reinforcement learning with double Q-learning," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 30, 2016.

[14] J. He, J. Chen, X. He, J. Gao, L. Li, L. Deng, and M. Ostendorf, "Deep reinforcement learning with a natural language action space," in *Annual Meeting of the Association for Computational Linguistics (ACL)*, 2016. Introduces the deep reinforcement relevance network (DRRN).

[15] M. Biagiola, A. Stocco, F. Ricca, and P. Tonella, "Diversity-based web test generation," in *Proceedings of the 27th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering (ESEC/FSE)*, 2019.