



H	Outer molding: 45P PVC, blue	1PC	
G	Inner molding: PE, white	1PC	
F	DB15 male connector core, with 2 screws	1SET	
E	Cable: UL2464, 20AWG*4C+20AWG*2P+drian+Al-foil, OD=8.5 ±0.2mm, black PVC jackte, 330mm	2PCS	
D	Overmolding: 45P PVC molded, white	1PC	
C	Overmolding: 45P PVC molded, black	1PC	
B	Type II Deutsch Equivalent 9Pin plug: green core, red rubber seal, inner round ring & 9 terminals	2SETS	
A	Type I Deutsch Equivalent 9Pin receptacle: black core, red rubber seal, inner round ring & 9 terminals	2SETS	
Item	SPEC	QTY	Remark

TESTING

- Any Open, Short Miswiring & Intermittent are not permitted.
- Contact Resistance: 5 Ω.
- Insulation Resistance: 5MΩ/300V DC MIN.
- This product is RoHS compliant.

		Name	2*J1939 Dual-headed to DB15 Male		
		Customer	KL68		
DWG	Jacky Pang	Part No.		Rev.	1.0
Check	Alex Young	Date	2020.08.31	N.W.	
Aprd		DWG No.	KL68-08	Unit	MM