

DIMENSIONS ON SITE AND SHALL REPORT ANY DISCREPANCIES OR OMISSIONS TO THE THE ARCHITECTS OFFICE PRIOR TO START OF WORK OR DURING SETTING OUT. REPORT TO THE ERRORS OR DEPARTURES FROM GOOD PRACTICE.

EXTENT AND NATURE OF ALL CONDITIONS AFFECTING THE WORK, NOT EXCLUDING THE LOCATION OF ALL BURIED

MATERIALS SHALL BE THE BEST OF THEIR RESPECTIVE KINDS OF THE PLANNING DEPARTMENT AND / OR THE FIRE PREVENTION OFFICER FOR ANY WORKS UNDER THEIR RESPECTIVE JURISDICTION REQUIRING INSPECTIONS PRIOR TO

ternal brickwork woodfloat sand/cement render. Interior wet areas render and two coats extern

square edge trim. All tile edges to be flash and dead straight with tiles line.

waimburn or two air-vertis per room, exact positioning to be to builder's discretion almough norm symmetry is to be prioritised. Rooms without direct external ventilation to have either perforated 60x600mm trap door or MV. 20mm plywood curtain pelmet to run from bulkhead full length along window side with 220mm vermin screened perforations at 600mm cfc. See detail. Ordinary pelmets above window opening for other rooms with no bulkheads.

accessible and secured to a wall @1,3m centre. Spotlights to be wired separate for min. 5KVA



Tele :+263 772 452 534, 0733 999 789

		SIGNATURE	DATE	۸۸
	DESIGNED	A.M		AU
	DRAWN	A.M		REVISION B
	VERIFIED	K. M		STATUS LEGEND  I = INFORMATION
	VALIDATED	К. М		T = TENDER C = CONSTRUCTION AB = AS BUILT CA = COUNCIL APPROVAL

Scale: 1:100, 1:200, 1:20, 1:25, 1:10

FLOOR PLAN, ELEVATIONS, SITE PLAN, SECTIONS,

STATUS: CLIENT PRESENTATION

190225