

Module Interface Specification for UnderTree

Team 22, Capstoners
Palanichamy Veerash
Kannammalil Kevin
Qureshi Eesha
Ahmed Faiq

April 5, 2023

1 Revision History

Date	Version	Notes
Jan 13th	1.0	Created MIS Document
Jan 14th	1.1	Assigned Sections
Jan 17th	1.2	Completed Modules
Jan 18th 2022	1.3	Final Changes

2 Symbols, Abbreviations and Acronyms

See SRS Documentation at [SRS](#)

Contents

1	Revision History	i
2	Symbols, Abbreviations and Acronyms	ii
3	Introduction	1
4	Notation	1
5	Module Decomposition	2
6	MIS of PDF Module	3
6.1	Module	3
6.2	Uses	3
6.3	Syntax	3
6.3.1	Exported Constants	3
6.3.2	Exported Access Programs	3
6.4	Semantics	3
6.4.1	State Variables	3
6.4.2	Environment Variables	3
6.4.3	Assumptions	4
6.4.4	Access Routine Semantics	4
6.4.5	Local Functions	4
7	MIS of File Services Module	5
7.1	Module	5
7.2	Uses	5
7.3	Syntax	5
7.3.1	Exported Constants	5
7.3.2	Exported Access Programs	5
7.4	Semantics	5
7.4.1	State Variables	5
7.4.2	Environment Variables	5
7.4.3	Assumptions	5
7.4.4	Access Routine Semantics	5
7.4.5	Local Functions	6
8	MIS of File Data Module	7
8.1	Module	7
8.2	Uses	7
8.3	Syntax	7
8.3.1	Exported Data Types	7
8.3.2	Exported Access Programs	7

8.4	Semantics	7
8.4.1	State Variables	7
8.4.2	Environment Variables	7
8.4.3	Assumptions	7
8.4.4	Access Routine Semantics	7
8.4.5	Local Functions	7
9	MIS of Chat Module	8
9.1	Module	8
9.2	Uses	8
9.3	Syntax	8
9.3.1	Exported Constants	8
9.3.2	Exported Access Programs	8
9.4	Semantics	8
9.4.1	State Variables	8
9.4.2	Environment Variables	8
9.4.3	Assumptions	9
9.4.4	Access Routine Semantics	9
9.4.5	Local Functions	9
10	MIS of Chat Data Module	10
10.1	Module	10
10.2	Uses	10
10.3	Syntax	10
10.3.1	Exported Data Types	10
10.3.2	Exported Constants	10
10.3.3	Exported Access Programs	10
10.4	Semantics	10
10.4.1	State Variables	10
10.4.2	Environment Variables	10
10.4.3	Assumptions	10
10.4.4	Access Routine Semantics	10
10.4.5	Local Functions	10
11	MIS of Chat Services Module	11
11.1	Module	11
11.2	Uses	11
11.3	Syntax	11
11.3.1	Exported Constants	11
11.3.2	Exported Access Programs	11
11.4	Semantics	11
11.4.1	State Variables	11
11.4.2	Environment Variables	11

11.4.3	Assumptions	11
11.4.4	Access Routine Semantics	11
11.4.5	Local Functions	12
12	MIS of Chat Database Interface Module	13
12.1	Module	13
12.2	Uses	13
12.3	Syntax	13
12.3.1	Exported Constants	13
12.3.2	Exported Access Programs	13
12.4	Semantics	13
12.4.1	State Variables	13
12.4.2	Environment Variables	13
12.4.3	Assumptions	13
12.4.4	Access Routine Semantics	13
12.4.5	Local Functions	14
13	MIS of Instructions View Module	15
13.1	Module	15
13.2	Uses	15
13.3	Syntax	15
13.3.1	Exported Constants	15
13.3.2	Exported Access Programs	15
13.4	Semantics	15
13.4.1	State Variables	15
13.4.2	Environment Variables	15
13.4.3	Assumptions	15
13.4.4	Access Routine Semantics	16
13.4.5	Local Functions	16
14	MIS of File Database Interface Module	17
14.1	Module	17
14.2	Uses	17
14.3	Syntax	17
14.3.1	Exported Constants	17
14.3.2	Exported Access Programs	17
14.4	Semantics	17
14.4.1	State Variables	17
14.4.2	Environment Variables	17
14.4.3	Assumptions	17
14.4.4	Access Routine Semantics	17
14.4.5	Local Functions	18

15 MIS of Project Editing Module	19
15.1 Module	19
15.2 Uses	19
15.3 Syntax	19
15.3.1 Exported Constants	19
15.3.2 Exported Access Programs	19
15.4 Semantics	19
15.4.1 State Variables	19
15.4.2 Environment Variables	19
15.4.3 Assumptions	19
15.4.4 Access Routine Semantics	19
15.4.5 Local Functions	20
16 MIS of File List Module	21
16.1 Module	21
16.2 Uses	21
16.3 Syntax	21
16.3.1 Exported Constants	21
16.3.2 Exported Access Programs	21
16.4 Semantics	21
16.4.1 State Variables	21
16.4.2 Environment Variables	21
16.4.3 Assumptions	21
16.4.4 Access Routine Semantics	21
16.4.5 Local Functions	22
17 MIS of File Toolbar Module	23
17.1 Module	23
17.2 Uses	23
17.3 Syntax	23
17.3.1 Exported Constants	23
17.3.2 Exported Access Programs	23
17.4 Semantics	23
17.4.1 State Variables	23
17.4.2 Environment Variables	23
17.4.3 Assumptions	24
17.4.4 Access Routine Semantics	24
17.4.5 Local Functions	24
18 MIS of New File Module	25
18.1 Module	25
18.2 Uses	25
18.3 Syntax	25

18.3.1	Exported Constants	25
18.3.2	Exported Access Programs	25
18.4	Semantics	25
18.4.1	State Variables	25
18.4.2	Environment Variables	25
18.4.3	Assumptions	25
18.4.4	Access Routine Semantics	26
18.4.5	Local Functions	26
19	MIS of Upload File Module	27
19.1	Module	27
19.2	Uses	27
19.3	Syntax	27
19.3.1	Exported Constants	27
19.3.2	Exported Access Programs	27
19.4	Semantics	27
19.4.1	State Variables	27
19.4.2	Environment Variables	27
19.4.3	Assumptions	27
19.4.4	Access Routine Semantics	28
19.4.5	Local Functions	28
20	MIS of Editor File Module	29
20.1	Module	29
20.2	Uses	29
20.3	Syntax	29
20.3.1	Exported Constants	29
20.3.2	Exported Access Programs	29
20.4	Semantics	29
20.4.1	State Variables	29
20.4.2	Environment Variables	29
20.4.3	Assumptions	29
20.4.4	Access Routine Semantics	29
20.4.5	Local Functions	30
21	MIS of Projects Module	31
21.1	Module	31
21.2	Uses	31
21.3	Syntax	31
21.3.1	Exported Constants	31
21.3.2	Exported Access Programs	31
21.4	Semantics	31
21.4.1	State Variables	31

21.4.2	Environment Variables	31
21.4.3	Assumptions	31
21.4.4	Access Routine Semantics	31
21.4.5	Local Functions	31
22	MIS of Project List Module	32
22.1	Module	32
22.2	Uses	32
22.3	Syntax	32
22.3.1	Exported Constants	32
22.3.2	Exported Access Programs	32
22.4	Semantics	32
22.4.1	State Variables	32
22.4.2	Environment Variables	32
22.4.3	Assumptions	32
22.4.4	Access Routine Semantics	33
22.4.5	Local Functions	33
23	MIS of Project Deletion Module	34
23.1	Module	34
23.2	Uses	34
23.3	Syntax	34
23.3.1	Exported Constants	34
23.3.2	Exported Access Programs	34
23.4	Semantics	34
23.4.1	State Variables	34
23.4.2	Environment Variables	34
23.4.3	Assumptions	34
23.4.4	Access Routine Semantics	35
23.4.5	Local Functions	35
24	MIS of Project Creation Module	36
24.1	Module	36
24.2	Uses	36
24.3	Syntax	36
24.3.1	Exported Constants	36
24.3.2	Exported Access Programs	36
24.4	Semantics	36
24.4.1	State Variables	36
24.4.2	Environment Variables	36
24.4.3	Assumptions	36
24.4.4	Access Routine Semantics	36
24.4.5	Local Functions	37

25 MIS of New Project Module	38
25.1 Module	38
25.2 Uses	38
25.3 Syntax	38
25.3.1 Exported Constants	38
25.3.2 Exported Access Programs	38
25.4 Semantics	38
25.4.1 State Variables	38
25.4.2 Environment Variables	38
25.4.3 Assumptions	39
25.4.4 Access Routine Semantics	39
25.4.5 Local Functions	39
26 MIS of Import Project Module	40
26.1 Module	40
26.2 Uses	40
26.3 Syntax	40
26.3.1 Exported Constants	40
26.3.2 Exported Access Programs	40
26.4 Semantics	40
26.4.1 State Variables	40
26.4.2 Environment Variables	40
26.4.3 Assumptions	41
26.4.4 Access Routine Semantics	41
26.4.5 Local Functions	41
27 MIS of Project Database Interface Module	42
27.1 Module	42
27.2 Uses	42
27.3 Syntax	42
27.3.1 Exported Constants	42
27.3.2 Exported Access Programs	42
27.4 Semantics	42
27.4.1 State Variables	42
27.4.2 Environment Variables	42
27.4.3 Assumptions	42
27.4.4 Access Routine Semantics	42
27.4.5 Local Functions	43
28 MIS of Project Services Module	44
28.1 Module	44
28.2 Uses	44
28.3 Syntax	44

28.3.1	Exported Constants	44
28.3.2	Exported Access Programs	44
28.4	Semantics	44
28.4.1	State Variables	44
28.4.2	Environment Variables	44
28.4.3	Assumptions	44
28.4.4	Access Routine Semantics	44
28.4.5	Local Functions	45
29	MIS of GitHub Module	46
29.1	Module	46
29.2	Uses	46
29.3	Syntax	46
29.3.1	Exported Constants	46
29.3.2	Exported Access Programs	46
29.4	Semantics	46
29.4.1	State Variables	46
29.4.2	Environment Variables	46
29.4.3	Assumptions	47
29.4.4	Access Routine Semantics	47
29.4.5	Local Functions	47
30	MIS of GitHub Services Module	48
30.1	Module	48
30.2	Uses	48
30.3	Syntax	48
30.3.1	Exported Constants	48
30.3.2	Exported Access Programs	48
30.4	Semantics	48
30.4.1	State Variables	48
30.4.2	Environment Variables	48
30.4.3	Assumptions	48
30.4.4	Access Routine Semantics	48
30.4.5	Local Functions	49
31	MIS of Authentication Module	50
31.1	Module	50
31.2	Uses	50
31.3	Syntax	50
31.3.1	Exported Constants	50
31.3.2	Exported Access Programs	50
31.4	Semantics	50
31.4.1	State Variables	50

31.4.2	Environment Variables	50
31.4.3	Assumptions	50
31.4.4	Access Routine Semantics	51
31.4.5	Local Functions	51
32	MIS of Auth Service Module	52
32.1	Module	52
32.2	Uses	52
32.3	Syntax	52
32.3.1	Exported Constants	52
32.3.2	Exported Access Programs	52
32.4	Semantics	52
32.4.1	State Variables	52
32.4.2	Environment Variables	52
32.4.3	Assumptions	52
32.4.4	Access Routine Semantics	52
32.4.5	Local Functions	53
33	MIS of Auth Database Interface Module	54
33.1	Module	54
33.2	Uses	54
33.3	Syntax	54
33.3.1	Exported Constants	54
33.3.2	Exported Access Programs	54
33.4	Semantics	54
33.4.1	State Variables	54
33.4.2	Environment Variables	54
33.4.3	Assumptions	54
33.4.4	Access Routine Semantics	54
33.4.5	Local Functions	55
34	MIS of Auth Data Module	56
34.1	Module	56
34.2	Uses	56
34.3	Syntax	56
34.3.1	Exported Data Types	56
34.3.2	Exported Constants	56
34.3.3	Exported Access Programs	56
34.4	Semantics	56
34.4.1	State Variables	56
34.4.2	Environment Variables	56
34.4.3	Assumptions	56
34.4.4	Access Routine Semantics	56

34.4.5 Local Functions	56
35 Appendix	58

3 Introduction

The following document details the Module Interface Specifications for UnderTree.

4 Notation

The structure of the MIS for modules comes from [Hoffman and Strooper \(1995\)](#), with the addition that template modules have been adapted from [Ghezzi et al. \(2003\)](#). The mathematical notation comes from Chapter 3 of [Hoffman and Strooper \(1995\)](#). For instance, the symbol $:=$ is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | \dots | c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by UnderTree.

Data Type	Notation	Description
character	char	a single symbol or digit
integer	\mathbb{Z}	a number without a fractional component in $(-\infty, \infty)$
natural number	\mathbb{N}	a number without a fractional component in $[1, \infty)$
real	\mathbb{R}	any number in $(-\infty, \infty)$
boolean	\mathbb{B}	a True or False value

The specification of UnderTree uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, UnderTree uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Table 1: Module Hierarchy

Level 1	Level 2
Hardware-Hiding Module	Project Editing Module Editor Module Syntax Highlighting Module File List Module File Toolbar Module New File Module Upload File Module User Cursors Module Text Highlighting Module File Synchronization Module File Services Module File Database Interface Module PDF Module PDF Renderer Module PDF Compiler Module Chat Module Chat Services Module Chat Database Interface Module Chat Socket Module Instructions View Module Projects Module Project List Module Project Deletion Module Project Creation Module New Project Module Import Project Module Project Services Module Project Database Interface Module GitHub Module GitHub Services Module Authentication Module Auth Service Module Auth Database Interface Module
Behaviour-Hiding Module	
Software Decision Module	File Data Module Chat Data Module Project Data Module Auth Data Module MongoDB Module

6 MIS of PDF Module

6.1 Module

PDF

6.2 Uses

PDFRenderer, FileServices

6.3 Syntax

6.3.1 Exported Constants

N/A

6.3.2 Exported Access Programs

Name	In	Out	Exceptions
init	String, String		
compileLatex			
downloadPDF			

6.4 Semantics

6.4.1 State Variables

projectName: String

fileName: String

6.4.2 Environment Variables

pdfComponent: The browser component that will display the PDF file

errorRenderer: The browser component that will display any error text

fileDownloader: The component responsible for downloading a file in a browser

compileButton: Button that will trigger the compilation of the LaTeX file, specifically calling the **handleCompileClicked()** function when clicked

downloadButton: Button that will download the PDF unto to the user's PC, specifically calling the **downloadPDF()** function when clicked

6.4.3 Assumptions

Upon loading the editor page, the *pdfComponent* displays an empty PDF file.

6.4.4 Access Routine Semantics

init(project, file):

- transition: *projectName*, *fileName* := project, file
Render *pdfComponent*. Also render *compileButton*, and *downloadButton* and attach *onClickListeners* on them.

compileLatex():

- transition: *pdfComponent*, *errorRenderer* :=
PDFRenderer.render((FileServices.compilePDF(*projectName*, *fileName*).error ≡ "") ⇒
FileServices.compilePDF(*projectName*, *fileName*).fileData|
true ⇒ NULL),
(FileServices.compilePDF(*projectName*, *fileName*)).error ≡ "") ⇒ NULL
| true ⇒
FileServices.compilePDF(*projectName*, bytes(*fileName*).error)

downloadPDF():

- transition: *fileDownloader* := add the file stored in *pdfComponent* to the download queue of the browser in *fileDownloader* regardless of whether the PDF file is empty or not.

6.4.5 Local Functions

N/A

7 MIS of File Services Module

7.1 Module

FileServices

7.2 Uses

AuthService, PDFCompiler, FileDatabaseInterface

7.3 Syntax

7.3.1 Exported Constants

N/A

7.3.2 Exported Access Programs

Name	In	Out	Exceptions
compilePDF	String, String	tuple of (fileData: Sequence of \mathbb{R} , error: String)	
renameFileByIndex	String, \mathbb{N} , String		
createNewFile	String, String		
uploadFile	String, String, String		

7.4 Semantics

7.4.1 State Variables

N/A

7.4.2 Environment Variables

JWT: JSON Web Token that is passed to the server from the user's client as a cookie

7.4.3 Assumptions

N/A

7.4.4 Access Routine Semantics

compilePDF(projectName, fileName):

- output: $\text{out} := \text{AuthService.authenticate}(JWT, \text{projectName}) \Rightarrow (\text{PDFCompiler.compile}(\text{FileDatabaseInterface.getFile}(\text{projectName}, \text{fileName})).\text{error} \equiv \text{NULL}) \Rightarrow \langle \text{PDFCompiler.compile}(\text{FileDatabaseInterface.getFile}(\text{projectName}, \text{fileName})).\text{data}, "" \rangle$

```

true  $\Rightarrow$ 
<"" , PDFCompiler.compile(FileDatabaseInterface.getFile(projectName, fileName)).error>
|
AuthService.authenticate(JWT, projectName)  $\equiv$  false  $\Rightarrow$  <"" , "failed to authenticate">

```

renameFileByIndex(projectName, currentIndex, newName):

- output: out := AuthService.authenticate(*JWT*, projectName) \equiv true \Rightarrow FileDatabaseInterface.renameFile(projectName, index, fileName)

createNewFile(projectName, fileName):

- output: out := AuthService.authenticate(*JWT*, projectName) \equiv true \Rightarrow FileDatabaseInterface.createNewFile(projectName, fileName)

uploadFile(projectName, fileName, fileData):

- output: out := AuthService.authenticate(*JWT*, projectName) \equiv true \Rightarrow FileDatabaseInterface.createNewFile(projectName, fileName) \Rightarrow FileDatabaseInterface.writeToFile(projectName, filename, fileData)

7.4.5 Local Functions

N/A

8 MIS of File Data Module

8.1 Module

FileData

8.2 Uses

N/A

8.3 Syntax

8.3.1 Exported Data Types

File: tuple of (fileName: String, fileType: String, filePath: String, contributors: ⟨String⟩ of size ?, documentID: string)

FileData: tuple of (projectName: String, owner: String, files: ⟨File⟩ of size ?) of size 1

ConnectedUser: tuple of (userName: String, profilePictureUrl: String) of size ?

8.3.2 Exported Access Programs

N/A

8.4 Semantics

8.4.1 State Variables

N/A

8.4.2 Environment Variables

N/A

8.4.3 Assumptions

N/A

8.4.4 Access Routine Semantics

N/A

8.4.5 Local Functions

N/A

9 MIS of Chat Module

9.1 Module

Chat

9.2 Uses

ChatServices, ChatSocket

9.3 Syntax

9.3.1 Exported Constants

N/A

9.3.2 Exported Access Programs

Name	In	Out	Exceptions
init	String		
updateChatMessage	String		
sendMessage			
processSocketEvents			

9.4 Semantics

9.4.1 State Variables

projectName: String

connectedUsers: Sequence of (tuple of (userName: String, profilePictureUrl: String))

messages: Sequence of (tuple of (userName: String, message: String))

chatMessage: String

9.4.2 Environment Variables

chatComponent: The overall state of the chat interface.

messageInputField: This input field is responsible for updating the chat message the user is sending, or specifically calls the **updateChatMessage(messageInputField.textValue)** function when the input value is updated.

sendChatButton: This button sends a new chat message from the user, or specifically calls the **sendChatMessage()** function when clicked.

9.4.3 Assumptions

The `init()` function is automatically called by the rendering library when we first render the module by using the project name passed to it from the url.

9.4.4 Access Routine Semantics

`init(project)`:

- transition: *projectName*, *connectedUsers*, *messages* := project, ChatServices.getConnectedUsers(project), ChatServices.getChatMessages(project)
- transition: *chatComponent* := //Described by the following operational spec
ChatSocket.connect(ChatServices.SERVER_URL||project)

Render messages, *connectedUsers.userName*, and *connectedUsers.profilePictureUrl*. Also render the *sendChatButton* and *messageInputField* on the user interface. Lastly, attach a `onClickListener` to the *sendChatButton* and a `keyPressListener` to *messageInputField*.

`updateChatMessage(newMessage)`:

- transition: *chatMessage* := newMessage

`sendMessage()`:

- transition: *chatComponent* := //Described by the following operational spec
ChatSocket.emit("newMessage", *chatMessage*)

`processSocketEvents()`:

Data is the JSON fields passed into the socket event into each event and then passed into each conditional. These events can be emitted from other clients or the Chat Services Module.

- transition: *connectUsers* :=
ChatSocket.on("newUser", data) \Rightarrow *connectedUsers* || $\langle \langle$ data.userName, data.profilePictureUrl $\rangle \rangle$
| ChatSocket.on("userRemoved", data) \Rightarrow \langle user : tuple of (userName: String, profilePictureUrl: String) \rangle | user \in *connectedUsers* \wedge user.userName \neq data.userName :
 \langle user.userName, user.profilePictureUrl \rangle
- transition: *messages* :=
ChatSocket.on("newMessage", data) \Rightarrow *messages* || $\langle \langle$ data.userName, data.message $\rangle \rangle$

9.4.5 Local Functions

N/A

10 MIS of Chat Data Module

10.1 Module

ChatData

10.2 Uses

N/A

10.3 Syntax

10.3.1 Exported Data Types

ChatMessage: tuple of (userName: String, message: String) of size ?

ConnectedUser: tuple of (userName: String, profilePictureUrl: String) of size ?

10.3.2 Exported Constants

N/A

10.3.3 Exported Access Programs

N/A

10.4 Semantics

10.4.1 State Variables

N/A

10.4.2 Environment Variables

N/A

10.4.3 Assumptions

N/A

10.4.4 Access Routine Semantics

N/A

10.4.5 Local Functions

N/A

11 MIS of Chat Services Module

11.1 Module

ChatServices

11.2 Uses

ChatData, ChatDatabaseInterface, ChatSocket, AuthService

11.3 Syntax

11.3.1 Exported Constants

SERVER_URL: The url of the main chat socket on the server.

11.3.2 Exported Access Programs

Name	In	Out	Exceptions
getConnectedUsers	String	Sequence of ChatData.ConnectedUser	
getChatMessages	String	Sequence of ChatData.ChatMessage	
processSocketEvents			

11.4 Semantics

11.4.1 State Variables

N/A

11.4.2 Environment Variables

httpServer: The REST API server setup in the backend that processes all requests on “/connectedUsers” to **getConnectedUsers(project)** and “/chatMessages” to **getChatMessages(project)**.

JWT: JSON Web Token that is passed to the server from the user’s client as a cookie

11.4.3 Assumptions

httpServer is initialized before any of the functions are called in this module.

11.4.4 Access Routine Semantics

getConnectedUsers(project):

- output: $\text{out} := \text{AuthService.authenticate}(JWT, \text{project}) \equiv \text{true} \Rightarrow \text{ChatDatabaseInterface.getConnectedUsers}(\text{project}) \mid \text{AuthService.authenticate}(JWT, \text{project}) \equiv \text{false} \Rightarrow \langle \rangle$

`getChatMessages(project):`

- output: $\text{out} := \text{AuthService.authenticate}(JWT, \text{project}) \equiv \text{true} \Rightarrow \text{ChatDatabaseInterface.getChatMessages}(\text{project}) \mid \text{AuthService.authenticate}(JWT, \text{project}) \equiv \text{false} \Rightarrow \langle \rangle$

`processSocketEvents():`

Data is the JSON fields passed into the socket event into each event and then passed into each conditional. These events can be emitted from other clients or the Chat Services Module.

- transition: //Described by the following operational spec

$$\begin{aligned} & (\text{ChatSocket.on}(\text{"connected"}, \text{data}) \wedge \text{AuthService.authenticate}(JWT, \text{project}) \equiv \text{true}) \\ & \Rightarrow (\text{ChatDatabaseInterface.addUser}(\text{data.userName}, \text{data.profilePictureUrl}, \text{data.project}) \\ & \wedge \text{ChatSocket.emit}(\text{"newUser"}, \text{data})) \mid \\ & (\text{ChatSocket.on}(\text{"connected"}, \text{data}) \wedge \text{AuthService.authenticate}(JWT, \text{project}) \equiv \text{false}) \\ & \Rightarrow (\text{ChatSocket.disconnect}(\text{data.userName})) \end{aligned}$$

$$\begin{aligned} & (\text{ChatSocket.on}(\text{"disconnect"}, \text{data}) \Rightarrow (\text{ChatDatabaseInterface.removeUser}(\text{data.userName}, \\ & \text{data.project}) \wedge \text{ChatSocket.emit}(\text{"userRemoved"}, \text{data}))) \end{aligned}$$

$$\begin{aligned} & (\text{ChatSocket.on}(\text{"newMessage"}, \text{data}) \wedge \text{AuthService.authenticate}(JWT, \text{project}) \equiv \\ & \text{true}) \Rightarrow (\text{ChatDatabaseInterface.addMessage}(\text{data.userName}, \text{data.message}, \text{data.project}) \\ & \mid \\ & (\text{ChatSocket.on}(\text{"newMessage"}, \text{data}) \wedge \text{AuthService.authenticate}(JWT, \text{project}) \equiv \\ & \text{false}) \Rightarrow (\text{ChatSocket.disconnect}(\text{data.userName})) \end{aligned}$$

11.4.5 Local Functions

N/A

12 MIS of Chat Database Interface Module

12.1 Module

ChatDatabaseInterface

12.2 Uses

ChatData, MongoDB

12.3 Syntax

12.3.1 Exported Constants

N/A

12.3.2 Exported Access Programs

Name	In	Out	Exceptions
getConnectedUsers	String	Sequence of ChatData.ConnectedUser	
getChatMessages	String	Sequence of ChatData.ChatMessage	
addUser	String, String, String		
removeUser	String, String		
addMessage	String, String, String		

12.4 Semantics

12.4.1 State Variables

12.4.2 Environment Variables

N/A

12.4.3 Assumptions

N/A

12.4.4 Access Routine Semantics

getConnectedUsers(projectName):

- output: out := Return the list of users associated with projectName in the chatUsers documents from MongoDB

getChatMessages(projectName):

- output: `out :=` Return all the chat messages in ascending order of time added with `projectName` in the chat documents from MongoDB

`addUser(userName, profilePictureUrl, projectName):`

- output: `out :=` Add a new user to `chatUsers` document with `projectName` in MongoDB with the following data `ChatData.ConnectedUser(userName, profilePicture)`

`removeUser(userName, projectName):`

- output: `out :=` Add a new user to `chatUsers` document with `projectName` and `ChatData.ConnectedUser.userName` *equiv* `userName` in MongoDB

`addMessage(userName, message, projectName):`

- output: `out :=` Add a new message to chat document with `projectName` in MongoDB with the following data `ChatData.ChatMessage(userName, message)`

12.4.5 Local Functions

N/A

13 MIS of Instructions View Module

13.1 Module

InstructionsView

13.2 Uses

N/A

13.3 Syntax

13.3.1 Exported Constants

N/A

13.3.2 Exported Access Programs

Name	In	Out	Exceptions
init			
openInstructions			
closeInstructions			

13.4 Semantics

13.4.1 State Variables

isOpen: \mathbb{B}

13.4.2 Environment Variables

instructionsModal: The popup UI component for displaying the instructions

openButton: Button that will trigger the **openInstructions()** function when clicked

closeButton: Button that will trigger the **closeInstructions()** function when clicked

13.4.3 Assumptions

The init function is ran on page load

13.4.4 Access Routine Semantics

init():

- transition: $isOpen := \text{false}$

Render *openButton* and *closeButton*, and attach onClickListeners on them.

openInstructions():

- transition: $\text{instructionsModal} := isOpen \equiv \text{false} \Rightarrow \text{instructionModal.render()}$

closeInstructions():

- transition: $\text{instructionsModal} := isOpen \equiv \text{true} \Rightarrow \text{instructionModal.unRender()}$

13.4.5 Local Functions

N/A

14 MIS of File Database Interface Module

14.1 Module

FileDatabaseInterface

14.2 Uses

MongoDB

14.3 Syntax

14.3.1 Exported Constants

N/A

14.3.2 Exported Access Programs

Name	In	Out	Exceptions
getFile	String, String	String	RecordDoesNotExist
renameFileByIndex	String, N	String	RecordDoesNotExist
createNewFile	String, String	String	
writeToFile	String, String, String	String	RecordDoesNotExist

14.4 Semantics

14.4.1 State Variables

14.4.2 Environment Variables

MongoDB: MongoDB is a database where the projects and files will be stored which can be represented mathematically as a set of projects which has a list of files

14.4.3 Assumptions

N/A

14.4.4 Access Routine Semantics

getFile(projectName, fileName):

- output: $out := MongoDB.GetOne(projectName, fileName)$
- exception: $exc := Throw\ a\ RecordDoesNotExist\ exception\ if\ no\ such\ record\ exists\ in\ MongoDB$

renameFileByIndex(projectName, index, newName):

- transition: $(\exists p | p \in \text{MongoDB.getFiles}() : p.\text{projectName} \equiv \text{projectName}) \Rightarrow (p.\text{files}[\text{index}].\text{fileName} := \text{newName})$
- exception: exc := Throw a RecordDoesNotExist exception if no such record exists in MongoDB

createNewFile(projectName, fileName):

- transition: MongoDB.InsertOne(projectName, fileName)
- exception: N/A

writeToFile(projectName, fileName, fileData):

- transition: $\exists p | p \in \text{MongoDB} \wedge p.\text{projectName} \equiv \text{projectName} : (\exists f | f \in p.\text{files} \wedge f.\text{fileName} \equiv \text{fileName} : f.\text{content} := \text{fileData})$
- exception: exc := Throw a RecordDoesNotExist exception if no such record exists in MongoDB

14.4.5 Local Functions

N/A

15 MIS of Project Editing Module

15.1 Module

ProjectEditor

15.2 Uses

ProjectDetails, PDF, FileList, Editor, Chat

15.3 Syntax

15.3.1 Exported Constants

15.3.2 Exported Access Programs

Name	In	Out	Exceptions
ProjectEditor			-

15.4 Semantics

15.4.1 State Variables

15.4.2 Environment Variables

editor: editor is the area where the current file to be edited will displayed

fileList: fileList is the area where the list of file in the current project will be displayed

projectDetails: projectDetails is the area where the details such as name and collaborators of the file will be displayed

pdf: pdf is the area where the compiled pdf of the current LaTeX file will be shown *chat*: chat is the area where chat between collaborators will be shown

15.4.3 Assumptions

N/A

15.4.4 Access Routine Semantics

ProjectEditor():

- transition: renders *editor*, *fileList*, *projectDetails*, *pdf*, *chat*
- exception: N/A

15.4.5 Local Functions

N/A

16 MIS of File List Module

16.1 Module

FileList

16.2 Uses

FileToolbar, FileServices, ProjectServices

16.3 Syntax

16.3.1 Exported Constants

16.3.2 Exported Access Programs

Name	In	Out	Exceptions
FileList	String		
openFilePressed	N		

16.4 Semantics

16.4.1 State Variables

projectName: String

16.4.2 Environment Variables

fileListArea: is the GUI component that contains the *fileToolbar* and *listArea*

fileToolbar: fileToolbar is a toolbar to do quick actions on file which is implemented by FileToolbar Module

listArea: listArea is a list which renders multiple GUI components into a list

fileButton: fileButton is a gui component that will trigger openFilePressed()

16.4.3 Assumptions

N/A

16.4.4 Access Routine Semantics

FileList(project):

- transition:
projectName := project

$\forall i | 0 \leq i \leq \text{SIZE} : \text{add}(\text{ProjectServices.getFileName}(\text{projectName}, \text{fileName})[i], i)$
 where SIZE is the size of the list returned by ProjectServices.getFileName(projectName, fileName)

render *fileToolbar* and *listArea* in fileList Area

- exception: N/A

16.4.5 Local Functions

add(fileName):

- transition: add a new *fileButton* with the name *filename* to *listArea* where when *fileButton* is pressed, it will call openFilePressed(fileName)

17 MIS of File Toolbar Module

17.1 Module

FileToolbar

17.2 Uses

NewFile, UploadFile, DeleteFile, FileServices

17.3 Syntax

17.3.1 Exported Constants

17.3.2 Exported Access Programs

Name	In	Out	Exceptions
FileToolbar	string, \mathbb{N}		
newFilePressed			
uploadFilePressed			
deleteFilePressed			
renameFilePressed			RenameFailed

17.4 Semantics

17.4.1 State Variables

projectName: String

currentFileIndex: \mathbb{N}

17.4.2 Environment Variables

newFileButton: is a button that will trigger newFilePressed() when it is pressed

uploadFileButton: is a button that will trigger uploadFilePressed() when it is pressed

deleteFileButton: is a button that will trigger deleteFilePressed() when it is pressed

renameFileButton: is a button that will trigger renameFilePressed() when it is pressed

newFileModal: is a modal implemented by NewFile module

uploadFileModal: is a modal implemented by UploadFile module

renameFileInputField: it is an input field used to type a new name for the file

17.4.3 Assumptions

N/A

17.4.4 Access Routine Semantics

FileToolbar(project, index):

- transition:
projectName := project
currentFileIndex := index
render *newFileButton* and *uploadFileButton*

- exception: N/A

newFilePressed():

- transition: render *newFileModal* and make it visible
- exception: N/A

uploadFilePressed():

- transition: render *uploadFileModal* and make it visible
- exception: N/A

deleteFilePressed():

- transition: renders *deleteFileModal* modal onto the screen using the current file index as a parameter: DeleteFile(currentFileIndex)
- exception: N/A

renameFilePressed():

- transition: renders *renameFileInputField* on top of the button of the current file selected in the list of files. Once the new name is typed and *Enter* key is pressed, the following steps will happen:

FileServices.renameFileInProjectByIndex(projectName, currentFileIndex, newName)
where *newName* is the name typed in *renameFileInputField*

- exception: RenameFailed

17.4.5 Local Functions

N/A

18 MIS of New File Module

This module is a GUI component

18.1 Module

NewFile

18.2 Uses

FileServices

18.3 Syntax

18.3.1 Exported Constants

18.3.2 Exported Access Programs

Name	In	Out	Exceptions
NewFile	String		-
confirmButtonPressed			FileNotCreated
cancelButtonPressed			-

18.4 Semantics

18.4.1 State Variables

projectName: String

18.4.2 Environment Variables

fileNameInputField: input field where the name of the file will be inputted

confirmButton: button that will trigger confirmButtonPressed when it is pressed

cancelButton: button that will trigger cancelButtonPressed when it is pressed

18.4.3 Assumptions

N/A

18.4.4 Access Routine Semantics

NewFile(project):

- transition:
projectName := project
renders *fileNameInputField*, *confirmButton*, *cancelButton*
- exception: N/A

confirmButtonPressed():

- transition: FileServices.createNewFile(projectName)
- exception: FileNotCreated

cancelButtonPressed():

- transition: closes this modal
- exception: N/A

18.4.5 Local Functions

N/A

19 MIS of Upload File Module

This module is a GUI component

19.1 Module

UploadFile

19.2 Uses

FileServices

19.3 Syntax

19.3.1 Exported Constants

19.3.2 Exported Access Programs

Name	In	Out	Exceptions
UploadFile	String		-
confirmButtonPressed			FileNotCreated
cancelButtonPressed			-
onChange			-

19.4 Semantics

19.4.1 State Variables

projectName: String

file: File # File is web representation of a file

19.4.2 Environment Variables

fileInput: file uploader GUI component that opens the window that lets you choose your local file and will trigger onChange(event) once file is selected

confirmButton: button that will trigger confirmButtonPressed when it is pressed

cancelButton: button that will trigger cancelButtonPressed when it is pressed

19.4.3 Assumptions

N/A

19.4.4 Access Routine Semantics

UploadFile(project):

- transition:
 projectName := project
 renders *fileInput*, *confirmButton*, *cancelButton*
- exception: N/A

confirmButtonPressed():

- transition: FileServices.uploadFile(projectName, file)
- exception: FileNotCreated

cancelButtonPressed():

- transition: closes this modal
- exception: N/A

onChange(event):

- transition: file := event.target.files[0]
- exception: N/A

19.4.5 Local Functions

N/A

20 MIS of Editor File Module

This module is a GUI component

20.1 Module

Editor

20.2 Uses

UserCursor, TextHighlighting, SyntaxHighlighting, FileSynchronization

20.3 Syntax

20.3.1 Exported Constants

20.3.2 Exported Access Programs

Name	In	Out	Exceptions
init	string, setCurrentText: (string \rightarrow void)		-

20.4 Semantics

20.4.1 State Variables

modified: \mathbb{B}

documentID: string

20.4.2 Environment Variables

codeMirror: codeMirror is the editor component that is implemented by CodeMirror library
localStorage: localStorage is storage used by the browser which Undertree will use to store data such as username

websocketProvider: websocketProvider is a web socket used by the YJS library to synchronize file content between the collaborators

20.4.3 Assumptions

Editor.init() is called during the initial render

20.4.4 Access Routine Semantics

init(currentFilePath, setCurrentText):

- transition: *webSocketProvider* is assigned a new instance of a socket created using *currentFilePath*. Registers *UserCursor*, *SyntaxHighlighting* modules with *codeMirror*. Binds *codeMirror* to *webSocketProvider* so that the editor is synchronized using YJS's websocket. *codeMirror* also gets binded to event listener that will call *setCurrentText(t)* and *addUserToModified()* whenever the editor is updated, where *t* is the text in the editor. Lastly, *documentID := currentFilePath*
- exception: N/A

20.4.5 Local Functions

addUserToModified():

- transition: *modified = true* \Rightarrow *modified := true* and make a API call to the server to add *localStorage.username* to the list of the contributor for the file with file path equals to *documentID*.

21 MIS of Projects Module

21.1 Module

Projects

21.2 Uses

ProjectList, ProjectCreation

21.3 Syntax

21.3.1 Exported Constants

21.3.2 Exported Access Programs

Name	In	Out	Exceptions
createProjectButtonPressed			-

21.4 Semantics

21.4.1 State Variables

21.4.2 Environment Variables

createProjectButton: a button that leads to the project creation screen implemented in the projectCreation module, triggers the createProjectButtonPressed() function

projectList: a GUI component implemented in the projectList module

21.4.3 Assumptions

N/A

21.4.4 Access Routine Semantics

createProjectButtonPressed():

- transition: triggers ProjectCreation.ProjectCreation()
- exception: N/A

21.4.5 Local Functions

N/A

22 MIS of Project List Module

22.1 Module

ProjectList

22.2 Uses

ProjectServices, ProjectDeletion

22.3 Syntax

22.3.1 Exported Constants

22.3.2 Exported Access Programs

Name	In	Out	Exceptions
ProjectList			-
openButtonPressed			-
deleteButtonPressed			-

22.4 Semantics

22.4.1 State Variables

selectedProject: String

22.4.2 Environment Variables

projectList: projectList is the area where the list of projects is displayed

projectLabel: project is a block in the projectList for an individual project being displayed

openButton: openButton is a button next to a projectLabel, clicking it triggers openButtonPressed()

deleteButton: deleteButton is a button next to a projectLabel, clicking it triggers deleteButtonPressed()

22.4.3 Assumptions

N/A

22.4.4 Access Routine Semantics

openButtonPressed():

- transition: triggers ProjectEditing.ProjectEditor()
- exception: N/A

deleteButtonPressed():

- transition: triggers ProjectDeletion.ProjectDeletion()
- exception: N/A

ProjectList():

- transition: renders ProjectList module
- exception: N/A

22.4.5 Local Functions

N/A

23 MIS of Project Deletion Module

23.1 Module

ProjectDeletion

23.2 Uses

ProjectServices

23.3 Syntax

23.3.1 Exported Constants

23.3.2 Exported Access Programs

Name	In	Out	Exceptions
ProjectDeletion			-
confirmButtonPressed			-
cancelButtonPressed			-

23.4 Semantics

23.4.1 State Variables

projectName: String

ownerName: String

23.4.2 Environment Variables

confirmButton: *confirmButton* is the button that will appear in the modal to confirm delete action. It will trigger the *confirmButtonPressed()* function.

confirmActionMessage: *confirmActionMessage* is a text message that will ask the user if they are sure they want to delete the selected project

cancelButton: *cancelButton* is the button that will appear in the modal to abort deletion and return, it will trigger the *cancelButtonPressed()* function

successMessage: a message showing that the deletion was successful

23.4.3 Assumptions

N/A

23.4.4 Access Routine Semantics

ProjectDeletion():

- transition: renders ProjectDeletion module
- exception: N/A

confirmButtonPressed():

- transition: triggers ProjectServices.deleteProject(projectName, ownerName), renders *successMessage*, closes *confirmActionMessage*
- exception: N/A

cancelButtonPressed():

- transition: closes *confirmActionMessage*
- exception: N/A

23.4.5 Local Functions

N/A

24 MIS of Project Creation Module

24.1 Module

ProjectCreation

24.2 Uses

NewProject, ImportProject

24.3 Syntax

24.3.1 Exported Constants

24.3.2 Exported Access Programs

Name	In	Out	Exceptions
ProjectCreation			-
newButtonPressed			-
importButtonPressed			-

24.4 Semantics

24.4.1 State Variables

24.4.2 Environment Variables

createNewButton: button that will allow user to create a project from scratch, triggers newButtonPressed()

createFromImportButton: button that will allow user to import a project, triggers importButtonPressed()

24.4.3 Assumptions

N/A

24.4.4 Access Routine Semantics

newButtonPressed():

- transition: triggers NewProject.NewProject()
- exception: N/A

importButtonPressed():

- transition: triggers ImportProject.ImportProject()
- exception: N/A

ProjectCreation():

- transition: renders ProjectCreation module
- exception: N/A

24.4.5 Local Functions

N/A

25 MIS of New Project Module

25.1 Module

NewProject

25.2 Uses

ProjectServices

25.3 Syntax

25.3.1 Exported Constants

25.3.2 Exported Access Programs

Name	In	Out	Exceptions
NewProject			-
createButtonPressed			InvalidInput

25.4 Semantics

25.4.1 State Variables

projectName: String

ownerName: String

collaborators: Set of Strings

creationDate: String

25.4.2 Environment Variables

projectForm: Form area on page that contains input fields *projectNameField*: Text input field where user will enter the desired project name

collaboratorsField: Text input field where user will list the desired collaborators

creationDateTag: Text feild with auto-populated date

createButton: Button that will submit the project form content, triggers createButtonPressed()

25.4.3 Assumptions

N/A

25.4.4 Access Routine Semantics

NewProject():

- transition: renders NewProject module
- exception: N/A

createButtonPressed():

- transition: triggers ProjectServices.addProject(projectName, projectOwner, creationDate, collaborators, []), closes NewProject module
- exception: exc := Throw InvalidInputError if any of the input fields contain forbidden or null characters

25.4.5 Local Functions

N/A

26 MIS of Import Project Module

26.1 Module

ImportProject

26.2 Uses

ProjectServices

26.3 Syntax

26.3.1 Exported Constants

26.3.2 Exported Access Programs

Name	In	Out	Exceptions
ImportProject			-
createButtonPressed			InvalidInput
selectProjectButtonPressed			-

26.4 Semantics

26.4.1 State Variables

projectName: String

ownerName: String

collaborators: Set of Strings

creationDate: String

26.4.2 Environment Variables

projectList: Area on page that displays a list of possible projects to import from *selectProjectButton*: Button that triggers `selectProjectButtonPressed()` *projectDetails*: Form area on page that contains input fields *projectNameField*, *collaboratorsField*, *creationDateTag*, and *createButton*

projectNameField: Text input field where user will enter the desired project name

collaboratorsField: Text input field where user will list the desired collaborators

creationDateTag: Text feild with auto-populated date

createButton: Button that will submit the project form content, triggers createButtonPressed()

26.4.3 Assumptions

N/A

26.4.4 Access Routine Semantics

ImportProject():

- transition: renders ImportProject module
- exception: N/A

selectProjectButtonPressed():

- transition: triggers ProjectServices.getProject(projectName, ownerName), renders *projectDetails*
- transition: projectName := ProjectServices.getProject().projectName
- transition: collaborators := ProjectServices.getProject().collaborators
- transition: creationDate := ProjectServices.getProject().date
- exception: N/A

createButtonPressed():

- transition: triggers ProjectServices.addProject(projectName, projectOwner, creationDate, collaborators, []), closes ImportProject module
- exception: exc := Throw InvalidInputError if any of the input fields contain forbidden or null characters

26.4.5 Local Functions

N/A

27 MIS of Project Database Interface Module

27.1 Module

ProjectDatabaseInterface

27.2 Uses

ProjectData

27.3 Syntax

27.3.1 Exported Constants

27.3.2 Exported Access Programs

Name	In	Out	Exceptions
getProject	String, String, String	Sequence of Strings	RecordDoesNotExist
addProject	String, String, String[], String[]		InvalidInput
deleteProject	String, String		RecordDoesNotExist
editProjectDetail	String, String, String, String		InvalidInput, RecordDoesNotExist

27.4 Semantics

27.4.1 State Variables

27.4.2 Environment Variables

projectDirectory: The storage on the server where project details are stored

27.4.3 Assumptions

N/A

27.4.4 Access Routine Semantics

getProject(projectName, projectOwner):

- output: out := Return the project associated with the project name and owner name from MongoDB if it exists
- exception: exc := Throw a RecordDoesNotExist exception if no such record exists in MongoDB

addProject(projectName, projectOwner, date, collaborators[], files[]):

- transition: Insert a record for a project into MongoDB with the given name, owner, date, collaborators, and files
- exception: `exc := Throw a InvalidInput exception` if any of the supplied parameters contain forbidden characters or are null

`deleteProject(projectName, projectOwner):`

- transition: Remove the record for the project associated with the project name and owner name from MongoDB if it exists
- exception: `exc := Throw a RecordDoesNotExist exception` if no such record exists in MongoDB

`editProjectDetail(projectName, owner, key, newValue):`

- transition: Update the given key with the given `newValue` for a record with the given `projectName` and `owner`
- exception: `exc := Throw a InvalidInput exception` if any of the supplied parameters contain forbidden characters or are null
- exception: `exc := Throw a RecordDoesNotExist exception` if no such record exists in MongoDB

27.4.5 Local Functions

N/A

28 MIS of Project Services Module

28.1 Module

ProjectServices

28.2 Uses

ProjectDatabaseInterface, ProjectData, AuthService

28.3 Syntax

28.3.1 Exported Constants

28.3.2 Exported Access Programs

Name	In	Out	Exceptions
deleteProject	String, String		-
addProject	String, String, String, String[], String[]		-
getProject	String, String	Sequence of Strings	-
editProjectDetail	String, String, String, String		-

28.4 Semantics

28.4.1 State Variables

28.4.2 Environment Variables

JWT: JSON Web Token that is passed to the server from the user's client as a cookie

28.4.3 Assumptions

AuthService.authenticate(JWT, project) will be called and all functions will only run if AuthService.authenticate(jwt, project) returns true.

28.4.4 Access Routine Semantics

getProject(projectName, projectOwner):

- output: out := Return ProjectDatabaseInterface.deleteProject(projectName, projectOwner)
- exception: N/A

addProject(projectName, projectOwner, date, collaborators[], files[]):

- transition: trigger ProjectDatabaseInterface.addProject(projectName, projectOwner, date, collaborators[], files[])

- exception: N/A

deleteProject(projectName, projectOwner):

- transition: returns ProjectDatabaseInterface.deleteProject(projectName, projectOwner)
- exception: N/A

editProjectDetail(projectName, owner, key, newValue):

- transition : returns ProjectDatabaseInterface.editProjectDetail(projectName, owner, key, newValue)
- exception: N/A

28.4.5 Local Functions

N/A

29 MIS of GitHub Module

29.1 Module

GitHub

29.2 Uses

GitHubServices

29.3 Syntax

29.3.1 Exported Constants

N/A

29.3.2 Exported Access Programs

Name	In	Out	Exceptions
viewLog			
commitChanges	Map of String		
pushChanges			

29.4 Semantics

29.4.1 State Variables

logReqData: Map of String

logData: Seq of String

changesSelected: Map of String

29.4.2 Environment Variables

viewLogButton: is a button that will trigger viewLog() when it is pressed

selectLines: is a button that allows user to highlight blocks of text for changes they want to commit which is then stored in changesSelected

commitChangesButton: is a button that will trigger commitChanges() when it is pressed

pushChangesButton: is a button that will trigger pushChanges() when it is pressed

29.4.3 Assumptions

You can only click the *pushChangesButton* if you've committed previously. The UnderTree user data is cached and can be retrieved from a browser cookie.

29.4.4 Access Routine Semantics

`viewLog()`: calls `GitHubServices.retrieveLog(logReqData)` and passes in the user that clicked it along with the necessary information in `logReqData`. The data is then retrieved from the backend and updates the log view.

`commitChanges()`: calls `GitHubServices.createCommit(data)` and passes in *changesSelected* along with other the necessary information in `data`.

`pushChanges()`: calls `GitHubServices.pushCommit(data)` and passes in the user that clicked it along with the necessary information in `data`.

29.4.5 Local Functions

N/A

30 MIS of GitHub Services Module

30.1 Module

GitHubServices

30.2 Uses

ProjectServices, FileServices

30.3 Syntax

30.3.1 Exported Constants

N/A

30.3.2 Exported Access Programs

Name	In	Out	Exceptions
retrieveLog	String		
createCommit	String		
pushCommit	String		

30.4 Semantics

30.4.1 State Variables

N/A

30.4.2 Environment Variables

N/A

30.4.3 Assumptions

N/A

30.4.4 Access Routine Semantics

retrieveLog(data): Extracts the user data from the parameter and calls AuthService.checkAuth(user, log) and validates that the user is authorized to make this operation. Then it obtains the project id from the data object, based on that user object, It runs a GitHub API to retrieve the logs and then returns the logs.

createCommit(data): Extracts the user data from the parameter and calls AuthService.checkAuth(user, commit) and validates that the user is authorized to make this operation. Then it obtains

the necessary information from the data object, like user id, project id and file content. It then gets the HEAD commit by calling `getHEADCommit()`, and the tree that the HEAD commit points to by calling `getTree()`. Then it creates a new tree with the new content and creates a new commit. This commit is then stored in Project Data for later when the user wants to push it.

`pushCommit(data)`: Extracts the user data from the parameter and calls `AuthService.checkAuth(user, push)` and validates that the user is authorized to make this operation. Then it obtains the latest commit from Project Data and then pushes it to GitHub using the API. It will use the SHA from the commit to update the reference, effectively moving the HEAD reference to the latest commit.

30.4.5 Local Functions

`getHEADCommit()`: Obtains the commit that HEAD points to using the GitHub API and returns it.

`getTree()`: Obtains the tree that HEAD commit refers to using the GitHub API and returns it.

31 MIS of Authentication Module

31.1 Module

Authentication

31.2 Uses

AuthService

31.3 Syntax

31.3.1 Exported Constants

N/A

31.3.2 Exported Access Programs

Name	In	Out	Exceptions
loginUser	String		
logoutUser	String		
openLogin			
closeLogin			

31.4 Semantics

31.4.1 State Variables

openLogin: \mathbb{B}

31.4.2 Environment Variables

loginButton: is a button that will trigger **openLogin()** when it is pressed

loginModal: The popup UI component for displaying the login form, it renders based on the value of **openLogin()**

submitLogin: is a button that will trigger **loginUser()** when it is pressed and if successful, triggers **closeLogin()**

logoutButton: is a button that will trigger **logoutUser()** when it is pressed

31.4.3 Assumptions

The user's auth data will be cached on browser which can be retrieved as well.

31.4.4 Access Routine Semantics

`loginUser(userData)`: Calls the `AuthService.loginAuth(userData)` and passes along the login details that the user entered.

`logoutUser(userData)`: Calls `AuthService.logoutAuth(userData)` passing along the `userData` saved on browser.

`openLogin()`: Assigns `openLogin` value to `True`, which opens the login modal.

`closeLogin()`: Assigns `openLogin` value to `False`, which closes the login modal.

31.4.5 Local Functions

N/A

32 MIS of Auth Service Module

32.1 Module

AuthService

32.2 Uses

AuthDatabaseInterface, AuthData

32.3 Syntax

32.3.1 Exported Constants

N/A

32.3.2 Exported Access Programs

Name	In	Out	Exceptions
loginAuth	String		
logoutAuth	String		
checkAuth	String, String	\mathbb{B}	
authenticate	String, String	\mathbb{B}	

32.4 Semantics

32.4.1 State Variables

N/A

32.4.2 Environment Variables

N/A

32.4.3 Assumptions

N/A

32.4.4 Access Routine Semantics

loginAuth(userData): Extracts the code needed to authenticate with the GitHub API, and then uses that to receive the tokens from GitHub which will be stored to make GitHub operations on behalf of the user by calling AuthDatabaseInterface.saveToken(token).

`logoutAuth(userData)`: Retrieves the access token of the user and then communicates with the GitHub API to delete it to log the user out of the system.

`checkAuth(userData, operation)`: Uses the access token to determine the user's roles and if they are authorized to perform the GitHub operation that is requested and then returns a boolean based on if it accepts or rejects the request.

`authenticate(jwt, projectName)`: Validates the JWT token and that the user logged in to the browser has access to the project. It returns a boolean based on the answer.

32.4.5 Local Functions

N/A

33 MIS of Auth Database Interface Module

33.1 Module

AuthDatabaseInterface

33.2 Uses

AuthData

33.3 Syntax

33.3.1 Exported Constants

N/A

33.3.2 Exported Access Programs

Name	In	Out	Exceptions
saveToken	String		
tokenExists	String	\mathbb{B}	

33.4 Semantics

33.4.1 State Variables

N/A

33.4.2 Environment Variables

N/A

33.4.3 Assumptions

N/A

33.4.4 Access Routine Semantics

saveToken(token): Receives the token and saves it in the MongoDB database based on the type of token.

tokenExists(token): Checks to see if the token exists in the database to validate several use cases like the user is logged in.

33.4.5 Local Functions

N/A

34 MIS of Auth Data Module

34.1 Module

AuthData

34.2 Uses

N/A

34.3 Syntax

34.3.1 Exported Data Types

UserData: tuple of (userName: String, token: String)

34.3.2 Exported Constants

N/A

34.3.3 Exported Access Programs

N/A

34.4 Semantics

34.4.1 State Variables

N/A

34.4.2 Environment Variables

N/A

34.4.3 Assumptions

N/A

34.4.4 Access Routine Semantics

N/A

34.4.5 Local Functions

N/A

References

- Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. *Fundamentals of Software Engineering*. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.
- Daniel M. Hoffman and Paul A. Strooper. *Software Design, Automated Testing, and Maintenance: A Practical Approach*. International Thomson Computer Press, New York, NY, USA, 1995. URL <http://citeseer.ist.psu.edu/428727.html>.

35 Appendix

[Extra information if required —SS]