

# Module Guide for UnderTree

Team 22, Capstoners  
Palanichamy Veerash  
Kannammalil Kevin  
Qureshi Eesha  
Ahmed Faiq

April 5, 2023

# 1 Revision History

Date	Version	Notes
January 14	1.0	Initial document created
January 15	1.1	Anticipated changes and hierarchy diagram added
January 17	1.2	Rest of document finished
April 5	1.5	Final document changes

## 2 Reference Material

This section records information for easy reference.

### 2.1 Abbreviations and Acronyms

symbol	description
AC	Anticipated Change
DAG	Directed Acyclic Graph
M	Module
MG	Module Guide
OS	Operating System
R	Requirement
SC	Scientific Computing
SRS	Software Requirements Specification
HTTP	Hypertext Transfer Protocol, a protocol used to communicate over the internet
TCP	Transmission Control Protocol, a protocol used to communicate over the internet
PDF	A file type to display text and images

# Contents

<b>1</b>	<b>Revision History</b>	<b>i</b>
<b>2</b>	<b>Reference Material</b>	<b>ii</b>
2.1	Abbreviations and Acronyms . . . . .	ii
<b>3</b>	<b>Introduction</b>	<b>1</b>
<b>4</b>	<b>Anticipated and Unlikely Changes</b>	<b>2</b>
4.1	Anticipated Changes . . . . .	2
4.2	Unlikely Changes . . . . .	3
<b>5</b>	<b>Module Hierarchy</b>	<b>4</b>
<b>6</b>	<b>Connection Between Requirements and Design</b>	<b>6</b>
<b>7</b>	<b>Module Decomposition</b>	<b>7</b>
7.1	Hardware Hiding Modules (M1) . . . . .	7
7.2	Behaviour-Hiding Module . . . . .	7
7.2.1	Project Editing Module (M2) . . . . .	7
7.2.2	Editor Module (M3) . . . . .	7
7.2.3	Syntax Highlight Module (M4) . . . . .	8
7.2.4	File List Module (M6) . . . . .	8
7.2.5	File Toolbar Module (M7) . . . . .	8
7.2.6	New File Module (M8) . . . . .	8
7.2.7	Upload File Module (M9) . . . . .	8
7.2.8	User Cursors Module (M10) . . . . .	9
7.2.9	Text Highlighting Module (M11) . . . . .	9
7.2.10	File Synchronization Module (M12) . . . . .	9
7.2.11	File Services (M13) . . . . .	9
7.2.12	File Database Interface Module (M14) . . . . .	10
7.2.13	PDF Module (M15) . . . . .	10
7.2.14	PDF Renderer Module (M16) . . . . .	10
7.2.15	PDF Compiler Module (M17) . . . . .	10
7.2.16	Chat Module (M18) . . . . .	11
7.2.17	Chat Services Module (M19) . . . . .	11
7.2.18	Chat Database Interface Module (M20) . . . . .	11
7.2.19	Chat Socket Module (M21) . . . . .	11
7.2.20	Instructions View Module (M23) . . . . .	12
7.2.21	Projects (M24) . . . . .	12
7.2.22	Project List (M25) . . . . .	12
7.2.23	Project Deletion (M26) . . . . .	12
7.2.24	Project Creation (M27) . . . . .	13

7.2.25	New Project (M28)	13
7.2.26	Import Project (M29)	13
7.2.27	Project Services (M30)	13
7.2.28	Project Database Interface (M31)	14
7.2.29	GitHub Module (M33)	14
7.2.30	GitHub Services Module (M34)	14
7.2.31	Authentication Module (M35)	14
7.2.32	Auth Service Module (M36)	14
7.2.33	Auth Database Interface Module (M37)	15
7.3	Software Decision Module	15
7.3.1	File Data Module (M40)	15
7.3.2	Chat Data Module (M22)	15
7.3.3	Project Data (M32)	15
7.3.4	Auth Data Module (M38)	16
7.3.5	MongoDB Module (M39)	16
<b>8</b>	<b>Traceability Matrix</b>	<b>17</b>
<b>9</b>	<b>Use Hierarchy Between Modules</b>	<b>22</b>

## List of Tables

1	Module Hierarchy	6
2	Trace Between Functional Requirements and Modules	17
3	Trace Between Nonfunctional Requirements and Modules	19
4	Trace Between Anticipated Changes and Modules	21

## List of Figures

1	Use hierarchy among modules Image source	22
---	------------------------------------------	----

### 3 Introduction

Decomposing a system into modules is a commonly accepted approach to developing software. A module is a work assignment for a programmer or programming team (?). We advocate a decomposition based on the principle of information hiding (?). This principle supports design for change, because the “secrets” that each module hides represent likely future changes. Design for change is valuable in SC, where modifications are frequent, especially during initial development as the solution space is explored.

Our design follows the rules layed out by ?, as follows:

- System details that are likely to change independently should be the secrets of separate modules.
- Each data structure is implemented in only one module.
- Any other program that requires information stored in a module’s data structures must obtain it by calling access programs belonging to that module.

After completing the first stage of the design, the Software Requirements Specification (SRS), the Module Guide (MG) is developed (?). The MG specifies the modular structure of the system and is intended to allow both designers and maintainers to easily identify the parts of the software. The potential readers of this document are as follows:

- New project members: This document can be a guide for a new project member to easily understand the overall structure and quickly find the relevant modules they are searching for.
- Maintainers: The hierarchical structure of the module guide improves the maintainers’ understanding when they need to make changes to the system. It is important for a maintainer to update the relevant sections of the document after changes have been made.
- Designers: Once the module guide has been written, it can be used to check for consistency, feasibility, and flexibility. Designers can verify the system in various ways, such as consistency among modules, feasibility of the decomposition, and flexibility of the design.

The rest of the document is organized as follows. Section 4 lists the anticipated and unlikely changes of the software requirements. Section 5 summarizes the module decomposition that was constructed according to the likely changes. Section 6 specifies the connections between the software requirements and the modules. Section 7 gives a detailed description of the modules. Section 8 includes two traceability matrices. One checks the completeness of the design against the requirements provided in the SRS. The other shows the relation between anticipated changes and the modules. Section 9 describes the use relation between modules.

## 4 Anticipated and Unlikely Changes

This section lists possible changes to the system. According to the likeliness of the change, the possible changes are classified into two categories. Anticipated changes are listed in Section 4.1, and unlikely changes are listed in Section 4.2.

### 4.1 Anticipated Changes

Anticipated changes are the source of the information that is to be hidden inside the modules. Ideally, changing one of the anticipated changes will only require changing the one module that hides the associated decision. The approach adapted here is called design for change.

- AC1:** The data structure and algorithm used to implement the virtual hardware.
- AC2:** How the components related to project editing will be displayed
- AC3:** How the current file being edited is displayed
- AC4:** The algorithm used to highlight syntax of the LaTeX code
- AC6:** How the list of files in the current project being edited will be displayed
- AC7:** The actions available on the file toolbar
- AC8:** Inputs needed to create a new file
- AC9:** Inputs needed to upload a file
- AC10:** Algorithm used for determine cursor position for all users currently editing the file
- AC11:** Algorithm used for highlighting text selected by other users
- AC12:** Algorithm used for synchronizing the file for all the users currently editing the file
- AC13:** The data type used to store files
- AC14:** The database queries used to save and retrieve file data
- AC15:** How the user will trigger the compilation of the LaTeX and download of the PDF file
- AC16:** How the user will view the PDF file
- AC17:** The algorithm used to compile the LaTeX code into a PDF
- AC18:** How the user will view and interact with the chat messages
- AC19:** The algorithm used to send and receive chat messages

**AC20:** The database queries used to save and retrieve chat data

**AC21:** The communication protocol used to communicate between users

**AC22:** The data type used for chat messages

**AC23:** How the instructions are displayed

**AC24:** How informational and actionable items related to project are displayed

**AC25:** How the project list are displayed

**AC26:** The methods used to delete a project

**AC27:** Different methods to create a project

**AC28:** Inputs needed to create a new project

**AC29:** Inputs needed to import a project

**AC30:** The different services offered in regards to creation, editing, and reading projects

**AC31:** The algorithm used to fetch project data from the database

**AC32:** The format of project data

**AC33:** The user interface to interact with GitHub

**AC34:** The user interface to login and logout with GitHub

**AC35:** The algorithm to authenticate the user with GitHub

**AC36:** The functions used to save and retrieve authentication data for a user

**AC37:** The datatype for authenticating a user

**AC40:** How data is stored

## 4.2 Unlikely Changes

The module design should be as general as possible. However, a general system is more complex. Sometimes this complexity is not necessary. Fixing some design decisions at the system architecture stage can simplify the software design. If these decision should later need to be changed, then many parts of the design will potentially need to be modified. Hence, it is not intended that these decisions will be changed.

**UC1:** Input using mouse and keyboard



**UC2:** Output using computer monitor. Limited but existing functionality for mobile devices

**UC3:** Utilizing GitHub for version control

**UC4:** Using access tokens and JWTs to authentication and security

## 5 Module Hierarchy

This section provides an overview of the module design. Modules are summarized in a hierarchy decomposed by secrets in Table 5. The modules listed below, which are leaves in the hierarchy tree, are the modules that will actually be implemented.

**M1:** Hardware-Hiding Module

**M2:** Project Editing Module

**M3:** Editor Module

**M4:** Syntax Highlighting Module

**M6:** File List Module

**M7:** File Toolbar Module

**M8:** New File Module

**M9:** Upload File Module

**M10:** User Cursors Module

**M11:** Text Highlighting Module

**M12:** File Synchronization Module

**M13:** File Services Module

**M14:** File Database Interface Module

**M15:** PDF Module

**M16:** PDF Renderer Module

**M17:** PDF Compiler Module

**M18:** Chat Module

**M19:** Chat Services Module

**M20:** Chat Database Interface Module

**M21:** Chat Socket Module

**M22:** Chat Data Module

**M23:** Instructions View Module

**M24:** Projects

**M25:** Project List

**M26:** Project Deletion

**M27:** Project Creation

**M28:** New Project

**M29:** Import Project

**M30:** Project Services

**M31:** Project Database Interface

**M32:** Project Data

**M33:** GitHub Module

**M34:** GitHub Services Module

**M35:** Authentication Module

**M36:** Auth Service Module

**M37:** Auth Database Interface Module

**M38:** Auth Data Module

**M39:** MongoDB

**M40:** File Data

Table 1: Module Hierarchy

Level 1	Level 2
Hardware-Hiding Module	Project Editing Module Editor Module Syntax Highlighting Module File List Module File Toolbar Module New File Module Upload File Module User Cursors Module Text Highlighting Module File Synchronization Module File Services Module File Database Interface Module PDF Module PDF Renderer Module PDF Compiler Module Chat Module Chat Services Module Chat Database Interface Module Behaviour-Hiding Module Chat Socket Module Instructions View Module Projects Module Project List Module Project Deletion Module Project Creation Module New Project Module Import Project Module Project Services Module Project Database Interface Module GitHub Module GitHub Services Module Authentication Module Auth Service Module Auth Database Interface Module
Software Decision Module	File Data Module Chat Data Module Project Data Module Auth Data Module MongoDB Module

## 6 Connection Between Requirements and Design

The design of the system is intended to satisfy the requirements developed in the SRS. In this stage, the system is decomposed into modules. The connection between requirements and modules is listed in Table 2 and 3.

## 7 Module Decomposition

Modules are decomposed according to the principle of “information hiding” proposed by ?. The *Secrets* field in a module decomposition is a brief statement of the design decision hidden by the module. The *Services* field specifies *what* the module will do without documenting *how* to do it. For each module, a suggestion for the implementing software is given under the *Implemented By* title. If the entry is *OS*, this means that the module is provided by the operating system or by standard programming language libraries. *UnderTree* means the module will be implemented by the UnderTree software.

Only the leaf modules in the hierarchy have to be implemented. If a dash (–) is shown, this means that the module is not a leaf and will not have to be implemented.

### 7.1 Hardware Hiding Modules (M1)

**Secrets:** The data structure and algorithm used to implement the virtual hardware.

**Services:** Serves as a virtual hardware used by the rest of the system. This module provides the interface between the hardware and the software. So, the system can use it to display outputs or to accept inputs.

**Implemented By:** OS

### 7.2 Behaviour-Hiding Module

#### 7.2.1 Project Editing Module (M2)

**Secrets:** How the components related to project editing will be displayed

**Services:** Displays the various components of project editing which are the file editor, file list, PDF output and information about the project being edited

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

#### 7.2.2 Editor Module (M3)

**Secrets:** How the current file being edited is displayed

**Services:** Displays the content of the current file being edited and details about that file

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.3 Syntax Highlight Module (M4)

**Secrets:** The algorithm used to highlight syntax of the LaTeX code

**Services:** T module will highlight the text based on LaTeX syntax

**Implemented By:** Highlight.js

**Type of Module:** Library

### 7.2.4 File List Module (M6)

**Secrets:** How the list of files in the current project being edited will be displayed

**Services:** Displays the list of files in the current project and allows the user to open them in the editor, rename or delete a file

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.5 File Toolbar Module (M7)

**Secrets:** The actions available on the file toolbar

**Services:** Allows for actions regarding file such as adding a new file or uploading a new file

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.6 New File Module (M8)

**Secrets:** Inputs needed to create a new file

**Services:** Creates a new file in the project using name and extension as input

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.7 Upload File Module (M9)

**Secrets:** Inputs needed to upload a file

**Services:** Uploads a local file to the current project being edited

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.8 User Cursors Module (M10)

**Secrets:** Algorithm used for determine cursor position for all users currently editing the file

**Services:** Gives the current cursor position for the a spcecific user in the editor

**Implemented By:** YJS

**Type of Module:** Library

### 7.2.9 Text Highlighting Module (M11)

**Secrets:** Algorithm used for highlighting text selected by other users

**Services:** Gives the current highlighted text for the a specific user in the editor

**Implemented By:** YJS

**Type of Module:** Library

### 7.2.10 File Synchronization Module (M12)

**Secrets:** Algorithm used for synchronizing the file for all the users currently editing the file

**Services:** Displays the file with all the changes made by different collaborators up until that current instance of time

**Implemented By:** YJS

**Type of Module:** Abstract Object

### 7.2.11 File Services (M13)

**Secrets:** The data type used to store files

**Services:** Offers services for creating new file, editing existing files, deleting a file, and getting information about one or more files

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.12 File Database Interface Module (M14)

**Secrets:** The database queries used to save and retrieve file data

**Services:** This module is responsible for providing the functions to make the relevant queries to save and retrieve file data

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.13 PDF Module (M15)

**Secrets:** How the user will trigger the compilation of the LaTeX and download of the PDF file

**Services:** This module is responsible for allowing the user to download, and start the compilation for the LaTeX to PDF

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.14 PDF Renderer Module (M16)

**Secrets:** How the user will view the PDF file

**Services:** This module is responsible for allowing the user to view the LaTeX file

**Implemented By:** [PDF.js](#)

**Type of Module:** Abstract Object

### 7.2.15 PDF Compiler Module (M17)

**Secrets:** The algorithm used to compile the LaTeX code into a PDF

**Services:** Upon getting a request from the PDF module to compile the PDF this module is used to convert the LaTeX code into a PDF which the user can view

**Implemented By:** [node-LaTeX](#)

**Type of Module:** Library

### 7.2.16 Chat Module (M18)

**Secrets:** How the user will view and interact with the chat messages

**Services:** This module is responsible for allowing the user to view and input chat messages

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.17 Chat Services Module (M19)

**Secrets:** The algorithm used to send and receive chat messages

**Services:** This module is responsible for sending and receiving chat messages between users

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.18 Chat Database Interface Module (M20)

**Secrets:** The database queries used to save and retrieve chat data

**Services:** This module is responsible for providing the functions needed to make the relevant queries to save and retrieve chat data

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.19 Chat Socket Module (M21)

**Secrets:** The communication protocol used to communicate between users

**Services:** This module is responsible for providing the web sockets needed to communicate between users in a synchronized manner

**Implemented By:** [Socket.IO](#)

**Type of Module:** Abstract Object



### 7.2.20 Instructions View Module (M23)

**Secrets:** How the instructions are displayed

**Services:** This module is responsible for allowing users to open and close as well as view the instructions in an organized manner

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.21 Projects (M24)

**Secrets:** How informational and actionable items related to project are displayed

**Services:** This module displays the project list, allows the creation of new project and also displays other items related to projects

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.22 Project List (M25)

**Secrets:** How the project list are displayed

**Services:** This module displays a list of all the available projects to the user which can be opened or deleted

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.23 Project Deletion (M26)

**Secrets:** The methods used to delete a project

**Services:** Allows users to delete the project

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

#### 7.2.24 Project Creation (M27)

**Secrets:** The modal that contains the different methods to create a project (creation or import)

**Services:** Presents a user interface for users to choose how they want to create their project either from scratch or importing a pre-existing project

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

#### 7.2.25 New Project (M28)

**Secrets:** Inputs needed to create a new project

**Services:** Presents a user interface for users to create, title and add contributors to a new project from scratch

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

#### 7.2.26 Import Project (M29)

**Secrets:** Inputs needed to import a project

**Services:** This module provides a user interface for the user to import pre-existing projects into UnderTree

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

#### 7.2.27 Project Services (M30)

**Secrets:** The different services offered in regards to creation, editing, and reading projects

**Services:** Offers services for creating new project, editing existing project, deleting a project, and getting information about one or more projects

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.28 Project Database Interface (M31)

**Secrets:** The algorithm used to fetch project data from the database

**Services:** Offers service to modify project data in the database

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.29 GitHub Module (M33)

**Secrets:** The logic to display the GitHub buttons and modal

**Services:** Responsible for receiving the user data.

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.30 GitHub Services Module (M34)

**Secrets:** The algorithm to communicate with GitHub API

**Services:** Responsible for performing the GitHub operations.

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.31 Authentication Module (M35)

**Secrets:** The algorithm to access different authorization modules

**Services:** This module determines which module to use based on the action the user is performing

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### 7.2.32 Auth Service Module (M36)

**Secrets:** The algorithm to handle the HTTPS requests and authentication

**Services:** This module contains the main logic for authentication with GitHub

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

### **7.2.33 Auth Database Interface Module (M37)**

**Secrets:** The algorithm to save user authentication data

**Services:** This module serves as a wrapper and makes queries with the database MongoDB.

**Implemented By:** UnderTree

**Type of Module:** Abstract Object

## **7.3 Software Decision Module**

### **7.3.1 File Data Module (M40)**

**Secrets:** The data type used for files

**Services:** This module stores the datatype that will be used to represent file system in each project

**Implemented By:** UnderTree

**Type of Module:** Record

### **7.3.2 Chat Data Module (M22)**

**Secrets:** The data type used for chat messages

**Services:** This module stores the datatype that will be used to represent chat messages

**Implemented By:** UnderTree

**Type of Module:** Record

### **7.3.3 Project Data (M32)**

**Secrets:** The format of project data

**Services:** Represents the format for the project data

**Implemented By:** UnderTree

**Type of Module:** Record

#### 7.3.4 Auth Data Module (M38)

**Secrets:** The data types in authentication are declared here

**Services:** This module allows for the storing and retrieving of several key data structures that will be used for authentication.

**Implemented By:** UnderTree

**Type of Module:** Record

#### 7.3.5 MongoDB Module (M39)

**Secrets:** How data is stored

**Services:** Allows you to retrieve and store data from the database

**Implemented By:** MongoDB

**Type of Module:** Library

## 8 Traceability Matrix

This section shows two traceability matrices: between the modules and the requirements and between the modules and the anticipated changes.

Table 2: Trace Between Functional Requirements and Modules

Req.	Modules
FR1	M23
FR2	M23
FR3	M33, M34, M35, M36
FR4	M33, M34, M35, M36
FR5	M24, M27, M28, M30, M31, M32
FR6	M24, M27, M28, M30, M31, M32
FR7	M33, M34, M37, M38, M39
FR8	M24, M27, M29, M30, M31, M32
FR9	M30, M31, M32, M33, M??
FR10	M30, M31, M32, M33
FR11	M26, M30, M31, M32, M39
FR12	M26, M30, M31, M32, M39
FR13	M24, M25, M30, M31, M32, M39
FR14	M24, M25, M30, M31, M32, M39
FR15	M24, M25, M30, M31, M32, M39
FR16	M2, M25, M30, M31, M32, M33, M35, M39
FR17	M2, M25, M30, M31, M32, M33, M35, M39
FR18	M6, M13, M14
FR19	M6, M13, M14
FR20	M3, M10
FR21	M3, M12
FR22	M3, M4
FR23	M3

---

FR24	M7, M8
FR25	M7, M8
FR26	M6, M13, M14, M??
FR27	M7, M9
FR28	M6, M13, M14
FR29	M6, M7
FR30	M6, M13, M14
FR31	M6
FR32	M13, M14
FR33	M13, M14
FR34	M3
FR35	M3, M13, M14, M38
FR36	M13, M14, M17
FR37	M2, M15
FR38	M13, M14, M17
FR39	M2, M15, M16
FR40	M2,M??
FR41	M2,M??
FR42	M2
FR43	M18
FR44	M18, M19, M20, M21, M22
FR45	M33, M35
FR46	M33, M35
FR47	M33, M35

---

Table 3: Trace Between Nonfunctional Requirements and Modules

Req.	Modules
NFR1	M2, M3, M18, M23, M24
NFR1	M2, M3, M18, M23, M24
NFR3	M2, M3, M18, M23, M24
NFR4	M33, M34, M35, M35
NFR5	M2, M3, M18, M23, M24
NFR6	M24, M27, M28, M30, M31, M32
NFR7	M33, M34, M35, M36, M37
NFR8	M2, M3, M18, M23, M24
NFR9	M30, M31, M32, M33, M39
NFR10	M30, M31, M32, M33
NFR11	M26, M30, M31, M32, M39
NFR12	M26, M30, M31, M32, M39
NFR13	M24, M25, M30, M31, M32, M39
NFR14	M24, M25, M30, M31, M32, M39
NFR15	M24, M25, M30, M31, M32, M39
NFR16	M2, M25, M30, M31, M32, M33, M34, M39
NFR17	M2, M25, M30, M31, M32, M33, M34, M39
NFR18	M6, M13, M14
NFR19	M6, M13, M14
NFR20	M3, M10
NFR21	M3, M12
NFR22	M3, M4
NFR23	M3



---

NFR24	M7, M8
NFR25	M7, M8
NFR26	M6, M13, M14
NFR27	M7, M9
NFR28	M6, M13, M14
NFR29	M6, M7
NFR30	M6, M13, M14
NFR31	M2, M3, M18, M23, M24
NFR32	M13, M14
NFR33	M13, M14
NFR34	M2, M3, M18, M23, M24
NFR35	M3, M13, M14
NFR36	M13, M14, M17
NFR37	M2, M15
NFR38	M13, M14, M17
NFR39	M2, M15, M16
NFR40	M2, M38
NFR44	M18, M19, M20, M21, M22

---

Table 4: Trace Between Anticipated Changes and Modules

<b>AC</b>	<b>Modules</b>
AC1	M1
AC2	M2
AC3	M3
AC4	M4
AC6	M6
AC7	M7
AC8	M8
AC9	M9
AC10	M10
AC11	M11
AC12	M12
AC13	M13
AC14	M14
AC15	M15
AC16	M16
AC17	M17
AC18	M18
AC19	M19
AC20	M20
AC21	M21
AC22	M22
AC23	M23
AC24	M24
AC25	M25
AC26	M26
AC27	M27
AC28	M28
AC29	M29
AC30	M30
AC31	M31
AC32	M32

