


AUTOMOBILE & ELECTRIC VEHICLES

TASK 4 • EV THERMAL MANAGEMENT SYSTEM & BATTERY COOLING ANALYSIS

PREPARED BY

RUTHVIK REDDY ANUMANDLA



REPORT OBJECTIVE

This report completes the five required components of the provided Maincrafts Task 4: EV thermal management, battery cooling methods, thermal runaway and safety, temperature effects on performance, and an industry-level EV case study. The structure follows the terminology and expected outputs in the assignment.

01 EV THERMAL MANAGEMENT FUNDAMENTALS

Thermal management is the coordinated control of temperature in the battery, electric motor, inverter/power electronics and cabin-related thermal circuits. EV energy conversion is not perfectly lossless, so part of the electrical energy becomes heat. The thermal system must reject heat when components are hot and provide heat when components are too cold.

Why thermal management is needed

Battery temperature influences power capability, charging acceptance, efficiency, ageing and safety. Very low temperature can increase internal resistance, reduce available power and reduce practical range. High temperature accelerates degradation and can increase safety risk. Motors and inverters also require temperature control because electrical and mechanical losses appear as heat.

Main objectives

- Keep battery, motor and power electronics within safe operating limits.
- Maintain reasonably uniform temperature distribution across cells/modules.
- Remove heat effectively during high load and fast charging.
- Minimize the auxiliary energy consumed by pumps, fans, compressors and other thermal equipment.
-

Main sources of EV heat

- **Battery charging/discharging:** resistive and electrochemical heat generation increases with operating current.
- **Motor losses:** copper, iron/core, switching-related and mechanical losses become heat.
- **Inverter/power electronics:** semiconductor conduction and switching losses generate heat.
- **HVAC and auxiliary systems:** cabin thermal demand interacts with the vehicle thermal circuit.

Impact of overheating: reduced efficiency, power derating, faster battery ageing, reduced usable life and increased safety risk. At sufficiently severe temperatures, self-heating can progress toward thermal runaway.

Conceptual thermal path: **Battery** → cooling plate/coolant → pump/chiller/radiator → heat rejection; Motor/Inverter → coolant loop → radiator/heat exchanger; HVAC/heat pump ↔ shared thermal hardware depending on architecture.

02 BATTERY COOLING METHODS

Battery cooling is required because cells generate heat during charging, discharging and high-power operation. The assignment identifies three major approaches: air cooling, liquid cooling and phase-change cooling. The selection depends on heat-transfer capability, packaging, cost, weight, control complexity and operating environment.

Air cooling

Air cooling moves air around or through the battery pack. It is simple, relatively inexpensive and easy to service. Its limitation is lower heat-transfer capability compared with liquid systems, making tight temperature uniformity difficult in demanding high-power or repeated fast-charging conditions.

Liquid cooling

Liquid cooling circulates coolant through channels, plates or cold plates close to the cells. It provides strong heat-transfer capability and controlled flow, making it suitable for modern high-power EV packs. The trade-off is higher complexity because pumps, hoses, valves, heat exchangers, coolant and leak-management provisions are needed.

Phase-change cooling

Phase-change cooling uses a material that absorbs significant heat while changing phase. It can provide thermal buffering and limit rapid temperature rise, but material containment, packaging and heat recovery/regeneration must be considered. The assignment treats this as an advanced approach.

Cooling Type	Efficiency	Cost	Usage	Advantages
Air cooling	Low–moderate	Low	Simple/low-power EV packs	Simple, low cost, low component count, no
Liquid cooling	High	Moderate–high	Modern high-power EVs; demanding charg	High heat-transfer capability; better temper
Phase-change cooling	High thermal buffering	Higher / application de	Advanced designs and research applicatio	Absorbs heat during phase transition; limits

Series vs. parallel cooling

In a series arrangement, coolant or air encounters regions sequentially, so downstream sections may see different thermal conditions from upstream sections. A parallel arrangement divides flow among branches and can improve temperature uniformity when flow is balanced correctly. Pressure drop, flow distribution, packaging and cell-to-cell temperature variation are key design considerations.

Cooling-system design criteria

- Heat removal must cover peak electrical load and fast charging.
- Temperature uniformity matters because large cell-to-cell differences can cause unequal ageing and electrical behaviour.
- Auxiliary energy use should be minimized; excessive pump/fan operation can reduce net efficiency.
- Liquid systems require attention to leak prevention, electrical isolation, corrosion resistance and serviceability.
- Thermal control should be coordinated with battery monitoring so cooling is increased before unsafe conditions develop.

03 THERMAL RUNAWAY & BATTERY SAFETY

Thermal runaway is a chain reaction in which a battery cell enters a self-heating condition and heat generation exceeds the ability of the system to remove heat. The assignment identifies rapid temperature rise and fire or explosion as possible outcomes. Thermal runaway can begin through electrical, thermal or mechanical abuse and may propagate from one cell to neighbouring cells.

Thermal runaway process

- **Initiating fault:** overcharging, internal/external short circuit, physical damage, extreme temperature or loss of cooling.
- **Heat accumulation:** local heat generation raises cell temperature faster than heat can be rejected.
- **Internal reactions accelerate:** separator damage, electrolyte decomposition and other exothermic reactions increase heat generation.
- **Self-heating:** the cell temperature rises without an equivalent external heat input.
- **Propagation:** heat from the failed cell can drive neighbouring cells toward critical conditions.

Major causes and risk conditions

- Overcharging or abnormal charging conditions.
- Electrical short circuits, including internal faults.
- Mechanical damage, crushing, penetration or deformation.
- Poor cooling, blocked flow, failed pumps or excessive ambient temperature.
- Manufacturing defects or damaged cells that create local internal faults.

Role of the Battery Management System (BMS)

The BMS is a major protection layer. It monitors electrical and thermal variables and uses that information to control or interrupt operation. Temperature sensors provide feedback about cell/module conditions. When an unsafe condition is detected, the BMS can limit charging/discharging power, request thermal conditioning, trigger warnings and use contactor-based isolation or other protection strategies depending on the vehicle architecture.

The BMS does not physically remove heat by itself. It works together with the thermal management system: the thermal system provides cooling/heating capability, while the BMS provides monitoring, limits, control logic and fault-response decisions.

Safety mechanisms

- **Temperature monitoring:** frequent measurement of cell/module temperatures.
- **Electrical protection:** over-voltage, under-voltage, over-current and abnormal charging detection.
- **Thermal control:** active cooling/heating to maintain an appropriate operating region.
- **Isolation:** high-voltage contactors and protective devices can disconnect the battery when required.
- **Propagation resistance:** spacing, barriers, venting paths and pack-level design can reduce propagation probability or speed.
- **Fault diagnostics:** abnormal temperature trends and sensor disagreement can be detected before conditions become severe.

Safety conclusion: A safe EV battery pack uses multiple layers—cell design, pack mechanical protection, thermal control, sensing, BMS logic and electrical isolation. No single layer should be treated as sufficient by itself.

04 TEMPERATURE IMPACT ON PERFORMANCE

Battery temperature influences electrochemical reaction rates, internal resistance, charging acceptance, power capability, efficiency and ageing. The assignment asks for high- and low-temperature effects, an ideal operating range and a conceptual performance-versus-temperature graph.

High-temperature operation

At elevated temperature, reaction kinetics may initially be more favourable than in a very cold battery, but sustained high temperature accelerates degradation. Long exposure can increase capacity and power fade and raises safety concerns because abnormal reactions can become easier to initiate or accelerate. Thermal control therefore aims to prevent sustained excessive temperature rather than simply maximizing cooling at all times.


Low-temperature operation

At low temperature, ionic transport and reaction kinetics become less favourable and internal resistance rises. The result can be lower available power, reduced efficiency, slower charging acceptance and reduced practical range. EVs may therefore precondition the battery before demanding charging or driving conditions.

Ideal temperature region

The assignment gives an approximate ideal battery temperature of **20–40°C**. This is a conceptual learning range, not a universal specification for every chemistry and vehicle. Actual limits depend on cell chemistry, pack design, operating condition and manufacturer calibration.

Conceptual performance-versus-temperature relationship



Interpretation: performance is conceptually lower in very cold conditions because of increased resistance and slower electrochemical kinetics. It improves through a moderate region and then declines as temperature becomes excessive because thermal stress and degradation become important. The graph is conceptual, as requested by the assignment, and is not experimental data from a particular battery.

Practical thermal-control strategy

- Precondition the battery before high-power charging when it is too cold or too hot.
- Use coolant flow, fans, chillers, heat pumps or other thermal devices according to demand.
- Avoid unnecessary auxiliary thermal-system energy consumption through feedback control.
- Maintain temperature uniformity so cells do not experience very different ageing conditions.
- Use BMS limits to reduce current/power when temperature moves outside safe operating conditions.

Deliverable 4: Temperature-performance relation completed with a conceptual graph.

05 INDUSTRY-LEVEL CASE STUDY • TESLA MODEL 3

Selected EV: Tesla Model 3

The assignment allows Tata Nexon EV, Tesla Model 3 or Hyundai Kona Electric. Tesla Model 3 is selected because its thermal architecture is a useful example of an integrated EV system combining battery cooling/heating, powertrain cooling and HVAC/heat-pump functions. Model 3 configurations vary by production year and version, so the discussion focuses on documented thermal architecture rather than claiming every Model 3 has identical hardware.

Battery type

Model 3 has been produced with multiple battery configurations and cell chemistries across different years and variants. Therefore, a single chemistry should not be assigned to every Model 3. The important thermal-management point is that the high-voltage battery is actively temperature-managed rather than being only a passive air-cooled enclosure.

Cooling and thermal system used

Tesla Model 3 service documentation identifies a liquid coolant system with dedicated coolant pumps, radiator, battery coolant paths and heat exchangers. Heat-pump-equipped vehicles also include components such as a chiller, coolant bottle, heat-pump hardware, a supermanifold and an Octovalve. Separate procedures for heat-pump and non-heat-pump versions show that the architecture varies by configuration.

The system can be understood as an integrated thermal network. Coolant is circulated through battery and powertrain circuits. Heat can be rejected through a radiator, while a chiller can couple the battery coolant circuit to the refrigeration system when additional cooling is required. In heat-pump versions, thermal energy can also be moved for heating functions.

Battery thermal control during charging

Tesla's Model 3 owner's manual describes battery preconditioning before reaching a charging location. When navigating to a Tesla charging location, the vehicle can pre-heat the high-voltage battery so that it reaches a more suitable temperature for charging. This demonstrates proactive thermal control: the system prepares the battery before the highest-power event instead of waiting for temperature to become unsuitable.

Documented thermal-management components

Component / function	Role in thermal management
HV battery coolant circuit	Moves heat into or out of the battery thermal path.
Coolant pump	Provides controlled coolant circulation through battery/powertrain circuits.
Radiator	Rejects heat from coolant to ambient air.
Chiller	Transfers heat between battery coolant and the refrigeration system when cooling is required.
Heat pump (where equipped)	Provides heating/cooling functionality and can reuse thermal energy within the integrated system.
Supermanifold / Octovalve	Routes thermal flows among different parts of the integrated thermal system in heat-pump versions.
Temperature/pressure sensing	Provides information for monitoring, diagnosis and thermal control.

Why this cooling system is used

A modern EV requires more than a simple radiator because the battery must be controlled across a wide range of conditions. High charging power and vehicle load generate heat, while cold weather can make the battery too cold for efficient operation. An actively controlled liquid system can move heat where it is needed, reject excess heat and precondition the battery. Integration with HVAC/heat-pump hardware can improve energy utilization.

Real-world engineering value

The Model 3 case demonstrates that thermal management is an integrated vehicle-level engineering problem. Battery, inverter, drive units and cabin thermal requirements can interact. An integrated architecture can route thermal energy between subsystems, providing flexibility and potentially better energy efficiency, at the cost of greater component, control and service complexity.

05 CASE STUDY ANALYSIS • CONCLUSION • CHECKLIST

Advantages of the Tesla Model 3 thermal approach

- **High heat-transfer capability:** liquid cooling suits high-power battery and powertrain operation.
- **Active temperature control:** the system can cool or heat rather than only rejecting heat.
- **Preconditioning:** the battery can be brought toward a more suitable temperature before high-power charging.
- **Thermal integration:** battery, powertrain and HVAC functions can share thermal hardware in heat-pump-equipped configurations.
- **Control flexibility:** pumps, valves, sensors and thermal modules allow the vehicle to adapt thermal flow to operating conditions.

Limitations and engineering trade-offs

- **Complexity:** integrated thermal systems need more valves, pumps, hoses, heat exchangers, sensors and control software than simple air cooling.
- **Auxiliary energy use:** pumps, fans and refrigeration equipment consume electrical energy, so thermal control must be optimized.
- **Service requirements:** coolant filling, bleeding, leak checks and diagnostics require controlled procedures.
- **Configuration variation:** Model 3 thermal hardware differs between heat-pump and non-heat-pump vehicles and across model years.
- **Failure consequences:** loss of coolant flow or thermal-system faults can reduce charging/power capability and may trigger protective limits.

Real-world performance impact

The practical benefit of thermal management appears during high-power charging, repeated acceleration, sustained high load and cold ambient conditions. In hot conditions, active cooling helps prevent excessive temperature rise and protects performance and battery life. In cold conditions, preconditioning and heating can improve charging readiness and usable power. The objective is not to make the battery as cold as possible; it is to maintain an appropriate operating region while minimizing thermal-system energy consumption.

Overall conclusion

EV thermal management is a core part of electric-vehicle design because temperature affects performance, efficiency, range, durability and safety. Battery cooling can use air, liquid or advanced phase-change methods, with liquid cooling providing strong heat-transfer capability for demanding modern EV applications. Thermal runaway must be addressed through multiple layers including cell/pack design, temperature sensing, BMS control, electrical isolation and propagation resistance. Cold conditions can reduce power and efficiency, while sustained high temperatures accelerate degradation and increase safety risk.

The Tesla Model 3 case study shows how an industry EV combines liquid coolant circulation, pumps, radiators, battery thermal paths and, on heat-pump versions, a more integrated thermal network. Battery preconditioning before charging demonstrates the importance of proactive thermal control. The main engineering lesson is that thermal management should be designed as an integrated system rather than as an isolated battery-cooling function.

Final submission checklist

Required output	Where completed
Thermal system explanation	Section 01 – need, heat sources and overheating impact
Cooling system comparison	Section 02 – air, liquid and phase-change comparison
Safety analysis	Section 03 – thermal runaway, BMS and safety mechanisms
Temperature-performance relation	Section 04 – high/low temperature effects + conceptual graph
EV case study	Section 05 – Tesla Model 3 thermal system, safety and performance analysis