

DAA-LAB-6

N.RUTHVIK

2000031205

In Lab:

- 1) Marc loves cupcakes, but he also likes to stay fit. Each cupcake has a calorie count, and Marc can walk a distance to expend those calories.

If Marc has eaten j cupcakes so far, after eating a cupcake with c calories he must walk at least $2^j * c$ miles to maintain his weight. For example, if he eats 3 cupcakes with calorie counts in the following order: [5,10,7], the miles he will need to walk are $(2^0 * 5) + (2^1 * 10) + (2^2 * 7) = 5 + 20 + 28 = 53$. This is not the minimum, though, so we need to test other orders of consumption. In this case, our minimum miles is calculated as $(2^0 * 10) + (2^1 * 7) + (2^2 * 5) = 10 + 14 + 20 = 44$.

Given the individual calorie counts for each of the cupcakes, determine the minimum number of miles Marc must walk to maintain his weight. Note that he can eat the cupcakes in any order.

Sample Input:

```
3
1 3 2
```

Sample Output:

```
1 1
```

Code:

```
#include <math.h>

#include <stdio.h>

#include <string.h>

#include <stdlib.h>

#include <assert.h>

#include <limits.h> #include <stdbool.h>

int cmpfunc (const void * a, const void * b)

{

    return ( *(int*)a - *(int*)b );
```

```

}

int main(){

    int n;

    scanf("%d",&n);    int *calories =
    malloc(sizeof(int) * n);    for(int calories_i = 0;
    calories_i < n; calories_i++){
    scanf("%d",&calories[calories_i]);

        }

    qsort(calories,n,sizeof(int),cmpfunc);

    long long int a=0; int i;    for(i=n-1;i>=0;i--
    ){        a=a+calories[i]*pow(2,n-1-i);

        }

    printf("%lld",a);    //
    your code goes here

    return 0;

}

```

GDB online Debugger | Compiler x DAA-RB-20CS2220RB 2021-22 E x GDB online Debugger | Compiler x +

onlinegdb.com

Apps https://www.youtub... C https://www.couse... LinkedIn Learning... KL University ERP https://moodle.klun... https://www.instagram... WhatsApp Competitive Progra... Guest Portal

OnlineGDB beta
online compiler and debugger for c/c++

Welcome, **shaik imran shareef** ▲

Create New Project

My Projects

Classroom **new**

Learn Programming

Programming Questions

Logout

f + 135K

main.c

```
1 #include <math.h>
2 #include <stdio.h>
3 #include <string.h>
4 #include <stdlib.h>
5 #include <assert.h>
6 #include <limits.h>
7 #include <stdbool.h>
8 int cmpfunc (const void * a, const void * b)
9 {
10     return ( *(int*)a - *(int*)b );
11 }
12 int main(){
13     int n;
14     scanf("%d",&n);
15     int *calories = malloc(sizeof(int) * n);
16     for(int calories_i = 0; calories_i < n; calories_i++){
17         scanf("%d",&calories[calories_i]);
```

input

```
3
1
3
2
11

...Program finished with exit code 0
Press ENTER to exit console.
```

About • FAQ • Blog • Terms of Use • Contact Us • GDB
Tutorial • Credits • Privacy
© 2016 - 2022 GDB Online

Output: