

4.2. Scripts in Postman

Postman Scripts

1. Postman scripts can be written at different stages

a. **Pre-request scripts:** Run before the request is sent.

i. Used to create variables before sending requests


b. **Post-response scripts:** Run after receiving the response.

i. Used to create Assertions or validations after receiving responses.

ii. Used to Delete variables after receiving responses.


Workflow of scripts

→ **Pre-request Script** → **Request** → **Response** → **Post-response**



Scripts Execution Order

→ Scripts will be executed in 3 levels



◆ **Collection:** A group of requests.

◆ **Folder:** Subgroups within a collection.

◆ **Request:** Individual HTTP requests (GET, POST, etc.).

→ A pre-request script associated with a collection will run prior to every request in the collection.

→ A pre-request script associated with a folder will run prior to every direct child request in the folder.


→ A post-response script associated with a collection will run after every request in the collection.

- A post-response script associated with a folder will run after every direct child request in the folder.

Workout in Postman Tool

1. Create a Hierarchy as below

- a. Collection (Day4_Variables Collection) → Folder (myfolder) → Request (getusers)



2. Every Level will be having Scripts and inside it we will have Pre-request and Post-response

3. Add Scripts as below for every level

a. Collection Level

- i. **Pre-request** → `console.log("Pre-request script at collection level");`
- ii. **Post-response** → `console.log("Post-response script at collection level");`


b. Folder Level

- i. **Pre-request** → `console.log("Pre-request script at Folder level");`
- ii. **Post-response** → `console.log("Post-response script at Folder level");`

c. Request Level

- i. **Pre-request** → `console.log("Pre-request script at Request level");`
- ii. **Post-response** → `console.log("Post-response script at Request level");`

4. Click on Collection → Run collection and observe output in Console



Run order

☒ GET getusers

☐ GET Get Users_globalVar

☐ GET Get Users_EnvVar

☐ GET Get Users_CollectVar

☐ GET Get Users_LocalVar

☐ POST createuser

Deselect All Select All Reset

Functional Performance

Choose how to run your collection

☒ Run manually
Run this collection in the Collection Runner.
 ☐ Schedule runs
Periodically run collection at a specified time on the Postman Cloud.
 ☐ Automate runs via CLI
Configure CLI command to run on your build pipeline.

Run configuration

Iterations ①

1

Delay ①

0 ms

Data file ①

Select File

☐ Persist responses for a session ①
 ☐ Turn off logs during run ①

> Advanced settings

Run Day4_VariablesAndScripts

Day4_VariablesAndScripts - Run results

Run Again

Automate Run ▾

+ New Run

Export Results

Ran today at 01:18:25 · [View all runs](#)

Source	Environment	Iterations	Duration	All tests	Avg. Resp. Time
Runner	none	1	453ms	0	96 ms

RUN SUMMARY

GET getusers

1

0 | 0

View Results

Day4_VariablesAndScripts - Run results

Run Again

Automate Run ▾

+ New Run

Export Results

Ran today at 01:18:25 · [View all runs](#)

Source	Environment	Iterations	Duration	All tests	Avg. Resp. Time
Runner	none	1	453ms	0	96 ms

All Tests Passed (0) Failed (0) Skipped (0)

View Summary

Iteration 1

1

GET Day4_VariablesAndScripts / myfolder / getusers

Response Headers Request

200 96 ms 1.548 KB

General

URL: https://reqres.in/api/users?page=2

Method: GET

GET getusers

https://reqres.in/api/users?page=2

200 OK

No tests found

Online Find and replace Console Import Complete

"Pre-request script at collection level"

"Pre-request script at folder level"

"Pre-request script at request level"

▶ GET https://reqres.in/api/users?page=2

"Post-response script at collection level"

"Post-response script at folder level"

"Post-response script at request level"

29

Creating and Managing Variables with Scripts

Creating Variables in Pre-request Scripts

1. We can set variables before sending a request using JavaScript.
 - a. **Global Variable** → `pm.globals.set("userid_global", "2");`
 - b. **Environment Variable** → `pm.environment.set("userid_qa_env", "2");`
 - c. **Collection Variable** → `pm.collectionVariables.set("userid_collect", "2");`
 - d. **Local Variable** → `pm.variables.set("userid_local", "2");`

Workout in Postman Tool

1. In **getusers requests** pre-request script create variables using JavaScript and replace respective variable (in the pic only global) in the url.

Pre-request script in request

//global variable

```
pm.globals.set("userid_global", "2");
```

//environment variable


```
pm.environment.set("userid_qa_env", "2");
```

//collection variable

```
pm.collectionVariables.set("userid_collect", "2");
```

//local variable

```
pm.variables.set("userid_local", "2");
```



2. Environmental variable will only create when we select existing environment. If we dont select Environmental variable will not be created.
3. In the Variables Section we can see variables got created through script also.
4. Creating variables at requests level through JS is recommended than folder or collection level.

Note

→ If we don't know JavaScript we can use **Snippets**

◆ Click on **>** → use existing snippet Snippet



Retrieving and Removing Variables in Post-response Scripts

1. Retrieve a Variable Value

- `console.log(pm.globals.get("userid_global"));`
- `console.log(pm.environment.get("userid_qa_env"));`
- `console.log(pm.collectionVariables.get("userid_collect"));`
- `console.log(pm.variables.get("userid_local"));`

2. Unset (Remove) a Variable → After getting the response

- `pm.globals.unset("userid_global");`
- `pm.environment.unset("userid_qa_env");`
- `pm.collectionVariables.unset("userid_collect");`
- `pm.variables.unset("userid_local");`

Post-response script in request

//global variable

`console.log(pm.globals.get("userid_global"));`

`pm.globals.unset("userid_global");`

//environment variables

`console.log(pm.environment.get("userid_qa_env"));`

`pm.environment.unset("userid_qa_env");`

//collection var


```
console.log(pm.collectionVariables.get("userid_collect"));
```

```
pm.collectionVariables.unset("userid_collect");
```

//local var

```
console.log(pm.variables.get("userid_local"));
```

```
pm.variables.unset("userid_local");
```



Observation

→ Upon using unset variables got delete from variable section also.

→ **console.log()** is used for printing output in the Console

Using Variables Inside the Request Body

→ We can set and use variables in the request body to make dynamic requests.

→ **Create Local Variables in Pre-request Script**

- ◆ `pm.variables.set("name", "Madhan Mohan");`
- ◆ `pm.variables.set("job", "Senior Associate Consultant and Trainer");`

→ **POST Request Example**

- ◆ URL: `https://reqres.in/api/users`
- ◆ **Request Body**

```
{  
  
  "name": "{{name}}",  
  
  "job": "{{job}}"  
}
```

→ Here, `{{name}}` and `{{job}}` will be replaced with the values "Madhan Mohan" and "Senior Associate Consultant and Trainer" dynamically.

Workout in Postman Tool

1. Create a **createuser** post request in same Day4_Variables collection

a. **`https://reqres.in/api/users`**

b. Click on Pre-request and create variables

i. **`pm.variables.set("myname","Madhan Mohan");`**

ii. **`pm.variables.set("myjob","Senior Associate Consultant and Trainer");`**

c. Click on Body → raw → select JSON from dropdown → create JSON body

```
{  
  "name": "{{myname}}",  
  "job": "{{myjob}}"  
}
```

d. Now Send the request and we can see the response as below



e. Click on Post-response and add assertions and managing variables script before sending the request.

Post-response script in request

```
pm.variables.unset("myname");
```

```
pm.variables.unset("myjob");
```

```
// Test to check if the status code is 200
```

```
pm.test("Status code is 201", () => {
```

```
  pm.response.to.have.status(201);
```

```
});
```

```
// Test to verify the status code name contains "Created"
```

```
pm.test("Status code name has string", () => {
```

```

pm.response.to.have.status("Created");
});

// Parse the JSON response

const jsonData = pm.response.json();

pm.test("Values of fields in response", () => {

    pm.expect(jsonData.name).to.eql("Madhan Mohan");

    pm.expect(jsonData.job).to.eql("Senior Associate Consultant and Trainer");

});

```

