
SunBeam Institute of Information & Technology, Hinjwadi, Pune & Karad.



### Q. Why there is a need of an OS?

- Computer is a **machine/hardware** does different tasks efficiently & accurately.
- Basic functions of computer:
  - 1. Data Storage
  - 2. Data Processing
  - 3. Data Movement
  - 4. Control
- As any user cannot communicates/interacts directly with computer hardware to do different tasks, hence there is need of some interface between user and hardware and to provide this interface is the job of an OS.







#### Q. What is a Software?

- Software is a collection of programs.

### Q. What is a Program?

- Program is a finite set of instructions written in any programming language (either low level or high level programming language) given to the machine to do specific task.
- 3 types of programs are there:
- 1. "user programs": programs defined by the programmer user/developers e.g. main.c, hello.java, addition.cpp etc....
- 2. "application programs": programs which comes with an OS/can be installed later e.g. MS Office, Notepad, Compiler, IDE's, Google Chrome, Mozilla Firefox, Calculator, Games etc....
- **3. "System Programs":** programs which are inbuilt in an OS/part of an OS. e.g. Kernel, Loader, Scheduler, Memory Manager etc...




#### Q. What is an IDE (Integrated Software Developement)?

- It is an application software i.e. collection of tools/application programs like source code editor, preprocessor, compiler, linker, debugger etc... required for faster software development.
- e.g. VS code editor, MS Visual Studio, Netbeans, Android Studio, Turbo C etc....
- **Source Code** Program written in any programming langauge.
- 1. "Editor": it is an application program used to write a source code.
- e.g. notepad, vi editor, gedit etc...
- 2. "Preprocessor": it is an application program gets executes before compilation and does two jobs it executes all preprocessor directives and removes all comments from the source code.
  - e.g. cpp
- 3. "Compiler": it is an application program which converts high level programming language code into low level programming language code i.e. human understandable language code into the machine understandable language code.
  - e.g. gcc, tc, visual c etc...



- **4. "Assembler":** it is an application program which converts assembly language code into machine language code/object code. e.g. masm, tasm etc...
- **5.** "Linker": it is system program which links object file/s of a program with precompiled object modules of library functions exists in a lib folder and creates final single executable file.
  - e.g. Id: link editor in Linux.
- **Loader:** It is a system program (i.e. inbuilt program of an OS) which loads an executable file from **HDD** into the **main memory.**
- **Dispatcher**: It is a system program (i.e. inbuilt program of an OS) which loads data & instructions of a program which is in the **main memory** onto **the CPU** (i.e. into the CPU registers).







Structure of an executable file ELF file format in Linux 1. primary header/exe header: it contains information which is required to starts an primary heade execution of the program. /elf header e.g. - addr of an entry point function --> main() function bss section - magic number: it is constant number generated by the compiler which is file format specific. data section - magic number in Linux starts with ELF in its eq hexadecimal format. - info about remaining sections. rodata section 2. bss(block started by symbol) section: it contains uninitialized global & static vars 3. data section: it contains initialized global & static vars code/text **4. rodata (readonly data ) section:** it contains string literals and constants. section 5. code/text section: it contains an executable instructions symbol table 6. symbol table: it contains info about functions and its vars in a tabular format. program.out Hard Disk Drive



# Q. What is an Operating System?

- An OS is a **system software** (i.e. collection of system programs) which **acts as an interface between user and hardware.**
- An OS also acts as an interface between programs(user & application programs) and hardware.
- An OS allocates resources like main memory, CPU time, i/o devices access etc... to all running programs, hence it is also called as a resource allocator.
- An OS controls an execution of all programs, it also controls hardware devices which are connected to the computer system and hence it is also called as a **control program**.



### Q. What is an Operating System?

- An OS manages limited available resources among all running programs, hence it is also called as a **resource manager**.
- An OS is a software (i.e. collection of thousands of system programs and utitlity programs in a binary format) comes either in CD/DVD/PD, has following main components:
- 1. Kernel: It is a core program/part of an OS which runs continuosly into the main memory does basic minimal functionalities of it.
- e.g. Linux: vmlinuz, Windows: ntoskrnl.exe
- **2. Utility Programs Softwares:** e.g. disk manager, windows firewall, anti-virus software etc...
- **3. Application Programs Softwares:** e.g. google chrome, shell, notepad, msoffice etc...



### # Functions of an OS:

# Basic minimal functionalities/Kernel functionalities - must be supported by any OS - compulsory functionalities:

- 1. Process Management
- 2. Memory Management
- 3. Hardware Abstraction
- 4. CPU Scheduling
- 5. File & IO Management

### **Extra utility functionalities/optional:**

- 6. Protection & Security
- 7. User Interfacing
- 8. Networking



#### # Booting:

- There are two steps of booting:

#### 1. Machine Boot:

**Step-1:** when we switched on the power supply current gets passed to the motherboard on which from ROM memory one micro-program gets executes first called as **BIOS(Basic Input Output System)**.

**Step-2:** first step of BIOS is **POST(Power On Self Test),** under POST it checks wheather all peripheral devices are connected properly or not and their working status.

**Step-3:** After POST it invokes **Bootstrap Loader** programs, which searches for available **bootable devices** presents in the system, and it selects only one bootable device at a time as per the priority decided in BIOS settings.

#### 2. System Boot:

**Step-4:** After selection of a bootable device (budefault HDD), **Bootloader Program** in it gets invokes which displays list of names operating systems installed on the disk, from which user need to select any one OS.


Step-5: Upon selection of an OS, Bootstrap Program of that OS gets invokes, which locates the kernel and load into the main memory



### **# UNIX Operating System:**

- UNIX: UNICS Uniplexed Information & Computing Services/System.
- UNIX was developed at **AT&T Bell Labs** in US, in the decade of 1970's by **Ken Thompson, Denies Ritchie** and team.
- It was first run on a machine **DEC-PDP-7** (Digital Equipment Corporation
- Programmable Data Processing-7).
- UNIX is the first multi-user, multi-programming & multi-tasking operating system.
- UNIX was specially designed for developers by developers
- System architecture design of UNIX is followed by all modern OS's like Windows, Linux, MAC OS X, Android etc..., and hence UNIX is referred as mother of all modern operating systems.







- Kernel acts as an interface between programs and hardware.
- Operating System has subsystems like System Call Interface Block, File Subsystem Block, Process Control Subsystem Block (which contains IPC, Memory Management & CPU Scheduling), Device Driver, Hardware Control/Hardware Abstraction Layer.
- There are two major subsystems:
- 1. Process Control Subsystem
- 2. File Subsystem
- In UNIX, whatever is that can be stored is considered as a file and whatever is active is reffered as a process.
- File has space & Process has life.



- From UNIX point of view all devices are considered as a file
- In UNIX, devices are catagorises into two catagories:
- **1. Character Devices:** Devices from which data gets transfered character by character --> character special device file e.g. keyboard, mouse, printer, monitor etc...
- **2. Block Devices:** Devices from which data gets transfered block by block --> block special device file e.g. all storage devices.
- **Device Driver:**It is a program/set of programs enable one or more hardware devices to communicate with the computer's operating system.



- Hardware Control Layer/Block does communication with control logic block i.e. controller of a hardware.
- **# System Calls:** are the functions defined in a C, C++ & Assembly languages, which provides interface of services made available by the kernel for the user (programmer user).
- If programmers want to use kernel services in their programs, it can be called directly through system calls or indirectly through set of libary functions provided by that programming language.
- There are 6 catagories of system calls:
- 1. Process Control System Calls: e.g. fork(), \_exit(), wait() etc...
- 2. File Operations System Calls: e.g. open(), read(), write(), close() etc...
- 3. Device Control System Calls: e.g. open(), read(), write(), ioctl() etc...



- **4. Accounting Information System Calls:** e.g. getpid(), getppid(), stat() etc...
- **5. Protection & Security System Calls:** e.g. chmod(), chown() etc...
- **6. Inter Process Communication System Calls:** e.g. pipe(), signal(), msgget() etc...
- In UNIX 64 system calls are there.
- In Linux more than 300 system calls are there
- In Windows more than 3000 system calls are there
- When system call gets called the CPU switched from user defined code to system defined code, and hence system calls are also called as **software interrupts/trap**.



### **# Dual Mode Operation:**

- System runs in two modes:
- 1. System Mode
- 2. User Mode

### 1. System Mode:

- When the CPU executes system defined code instructions, system runs in a system mode.
- System mode is also reffered as kernel mode/monitor mode/supervisor mode/priviledged mode.

#### 2. User Mode:

- When the CPU executes user defined code instructions, system runs in a user mode.
- User mode is also reffered as non-priviledged mode.
- Throughout execution, the CPU keeps switch between kernel mode and user mode



### **# Dual Mode Operation:**

- Throughout an execution of any program, the CPU keeps switcesh in between kernel mode and user mode and hence system runs in two modes, it is reffered as **dual mode operation**.
- To differentiate between user mode and kernel mode one bit is there onto the CPU which is maintained by an OS, called as **mode bit**, by which the CPU identifies wheather currently executing instruction is of either system defined code instruction/s or user defined code instruction/s.
- In Kernel mode value of **mode bit = 0**, whereas
- In User mode mode bit = 1.



### **# Process Management**

- When we say an OS does process management it means an OS is responsible for process creation, to provide environment for an execution of a process, resource allocation, scheduling, resources management, inter process comminication, process coordination, and terminate the process.

## Q. What is a Program?

- User view: Program is a finite set of instructions written in any programming language given to the machine to do specific task.
- System view: Program is an executable file in HDD which divided logically into sections like exe header, bss section, data section, rodata section, code section, symbol table.



### Q. What is a Process?

#### **User view:**

- Program in execution is called as a process.
- Running program is called as a process.
- When a program gets loaded into the main memory it is reffered as a process.
- Running instance of a program is reffered as a process.


### **System view:**

- Process is a program loaded into the main memory which has got PCB into the main memory inside kernel space and program itself into the main memory inside user space has got **bss section, rodata section, code section**, and two new sections gets added for the process:

**stack section:** contains function activation records of called functions.

heap section: dynamically allocated memory








- As a kernel, core program of an a OS runs continuously into the main memory, part of the main memory which is occupied by the kernel reffered as kernel space and whichever part is left is reffered as an user space, so main memory is divided logically into two parts: kernel space & user space.
- User programs gets loaded into the user space only.
- When we execute a program or upon submission of a process very first one structure gets created into the main memory inside kernel space by an OS in which all the information which is required to control an execution of that process can be kept, this structure is reffered as a **PCB**: **Process Control Block**, is also called as a **Process Descriptor**.
- Per process one PCB gets created and PCB remains inside the main memory throughout an execution of a program, upon exit PCB gets destroyed from the main memory.
- PCB mainly contains: PID, PPID, PC, CPU sched information, memory management information, information about resources allocated for that process, execution context etc...



#### **# Process States:**

- Throughout execution, process goes through different states out of which at a time it can be only in a one state.
- States of the process:
- 1. New state: upon submission or when a PCB for a process gets created into the main memory process is in a new state.
- 2. Ready state: after submission, if process is in the main memory and waiting for the CPU time, it is in a ready state.
- **3. Running state:** if currently the CPU is executing any process then state of that process is considered as a running state.
- **4. Waiting state:** if a process is requesting for any i/o device then state of that process is considered as a waiting state.
- **5. Terminated state:** upon exit, process goes into terminated state and its PCB gets destroyed from the main memory.







- 1. multi-programming: system in which more than one processes can be submitted/an execution of more than one programs can be started at a time.
- degree of multi-programming: no. of programs that can be submitted into the system at a time.
- **2. multi-tasking:** system in which, the CPU can execute more than one programs simultaneously/concurrently, the speed at which it executes multiple programs simultaneosuly it seems that it executes multiple programs at a time.

### At a time the CPU can execute only one program

- time-sharing: system in which CPU time gets shared among all running programs.
- **3. multi-threading:** system in which it seems that the CPU can execute more than one threads which are of either same process or are of different processes simultaneously/concurrently.
- **4. multi-processor:** system can run on a machine in which more than one CPU's are connected in a closed circuit.
- 5. multi-user: system in which multiple users can loggedin at a time.



#### **# Process States:**

- To keep track on all running programs, an OS maintains few data structures reffered as kernel data structures:
- 1. Job queue: it contains list of PCB's of all submitted processes.
- **2. Ready queue:** it contains list of PCB's of processes which are in the main memory and waiting for the CPU time.
- **3. Waiting queue:** it contains list of PCB's of processes which are requesting for that particular device.
- 1. Job Scheduler/Long Term Scheduler: it is a system program which selects/schedules jobs/processes from job queue to load them onto the ready queue.
- **2. CPU Scheduler/Short Term Scheduler:** it is a system program which selects/schedules job/process from ready queue to load it onto the CPU.
- **Dispatcher:** it is a system program which loads a process onto the CPU which is scheduled by the CPU scheduler, and the time required for the dispatcher to stops an execution of one process and to starts an execution of another process is reffered as **dispatcher latency.**



#### **# Context Switch:**

- As during context-switch, the CPU gets switched from an execution context of one process onto an execution context of another process, and hence it is reffered as "context-switch".
- context-switch = state-save + state-restore
- **state-save** of suspended process can be done i.e. an execution context of suspended process gets saved into its PCB.
- state-restore of a process which is scheduled by the CPU scheduler can be done by the dispacther, dispather copies an execution context of process scheduled by the cpu scheduler from its PCB and restore it onto the CPU registers.
- When a high priority process arrived into the ready queue, low priority process gets suspended by means of sending an interrupt, and control of the CPU gets allocated to the high priority process, and its execution gets completed first, then low priority process can be resumed back, i.e. the CPU starts executing suspended process from the point at which it was suspended and onwards.



- CPU Scheduler gets called in the following four cases:
- **Case-1: Running -> Terminated**
- **Case-2: Running -> Waiting**
- Case-3: Running -> Ready
- **Case-4: Waiting -> Ready**
- There are two types of CPU scheduling:
- 1. Non-preemptive: under non-preemptive cpu scheduling, process releases the control of the CPU by its own i.e. voluntarily.
- e.g. in above case 1 & case 2
- 2. Preemptive: under preemptive cpu scheduling, control of the CPU taken away forcefully from the process.
- e.g. in above case 3 & 4.



- Following algorithms used for CPU Scheduling:
- 1. FCFS (First Come First Served) CPU Scheduling
- 2. SJF (Shortest Job First) CPU Scheduling
- 3. Round Robin CPU Scheduling
- 4. Priority CPU Scheduling
- Multiple algorithms are there for CPU scheduling, so there is need to decide which algorithm is best suited at specific situation and which algorithm is an efficient one, to decide this there are certain criterias called as **scheduling criterias**: **cpu utilization**, **throughput**, **waiting time**, **response time and turn-around-time**.



### **# CPU Scheduling Criterias:**

- 1. CPU Utilization: one need to select such an algorithm in which utilization of the CPU must be as maximum as a possible.
- 2. Throughput: total work done per unit time. One need to select such an algorithm in which throughput must be as maximum possible.
- **3. Waiting Time:** it is the toal amount of time spent by the process into the ready queue for waiting to get control of the CPU from its time of submission. One need to select such an algorithm in which waiting time must be as **minimum** as possible.
- **4. Response Time:** it is a time required for the process to get first response from the CPU from its time of submission. One need to select such an algorithm in which response time must be as **minimum** as possible.



- **5. Turn-Around-Time:** it is the total amount of time required for the process to complete its execution from its time of submission.
- One need to select such an algorithm in which turn-around-time must be as **minimum** as possible.
- Turn-around-time is the sum of periods spent by the process into ready queue for waiting and onto the CPU for execution from its time of submission.
- **Execution Time:** it is the total amount of time spent by the process onto the CPU to complete its execution.
- **CPU Burst Time:** total no. of CPU cycles required for the process to complete its execution.
- Turn-Around-Time = Waiting Time + Execution Time.



### 1. FCFS (First Come First Served ) CPU Scheduling

- In this algorithm, process which is arrived first into the ready queue gets the control of the CPU first i.e. control of the CPU gets allocated for processes as per their order of an arrival into the ready queue.
- This algorithm is simple to impelement and can be implemented by using fifo queue.
- It is a non-preemptive scheduling algorithm.
- # Convoy effect: due to an arrival of longer processes before shorter processes, shorter processes has to wait for longer time and their average waiting time gets increases, which results into an increase in an average turn-around-time and hence overall system performance gets down.



### 2. SJF(Shortest Job First) CPU Scheduling:

- In this algorithm, process which is having minimum CPU burst time gets the control of the CPU first.
- SJF algorithm ensures minimum waiting time.
- Under non-preemptive SJF, algorithm fails if the submission time of processes are not same, and hence it can be implemented as preemptive as well.
- Non-preemptive SJF is also called as SNTF(Shortest-Next-Time-First).
- Preemptive SJF is also called as SRTF(Shortest-Remaining-Time-First).

**Starvation:** in this algorithm, as shorter processes has got higher priority, process which is having larger CPU burst time may gets blocked i.e. control of the CPU will never gets allocated for it, such situation is called as **starvation/indefinite blocking.** 



### 3. Round Robin Scheduling Algorithm

- In this algorithm, before allocating the CPU for processes, some fixed **time slice** or **time quantum** gets decided in advanced, and at any given time control of the CPU may remains allocated with any process maximum for that decided time-slice, once the given time slice is finished of that process, it gets suspended and control of the CPU will be allocated to the next process again for maximum that decided time slice and so on..., each process gets control of the CPU in a round robin manner i.e. cpu gets shared among processes equally.
- If any process completes its execution before allocated time slice then control of the CPU will be released by that process and CPU gets allocated to the next process as soon as it is completed for effective utilization of the CPU.
- There is no starvation in RR Scheduling algorithm.
- This algorithm is **purely preemptive.**
- This algorithm ensures minimum response time.
- If time slice is minimum then there will be extra overhead onto the CPU due to frequent context-switch.



#### 4. Priority Scheduling

- In this algorithm, process which is having highest priority gets control of the CPU first, each process is having priority in its PCB.
- priority for a process can be decided by two ways:
- **1. internally -** priority for process can be decided by an OS depends on no. of resources required for it.
- 2. externally priority for process can be decided by the user depends on requirement.
- Minimum priority value indicates highest priority.
- This algorithm is purely preemptive.
- Due to the very low priority process may gets blocked into the ready queue and control of the CPU will never gets allocated for such a process, this situation is reffered as a starvation or indifinite blocking.
- **Ageing:** it is a technique in which, **an OS gradually increments priority of blocked process**, i.e. priority of blocked process gets incremented after some fixed time interval by an OS, so that priority of blocked process becomes sufficient enough to get control of the CPU, and starvation can be avoided.



#### **Inter Process Communication**

- Processes running into the system can be divided into two catagories:

#### 1. Independent Processes:

- Process which do not shares data (i.e. resources) with any other process reffered as an **independent process**. **OR** Process which **do not affects** or **not gets affected by any other process** reffered as an independent process.

#### 2. Co-operative Processes:

- Process which shares data (i.e. resources) with any other process reffered as cooperative process. **OR** Process which affects or gets affected by any other process reffered as co-operative process.

#### Q. Why there is need of an IPC?


As concurrently executing co-operative processes shares common resources, so there are quite chances to occur conflictions between them and to avoid this conflictions there is a need of communication takes place between them.



#### What is an Inter Process Communication?

- An IPC is one of the important service made available by the kernel, by using which co-operative processes can communicates with each other.
- Inter process communication takes place only between co-operative processes.
- Any process cannot directly communicates with any other process, hence there is a need of some medium, to provide this medium is the job of an OS/Kernel.
- There are two techniques by which IPC can be done/there are two IPC Models:
- 1. Shared MeMemory Model: under this technique, processes can communicates with each other by means of reading and writing data into the shared memory region (i.e. it is a region/portion of the main memory) which is provided by an OS temporarily on request of processes want to communicates.
- 2. Message Passing Model: under this technique, processes can communicates with each other by means of sending messages.
- Any process cannot directly send message to any other process.
- Shared Memory Model is faster than Message Passing Model.





SHARED MEMORY MODEL



#### **Inter Process Communication**

2. Message Passing Model: there are further different IPC techniques under message passing model.

#### i. Pipe:

- By using Pipe mechanism one process can send message to another process, viceversa is not possible and hence it is a unidirectional communication technique.
- In this IPC mechanism, from one end i.e. from **write end** one process can writes data into the pipe, wheras from another end i.e. from **read end**, another process can read data from it, and communication takes place.
- There are two types of pipes:
- 1. unnamed pipe: in this type of pipe mechanism, only related processes can communicates by using pipe ( | ) command.
- 2. named pipe: in this type of pipe mechanism, related as well as non-related processes can communicates by using pipe() system call.
- By using Pipe only processes which are running in the same system can communicates,




#### **Inter Process Communication**

#### ii. Message Queue:

- By using message queue technique, processes can communicates by means of sending as well as recieving **message packets** to each other via **message queue** provided by the kernel, and hence it is a **bidirectional communication**.
- Message Packet: Message Header(Information about the message) + Actual Message.
- Internally an OS maintains message queue in which message packets sent by one process are submitted and can be sent to reciever process and vice-versa.
- By using message queue technique, only processes which are running in the same system can communicates.



#### **Inter Process Communication**





# **Inter Process Communication iii. Signals:**

- Processes communicates by means of sending signals as well.
- One process can send signal to another process through an OS.
- An OS sends signal to any process but any other process cannot sends signal to an OS.

**Example:** When we shutdown the system, an OS sends **SIGTERM** signal to all processes, due to which processes gets **terminated normally**, but few processes can handle SIGTERM i.e. even after recieving this signal from an OS they continues execution, to such processes an OS sends **SIGKILL** signal due to which processes gets **terminated forcefully.** 

- e.g. SIGSTOP, SIGCONT, SIGSEGV etc...
- By using signal ipc technique, only processes which are running in the same system can communicates.



# Inter Process Communication iv. Socket

- Limitation of above all IPC techniques is, only processes which are running on the same system can communicates, so to overcome this limitation Socket IPC mechanism has been designed.
- By using socket IPC mechanism, process which is running on one machine can communicates with process running on another machine, whereas both machines are at remote distance from each other and provided they connected in a network (either LAN / WAN/Internet).
- Socket = IP Address + Port Number.
- e.g. chatting application.



# # Process Coordination / Process Synchronization Why Process Co-ordination/Synchronization?


- If concurrently executing co-operative processes are accessing common resources, then conflictions may takes place, which may results into the problem of **data incosistency**, and hence to avoid this problem co-ordination / synchronization between these processes is required.

**Race Condition:** if two or more processes are trying to access same resource at a time, race condition may occures, and **data inconsistency** problem may takes place due to race condition.

- Race condition can be avoided by an OS by
- 1. deciding order of allocation of resource for processes, and
- 2. whichever changes did by the last accessed process onto the resource remains final changes.



#### **Critical Section Problem:**



"data incosistency" problem occure in above case only when both the sections of process A & B are runniing at a same time, and hence these sections are reffered as critical section, and hence data inconsistency problem may occure when two or more processes are running in their critical sections at a same time, and this problem is also reffered as "critical section problem".



#### **Synchronization Tools:**

- 1. Semaphore: there are two types of semaphore
- i. Binary semaphore: can be used when at a time resource can be acquired by only one process.
- It is an integer variable having either value is 0 or 1.
- ii. Counting / Classic semaphore: can be used when at a time resource can be acquired by more than one processe
- 2. Mutex Object: can be used when at a time resource can be acquired by only one process.
- Mutex object has two states: **locked** & **unlocked**, and at a time it can be only in a one state either locked or unlocked.
- Semaphore uses **signaling mechanism**, whereas mutex object uses **locking and unlocking mechanism**.




#### **Deadlock:**

- There are four neccessary and sufficient conditions to occure deadlock / characteristics of deadlock:
- 1. Mutual Exclusion: at a time resource can be acquired by only one process.
- 2. No Preemption: control of the resource cannot be taken away forcefully from any process.
- 3. Hold & Wait: every process is holding one resource and waiting for the resource which is held by another process.
- **4. Circular Wait:** if process P1 is holding resource and waiting for the resource held by another process P2, and process P2 is also holding one resource and waiting for the resource held by process P1.



#### **Deadlock: Resource Allocation Graph**





- Three deadlock handling methods are there:
- 1. Deadlock Prevention: deadlock can be prevented by discarding any one condition out of four neccessary and sufficient conditions.
- 2. Deadlock Detection & Avoidance: before allocating resources for processes all input can be given to deadlock detection algorithm in advanced and if there are chances to occure deadlock then it can be avoided by doing neccessary changes.
- There are two deadlock detection & avoidance algorithms:
- 1. Resource Allocation Graph Algorithm
- 2. Banker's Algorithm



### 3. Deadlock Recovery:

- System can be recovered from the deadlock by two ways:
- 1. Process termination: in this method randomly any one process out of processes causes deadlock gets selected and terminated forcefully to recover system from deadlock.
- Process which gets terminated forcefully in this method is reffered as a **victim process**.
- **2. Resource preemption:** in this method control of the resource taken away forcefully from a process to recover system from deadlock.




#### **# Memory Management**

# Q. Why there is a need of memory (main memory )management?

- As main memory is must for an execution of any program and it is a limited memory, hence an OS manages main memory.
- To achieve maximum CPU utilization, an OS must support multitasking, and to support multi-tasking multiple porcesses must be submitted into the system at a time i.e. it must support multiprogramming, but as main memory is limited to support multiprogramming an OS has to do memory management to complete an execution of all submitted processes.
- Memory space of one process should gets protected from another process.







Main Memory

#### **# Swapping:**

- Swap area: it is a portion of the hard disk drive (keep reserved while installation of an OS) can be used by an OS as an extension of the main memory in which inactive running programs can be kept temporarily and as per request processes can be swapped in and swapped out between swap area and the main memory.
- In Linux swap area can be maintained in the form of swap partition, whereas in Windows swap area can be maintained in the form of swap files.
- Conventionally size of the swap area should be doubles the size of the main memory, i.e. if the size of main memory is 2 GB then size of swap area should be 4 GB, if the size of main memory is 4 GB then size of swap area should be 8 GB and so on.



### **# Swapping:**

- Swapping done by the system program of an OS named as **Memory Manager**, it swap ins active running programs into the main memory from swap area and swap outs inactive running programs from the main memory and keep them temporarily into the swap area.
- there are two variants of swapping: swap in & swap out.



### **# Swapping:**

- Swapping done by the program of an OS named as **Memory Manager**, it swapin active programs into the main memory from swap area and swapout inactive running programs from the main memory and keep them temporarily into the swap area.
- there are two variants of swapping: swapin & swapout.



- Addresses generated by compiler (i.e. compiler + linker) are reffered as **logical addresses**.
- Addresses which can be see by the process when it is in the main memory reffered as **physical addresses**.
- MMU (Memory Management Unit): wich is a hardware unit converts logical address into physical address.
- MMU is a hardware contains **adder circuit, comparator circuit, base register and limit register.** Values of base register and limit registers gets change during context-switch, and memory space of one process gets protected from another process.
- CPU always executes program in its logical memory space.



#### **Memory Allocation:**

- When a process is requesting for the main memory, there are two methods by which memory gets allocated for any process
- 1. Contiguos Memory Allocation
- 2. Non-contiguos Memory Allocation

#### 1. Contiguos Memory Allocation:

Under this method, process can complete its execution only if memory gets allocated for it in a contiguos manner.

- There are two methods by which memory gets allocated for process under contiguos memory allocation method.
- 1. Fixed Size Partitioning
- 2. Variable Size Partitioning



#### 1. Fixed Size Partitioning:

- In this method, physical memory i.e. main memory (user space) is divided into fixed number of partitions and size of each partition is remains fixed.
- If any process is requesting for the memory it can be loaded into main memory in any free partition in which it can be fit.

#### **# Advantages:**

- This method is simple to implement



### # Disadvantages:

- Internal fragmentation: if memory remains unused which is internal to the partition.
- **Degree of multi-programming** is limited to the number of partitions in the main memory.
- Maximum size of a process is limited to max size partition in the main memory.
- To overcome limitations/disadvantages of fixed size partitioning method, variable/dynamic size partitioning method has been designed.



#### 2. Variable/Dynamic Size Partitioning:

- In this method, initially whole user space i.e. physical memory is considered as a single free partition, and processes gets loaded into the main memory as they request for it.
- Size of partition and number of partitions are not fixed in advanced, it gets decided dynamically.

#### **# Advantages:**

- there are very less chances of internal fragmentation
- Degree of multi-programming is not limited/fixed
- Size of the process is not also limited, any size process may get load into the main memory.

#### **# Disadvantages:**

- External fragmentation: due to loading and removing of processes into and from the main memory, main memory is fragmented i.e. gets devided into used partitions and free partitions.



#### 2. Variable/Dynamic Size Partitioning:

- External fragmentation: due to loading and removing of processes into and from the main memory, main memory gets fragmented i.e. it gets divided into used partitions and free partitions.
- In such case, if any new process is requesting for the memory and even if the requested size of memory is available, but due to unavailability of the memory in a contuguos manner request of that process cannot be accepted, this problem is reffered as an **external fragmentation**.
- External fragmentation is the biggest problem under contiguos memory allocation, and hence there are two solutions on this problem:

#### 1. Compaction

#### 2. Non-contiguos Memory Allocation



- **1. Compaction:** shuffling of main memory can be done in such a way that all used partitions can be shifted to one side and all free partitions can be shifted to other side and contiguos large free partition will be made available for the new processes.
- Compaction is practically not feasible as there is need to do recalculations of addresses every time.

#### 2. Non-contiguos Memory Allocation:

- Under this method, process can complete its execution even if memory gets allocated for it in a non-contiguos manner, and it can be achieved by two memory management techniques:

#### 1. Segmentation

#### 2. Paging

- So by using segmentation & paging techniques, process can complete its execution even after memory gets allocated for it in a **non-contiguos manner.** 



#### 1. Segmentation

- In this technique, process in its logical memory is divided into small size segments like **stack segment**, **heap segment**, **data segment**, **bss segment**, **rodata segment**, **code segment etc**..., and when process is requesting for memory it is not requesting memory contiguosly for whole process, memory gets allocated contiguosly only for small size segments, and segments of one process may get load into the memory randomly at any locations, i.e. for a process memory gets allocated in a **non-contiguos manner**, and then only an execution of a process can be completed.
- As segments of a one process gets loaded randomly into the main memory, and in a system thousands processes are running at a time, hence to keep track on all the segments of each process, an OS maintains **one table per process** reffered as a **segmentation table** in which information about all the segments of that process can be kept.
- Using segmentation an external fragmentation can be reduced but cannot be completely avoided => to overcome this limitation paging technique has been designed.




#### # Segmentation

Big size process gets divided logically into small size segments

#### Process: Size 7 K

0	stack	1K
1	heap	1K
2	rodata	1K
3	data	2K
4	code	2K






#### 2. Paging

- In this technique, **physical memory** (i.e. user space of a main memory) is divided into fixed size of blocks reffered as **frames**, and process's **logical memory** space is divided into same size of blocks reffered as **pages**, whereas maximum size of page must be equal to size of frame, i.e. if e.g. size of frame = 4K, then maximum size of each page must be 4K, size of page may be less than 4K.
- As process is divided into pages, so when it is requesting for memory, pages of one process may gets loaded into the main memory at any free frames, and for a process memory gets allocated in a non-contiguos manner.
- As pages of a one process gets loaded randomly into the main memory, and in a system thousands processes are running at a time, so to keep track on all the pages of each process, an OS maintains one table per process reffered as a **page table** in which information about all the pages of that process can be kept.
- There is no external fragmentation in paging.
- Internal fragmentation may exists in paging when the size of page is less than size of frame.







#### **Virtual Memory Management:**

- As we seen an OS does memory management for completing an execution of multiple submitted processes at once.
- An OS also able to complete an execution of such a process having size bigger than size of main memory itself, and to achieve this an OS manages swap area memory as well with main memory and hence it is reffered as **virtual memory management.**
- As an OS manages such a memory which is physically not a main memory and hence it is reffered as virtual memory management.
- Virtual memory management can be implemented by using Paging + Swapping.
- In this technique for a process to complete its execution it is not mandatory it must exists wholely in a main memory, even its part is their into the main memory then execution of such process can be completed part by part.
- Big size process is divided into pages and when a process is requesting for memory few pages gets loaded into the main memory and few pages can be kept into the swap area, and as per the request pages of that process can swappedin and swapped out between main memory and swap area.



#### **Virtual Memory Management:**

- **Demand Paging:** any page of a process gets loaded into the main memory only after requesting by that process i.e. on demand and hence reffered as **demand paging**, page which is never requested never gets loaded into the main memory and hence it also called as **pure demand paging**.
- If a process is requesting for any page and if that page is not exists in the main memory, then it is referred as **page fault**.
- As the size of process may be bigger than size of main memory itself, and in a system multiple processes are running at a time, hence no. of pages are more than no. of frames, so there are quite good chances that all frames becomes full, and in this case if any process is requesting for a page which does not exists in the main memory at that time there is need to remove any one page from the main memory so that into that free frame requested page will get loaded.
- So there is need to decide which page should get removed and requested page gets replaced in that frame, to do this there are certain algorithms referred as **page replacement algorithms.**



#### **Page Replacement Algorithms:**

- 1. FIFO Page Replacement: page which was inserted first gets replaced by the requested page.
- 2. Optimal Page Replacement: page which will not get used in a near future gets replaced by the requested page
- 3. LRU(Least Recently Used) Page Replacement: least recently used page gets replaced by the requested page.
- **4. LFU(Least Frequently Used) Page Replacement:** least frequetly used page gets replaced by the requested page.
- **5. MFU(Most Frequently Used) Page Replacement:** most frequetly used page gets replaced by the requested page.
- Algorithms 1, 2 & 3 uses **stack based** approach, whereas algorithms 4 & 5 uses counting based approach.
- Conceptually Optimal Page Replacement is the most efficient page replacement algorithm, as no. of page faults in this algorithm are very less, but as its practical implementation is not feasible hence LRU is the most efficient algorithm (implementationwise).



- Thrashing: If any process spends more time on paging rather than execution, then this high paging activity is referred as thrashing.



Linux Commands
Sachin G. Pawar.
SunBeam Institute of
Information & Technology,
Pune & Karad.



- # Introduction to Linux
- # Linux Heirarchical Filesystem Structure
- # What is a Path? What is an absolute path & relative path
- **# Linux Commands:**
- **File, Directory and Filesystem commands:** pwd, cd, ls, mkdir, rmdir, rm, cat, whatis, whereis, man, cat, tac
- **Redirection Operators:** input (<), output (>) and error (2>) redirection operators.
- **Pipe (|) operator :** cascadding of commands like head, tail, sort, uniq, cut, tr, less etc ... with pipe command
- Multi-user Commands: w, who, whoami, sudo adduser, sudo deluser
- **Permission Commands:** chmod, chown etc...
- **Grep Command**



#### # Introduction to Linux

- Linux is a family of open source UNIX like Operating Systems based on the Linux kernel.
- An Operating System kernel <u>vmlinuz</u> first released on <u>September 17</u>, <u>1991, by Linus Torvalds.</u>
- Linus Torvalds is the Finnish-American software engineer who is the creator and, historically, the main developer of the <u>Linux kernel</u>, used by <u>Linux distributions</u> and other operating systems such as <u>Android</u>.
- There are commercially-backed distributions, such as **Fedora (Red Hat)**, **openSUSE (SUSE)** and **Ubuntu (Canonical Ltd.)**, and entirely community-driven distributions, such as **Debian**, **Slackware**, **Gentoo** and **Arch Linux**.



#### # Introduction to Linux:

- As any user cannot directly interacts with computer hardware system, so there is a need of some interface between user and hardware and to provide this interface is the job of an OS.
- An OS is a **system software** (i.e. collection of system programs) which acts as an interface between **user** and **hardware** (i.e. computer hardware system mainly contains CPU, Memory Devices & IO Devices).
- Any user as well cannot directly interacts with an OS, so there are two types of interfaces by which user can interacts with an OS:
- 1. CUI/CLI: Command User Interface/Command Line Interface
- 2. GUI: Graphical User Interface



#### 1. CUI/CLI: Command User Interface/Command Line Interface

- User can interacts with an OS by means of entering commands in text format.
- Program like "shell" in linux which acts as a CLI "Command Line Interpreter" which takes command from the user and invokes kernel functionalities.
- Windows cmd.exe
- MSDOS command.com
- Linux terminal/shell programs => bash, bsh, ksh, csh etc...

## 2. GUI: Graphical User Interface

- User can interacts with the OS by means of making events like right click, click on buttons, menu, menu bar, start window, etc....
- Windows explorer.exe
- Linux GNOME/KDE
- GNOME GNU Network Object Model Environment (Ubuntu, Redhat, Centos ....) KDE - Kommon Desktop Environment (Kubuntu, SuSE )



#### # Linux Filesystem Structure:

- While an installation of Linux system we need to create two partitions:
- 1. swap partition
- 2. "/" (root) partition also called as data partition
- Linux follows FHS i.e. FileSystem Heirarchy Standards.
- Data can be store into the "data partition" in an organized manner, so linux filesystem structure is having heirarchical structure, which is like an inverted tree.
- When any user loggedin into the system or opens a terminal, system takes the user bydefualt into the user's home dir.
- Linux filesystem structure starts with **root dir** ("/"), and all the data can be stored or kept inside it under sub-dir's in an organized manner.
- root dir i.e. "/" dir contains sub-dir's like: "/boot", "/bin", "/sbin", "/etc", "/lib", "/usr", "/home", "/root" "/mnt", "/dev" etc....



#### # Linux Filesystem Structure:

- 1. "/boot":
- it contains information about booting the system
- it contains linux kernel by the name **vmlinuz**.
- 2. "/bin": contains user commands in a binary format, e.g. commands like ls, cat, cp, mv etc...
- 3. "/sbin": contains admin/system commands in a binary format, e.g. lscpu, adduser, deluser, mkfs etc...
- 4. "/home": contains home dir's of all users for multi-user system.
- for any user on its creation of an account by default subdir by the name of the user got created by the operating system, in which that user can store data, user can have read, write as well execute perms in that dir.
- 5. "/root": root is a home dir of root user
- **6.** "/etc": contains host specific system configuration files it is like a "control panel" in windows. In computing configuration files (or config files) are files used to configure the parameters and initial settings for some computer programs. They are used for user applications, server processes and operating system settings.



- # Linux Filesystem Structure:
- 7. "/dev": contains device files
- 8. "/lib": contains shared libraries required for /bin and /sbin.
- 9. "/mnt": contains temporarily mounted filesystems
- 10. "/media": mount point for removable media such as CDROMs.
- 11. "/opt": contains optional application software packages.
- 12. "/proc": virtual filesystem provides process and kernel information as a files. In Linux, corresponds to a procfs mount. Generally automatically generated and populated by the system, on the fly.



- # path it is an unique location of any file in a filesystem structure that can be represented in a string format i.e. in sequence of chars format seperated filenames/sub-dir names by delimiter char or delimiter.
- e.g. "/home/sunbeam/aug2021/dac/linux\_command.txt"
- there are three delimiter chars:
- 1. slash ("/") -- In Linux
- 2. backslash ("\") -- In Windows
- 3. colon (":") -- In Linux as well as in Windows
- In Linux there are two ways by which we can mention path of any file/dir:
- 1. absolute path: path of any file/dir with respect to root directory ("/") i.e. it is a full path of any file/dir which starts with root dir ("/").
- 2. relative path: path of any file/dir with respect to the current working dir.



- UNIX/Linux considers/treats everything as a file, i.e. from UNIX point of veiw (as Linux is UNIX like/based OS) there are 7 types of files in UNIX/Linux:
- 1. regular file (-): linux treats all text files, source files, audio files video files, image files etc.... as a regular files.
- **2. directory file (d):** directory file is a special type of file whose contents are name of files and sub dir's.
- 3. character special device file (c): devices from which data gets transferred character by character i.e. byte by byte are called as character devices, UNIX/Linux treats all char devices as a character special device files. e.g. KBD, Monitor, Printer, serial ports & parellel ports etc...
- 4. block special device file (b): devices from which data gets transefered block by block i.e. sector by sector are called as block devices, UNIX/Linux treats all block devices as block special device files.
- e.g. all storage devices are block devices
- Information of device files gets loaded into "/dev" while booting.



- **5. socket file (s):** this is a special type of file can be used for an IPC.
- **6. named pipe file (p)**: this file can be used for an IPC by pipe() system call internally.
- 7. linkable file (1): this is a special type of file which contains info about another file.

It is same as short cut files in Windows.



#### # Command Name: "pwd" - print/present working directory

- this command displays an absolute path (i.e. full path) of the present/current working directory
- pwd command internally refers the value of shell variable by the name "PWD".

```
# Command Name: "cd" - to change current working directory - to navigate throughout filesystem structure.
```

**\$cd <dirpath>** -- change dir to the dirpath, whereas dirpath may an absolute path or relative path.

```
$cd / => goto the root directory, "/" slash is user short hand variable
```

\$cd ~ => goto the user's home dir, "~" tild symbol is user short hand variable contains an absolute path of currently loggedin user.

```
$cd => goto the user's home dir
```

- **\$cd** => goto the previously accessed directory
- **\$cd**. => remains in current dir
- **\$cd..** => goto the parent dir of the current working dir



- # Command Name: "Is" to display contents of the directory/list directory contents. contents of the directory files are nothing but names of files and sub-dir's in it.
  \$ls <dirpath> => it displays contents of the dir by the name "dirpath".
  \$ls => bydefault it displays contents of the current directory column wise in a alphabatically sorted manner
  \$ls -l => it displays contents of the dir in a listing format with more details total n, n = total no. of data blocks allocated for the files and sub dir's in a given dir listed below.
- **feild-1:** first char of feild-1 denotes type of the file, next 3 chars of field-1 denotes access perms for user/owner of a file, next 3 chars of field-1 denotes access perms for group members and last 3 chars of field-1 denotes access perms for others. **feild-2:** denotes **no. of links (i.e. hard links )** exists for that file, for **regular file bydefault no. of links i.e. link count = 1** and for **directory file bydefualt no. of links i.e. link count = 2.**



- # Command Name: "ls" to display contents of the directory/list directory contents.
- contents of the directory files are nothing but name of files and sub-dir's.
- **\$ls <dirpath>** => it displays contents of the dir by the name "dirpath".
- **\$ls** => bydefault it displays contents of the current directory column wise in a sorted manner
- **\$ls -l** => it displays contents of the dir in a listing format.
- **total n**, n = total no. of data blocks allocated for the files and sub dir's in a given dir listed below.
- **feild-1:** first char of feild 1 denotes type the file next 3 chars of field 1 denotes access perms for user/owner of a file, next 3 chars of field 1 denotes access perms for group members last 3 chars of field 1 denotes access perms for others. **feild-2:** denotes no. of links (i.e. hard links) exists for that file for regular file bydefualt no. of links i.e. link count = 1 and for directory file bydefualt no. of links i.e. link count = 2.



- **feild-3**: denotes name of an user/owner
- feild-4: denotes name of group
- **feild-5**: denotes size of the file
- feild-6: denotes time stamps date of creation and last modified date & time in ISO
- format.
- feild-7: name of the file
- In UNIX/Linux filename starts with (".") is considered as a hidden file, the period (".") options/flags/args thta can be used with ls command:
- -h: displays size of the files in human redable format
- -l: displays contents of the dir in a listing format
- -a: display all contents of the dir (including hidden files)
- **-A:** display all contents of the dir (including hidden files but excluding entries for "." & "..").
- -i: displays an iNode number of the file, inode number is an unique idenfier of the file. etc.....
- explore more options from man pages with man command.



- # Command Name: "man" an interface to the system reference manuals
- man is the system's manual pager, each page argument given to man is normally the name of a program, utility or function. The manual page associated with each of these arguments is then found and displayed. A section, if provided, will direct man to look only in that section of the manual. Below shows the section numbers of the manual followed by the types of pages they contain.
  - 1 Executable programs or shell commands
  - 2 System calls (functions provided by the kernel)
  - 3 Library calls (functions within program libraries)
  - 4 Special files (usually found in /dev)
  - 5 File formats and conventions, e.g. /etc/passwd
  - 6 Games
  - 7 Miscellaneous (including macro packages and conventions), e.g. man(7), groff(7)
  - 8 System administration commands (usually only for root)
  - 9 Kernel routines [Non standard]
- **\$ man man** => display information about man command.



Linux Commands
Sachin G. Pawar.
SunBeam Institute of
Information & Technology,
Pune & Karad.



- **# Introduction to Linux**
- # Linux Heirarchical Filesystem Structure
- # What is a Path? What is an absolute path & relative path
- **# Linux Commands:**
- **File, Directory and Filesystem commands:** pwd, cd, ls, mkdir, rmdir, rm, cat, whatis, whereis, man, cat, tac
- **Redirection Operators:** input (<), output (>) and error (2>) redirection operators.
- **Pipe (|) operator :** cascadding of commands like head, tail, sort, uniq, cut, tr, less etc ... with pipe command
- **Permission Commands:** chmod
- **Grep Command**



#### # Introduction to Linux

- Linux is a family of open source UNIX like Operating Systems based on the Linux kernel.
- An Operating System kernel <u>vmlinuz</u> first released on <u>September 17</u>, <u>1991, by Linus Torvalds.</u>
- Linus Torvalds is the Finnish-American software engineer who is the creator and, historically, the main developer of the <u>Linux kernel</u>, used by <u>Linux distributions</u> and other operating systems such as <u>Android</u>.
- There are commercially-backed distributions, such as **Fedora (Red Hat)**, **openSUSE (SUSE)** and **Ubuntu (Canonical Ltd.)**, and entirely community-driven distributions, such as **Debian**, **Slackware**, **Gentoo** and **Arch Linux**.



#### # Introduction to Linux:

- As any user cannot directly interacts with computer hardware system, so there is a need of some interface between user and hardware and to provide this interface is the job of an OS.
- An OS is a **system software** (i.e. collection of system programs) which acts as an interface between **user** and **hardware** (i.e. computer hardware system mainly contains CPU, Memory Devices & IO Devices).
- Any user as well cannot directly interacts with an OS, so there are two types of interfaces by which user can interacts with an OS:
- 1. CUI/CLI: Command User Interface/Command Line Interface
- 2. GUI: Graphical User Interface



#### 1. CUI/CLI: Command User Interface/Command Line Interface

- User can interacts with an OS by means of entering commands in text format.
- Program like "shell" in linux which acts as a CLI "Command Line Interpreter" which takes command from the user and invokes kernel functionalities.
- Windows cmd.exe
- MSDOS command.com
- Linux terminal/shell programs => bash, bsh, ksh, csh etc...

## 2. GUI: Graphical User Interface

- User can interacts with the OS by means of making events like right click, click on buttons, menu, menu bar, start window, etc....
- Windows explorer.exe
- Linux GNOME/KDE
- GNOME GNU Network Object Model Environment (Ubuntu, Redhat, Centos ....) KDE - Kommon Desktop Environment (Kubuntu, SuSE )



#### # Linux Filesystem Structure:

- While an installation of Linux system we need to create two partitions:
- 1. swap partition
- 2. "/" (root) partition also called as data partition
- Linux follows FHS i.e. FileSystem Heirarchy Standards.
- Data can be store into the "data partition" in an organized manner, so linux filesystem structure is having heirarchical structure, which is like an inverted tree.
- When any user loggedin into the system or opens a terminal, system takes the user bydefualt into the user's home dir.
- Linux filesystem structure starts with **root dir** ("/"), and all the data can be stored or kept inside it under sub-dir's in an organized manner.
- root dir i.e. "/" dir contains sub-dir's like: "/boot", "/bin", "/sbin", "/etc", "/lib", "/usr", "/home", "/root" "/mnt", "/dev" etc....



#### # Linux Filesystem Structure:

- 1. "/boot":
- it contains information about booting the system
- it contains linux kernel by the name **vmlinuz**.
- 2. "/bin": contains user commands in a binary format, e.g. commands like ls, cat, cp, mv etc...
- 3. "/sbin": contains admin/system commands in a binary format, e.g. lscpu, adduser, deluser, mkfs etc...
- 4. "/home": contains home dir's of all users for multi-user system.
- for any user on its creation of an account by default subdir by the name of the user got created by the operating system, in which that user can store data, user can have read, write as well execute perms in that dir.
- 5. "/root": root is a home dir of root user
- **6.** "/etc": contains host specific system configuration files it is like a "control panel" in windows. In computing configuration files (or config files) are files used to configure the parameters and initial settings for some computer programs. They are used for user applications, server processes and operating system settings.



- # Linux Filesystem Structure:
- 7. "/dev": contains device files
- 8. "/lib": contains shared libraries required for /bin and /sbin.
- 9. "/mnt": contains temporarily mounted filesystems
- 10. "/media": mount point for removable media such as CDROMs.
- 11. "/opt": contains optional application software packages.
- 12. "/proc": virtual filesystem provides process and kernel information as a files. In Linux, corresponds to a procfs mount. Generally automatically generated and populated by the system, on the fly.



- # path it is an unique location of any file in a filesystem structure that can be represented in a string format i.e. in sequence of chars format seperated filenames/sub-dir names by delimiter char or delimiter.
- e.g. "/home/sunbeam/aug2021/dac/linux\_command.txt"
- there are three delimiter chars:
- 1. slash ("/") -- In Linux
- 2. backslash ("\") -- In Windows
- 3. colon (":") -- In Linux as well as in Windows
- In Linux there are two ways by which we can mention path of any file/dir:
- 1. absolute path: path of any file/dir with respect to root directory ("/") i.e. it is a full path of any file/dir which starts with root dir ("/").
- 2. relative path: path of any file/dir with respect to the current working dir.



- UNIX/Linux considers/treats everything as a file, i.e. from UNIX point of veiw (as Linux is UNIX like/based OS) there are 7 types of files in UNIX/Linux:
- 1. regular file (-): linux treats all text files, source files, audio files video files, image files etc.... as a regular files.
- **2. directory file (d):** directory file is a special type of file whose contents are name of files and sub dir's.
- 3. character special device file (c): devices from which data gets transferred character by character i.e. byte by byte are called as character devices, UNIX/Linux treats all char devices as a character special device files. e.g. KBD, Monitor, Printer, serial ports & parellel ports etc...
- 4. block special device file (b): devices from which data gets transefered block by block i.e. sector by sector are called as block devices, UNIX/Linux treats all block devices as block special device files.
- e.g. all storage devices are block devices
- Information of device files gets loaded into "/dev" while booting.



- **5. socket file (s):** this is a special type of file can be used for an IPC.
- **6. named pipe file (p)**: this file can be used for an IPC by pipe() system call internally.
- 7. linkable file (1): this is a special type of file which contains info about another file.

It is same as short cut files in Windows.



#### # Command Name: "pwd" - print/present working directory

- this command displays an absolute path (i.e. full path) of the present/current working directory
- pwd command internally refers the value of shell variable by the name "PWD".
- # Command Name: "cd" to change current working directory to navigate throughout filesystem structure.
- **\$cd <dirpath>** -- change dir to the dirpath, whereas dirpath may an absolute path or relative path.
- **\$cd** / => goto the root directory, "/" **slash** is **user short hand variable**
- \$cd ~ => goto the user's home dir, "~" tild symbol is user short hand variable contains an absolute path of currently loggedin user.
- **\$cd** => goto the user's home dir
- **\$cd** => goto the previously accessed directory
- **\$cd**. => remains in current dir
- **\$cd..** => goto the parent dir of the current working dir



- # Command Name: "ls" to display contents of the directory/list directory contents.
   contents of the directory files are nothing but names of files and sub-dir's in it.
  \$ls <dirpath> => it displays contents of the dir by the name "dirpath".
  \$ls => bydefault it displays contents of the current directory column wise in a alphabatically sorted manner
  \$ls -l => it displays contents of the dir in a listing format with more details total n, n = total no. of data blocks allocated for the files and sub dir's in a given dir listed below.
  feild-1: first char of feild-1 denotes type of the file, next 3 chars of field-1 denotes
- access perms for user/owner of a file, next 3 chars of field-1 denotes access perms for group members and last 3 chars of field-1 denotes access perms for others. **feild-2:** denotes **no. of links (i.e. hard links )** exists for that file,
- for regular file bydefault no. of links i.e. link count = 1 and
- for directory file by defualt no. of links i.e. link count = 2.



- # Command Name: "ls" to display contents of the directory/list directory contents.
- contents of the directory files are nothing but name of files and sub-dir's.
- **\$ls <dirpath>** => it displays contents of the dir by the name "dirpath".
- **\$ls** => bydefault it displays contents of the current directory column wise in a sorted manner
- **\$ls -l** => it displays contents of the dir in a listing format.
- **total n**, n = total no. of data blocks allocated for the files and sub dir's in a given dir listed below.
- **feild-1:** first char of feild 1 denotes type the file next 3 chars of field 1 denotes access perms for user/owner of a file, next 3 chars of field 1 denotes access perms for group members last 3 chars of field 1 denotes access perms for others. **feild-2:** denotes no. of links (i.e. hard links ) exists for that file for regular file
- by definite on the links (i.e. fland finks) exists for that the for regular fine by defualt no. of links i.e. link count = 1 and for directory file by defualt no. of links i.e. link count = 2.



- **feild-3**: denotes name of an user/owner
- feild-4: denotes name of group
- **feild-5**: denotes size of the file
- feild-6: denotes time stamps date of creation and last modified date & time in ISO
- format.
- feild-7: name of the file
- In UNIX/Linux filename starts with (".") is considered as a hidden file, the period (".") options/flags/args thta can be used with ls command:
- -h: displays size of the files in human redable format
- -l: displays contents of the dir in a listing format
- -a: display all contents of the dir (including hidden files)
- -A: display all contents of the dir (including hidden files but excluding entries for "." & "..").
- -i: displays an iNode number of the file, inode number is an unique idenfier of the file. etc.....
- explore more options from man pages with man command.



- # Command Name: "man" an interface to the system reference manuals
- man is the system's manual pager, each page argument given to man is normally the name of a program, utility or function. The manual page associated with each of these arguments is then found and displayed. A section, if provided, will direct man to look only in that section of the manual. Below shows the section numbers of the manual followed by the types of pages they contain.
  - 1 Executable programs or shell commands
  - 2 System calls (functions provided by the kernel)
  - 3 Library calls (functions within program libraries)
  - 4 Special files (usually found in /dev)
  - 5 File formats and conventions, e.g. /etc/passwd
  - 6 Games
  - 7 Miscellaneous (including macro packages and conventions), e.g. man(7), groff(7)
  - 8 System administration commands (usually only for root)
  - 9 Kernel routines [Non standard]
- **\$ man man** => display information about man command.



```
# Command Name: "tac"
# Command Name: "whatis"
# Command Name: "whereis"
# Command Name: "cat" - concatenate contents of file/s and print on
the standard output
# Command Name: "touch" - change file timestamps
# Command Name: "cp" -
# Command Name: "mv" -
# Command Name: "mkdir" -
# Command Name: "rmdir" -
# Command Name: "rm" -
# Command Name: "alias"
# Command Name: "unalias"
```



#### # Redirection Operators:

- OS bydefualt opens 3 files for any program:
- 1. stdin: standard input buffer bydefault any program accepts/reads input from stdin file/buffer.
- 2. stdout: standard output buffer bydefault any program writes data into the stdout buffer.
- **3. stderr: standard error buffer** if any program is having an errors, those list of errors gets written bydefault into the "stderr" buffer and contents of stderr buffer gets displayed onto the standard output.

#### Three Redirection Operators are there:

- 1. Input redirection operator (<) -- left cheveron
- 2. Output redirection operator (>) -- right cheveron
- 3. Error redirection operator (2>)
- When any process gets terminated its exit status gets returned to an OS. Program can returns any one value out of following three values upon exit:
  - 0 successfull termination
  - >0 = 1 erroneous termination
  - <0 = -1 abnormal termination



- # Command Name: pipe (|) this command can be used to give/pass an output of one command as an input to another command. (|) => symbol for pipe command.
- It internally creates a temporary buffer for storing an output of one command which can be passed as an input to another command.

# Cascadding of following commands with pipe command:

- head
- tail
- sort
- uniq
- cut
- tr
- less



- # Command Name: "chmod" used to change file mode bits
- this command is used to change (i.e. to assign/ to remove) access permissions of a file for user/owner, group members and others.
- Access permissions can be assigned/removed for the file by two ways/formats:
- 1. Human Readable Format:
- **\$chmod +x filename**: to assign execute perm to all
- **\$chmod -x filename**: to remove an execute perm from all
- **\$chmod u+x filename**: to assign execute perm to user/owner of the file only
- **\$chmod g+x filename**: to assign execute perm to group members
- **\$chmod o+x filename**: to assign execute perm to others
- u user
- g group members
- o others
- + => assign permissions
- => remove permissions



#### 2. Octal Format:

Octal values: r : read => 4 w : write => 2 and x : execute => 1.

#### \$chmod 0ABC filename

- Above, in a first argument to chmod command, leading 0 indicates its an octal constant.

**A** => access perms of user/owner of the file

**B** => access perms for group members

**C** => access perms for others

**\$chmod 0777 filename**: to assign all perms to all

**\$chmod 0000 filename**: to remove all perms from all

**\$chmod 0644 filename**: to assign read as well as write perms to user/owner of a file, read only perm to group members and others.

**\$chmod 0755 filename**: to assign read, write as well as execute perms to user/owner of a file, and read and execute only perms to group members and others.



- # Command Name: "grep" globally search regular expression and print.
- grep command searches for **pattern/string/expression** in a file/files/filesystem structure and bydefault prints the matching line.
  - egrep <=> grep -E
  - fgrep <=> grep -F
  - rgrep <=> grep -r

Following options can be used with grep command:

- -i -- ignore case distinctions
- -v -- invert the sense of matching
- -w -- select only those lines containing matches that form whole words.
- -x -- select only those matches that exactly match the whole line
- -y -- obsolete synonym for -i



- **\$grep "java" sunbeam.txt** --> prints the lines matches with the pattern **\$grep -n "java" sunbeam.txt** --> prints the lines matches with line numbers **\$grep -c "java" sunbeam.txt** --> supress normal output; instead print a count of matching line for each input files, with -v option prints non-matching lines
- **\$grep -w "program" sunbeam.txt** --> prints the lines containg matches that form whole word
- **\$grep -A2 "device" sunbeam.txt** --> prints two lines **after** match is found including match line
- **\$grep -B2 "device" sunbeam.txt -->** prints two lines **before** match is found including match line
- **\$grep -C2 "device" sunbeam.txt** --> prints two line **after as well as before** match is found including match line.



- "anchoring":
- The carot (^) and and the are the meta characters.
- "^" -- at the begining of a line
- "\$" -- at the end of a line

```
$grep "is" taste.txt
$grep "^is" taste.txt
$grep "is$" taste.txt
$grep "^is$" taste.txt
```



```
# "character classes and bracket expressions":
$cat select.txt
$grep "bg" select.txt
$grep "b.g" select.txt -- the period "." matches any single character
$grep "b[a]g" select.txt -- "bracket expression"
$grep "b[ai]g" select.txt
$grep "b[aiu]g" select.txt
$grep "b[a-z]g" select.txt -- within "bracket expression" a "range
expression"
$grep "b*g" select.txt
$grep "b\*g" select.txt
$fgrep "b*g" select.txt OR grep -F "b*g" select.txt
```



```
# "repetition operators":
? -- at most once i.e. 0 or 1 no. of times occurences
* -- zero or more occurences
+ -- one or more occurences
{ n } -- exact n no. of occurences
{ n, } -- more or equal to n no. of occurences
{ , m } -- atmost m no. of occurences
{ n, m } -- more than or equal to n and less than or equal to m.
```



- **\$egrep "wo\*w" repeat.txt** --> preceding item will be matched zero or more times
- **\$egrep "wo?w" repeat.txt** --> preceding item is optional and matched at most once
- **\$egrep "wo+w" repeat.txt** --> preceding item will be matched one or more times
- \$egrep "wo{n}w" repeat.txt --> preceding item will be matched exact n times
  \$egrep "wo{n,}w" repeat.txt --> preceding item will be matched exact n or
  more times
- **\$egrep "wo{,m}w" repeat.txt** --> preceding item will be matched atmost m times
- **\$egrep "wo{n,m}w" repeat.txt** --> preceding item will be matched atleast n times, but not more than m times.

